



SAFETY DATA SHEET

Revision Date: 09-04-2015

Version 5

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Code(s): 13069323-M
Product Name AQUASHIELD
Recommended use Complex grease
Uses advised against Any other purpose.

Manufacturer, Importer, Supplier

Houghton International Inc.
Madison & Van Buren Aves.
Valley Forge, PA 19482
Telephone: 610-666-4000 FAX: 610-666-1376
Website: www.houghtonintl.com
Customer Service: 888-459-9844

Houghton Canada
915 Meyerside Drive
Mississauga
ON L5T 1R8

Emergency telephone number

3E Company 1-866-519-4752 (USA, Canada, Mexico)
Company Access Code: 333938

SECTION 2: HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B

GHS Label elements, including precautionary statements

Signal Word
Warning

Hazard Statements
Causes skin irritation
Causes eye irritation



Precautionary Statements

Precautionary Statements - Prevention

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Specific treatment is urgent (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other information

Not applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture. Health hazard information is based on its ingredients.

Chemical Name	CAS-No	Weight %
Highly refined base oil (Viscosity >20.5 cSt @40°C)	-	25% - 60%
Butene, homopolymer (products derived from either/or But-1-ene/But-2-ene)	9003-29-6	25% - 60%
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	-	2.5% - 10%
Titanium dioxide	13463-67-7	0% - 1%
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	NOT AVAILABLE	0% - 1%
(Z)-N-9-octadecenylpropane-1,3-diamine	7173-62-8	0% - 1%

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346. See Section 15 for additional information on base oils.

** Substances for which there are Community workplace exposure limits.

SECTION 4: FIRST AID MEASURES**4.1. Description of first-aid measures****General advice**

Do not get in eyes, on skin, or on clothing. When symptoms persist or in all cases of doubt seek medical advice.

Inhalation

Move to fresh air.

Skin contact

Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing before re-use. If symptoms persist, call a physician.

Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice.
Protection of First-aiders	Use personal protective equipment. Avoid contact with skin, eyes and clothing.

4.2. Most important symptoms and effects, both acute and delayed

Main Symptoms Redness, Rash, Itching, Eye damage/irritation

4.3. Indication of immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment; Use CO2, dry chemical, or foam, Water spray or fog, Cool containers / tanks with water spray

Extinguishing media which shall not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire

5.2. Special hazards arising from the substance or mixture

Special Hazard

In the event of fire and/or explosion do not breathe fumes. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Thermal decomposition can lead to release of irritating gases and vapors. Water runoff can cause environmental damage.

Hazardous Decomposition Products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Special protective equipment for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and clothing.

Advice for non-emergency personnel Material can create slippery conditions.

Advice for emergency responders For personal protection see section 8.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dike to collect large liquid spills.

6.4. Reference to other sections

See Section 8/12/13 for additional information

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Advice on safe handling. Keep away from open flames, hot surfaces and sources of ignition.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition.

Recommended Shelf Life

No information available.

Incompatible Materials

Strong oxidizing agents, Strong acids, Strong bases

7.3. Specific end uses

Specific use(s)	Complex grease
------------------------	----------------

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	AIHA WEEL
Highly refined base oil (Viscosity >20.5 cSt @40°C) -	5 mg/m³ as mist	5 mg/m³ as mist		
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C) -	5 mg/m³ as mist	5 mg/m³ as mist		
Titanium dioxide 13463-67-7	TWA: 10 mg/m³	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³ total dust	IDLH: 5000 mg/m³	

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in *AFL-CIO v. OSHA*, 965 F.2d 962 (11th Cir., 1992).

Hydrocarbon solvent vapor mixtures which do not have substance specific occupational exposure limits may be evaluated by the Reciprocal Calculation Procedure (RCP) which assigns a recommended occupational exposure limit based on the mass composition and hydrocarbon group guidance values (GGVs). Applicable recommended occupational exposure limits are shown in the table below.

Chemical Name	RCP OEL	Manufacturer
Distillates (petroleum), hydrotreated middle	RCP: TWA 1200 mg/m³ 143ppm	

64742-46-7

Exposure controls**Engineering Measures**

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment**Eye/Face Protection**

Tightly fitting safety goggles.

Skin and body protection

Wear protective gloves/clothing.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Regular cleaning of equipment, work area and clothing is recommended.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Physical state @20°C
Odor

Grease
No information available

Appearance
Odor Threshold

greenish-blue
Not Applicable

PropertyValuesNote**pH**

Not applicable

Melting Point / Freezing Point

No information available

Boiling point/boiling range

No information available

Flash point

> 150 °C / > 302 °F

Cleveland Open Cup (COC)

Evaporation rate

No information available

Flammability (solid, gas)

No information available

Flammability Limits in Air**upper flammability limit**

No information available

Lower flammability limit

No information available

Vapor pressure

No information available

Vapor density

No information available

Relative density

No information available

Solubility(ies)

Insoluble in water

Partition coefficient: n-octanol/water

Not Applicable

Autoignition temperature

No information available

Decomposition temperature

No information available

Viscosity, kinematic

> 30 cSt @ 40 °C

ASTM D 445

Explosive properties

Not Applicable

Oxidizing Properties

Not Applicable

9.2 Other information**Viscosity, kinematic (100°C)**

No information available

Pour point

No information available

VOC Content (ASTM E-1868-10)

No information available

VOC Content

No information available

Density< 1000 kg/m³ @25 °C**SECTION 10: STABILITY AND REACTIVITY****10.1. Reactivity**

None under normal use conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None under normal use conditions

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition

10.5. Incompatible Materials

Strong oxidizing agents, Strong acids, Strong bases

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	There is no data available for this product.
Eye contact	Irritating to eyes.
Skin contact	Irritating to skin.
Ingestion	There is no data available for this product.

Component Information

Chemical Name	LD50 Oral (Rat)	LD50 Dermal (Rat/Rabbit)	LC50 Inhalation
Highly refined base oil (Viscosity >20.5 cSt @40°C) -	>2000 mg/kg	>2000 mg/kg	
Butene, homopolymer (products derived from either/or But-1-ene/But-2-ene) 9003-29-6		> 10250 mg/kg (Rat)	
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C) -	>2000 mg/kg	>2000 mg/kg	
Titanium dioxide 13463-67-7	> 5000 mg/kg (Rat)		
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl NOT AVAILABLE	>2000 mg/kg (Rat)		

Information on toxicological effects

Symptoms Moderate skin irritation. Irritating to eyes. Repeated or prolonged skin contact may cause

skin irritation and/or dermatitis and sensitization of susceptible persons.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization None known.

Germ Cell Mutagenicity None known.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7		Group 2B		X

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive toxicity None known.

Specific target organ systemic toxicity (single exposure) None known.

Specific target organ systemic toxicity (repeated exposure) None known.

Aspiration hazard None known.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic organisms Harmful to aquatic life with long lasting effects

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
Butene, homopolymer (products derived from either/or But-1-ene/But-2-ene)		>1000: 96 h Oncorhynchus mykiss mg/L LC50		>1000: 48 h Daphnia magna mg/L EC50
Titanium dioxide		>10000: 96 h Cyprinodon variegatus mg/L LC50		>100: 48 h Daphnia magna mg/L EC50
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	6.4: 96 h Pseudokirchneriella subcapitata mg/L EC50	8.5: 96 h Pimephales promelas mg/L LC50 24: 96 h Oncorhynchus mykiss mg/L LC50		91.4: 48 h Daphnia magna mg/L EC50
(Z)-N-9-octadecenylpropane-1,3-diamine	0.507: 72 h Desmodesmus subspicatus mg/L EC50	0.148: 96 h Brachydanio rerio mg/L LC50		> 0.2 - 0.04: 48 h Daphnia magna mg/L EC50

Persistence and degradability

The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

Bioaccumulation

No information available.

Mobility

Is not likely mobile in the environment due its low water solubility.

Other adverse effects No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Observe all label precautions until container is cleaned, reconditioned or destroyed.

SECTION 14: TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

ICAO/IATA Not regulated

IMDG/IMO Not regulated

SECTION 15: REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	Complies
AICS	Complies
PICCS	Complies
KECL	Complies
IECSC	Complies
ENCS	Does not Comply

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

ENCS - Japan Existing and New Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	no
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and

Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

SCAQMD Rule 1144

This product has not been tested for VOC content by the ASTM E-1868-10 method and is not approved for sale or distribution in the SCAQM District of California if the product is used as a metal forming, metal removal, metal treating, metal protection fluid or as a direct-contact lubricant.

California Proposition 65

WARNING: This product contains a chemical(s) known to the State of California to cause cancer and/or birth defects or other reproductive harm.

International Regulations

Mexico - Grade

Slight risk, Grade 1

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

D2B Toxic materials

Other information

Not applicable

The highly refined base oil (Viscosity >20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No
Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated	101316-72-7
Lubricating oils (petroleum), used, noncatalytically refined	101316-73-8
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4
Residual oils (petroleum), solvent-refined	64742-01-4
Extracts (petroleum), residual oil solvent	64742-10-5
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Residual oils (petroleum), hydrotreated	64742-57-0
Lubricating oils (petroleum), hydrotreated spent	64742-58-1
Residual oils (petroleum), solvent-dewaxed	64742-62-7
Distillates (petroleum), solvent-dewaxed heavy, paraffinic	64742-65-0
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based	72623-87-1
Lubricating oils	74869-22-0
Paraffin oils	8012-95-1
White mineral oil (petroleum)	8042-47-5
C18-C50 branched, cyclic and linear hydrocarbons – Distillates	848301-69-9

The highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No
Distillates (petroleum), straight-run middle	64741-44-2
Distillates (petroleum), heavy hydrocracked	64741-76-0
Distillates (petroleum), solvent refined light paraffinic	64741-89-5

Distillates (petroleum), hydrotreated middle	64742-46-7
Distillates (petroleum), hydrotreated middle	64742-46-7
Distillates (petroleum), hydrotreated light	64742-47-8
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
Distillates, petroleum, solvent-dewaxed light paraffinic	64742-56-9
Distillates (petroleum), solvent-dewaxed heavy, paraffinic	64742-65-0
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based	72623-87-1
White mineral oil (petroleum)	8042-47-5
C18-C50 branched, cyclic and linear hydrocarbons – Distillates	848301-69-9
Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE

SECTION 16: OTHER INFORMATION

NFPA **Health Hazard 2** **Flammability 1** **Instability 0** **Physical and chemical hazards -**

Key or legend to abbreviations and acronyms used in the safety data sheet

STOT SE - Specific target organ systemic toxicity (Single exposure)
 STOT RE - Specific target organ systemic toxicity (repeated exposure)
 TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 VOC - Volatile organic compounds
 NIOSH IDLH: Immediately Dangerous to Life or Health

Revision Date: 09-04-2015

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

end