

Custom Solutions & Manufacturing Excellence


From the day our company opened for business in 1947, our continuous growth as a U.S. manufacturer has been a great source of pride. We have accomplished this, in part, by providing custom solutions for your challenging circuit designs. Our products are designed to meet the highest quality standards as evidenced by the accreditation of our MIL-PRF-39010, "R" failure rate. No other company in the world maintains this highest industry standard, and it is back by over 250 million test unit hours.

The API Delevan team focuses on four pillars required by the engineering community: **Prototype Services** – We offer solutions in hours or days, not weeks or months. **Smallest Size** – Today's solutions, whether components or vertically integrated designs, must meet the needs of miniaturization. **Highest Performance** – We promise to deliver better electrical & mechanical performance than any other manufacturer in the industry. **Lowest Cost** – We realize the highest quality result at the lowest cost by adhering to daily Kaizen and Lean Manufacturing activities, producing one piece flow while simultaneously eliminating waste.

API Delevan has a reputation for developing application specific solutions in compliance with the industry's highest quality standards for an extraordinarily broad variety of products in every market segment. In addition to the 50 million standard products we manufacture every year, 40% of our business can be attributed to the custom designs our engineers provide.

Engineer to engineer solutions are the bedrock of custom designs, and our insistence on listening to, and working with, our customers accounts for the on-going success of this very important element of our business. The relationships we develop have been long-standing and mutually rewarding ones which we highly value.

Our Established Reliability Program has accumulated over 250 million hours of life testing. In addition to making available an engineering staff with over six decades of accrued experience, API maintains a modern environmental lab, testing capabilities and a R&D department. API Delevan believes value comes not just with quality, but also with resourcefulness.



API Delevan[®]
Tested Products. Valued Solutions.




Table of Contents

RF Inductors

Surface Mount

Series 100	12
Series 103	13
Series 105	14
Series 106	15
Series 108	14
Series 160	16
Series 0402R	4
Series S0402	5-6
Series 0603R	7
Series S0603	8-9
Series 0805R	10
Series 1008	20
Series HF1008	21
Series WW1008R	11
Series S1008	22
Series 1210	24
Series S1210	25
Series 1330	27
Series MIL1330	28
Series 1331	29
Series MIL1331	30
Series 1812	31
Series MIL1812	32
Series S1812	33
Series MILS1812	34
Series 2510	35
Series MIL2510	36
Series 3090	17
Series 3094	18
Series 4232	26
Series 4302	23
Series 4379	19
Series 4426	40
Series 4726	41
Series S4924	37
Series 5022	38-39
Series 5526	42

Thru-hole

Series 511	47
Series 0819	42
Series 0925	55
Series 1025	44
Series 1026	38
Series 1537	46
Series 1638	48
Series 1641	56
Series 1782	45
Series 1840	49
Series 1944	50
Series 1945	50
Series 2150	51
Series 2500	52
Series 2890	53
Series 4307	57
Series 4470	54
Series ER	58-61

Radial Leaded

Series 2020	62
Series 2534	65
Series 2727	63
Series 4445	64
Series 4554	66
Series 4564	67
Series 5400	67
Series 9405	68
Series 9406	68

Power Inductors

Surface Mount

Series P160	69
Series SP1008	70
Series SP1210	71
Series P1330	72
Series P1812	73
Series MILP1812	74
Series SP1812	75
Series 2512	76
Series 3483R	77
Series S3483R	77
Series SDS130R	78
Series SDS680R	79
Series SDS850R	80
Series 4501	81
Series 4448	82
Series 4922	83
Series MIL4922	84
Series 5500	87
Series 8532	85
Series MIL8532	86
Series HCT	88-89
Series LP4040R	83
Series LP5035R	83
Series LP5050R	83
Series LP5064R	83
Series LLST	90
Series PDxxxR	93-94
Series PTHF-SM & Series PTKM-SM	91-92
Series SPD42R	95
Series SPD62R	96
Series SPD73 & Series SPD74	97
Series SPD125 & Series SPD127	98

Thru-hole

Series 2256	99
Series 2474	100
Series 4590	101

Radial Leaded

Series 3443	102
Series DC630	103
Series DC780	104
Series DC1050	105
Series DC1390	106
Series HC	107
Series HTPT66	108
Series PT	109-112
Series PTHF & Series PTKM	113-114
Series PTHF-VM & Series PTKM-VM	114-116

EMI/RFI Suppressors

Surface Mount

Series EMI	117
Series 4221	118
Series 4222	119
Series SMB 2.5	120

Thru-hole

Series 4211	121
Series 4212	122
Series 4214	123

Cable

Series BF	124-126
Series CF	127-128

API Materials

Absorbers

Series FFAM	129
Series FFAT	130

CONTACT API DELEVAN FOR THE FOLLOWING:

Inductors –

Series 0920	
Series 1027	
Series 1325	
Series 1537-7XX	
Series 1539	
Series 1842	
Series 2502	
Series 2892	
Series 3500	
Series M0820	
Series M1330	
Series M1331	

Suppressors –

Series 7085/7273	
Series FTA	
Series PA	

Transformers

Common Mode Surface Mount

Series CM6296	133
Series CM6149	131
Series CM6350	134
Series CM6460	135
Series CM6560	136
Series CM6594	137
Series CM7560	138

Thru-hole

Series CM1011	132
Series CM7560	132
Series CM9900	139

Switch Mode - EE Core

Series 6655-6658	144
------------------	-----

Switch Mode - ETD Core

Series 6665-6668	145
------------------	-----

Laminated - PC Mount

Series 6012 - 6027	140
Series 6051 - 6055	141
Series 6443 - 6448	142

Laminated - Quick-Connect

Series 6494 - 6498	143
--------------------	-----

Technical

CONVERSION CHARTS


MIL Standard to Delevan	146-148
MIL-PRF-83446 to Delevan	149-151
MIL-PRF-27 to Delevan	152

Product Index	153
---------------	-----

SERIES**0402R**

Open Construction Wirewound Surface Mount Inductors

RF Inductors



• Actual Size (Max.)

Physical Parameters

	Inches	Millimeters
A	0.050 Max.	1.27 Max.
B	0.030 Max.	0.76 Max.
C	0.024 Max.	0.61 Max.
D	0.020 (Ref. only)	0.51 (Ref. only)
E	0.009 (Ref. only)	0.23 (Ref. only)
F	0.022 (Ref. only)	0.56 (Ref. only)
G	0.026	0.66
H	0.019	0.50
I	0.018	0.46

Operating Temperature Range -40°C to +125°C

Inductance and Q tested on HP4291A using HP16193A test fixture, or equivalent

Packaging Tape & reel (8mm): 7" reel, 4000 pieces max.

SERIES 0402R CERAMIC CORE


DASH NUMBER*	INDUCTANCE (nH) ±10%	Q MINIMUM	INDUCTANCE & Q TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
-1N0K	1.0	16	250	12,700	0.045	1360
-1N9K	1.9	16	250	11,300	0.070	1040
-2N0K	2.0	16	250	11,100	0.070	1040
-2N2K	2.2	19	250	10,800	0.070	960
-2N4K	2.4	15	250	10,500	0.070	790
-2N7K	2.7	16	250	10,400	0.120	640
-3N3K	3.3	19	250	7000	0.066	840
-3N6K	3.6	19	250	6800	0.066	840
-3N9K	3.9	19	250	5800	0.066	840
-4N3K	4.3	18	250	6000	0.091	700
-4N7K	4.7	15	250	4700	0.130	640
-5N1K	5.1	20	250	4800	0.083	800
-5N6K	5.6	20	250	4800	0.083	760
-6N2K	6.2	20	250	4800	0.083	760
-6N8K	6.8	20	250	4800	0.083	680
-7N5K	7.5	22	250	4800	0.104	680
-8N2K	8.2	22	250	4400	0.104	680
-8N7K	8.7	18	250	4100	0.200	480
-9N0K	9.0	22	250	4160	0.104	680
-10NK	10	21	250	3900	0.195	480
-11NK	11	24	250	3680	0.120	640
-12NK	12	24	250	3600	0.120	640
-13NK	13	24	250	3450	0.210	440
-15NK	15	24	250	3280	0.172	560
-16NK	16	24	250	3100	0.220	560
-18NK	18	24	250	3100	0.230	420
-19NK	19	24	250	3040	0.202	480
-20NK	20	25	250	3000	0.250	420
-22NK	22	25	250	2800	0.300	400
-23NK	23	24	250	2720	0.300	400
-24NK	24	25	250	2700	0.300	400
-27NK	27	24	250	2480	0.300	400
-30NK	30	25	250	2350	0.350	400
-33NK	33	24	250	2350	0.350	400
-36NK	36	24	250	2320	0.440	320
-39NK	39	25	250	2100	0.550	200
-40NK	40	24	250	2240	0.440	320
-43NK	43	25	250	2030	0.810	100
-47NK	47	20	250	2100	0.830	150
-51NK	51	25	250	1750	0.820	100
-56NK	56	22	250	1700	0.970	100
-68NK	68	22	250	1620	1.120	100


Optional Tolerances (except 1.0nH & 1.9nH): J = 5%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

LAND PATTERN DIMENSIONS



SERIES S0402**Hi-Rel Surface Mount
Chip Inductors**

Actual Size (Max.)

Physical Parameters

	Inches	Millimeters
D	0.006 - 0.010	0.152 - 0.254
A	0.037 - 0.043	0.940 - 1.092
B	0.018 - 0.025	0.457 - 0.635
C	0.030 Max.	0.762 Max.

Operating Temperature Range -55°C to +125°C**Current Rating at 90°C Ambient** +35°C Rise**Insulation Resistance at 100 Vdc** 1000 Mohm Min.**Dielectric Withstanding Voltage (DWV)** 200 Vrms.**Core Material / Termination**Al₂O₃ / Sintered MoMn / Electroplated Ni /
Electroplated Au Finish (RoHS)Termination Options: 1. Au Finish (RoHS)
2. SnPb Solder
3. Pb Free Solder (RoHS)**Electrical Characteristics** Measured at +25°C

DASH NUMBER*	INDUCTANCE (nH) ± 5%	Q MINIMUM	INDUCTANCE & Q TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
SERIES S0402						
-2N2J	2.2	18	250	8500	0.090	950
-3N3J	3.3	18	250	7000	0.080	800
-4N7J	4.7	14	250	4700	0.150	600
-6N8J	6.8	19	250	4800	0.100	600
-8N2J	8.2	20	250	4400	0.130	600
-10NJ	10.0	20	250	3900	0.210	475
-12NJ	12.0	21	250	3600	0.220	475
-15NJ	15.0	23	250	3280	0.220	475
-22NJ	22.0	24	250	2800	0.350	400
-27NJ	27.0	23	250	2480	0.360	400
-33NJ	33.0	23	250	2350	0.370	400
-47NJ	47.0	19	250	2100	0.830	150
-56NJ	56.0	21	250	1700	1.000	100
-68NJ	68.0	20	250	1620	1.180	100

Inductance Tolerance Options H (± 3%), G (± 2%), F (± 1%)

S0402 Test Plan Advantages

- Provides multiple screening alternatives
- Eliminates necessity for SCD's
- Provides quicker delivery
- Reduces overall costs

How To Order:**S0402**

(A)

8N2

(B)

G

(C)

2

(D)

S

(E)

(A) Inductor Series

(B) Inductance Value

(C) Inductance Tolerance

(D) Termination Finish

(E) Test Plan Screening

S0402 Test Plan Options


Ordering Option Code		S	C	B	D	E
Screening Level		MIL-STD-981 Class "S"	MIL-STD-981 Class "S" Modified	MIL-STD-981 Class "B"	MIL-STD-981 Class "B" Modified	High Temp
Test	Method					
Thermal Shock	MIL-PRF-83446	25 Cycles 1/ (-55°C to +125°C)	25 Cycles (-55°C to +125°C)	25 Cycles 1/ (-55°C to +125°C)	25 Cycles (-55°C to +125°C)	5 Cycles (-55°C to +175°C)
No-Load Burn-In	MIL-STD-981	125°C (96 hours)	125°C (96 hours)	125°C (96 hours)	125°C (96 hours)	200°C (96 hours)
Dielectric Withstanding Voltage	MIL-PRF-83446	200 Vrms		200 Vrms		
Insulation Resistance	MIL-PRF-83446	1000 Mohms		1000 Mohms		
Electrical Characteristics: L, Q, DCR, SRF	MIL-PRF-83446	•	•	•	•	•
Radiographic Inspection	MIL-STD-981	•				
Visual & Dimensional Examination (external)	MIL-PRF-83446	•	•	•	•	
* Electrical Characteristics (initial): L, Q, DCR, SRF	MIL-PRF-83446	•	•			
* Low Temperature Operation	MIL-PRF-83446	•	•			
* Temperature Rise	MIL-PRF-83446	•				•
* Overload	MIL-PRF-83446	•	•			•
* Moisture Resistance	MIL-PRF-83446	•				
* Electrical Characteristics: L and Q	MIL-PRF-83446	•	•			
* High Temperature Exposure	MIL-PRF-83446	•	•			
* Electrical Characteristics (final)	MIL-PRF-83446	•	•			
* Bond Strength	MIL-PRF-83446	•	•			
* Visual & Mechanical Examination (external)	MIL-PRF-83446	•	•			
* Visual & Mechanical Examination (internal)	MIL-STD-981	•				
* Solderability	MIL-PRF-83446	•	•			
* Electrical Characteristics (initial): L, Q, DCR, SRF	MIL-PRF-83446	•	•			
* Life	MIL-PRF-83446	2000 Hours (90°C Ambient)	500 Hours (90°C Ambient)			500 Hours (175°C Ambient)
* Dielectric Withstanding Voltage	MIL-PRF-83446	80 Vrms	80 Vrms			
* Insulation Resistance	MIL-PRF-83446	1000 Mohms	1000 Mohms			
* Electrical Characteristics (final): L, Q, DCR, SRF	MIL-PRF-83446	•	•			
* Visual & Mechanical Examination (external)	MIL-PRF-83446	•	•			
Mechanical Shock/Vibration	MIL-STD-883					•

*Destructive Test Units Required


1/ Continually monitor continuity during the entire final cycle to verify no intermittent conditions.

SERIES S0402

Hi-Rel Surface Mount
Chip Inductors

Suggested Land Patterns

Delevan Series	G		H		I	
	Inches	mm	Inches	mm	Inches	mm
S0402 Series	0.026	0.660	0.014	0.356	0.018	0.457



**S-Parameters (Typical)**

All product specifications and data contained herein are subject to change without notice to improve reliability, function, performance, design or otherwise.

SERIES**0603R**

Open Construction Wirewound Surface Mount Inductors

RF Inductors




Actual Size (Max.)

Physical Parameters

	Inches	Millimeters
A	0.071 Max.	1.80 Max.
B	0.045 Max.	1.14 Max.
C	0.040 Max.	1.02 Max.
D	0.030 (Ref. only)	0.76 (Ref. only)
E	0.018 (Ref. only)	0.44 (Ref. only)
F	0.040 (Ref. only)	1.03 (Ref. only)
G	0.040	1.03
H	0.025	0.64
I	0.025	0.64

Operating Temperature Range -40°C to +125°C
Inductance and Q tested on HP4291A using HP16193A test fixture, or equivalent

Packaging Tape & reel (8mm): 7" reel, 4000 pieces max.
**LAND PATTERN
DIMENSIONS**


DASH NUMBER*	INDUCTANCE (μH) ±10%	Q MINIMUM	INDUCTANCE & Q TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
SERIES 0603R CERAMIC CORE						
-1N6K	1.6	16	250	6000	0.040	700
-1N8K	1.8	16	250	6000	0.045	700
-3N3K	3.3	22	250	6000	0.080	700
-3N6K	3.6	22	250	5800	0.063	700
-3N9K	3.9	22	250	6000	0.080	700
-4N3K	4.3	22	250	5800	0.063	700
-4N7K	4.7	25	250	5800	0.120	700
-5N1K	5.1	20	250	5800	0.160	700
-5N6K	5.6	20	250	5800	0.170	700
-6N8K	6.8	27	250	5800	0.110	700
-7N5K	7.5	27	250	4800	0.110	700
-8N2K	8.2	27	250	4800	0.110	700
-8N7K	8.7	27	250	4800	0.110	700
-9N5K	9.5	27	250	4800	0.130	700
-10NK	10	31	250	4800	0.130	700
-11NK	11	31	250	4000	0.086	700
-12NK	12	35	250	4000	0.130	700
-15NK	15	35	250	4000	0.170	700
-16NK	16	35	250	3300	0.110	700
-18NK	18	35	250	3100	0.170	700
-22NK	22	38	250	3000	0.190	700
-24NK	24	38	250	2800	0.130	700
-27NK	27	40	250	2800	0.220	600
-30NK	30	40	250	2800	0.150	600
-33NK	33	40	250	2300	0.220	600
-36NK	36	40	250	2300	0.250	600
-39NK	39	40	250	2200	0.250	600
-43NK	43	38	200	2000	0.280	600
-47NK	47	38	200	2000	0.280	600
-56NK	56	38	200	1900	0.310	600
-68NK	68	37	200	1700	0.340	600
-72NK	72	34	150	1700	0.490	400
-82NK	82	34	150	1700	0.540	400
-101K	100	34	150	1400	0.580	400
-111K	110	32	150	1350	0.610	300
-121K	120	32	150	1300	0.650	300
-151K	150	32	100	1300	0.950	280
-181K	180	25	100	1200	1.400	250
-221K	220	25	100	1200	1.600	250
-271K	270	25	100	900	2.100	200
-331K	330	25	100	900	3.800	100
-391K	390	25	100	900	4.350	100

Optional Tolerances: 9.5nH & Lower J = 5%

All Other Values: J = 5% G = 2%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

SERIES S0603**Hi-Rel Surface Mount
Chip Inductors**

Actual Size (Max.)

Physical Parameters

	Inches	Millimeters
D	0.011 - 0.010	0.279 - 0.381
A	0.058 - 0.062	1.473 - 1.575
B	0.028 - 0.035	0.711 - 0.889
C	0.040 Max.	1.016 Max.

Operating Temperature Range -55°C to +125°C**Current Rating at 90°C Ambient** +35°C Rise**Insulation Resistance at 100 Vdc** 1000 Mohm Min.**Dielectric Withstanding Voltage (DWV)** 200 Vrms.**Core Material / Termination**Al₂O₃ / Sintered MoMn / Electroplated Ni /
Electroplated Au Finish (RoHS)Termination Options: 1. Au Finish (RoHS)
2. SnPb Solder
3. Pb Free Solder (RoHS)**Electrical Characteristics** Measured at +25°C

INDUCTANCE (nH) ± 5%
Q MINIMUM
INDUCTANCE & Q TEST
FREQUENCY (MHz)
SRF MINIMUM (MHz)
DC RESISTANCE
MAXIMUM (OHMS)
CURRENT RATING
MAXIMUM (mA)

SERIES S0603

-3N3J	3.3	18	250	6000	0.100	700
-5N6J	5.6	18	250	5800	0.190	700
-8N2J	8.2	24	250	4800	0.150	700
-10NJ	10.0	28	250	4800	0.160	700
-15NJ	15.0	32	250	4000	0.200	700
-22NJ	22.0	35	250	3000	0.220	700
-33NJ	33.0	37	250	2300	0.250	600
-39NJ	39.0	37	250	2200	0.280	600
-47NJ	47.0	35	200	2000	0.310	600
-56NJ	56.0	35	200	1900	0.340	600
-68NJ	68.0	34	200	1700	0.370	600
-82NJ	82.0	34	150	1700	0.570	400
-101NJ	100.0	31	150	1400	0.610	400
-151NJ	150.0	29	100	1300	0.980	280
-221NJ	220.0	22	100	1200	1.700	250
-271NJ	270.0	22	100	900	2.200	200

Inductance Tolerance Options H (± 3%), G (± 2%), F (± 1%)

S0603 Test Plan Advantages

- Provides multiple screening alternatives
- Eliminates necessity for SCD's
- Provides quicker delivery
- Reduces overall costs

How To Order:

S0603 **101N** **J** **1** **C**
(A) (B) (C) (D) (E)

(A) Inductor Series
(B) Inductance Value
(C) Inductance Tolerance
(D) Termination Finish
(E) Test Plan Screening

S0603 Test Plan Options


Ordering Option Code		S	C	B	D	E
Screening Level		MIL-STD-981 Class "S"	MIL-STD-981 Class "S" Modified	MIL-STD-981 Class "B"	MIL-STD-981 Class "B" Modified	High Temp
Test	Method					
Thermal Shock	MIL-PRF-83446	25 Cycles 1/ (-55°C to +125°C)	25 Cycles (-55°C to +125°C)	25 Cycles 1/ (-55°C to +125°C)	25 Cycles (-55°C to +125°C)	5 Cycles (-55°C to +175°C)
No-Load Burn-In	MIL-STD-981	125°C (96 hours)	125°C (96 hours)	125°C (96 hours)	125°C (96 hours)	200°C (96 hours)
Dielectric Withstanding Voltage	MIL-PRF-83446	200 Vrms		200 Vrms		
Insulation Resistance	MIL-PRF-83446	1000 Mohms		1000 Mohms		
Electrical Characteristics: L, Q, DCR, SRF	MIL-PRF-83446	•	•	•	•	•
Radiographic Inspection	MIL-STD-981	•				
Visual & Dimensional Examination (external)	MIL-PRF-83446	•	•	•	•	
* Electrical Characteristics (initial): L, Q, DCR, SRF	MIL-PRF-83446	•	•			
* Low Temperature Operation	MIL-PRF-83446	•	•			
* Temperature Rise	MIL-PRF-83446	•				•
* Overload	MIL-PRF-83446	•	•			•
* Moisture Resistance	MIL-PRF-83446	•				
* Electrical Characteristics: L and Q	MIL-PRF-83446	•	•			
* High Temperature Exposure	MIL-PRF-83446	•	•			
* Electrical Characteristics (final)	MIL-PRF-83446	•	•			
* Bond Strength	MIL-PRF-83446	•	•			
* Visual & Mechanical Examination (external)	MIL-PRF-83446	•	•			
* Visual & Mechanical Examination (internal)	MIL-STD-981	•				
* Solderability	MIL-PRF-83446	•	•			
* Electrical Characteristics (initial): L, Q, DCR, SRF	MIL-PRF-83446	•	•			
* Life	MIL-PRF-83446	2000 Hours (90°C Ambient)	500 Hours (90°C Ambient)			500 Hours (175°C Ambient)
* Dielectric Withstanding Voltage	MIL-PRF-83446	80 Vrms	80 Vrms			
* Insulation Resistance	MIL-PRF-83446	1000 Mohms	1000 Mohms			
* Electrical Characteristics (final): L, Q, DCR, SRF	MIL-PRF-83446	•	•			
* Visual & Mechanical Examination (external)	MIL-PRF-83446	•	•			
Mechanical Shock/Vibration	MIL-STD-883					•

*Destructive Test Units Required


1/ Continually monitor continuity during the entire final cycle to verify no intermittent conditions.

SERIES S0603

Hi-Rel Surface Mount
Chip Inductors

Suggested Land Patterns

Delevan Series	G		H		I	
	Inches	mm	Inches	mm	Inches	mm
S0603 Series	0.040	1.016	0.025	0.635	0.025	0.635



**S-Parameters (Typical)**

All product specifications and data contained herein are subject to change without notice to improve reliability, function, performance, design or otherwise.

SERIES**0805R**

Open Construction Wirewound Surface Mount Inductors

RF Inductors



Actual Size (Max.)

Physical Parameters

	Inches	Millimeters
A	0.090 Max.	2.29 Max.
B	0.068 Max.	1.73 Max.
C	0.060 Max.	1.52 Max.
D	0.050 (Ref. only)	1.27 (Ref. only)
E	0.018 (Ref. only)	0.44 (Ref. only)
F	0.040 (Ref. only)	1.03 (Ref. only)
G	0.070	1.78
H	0.040	1.02
I	0.030	0.76

Operating Temperature Range -40°C to +125°C


Inductance and Q tested on HP4291A using HP16193A test fixture, or equivalent

Packaging Tape & reel (8mm): 7" reel, 2000 pieces max.

SERIES 0805R CERAMIC CORE

DASH NUMBER*	INDUCTANCE (μH) ±10%	INDUCTANCE TEST FREQUENCY (MHz)	Q MINIMUM	SRF MINIMUM (MHz)	Q TEST	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
-2N8K	2.8	250	80	1500	7900	0.06	800
-3N0K	3.0	250	65	1500	7900	0.06	800
-3N3K	3.3	250	50	1500	6000	0.08	600
-5N6K	5.6	250	65	1000	5500	0.08	600
-6N8K	6.8	250	50	1000	5500	0.11	600
-7N5K	7.5	250	50	1000	4500	0.14	600
-8N2K	8.2	250	50	1000	4700	0.12	600
-10NK	10	250	60	500	4200	0.10	600
-12NK	12	250	50	500	4000	0.15	600
-15NK	15	250	50	500	3400	0.17	600
-18NK	18	250	50	500	3300	0.20	600
-22NK	22	250	55	500	2600	0.22	500
-24NK	24	250	50	500	2000	0.22	500
-27NK	27	250	55	500	2500	0.25	500
-33NK	33	250	60	500	2050	0.27	500
-36NK	36	250	55	500	1700	0.27	500
-39NK	39	250	60	500	2000	0.29	500
-43NK	43	200	60	500	1650	0.34	500
-47NK	47	200	60	500	1650	0.31	500
-56NK	56	200	60	500	1550	0.34	500
-68NK	68	200	60	500	1450	0.38	500
-82NK	82	150	65	500	1300	0.42	400
-91NK	91	150	65	500	1200	0.48	400
-101K	100	150	65	500	1200	0.46	400
-111K	110	150	50	250	1000	0.48	400
-121K	120	150	50	250	1100	0.51	400
-151K	150	100	50	250	920	0.56	400
-181K	180	100	50	250	870	0.64	400
-221K	220	100	50	250	850	0.70	400
-241K	240	100	44	250	690	1.00	350
-271K	270	100	48	250	650	1.00	350
-331K	330	100	48	250	600	1.40	310
-391K	390	100	48	250	560	1.50	290
-471K	470	50	33	100	375	1.70	220
-561K	560	25	23	50	340	1.90	210
-621K	620	25	23	50	220	2.20	210
-681K	680	25	23	50	200	2.20	190
-751K	750	25	23	50	200	2.30	180
-821K	820	25	23	50	200	2.35	180
-102K	1000	25	20	50	100	2.50	170
-122K	1200	7.9	18	25	100	2.50	170
-152K	1500	7.9	16	25	100	2.50	170
-182K	1800	7.9	16	7.9	80	2.50	170
-222K	2200	7.9	16	7.9	60	2.70	160
-272K	2700	7.9	16	7.9	50	2.95	150

LAND PATTERN DIMENSIONS




Optional Tolerances: 8.2nH & Lower J = 5%

All Other Values: J = 5% G = 2%

*Complete part # must include series # PLUS the dash #


For surface finish information, refer to www.delevanfinishes.com

SERIES**WW1008R**RoHS
Compliant**Open Construction
Wirewound Surface Mount Inductors****RF Inductors**

Actual Size (Max.)

Physical Parameters

	Inches	Millimeters
A	0.115 Max.	2.92 Max.
B	0.110 Max.	2.79 Max.
C	0.080 Max.	2.03 Max.
D	0.080 (Ref. only)	2.03 (Ref. only)
E	0.020 (Ref. only)	0.50 (Ref. only)
F	0.060 (Ref. only)	1.52 (Ref. only)
G	0.100	2.54
H	0.040	1.01
I	0.050	1.27

Operating Temperature Range -40°C to +125°C**Inductance and Q** tested on HP4291A using HP16193A test fixture, or equivalent**Packaging** Tape & reel (8mm): 7" reel, 2000 pieces max.**LAND PATTERN
DIMENSIONS**

DASH NUMBER*	INDUCTANCE (μH) ±10%	INDUCTANCE TEST FREQUENCY (MHz)	Q MINIMUM	FREQUENCY - Q TEST (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
SERIES WW1008R CERAMIC CORE							
-5N6K	5.6	50	50	1500	4000	0.15	1000
-10NK	10	50	50	500	4100	0.08	1000
-12NK	12	50	50	500	3300	0.09	1000
-15NK	15	50	50	500	2500	0.11	1000
-18NK	18	50	50	350	2400	0.12	1000
-22NK	22	50	55	350	2400	0.12	1000
-24NK	24	50	55	350	1900	0.12	1000
-27NK	27	50	55	350	1600	0.13	1000
-33NK	33	50	60	350	1600	0.14	1000
-39NK	39	50	60	350	1500	0.15	1000
-47NK	47	50	65	350	1500	0.16	1000
-56NK	56	50	65	350	1300	0.18	1000
-59NK	59	50	65	350	1250	0.20	1000
-68NK	68	50	65	350	1300	0.20	1000
-75NK	75	50	60	350	1100	0.21	1000
-82NK	82	50	60	350	1000	0.22	1000
-101K	100	25	60	350	1000	0.56	650
-121K	120	25	60	350	950	0.63	650
-151K	150	25	45	100	850	0.70	580
-181K	180	25	45	100	750	0.77	520
-221K	220	25	45	100	700	0.84	500
-241K	240	25	45	100	650	0.88	500
-271K	270	25	45	100	600	0.91	500
-301K	300	25	45	100	585	1.00	450
-331K	330	25	45	100	570	1.05	450
-361K	360	25	45	100	530	1.10	470
-391K	390	25	45	100	500	1.12	470
-431K	430	25	45	100	480	1.15	470
-471K	470	25	45	100	450	1.19	470
-561K	560	25	45	100	415	1.33	400
-621K	620	25	45	100	375	1.40	300
-681K	680	25	45	100	375	1.47	400
-751K	750	25	45	100	360	1.54	360
-821K	820	25	35	100	350	1.61	400
-911K	910	25	35	50	320	1.68	380
-102K	1000	25	35	50	290	1.75	370
-122K	1200	7.9	35	50	250	2.00	310
-152K	1500	7.9	28	50	200	2.30	330
-182K	1800	7.9	28	50	160	2.60	300
-222K	2200	7.9	28	50	160	2.80	280
-272K	2700	7.9	22	25	140	3.20	290
-332K	3300	7.9	22	25	110	3.40	290
-392K	3900	7.9	20	25	100	3.60	260
-472K	4700	7.9	20	25	90	4.00	260
-562K	5600	7.9	16	7.9	40	4.00	240
-682K	6800	7.9	18	7.9	40	4.90	200
-822K	8200	7.9	18	7.9	25	6.00	170
-103K	10000	2.5	18	7.9	20	9.00	150
-123K	12000	2.5	18	7.9	18	10.50	130
-153K	15000	2.5	18	7.9	15	11.50	120

Optional Tolerances: 27nH & Lower J = 5%


All Other Values: J = 5% G = 2%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

SERIES**100R
100****Micro i® Ribbon-Lead Inductors**

Actual Size

**Military Specifications MS21367 (LT10K)****Physical Parameters**

	Inches	Millimeters
A	0.065 Max.	1.65 Max.
B	0.100 ± 0.010	2.54 ± 0.254
C	0.100 ± 0.010	2.54 ± 0.254
D	0.210 Min.	5.33 Min.
E	0.012 ± 0.002 (Typ.)	0.30 ± 0.05
F	0.095 ± 0.015	2.41 ± 0.381
G	0.002 +0.001-0.000	0.05 +0.025-0.000

Weight Max. (Grams) 0.03**Current Rating at 90°C Ambient** 15°C Rise**Operating Temperature Range** -55°C to +105°C**Maximum Power Dissipation at 90°C** 0.0205 Watts

Notes 1) L, Q and SRF measured on Boonton Q and RX meters using special test fixtures. Details for fixtures available. 2) Part number and quantity will appear on package as units are too small for legible marking.

Core Material Iron (LT10K)

Mechanical Configuration 1) Units are epoxy encapsulated. 2) Leads are tin/lead plated Beryllium Copper 3) Gold Plated leads available on special order. 4) RoHS compliant part available by ordering 100R Series.

Packaging Bulk only**Made In the U.S.A. Patent Protected**



DASH NUMBER*	MIL DASH #	INDUCTANCE (μH)	TOLERANCE	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
MS21367 - SERIES 100 IRON CORE (LT10K)								
-150N	01	0.015	±30%	40	50.0	250	0.065	492
-220N	02	0.022	±30%	40	50.0	250	0.090	418
-330N	03	0.033	±30%	40	50.0	250	0.115	370
-470N	04	0.047	±30%	40	50.0	250	0.120	360
-680N	05	0.068	±30%	40	50.0	250	0.150	324
-101N	06	0.100	±30%	40	50.0	250	0.170	304
-121M	07	0.12	±20%	35	25.0	250	0.140	335
-151M	08	0.15	±20%	40	25.0	250	0.160	313
-181M	09	0.18	±20%	40	25.0	250	0.190	287
-221M	10	0.22	±20%	40	25.0	250	0.21	274
-271M	11	0.27	±20%	40	25.0	250	0.24	256
-331M	12	0.33	±20%	40	25.0	250	0.25	251
-391M	13	0.39	±20%	40	25.0	200	0.28	237
-471M	14	0.47	±20%	40	25.0	175	0.31	225
-561M	15	0.56	±20%	40	25.0	170	0.45	185
-681M	16	0.68	±20%	40	25.0	165	0.62	159
-821M	17	0.82	±20%	35	25.0	160	0.65	155
-102M	18	1.00	±20%	35	25.0	135	0.73	145
-122K	19	1.20	±10%	35	7.9	120	1.00	125
-152K	20	1.50	±10%	32	7.9	110	1.20	114
-182K	21	1.80	±10%	32	7.9	95	1.50	102
-222K	22	2.20	±10%	35	7.9	80	1.70	96
-272K	23	2.70	±10%	35	7.9	70	2.00	89
-332K	24	3.30	±10%	37	7.9	65	2.20	84
-392K	25	3.90	±10%	37	7.9	60	2.80	75
-472K	26	4.70	±10%	40	7.9	55	3.10	71
-562K	27	5.60	±10%	40	7.9	50	3.30	69
-682K	28	6.80	±10%	40	7.9	45	3.80	64
-822K	29	8.20	±10%	40	7.9	43	5.00	56
-103K	30	10.0	±10%	40	7.9	40	5.60	53

Parts listed above are QPL/MIL qualified

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

SERIES**103R
103****Micro i® Chip Inductors**

Actual Size

Military Specifications MIL-PRF-83446/04**Physical Parameters**

	Inches	Millimeters
A	0.075 Max.	1.91 Max.
B	0.100 ± 0.010	2.54 ± 0.25
C	0.100 ± 0.010	2.54 ± 0.25
D	0.050 Min.	1.27 Min.
E	0.015 Min. (Typ.)	0.38 Min. (Typ.)
F	0.020 Max. (Typ.)	0.51 Max. (Typ.)

Weight Max. (Grams) 0.03**Current Rating at 90°C Ambient** 35°C Rise**Operating Temperature Range** -55°C to +125°C**Maximum Power Dissipation at 90°C** 0.135 Watts****Note**

Self Resonant Frequency (SRF) Values above 250 MHz are calculated and for reference only.

Termination Finish Options (Part # Code)

Gold over Nickel (Standard): As shown.

Tin/Lead over Nickel: Add suffix "S" to part # (e.g., 103-102KS).

Mil type "A:" Gold over Nickel (Standard)

Mil type "B" or "F:" Tin/Lead (solder) over Nickel.

RoHS type: Order 103R - XXXKS

Mechanical Configuration

Units are epoxy encapsulated.

Contact areas for reflow soldering are gold plated per MIL-G-45204 Type 1-Grade A. Internal connections are thermal compression bonded.

Packaging Tape & reel (8mm): 7" reel, 2000 pieces max.; 13" reel, 8000 pieces max.**Made In the U.S.A.**



DASH NUMBER*	MIL DASH #	INDUCTANCE (μH) (see Note 3)	TOLERANCE	TEST FREQUENCY Q MINIMUM	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)**	CURRENT RATING MAXIMUM (mA)
M83446/04- SERIES 103 PHENOLIC CORE							
-100M/K	30/37	0.010	± 20% / ± 10%	60	50.0	2700	0.060
-120K	38	0.012	± 10%	57	50.0	2450	0.069
-150M/K	31/39	0.015	± 20% / ± 10%	55	50.0	2200	0.078
-180K	40	0.018	± 10%	52	50.0	2000	0.093
-220M/K	32/41	0.022	± 20% / ± 10%	50	50.0	1800	0.108
-270K	42	0.027	± 10%	49	50.0	1625	0.114
-330M/K	33/43	0.033	± 20% / ± 10%	48	50.0	1450	0.120
-390K	44	0.039	± 10%	45	50.0	1335	0.133
-470M/K	34/45	0.047	± 20% / ± 10%	42	50.0	1220	0.145
-560K	46	0.056	± 10%	39	50.0	1110	0.170
-680M/K	35/47	0.068	± 20% / ± 10%	36	50.0	1000	0.195
-820K	48	0.082	± 10%	34	50.0	915	0.212
-101M/K	36/49	0.100	± 20% / ± 10%	32	50.0	830	0.230
M83446/04- SERIES 103 FERRITE CORE							
-121K	01	0.12	± 10%	30	25.0	750	0.125
-151K	02	0.15	± 10%	25	25.0	650	0.175
-181K	03	0.18	± 10%	25	25.0	550	0.200
-221K	04	0.22	± 10%	25	25.0	450	0.220
-271K	05	0.27	± 10%	25	25.0	375	0.230
-331K	06	0.33	± 10%	25	25.0	300	0.235
-391K	07	0.39	± 10%	22	25.0	235	0.240
-471K	08	0.47	± 10%	22	25.0	215	0.260
-561K	09	0.56	± 10%	22	25.0	195	0.278
-681K	10	0.68	± 10%	22	25.0	175	0.520
-821K	11	0.82	± 10%	22	25.0	160	0.530
-102K	12	1.0	± 10%	22	25.0	145	0.540
-122K	13	1.2	± 10%	22	7.9	130	0.740
-152K	14	1.5	± 10%	22	7.9	115	0.840
-182K	15	1.8	± 10%	22	7.9	105	0.920
-222K	16	2.2	± 10%	22	7.9	85	1.00
-272K	17	2.7	± 10%	24	7.9	77	1.15
-332K	18	3.3	± 10%	24	7.9	70	1.40
-392K	19	3.9	± 10%	24	7.9	68	1.55
-472K	20	4.7	± 10%	24	7.9	60	1.80
-562K	21	5.6	± 10%	22	7.9	55	2.00
-682K	22	6.8	± 10%	22	7.9	50	2.20
-822K	23	8.2	± 10%	22	7.9	48	2.50
-103K	24	10.0	± 10%	24	7.9	40	3.45
-123K	25	12.0	± 10%	25	2.5	35	3.80
-153K	26	15.0	± 10%	25	2.5	30	5.60
-183K	27	18.0	± 10%	25	2.5	28	5.80
-223K	28	22.0	± 10%	25	2.5	25	6.40
-273K	29	27.0	± 10%	25	2.5	22	6.90

Parts listed above are QPL/MIL qualified

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

SERIES**105R & 108R
105 & 108****Micro i® Chip Inductors**

Actual Size

Military Specifications

Series 105 MIL-PRF-83446 (Reference)

Series 108 MIL-PRF-83446/8 (Reference)

Physical Parameters for Series 105

	Inches	Millimeters
A	0.075 Max.	1.91 Max.
B	0.100 ± 0.010	2.54 ± 0.25
C	0.100 ± 0.010	2.54 ± 0.25
D	0.050 Min.	1.27 Min.
E	0.015 Min. (Typ.)	0.38 Min. (Typ.)
F	0.020 Max. (Typ.)	0.51 Max. (Typ.)

Physical Parameters for Series 108

	Inches	Millimeters
A	0.070 Max.	1.78 Max.
B	0.100 ± 0.010	2.54 ± 0.254
C	0.100 ± 0.010	2.54 ± 0.254
D	0.050 Min.	1.27 Min.
E	0.025 ± 0.005 (Typ.)	0.635 ± 0.13 (Typ.)
F	0.020 Max. (Typ.)	0.51 Max. (Typ.)

Weight Max. (Grams) 0.05**Current Rating at 90°C Ambient** 35°C Rise**Operating Temperature Range** -55°C to +125°C**Maximum Power Dissipation at 90°C** 0.135 W

Mechanical Configuration Units are epoxy encapsulated. Contact areas for reflow soldering are gold plated per MIL-G-45204 Type 1-Grade A. Internal connections are thermal compression bonded.

Packaging Tape & reel (8mm): 7" reel, 2000 pieces max.; 13" reel, 8000 pieces max.


Made in the U.S.A.

MIL DASH # (Reference)	DASH NUMBER*	INDUCTANCE (μH)	TOLERANCE	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	MAXIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
SERIES 105 IRON CORE									
-121M		0.12	± 20%	40	25.0	500		0.14	830
-151M		0.15	± 20%	40	25.0	440		0.16	775
-181M		0.18	± 20%	40	25.0	405		0.19	710
-221K		0.22	± 10%	40	25.0	360		0.21	675
-271K		0.27	± 10%	40	25.0	330		0.23	650
-331K		0.33	± 10%	35	25.0	280		0.25	620
-391K		0.39	± 10%	35	25.0	185		0.28	585
-471K		0.47	± 10%	35	25.0	178		0.31	555
-561K		0.56	± 10%	35	25.0	163		0.45	460
-681K		0.68	± 10%	35	25.0	160		0.62	395
-821K		0.82	± 10%	30	25.0	155		0.65	385
-102K		1.0	± 10%	30	25.0	130		0.73	360
-122K		1.2	± 10%	25	7.9	115		1.0	310
-152K		1.5	± 10%	25	7.9	100		1.2	280
-182K		1.8	± 10%	25	7.9	90		1.5	250
-222K		2.2	± 10%	25	7.9	75		1.7	235
-272K		2.7	± 10%	25	7.9	68		2.0	220
-332K		3.3	± 10%	25	7.9	62		2.2	210
-392K		3.9	± 10%	25	7.9	57		2.8	185
-472K		4.7	± 10%	30	7.9	52		3.1	175
-562K		5.6	± 10%	30	7.9	47		3.3	170
-682K		6.8	± 10%	30	7.9	42		3.8	160
-822K		8.2	± 10%	30	7.9	40		5.0	135
-103K		10.0	± 10%	30	7.9	38		5.6	130
M83446/08- (Reference) SERIES 108 IRON CORE									
-123K	87	12.0	± 10%	36	2.5	26.0		4.0	79
-153K	88	15.0	± 10%	32	2.5	24.0		4.2	79
-183K	89	18.0	± 10%	32	2.5	21.0		4.4	75
-223K	90	22.0	± 10%	32	2.5	19.0		7.5	57
-273K	91	27.0	± 10%	32	2.5	14.0		8.0	55
-333K	92	33.0	± 10%	30	2.5	12.0		13.0	45
-393K	93	39.0	± 10%	30	2.5	10.0		17.0	38
-473K	94	47.0	± 10%	30	2.5	9.0		19.0	36
-563K	95	56.0	± 10%	30	2.5	8.5		23.0	33
-683K	96	68.0	± 10%	30	2.5	8.2		25.0	32
-823K	97	82.0	± 10%	30	2.5	8.0		28.0	30
-104K	98	100.0	± 10%	30	2.5	7.0		31.0	28

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

SERIES**106
Micro i®**Traditional
First Quality**Wire Bondable Chip Inductors**

Actual Size

Physical Parameters

	Inches	Millimeters
A	0.075 Max.	1.91 Max.
B	0.155 Max.	3.94 Max.
C	0.110 Max.	2.79 Max.
D	0.015 Ref.	0.38 Ref.
E	0.030 ± 0.005	0.76 ± 0.13
F	0.025 Min.	0.64 Min.

Weight Max. (Grams) 0.2**Current Rating at 90°C Ambient** 35°C Rise**Operating Temperature** -55°C to +125°C**Maximum Power Dissipation at 90°C** 0.140 W

Termination Areas Gold plated per MIL-G-45204, Type III; Grade A. Internal Connections are Thermal Compression Bonded

****Note** Self Resonant Frequency (SRF) values above 230 MHz are calculated and for reference only

Packaging Bulk only**Made in the U.S.A**

INDUCTANCE (μH) ±10%
TEST FREQUENCY (MHz)
Q MINIMUM
SRF MINIMUM (MHz)
DC RESISTANCE MAXIMUM (OHMS)
CURRENT RATING MAXIMUM (mA)

RF Inductors**SERIES 106 PHENOLIC CORE**

-100K	0.010	45	150	1700	0.070	1200
-120K	0.012	45	150	1600	0.070	1200
-150K	0.015	45	150	1500	0.070	1200
-180K	0.018	45	150	1400	0.070	1200
-220K	0.022	45	100	1300	0.070	1200
-270K	0.027	45	100	1200	0.070	1200
-330K	0.033	47	100	1100	0.070	1200
-390K	0.039	47	100	1000	0.070	1200
-470K	0.047	47	100	900	0.080	1100
-560K	0.056	47	100	850	0.090	1050
-680K	0.068	47	100	840	0.100	1000
-820K	0.082	47	100	750	0.110	960

SERIES 106 IRON CORE

-101K	0.10	40	25.0	550	0.15	820
-121K	0.12	42	25.0	400	0.20	710
-151K	0.15	42	25.0	350	0.25	635
-181K	0.18	45	25.0	300	0.30	580
-221K	0.22	45	25.0	260	0.33	550
-271K	0.27	45	25.0	230	0.37	520
-331K	0.33	45	25.0	200	0.40	500
-391K	0.39	45	25.0	190	0.45	475
-471K	0.47	45	25.0	180	0.50	450
-561K	0.56	42	25.0	170	0.55	425
-681K	0.68	42	25.0	160	0.60	410
-821K	0.82	42	25.0	150	0.70	380
-102K	1.0	42	25.0	130	0.80	355
-122K	1.2	36	7.9	120	0.90	335
-152K	1.5	36	7.9	100	1.10	300
-182K	1.8	38	7.9	90	1.30	265
-222K	2.2	38	7.9	85	1.50	250
-272K	2.7	41	7.9	82	1.70	230
-332K	3.3	42	7.9	75	1.80	225
-392K	3.9	42	7.9	65	2.00	215
-472K	4.7	41	7.9	55	2.30	200
-562K	5.6	41	7.9	45	2.60	185
-682K	6.8	36	7.9	40	2.80	180
-822K	8.2	36	7.9	35	3.00	175
-103K	10.0	36	7.9	33	3.30	165
-123K	12.0	32	2.5	26	4.00	150
-153K	15.0	32	2.5	24	5.20	135
-183K	18.0	32	2.5	21	4.50	130
-223K	22.0	32	2.5	19	7.50	110
-273K	27.0	32	2.5	14	8.00	105
-333K	33.0	30	2.5	12	13.0	85
-393K	39.0	30	2.5	10	17.0	75
-473K	47.0	30	2.5	9.0	19.0	70

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #



For surface finish information, refer to www.delevanfinishes.com

SERIES

**160R
160**



Micro i® Chip Inductors



Military Specifications MIL-PRF-83446/38

Physical Parameters

	Inches	Millimeters
A	0.080 Max.	2.03 Max.
B	0.145 to 0.155	3.68 to 3.94
C	0.115 to 0.125	2.92 to 3.18
D	0.070 Min.	1.78 Min.
E	0.020 to 0.030	0.508 to 0.762
F	0.020 Max. (Typ.)	0.51 Max.

Current Rating at 90°C Ambient 35°C Rise

Operating Temperature Range -55°C to +125°C

Maximum Power Dissipation at 90°C 0.175 W

Termination Standard: Tin/Lead Sn63

Notes 1) Designed specifically for reflow soldering and other high temperature processes with metalized edges to exhibit solder fillet. 2) Optional marking is available. Parts can be printed with dash number (ie 100, 120, etc.). Add suffix M to part number.

For inductance values above 560μH, consult factory.



Mechanical Configuration Units are epoxy encapsulated. Contact area for reflow are solder coated. Internal connections are thermal compression bonded.

Packaging Bulk only

Made in the U.S.A.

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%
*Complete part # must include series # PLUS the dash #
For surface finish information, refer to www.delevanfinishes.com

DASH NUMBER*	MIL DASH #	INDUCTANCE (μH)	TOLERANCE	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (ΩHMS)	CURRENT RATING MAXIMUM (mA)
M83446/38 – SERIES 160 PHENOLIC CORE								
-100MS	01	0.010	± 20%	48	150	900	0.050	1590
-120MS	02	0.012	± 20%	48	150	900	0.055	1515
-150MS	03	0.015	± 20%	48	150	900	0.060	1450
-180MS	04	0.018	± 20%	48	150	900	0.065	1395
-220MS	05	0.022	± 20%	48	100	900	0.070	1345
-270MS	06	0.027	± 20%	48	100	900	0.075	1295
-330MS	07	0.033	± 20%	48	100	900	0.075	1295
-390MS	08	0.039	± 20%	48	100	900	0.080	1255
-470MS	09	0.047	± 20%	48	100	850	0.085	1220
-560MS	10	0.056	± 20%	48	100	800	0.088	1195
-680MS	11	0.068	± 20%	48	100	750	0.093	1165
-820MS	12	0.082	± 20%	48	100	700	0.095	1150
M83446/38 – SERIES 160 IRON CORE								
-101KS	13	0.100	± 10%	50	25.0	600	0.075	1295
-121KS	14	0.120	± 10%	50	25.0	550	0.075	1295
-151KS	15	0.150	± 10%	50	25.0	420	0.085	1220
-181KS	16	0.180	± 10%	50	25.0	390	0.10	1125
-221KS	17	0.220	± 10%	50	25.0	340	0.11	1070
-271KS	18	0.270	± 10%	50	25.0	290	0.12	1025
-301KS	19	0.300	± 10%	50	25.0	250	0.13	985
-331KS	20	0.330	± 10%	50	25.0	230	0.14	950
-361KS	21	0.360	± 10%	50	25.0	220	0.15	915
-391KS	22	0.390	± 10%	50	25.0	210	0.16	890
-421KS	23	0.430	± 10%	50	25.0	200	0.17	860
-471KS	24	0.470	± 10%	50	25.0	190	0.18	835
-561KS	25	0.560	± 10%	50	25.0	180	0.20	795
-681KS	26	0.680	± 10%	50	25.0	170	0.23	740
-821KS	27	0.820	± 10%	50	25.0	150	0.26	695
-102JS	28	1.00	± 5%	50	25.0	140	0.34	610
-122JS	29	1.20	± 5%	36	7.9	130	0.42	545
-152JS	30	1.50	± 5%	36	7.9	120	0.56	475
-182JS	31	1.80	± 5%	36	7.9	100	0.76	410
-222JS	32	2.20	± 5%	36	7.9	98	0.93	370
-272JS	33	2.70	± 5%	40	7.9	91	1.2	325
-332JS	34	3.30	± 5%	40	7.9	76	1.3	310
-392JS	35	3.90	± 5%	47	7.9	48	1.5	290
-472JS	36	4.70	± 5%	47	7.9	46	1.7	275
-562JS	37	5.60	± 5%	44	7.9	42	1.8	270
-682JS	38	6.80	± 5%	40	7.9	39	1.9	255
-822JS	39	8.20	± 5%	40	7.9	30	2.4	230
-103JS	40	10.0	± 5%	46	7.9	26	3.2	200
-123JS	41	12.0	± 5%	41	2.5	24	3.7	185
-153JS	42	15.0	± 5%	46	2.5	23	3.8	180
-183JS	43	18.0	± 5%	46	2.5	22	4.2	175
-223JS	44	22.0	± 5%	47	2.5	18	5.5	150
-273JS	45	27.0	± 5%	47	2.5	17	6.1	145
-333JS	46	33.0	± 5%	47	2.5	13	6.6	140
-393JS	47	39.0	± 5%	50	2.5	12	7.0	135
M83446/38 – SERIES 160 FERRITE CORE								
-473JS	48	47.0	± 5%	50	2.5	11.0	8.3	125
-563JS	49	56.0	± 5%	50	2.5	10.0	8.9	120
-683JS	50	68.0	± 5%	50	2.5	9.1	13.0	100
-823JS	51	82.0	± 5%	50	2.5	8.6	14.0	95
-104JS	52	100.0	± 5%	47	2.5	7.6	16.0	90
-124JS	53	120.0	± 5%	30	0.79	6.8	17.0	85
-154JS	54	150.0	± 5%	32	0.79	5.6	18.0	80
-184JS	55	180.0	± 5%	32	0.79	4.5	22.0	75
-224JS	56	220.0	± 5%	32	0.79	4.0	28.0	70
-274JS	57	270.0	± 5%	32	0.79	3.8	32.0	65
-334JS	58	330.0	± 5%	32	0.79	3.5	44.0	55
-394JS	59	390.0	± 5%	32	0.79	3.4	48.0	50
-474JS	60	470.0	± 5%	28	0.79	3.2	75.0	42
-564JS	61	560.0	± 5%	28	0.79	2.8	81.0	40

SERIES**3090R**
3090RoHS
CompliantTraditional
First Quality**Micro i® Low Profile Chip Inductors**

Actual Size

Physical Parameters

	Inches	Millimeters
A	0.050 Max.	1.27 Max.
B	0.100±0.010	2.54±0.254
C	0.100±0.010	2.54±0.254
D	0.050 Min.	1.27 Min.
E	0.015 Min. (Typ.)	0.38 Min. (Typ.)
F	0.020 Max. (Typ.)	0.51 Max. (Typ.)

Current Rating at 90°C Ambient 35°C Rise**Operating Temperature Range** -55°C to +125°C**Maximum Power Dissipation at 90°C** 0.105 W**Core Material** Powdered iron core for improved temperature stability.**Mechanical Configuration** Units are epoxy encapsulated. Contact area for reflow soldering are gold plated per MIL-G-45204 Type 1 Grade A. Internal connections are thermal compression bonded.**Termination Finish Options**

Standard: Gold over Nickel.

For Tin/Lead over Nickel: Add suffix "S" to part number and allow an additional .010 inch for maximum height. For RoHS, order 3090R - XXXKS.

Notes 1) Designed specifically for reflow soldering and other high temperature processes with metalized edges to exhibit solder fillet. **2)** Self Resonant Frequency (SRF) values 250 MHz and above are calculated and for reference only.**Packaging** Tape & reel (8mm): 7" reel, 2000 pieces max.; 13" reel, 8000 pieces max.**MIL-PRF-83446** (Reference) for testing methods only.**Made in the U.S.A.**

DASH NUMBER*	INDUCTANCE (μH)	TOLERANCE	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	MAXIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
SERIES 3090 IRON CORE								
-100M	0.010	± 20%	42	50.0	1000	0.095	890	
-150M	0.015	± 20%	42	50.0	1000	0.115	810	
-220M	0.022	± 20%	40	50.0	1000	0.140	765	
-330K	0.033	± 10%	40	50.0	900	0.185	640	
-390K	0.039	± 10%	40	50.0	900	0.100	870	
-470K	0.047	± 10%	38	50.0	900	0.110	830	
-560K	0.056	± 10%	35	50.0	800	0.135	750	
-680K	0.068	± 10%	30	50.0	700	0.16	690	
-820K	0.082	± 10%	25	50.0	650	0.19	630	
-101K	0.10	± 10%	32	25.0	510	0.08	970	
-121K	0.12	± 10%	32	25.0	410	0.10	870	
-151K	0.15	± 10%	32	25.0	370	0.12	795	
-181K	0.18	± 10%	32	25.0	330	0.14	765	
-221K	0.22	± 10%	34	25.0	300	0.16	690	
-271K	0.27	± 10%	34	25.0	250	0.20	615	
-331K	0.33	± 10%	34	25.0	220	0.25	550	
-391K	0.39	± 10%	34	25.0	200	0.30	500	
-471K	0.47	± 10%	34	25.0	180	0.36	460	
-561K	0.56	± 10%	34	25.0	160	0.45	410	
-681K	0.68	± 10%	30	25.0	140	0.50	390	
-821K	0.82	± 10%	28	25.0	120	0.60	355	
-102K	1.00	± 10%	24	25.0	100	0.70	330	
-122K	1.20	± 10%	24	7.9	95	1.10	265	
-152K	1.50	± 10%	24	7.9	90	1.20	250	
-182K	1.80	± 10%	24	7.9	85	1.25	245	
-222K	2.20	± 10%	25	7.9	80	1.30	240	
-272K	2.70	± 10%	25	7.9	70	1.50	225	
-332K	3.30	± 10%	25	7.9	65	1.90	200	
-392K	3.90	± 10%	25	7.9	60	2.30	180	
-472K	4.70	± 10%	24	7.9	55	3.00	160	
-562K	5.60	± 10%	22	7.9	53	3.50	145	
-682K	6.80	± 10%	22	7.9	50	4.00	135	
-822K	8.20	± 10%	22	7.9	45	4.50	130	
-103K	10.0	± 10%	20	7.9	40	5.00	120	

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #



For surface finish information, refer to www.delevanfinishes.com

SERIES

3094R
3094



Micro i® Chip Inductors



Actual Size

Physical Parameters

	Inches	Millimeters
A	0.140 Max.	3.56 Max.
B	0.147 to 0.163	3.73 to 4.14
C	0.117 to 0.133	2.97 to 3.38
D	0.070 Min.	1.78 Min.
E	0.017 to 0.033	0.43 to 0.84
F	0.020 Max. (Typ.)	0.51 Max. (Typ.)

Current Rating at 90°C Ambient 35°C Rise
Operating Temperature Range -55°C to +125°C
Maximum Power Dissipation at 90°C 0.155 W

Inductance tolerance desired is specified by suffixing an alpha character to the part number: F = 1%, G = 2%, H = 3%, J = 5%, K = 10%, and M = 20%. Standard series tolerance is $\pm 10\%$. For inductance values less than $.10\mu\text{H}$, minimum tolerance is $\pm 5\%$.

Termination Standard: Tin/Lead Sn63

Mechanical Configuration Units are epoxy encapsulated. Contact area for reflow are solder coated. Internal connections are thermal compression bonded.

Notes 1) Designed specifically for reflow soldering and other high temperature processes with metalized edges to exhibit solder fillet. 2) Self Resonant Frequency (SRF) values 270 MHz and above are calculated and for reference only. 3) Optional marking is available.

Packaging Tape & reel (12mm): 7" reel, 650 pieces max.; 13" reel, 2500 pieces max.



MIL-PRF-83446/10 (Reference)

Made In the U.S.A.

*Complete part # must include series # PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com

RF Inductor							
MIL DASH # (Reference) DASH NUMBER*	INDUCTANCE (μH) ±10%	TEST FREQUENCY (MHz) Q MINIMUM	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)		
	M83446/10- (Reference) SERIES 3094 IRON CORE						
-100KS	62	0.010	60	150	2000.0	0.040	1000
-120KS	63	0.012	60	150	1800.0	0.040	1000
-150KS	64	0.015	60	150	1500.0	0.040	1000
-180KS	65	0.018	60	150	1500.0	0.040	1000
-220KS	66	0.022	60	100	1300.0	0.050	1000
-270KS	67	0.027	60	100	1300.0	0.050	1000
-330KS	68	0.033	60	100	1000.0	0.050	1000
-390KS	69	0.039	60	100	1000.0	0.060	900
-470KS	70	0.047	65	100	800.0	0.060	900
-560KS	71	0.056	65	100	760.0	0.060	900
-680KS	72	0.068	65	100	700.0	0.070	840
-820KS	73	0.082	65	100	650.0	0.070	840
-101KS	74	0.100	65	50	570.0	0.070	840
-121KS	75	0.120	65	50	520.0	0.070	840
-151KS	76	0.150	75	50	400.0	0.080	790
-181KS	77	0.180	75	50	360.0	0.080	790
-221KS	78	0.220	70	50	320.0	0.080	790
-271KS	79	0.270	70	50	270.0	0.10	700
-331KS	80	0.330	70	50	240.0	0.10	700
-391KS	81	0.390	70	50	220.0	0.10	700
-471KS	82	0.470	70	25	190.0	0.14	590
-561KS	83	0.560	70	25	170.0	0.19	510
-681KS	84	0.680	70	25	160.0	0.26	430
-821KS	85	0.820	75	25	150.0	0.30	400
-102KS	86	1.00	75	25	130.0	0.34	380
-122KS	87	1.20	65	7.9	120.0	0.45	330
-152KS	88	1.50	65	7.9	110.0	0.57	290
-182KS	89	1.80	65	7.9	100.0	0.72	260
-222KS	90	2.20	65	7.9	80.0	0.90	230
-272KS	91	2.70	65	7.9	60.0	1.10	210
-332KS	92	3.30	60	7.9	50.0	1.20	200
-392KS	93	3.90	60	7.9	45.0	1.40	180
-472KS	94	4.70	60	7.9	42.0	1.60	170
-562KS	95	5.60	65	7.9	40.0	1.80	160
-682KS	96	6.80	65	7.9	37.0	2.40	140
-822KS	97	8.20	65	7.9	34.0	3.00	130
-103KS	98	10.0	65	7.9	29.0	3.50	120
-123KS	99	12.0	60	2.5	27.0	3.60	118
-153KS	100	15.0	60	2.5	22.0	3.70	115
-183KS	101	18.0	60	2.5	17.0	3.80	114
-223KS	102	22.0	60	2.5	16.0	3.90	113
-273KS	103	27.0	65	2.5	15.0	4.00	110
-333KS	104	33.0	65	2.5	14.0	5.00	100
-393KS	105	39.0	65	2.5	13.0	7.00	84
-473KS	106	47.0	70	2.5	12.0	8.00	79
-563KS	107	56.0	70	2.5	11.0	10.0	70
-683KS	108	68.0	65	2.5	10.0	11.0	67
-823KS	109	82.0	60	2.5	9.0	12.0	64
-104KS	110	100.0	60	2.5	8.0	13.0	62
-124KS	111	120.0	40	0.79	7.0	14.0	59
-154KS	112	150.0	40	0.79	6.0	16.0	56
-184KS	113	180.0	40	0.79	5.0	18.0	52
-224KS	114	220.0	40	0.79	4.0	24.0	45
-274KS	115	270.0	40	0.79	3.3	25.0	44
-334KS	116	330.0	40	0.79	3.1	29.0	41
-394KS	117	390.0	40	0.79	2.9	32.0	39
-474KS	118	470.0	35	0.79	2.4	35.0	37
-564KS	119	560.0	35	0.79	2.1	45.0	33
-684KS	120	680.0	35	0.79	1.9	55.0	30
-824KS	121	820.0	30	0.79	1.8	70.0	26
-105KS	122	1000.0	30	0.79	1.7	80.0	25

SERIES**4379R Micro i®**
4379 Micro i®RoHS
CompliantTraditional
First Quality**Shielded Surface Mount Inductors**

Actual Size

Physical Parameters

	Inches	Millimeters
A	0.140 Max.	3.56 Max.
B	0.147 to 0.163	3.73 to 4.14
C	0.117 to 0.133	2.97 to 3.38
D	0.070 Min.	1.78 Min.
E	0.017 to 0.033	0.43 to 0.84
F	0.020 Max. (Typ.)	0.51 Max. (Typ.)

Current Rating at 90°C Ambient 35°C Rise**Operating Temperature** -55°C to +125°C**Maximum Power Dissipation at 90°C** 0.155 W**Termination** Standard: Tin/Lead Sn63

Inductance Tolerance Desired tolerance is specified by substituting alpha characters in the part number: H=3%, J=5%, K=10%, and M=20%. Standard series tolerance is $\pm 10\%$.

Mechanical Configuration Units are epoxy encapsulated. Contact area for reflow are solder coated. Internal connections are thermal compression bonded.

Notes 1) Designed specifically for reflow soldering and other high temperature processes with metalized edges to exhibit solder fillet. 2) Self Resonant Frequency (SRF) values 260 MHz and above are calculated and for reference only.

Packaging Tape & reel (12mm): 7" reel, 650 pieces max.; 13" reel, 2500 pieces max.

MIL-PRF-83446/11 (Reference)**Made in the U.S.A.**

Optional Tolerances: J = 5% H = 3%


*Complete part # must include series # PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com


MIL DASH # (Reference)
DASH NUMBER*
INDUCTANCE (μ H) $\pm 10\%$
TEST FREQUENCY (MHz)
Q MINIMUM
SRF MINIMUM (MHz)
MAXIMUM (MHz)
DC RESISTANCE
MAXIMUM (OHMS)
CURRENT RATING
MAXIMUM (mA)

M83446/11- (Ref.) SERIES 4379 FERRITE CORE & SLEEVE

-101KS	62	0.10	79	25.0	600	0.03	1000
-121KS	63	0.12	79	25.0	520	0.03	1000
-151KS	64	0.15	79	25.0	490	0.03	1000
-181KS	65	0.18	79	25.0	460	0.04	1000
-221KS	66	0.22	79	25.0	430	0.04	1000
-271KS	67	0.27	88	25.0	370	0.04	1000
-331KS	68	0.33	93	25.0	310	0.05	750
-391KS	69	0.39	102	25.0	280	0.05	750
-471KS	70	0.47	106	25.0	260	0.05	750
-561KS	71	0.56	106	25.0	240	0.06	700
-681KS	72	0.68	106	25.0	200	0.06	700
-821KS	73	0.82	106	25.0	185	0.06	700
-102KS	74	1.0	106	25.0	175	0.09	650
-122KS	75	1.2	90	7.9	150	0.09	650
-152KS	76	1.5	100	7.9	135	0.14	600
-182KS	77	1.8	100	7.9	120	0.20	500
-222KS	78	2.2	100	7.9	105	0.30	400
-272KS	79	2.7	100	7.9	85	0.40	350
-332KS	80	3.3	100	7.9	80	0.46	330
-392KS	81	3.9	105	7.9	64	0.52	310
-472KS	82	4.7	115	7.9	56	0.54	300
-562KS	83	5.6	115	7.9	49	0.60	285
-682KS	84	6.8	115	7.9	45	0.66	270
-822KS	85	8.2	115	7.9	41	1.00	225
-103KS	86	10	100	7.9	39	1.20	200
-123KS	87	12	100	2.5	34	1.5	180
-153KS	88	15	100	2.5	30	1.8	170
-183KS	89	18	100	2.5	26	1.9	160
-223KS	90	22	105	2.5	23	2.1	150
-273KS	91	27	110	2.5	20	2.4	140
-333KS	92	33	120	2.5	18	2.7	130
-393KS	93	39	120	2.5	17	3.1	125
-473KS	94	47	120	2.5	16	3.2	125
-563KS	95	56	110	2.5	14	3.5	120
-683KS	96	68	110	2.5	12	4.0	111
-823KS	97	82	110	2.5	10	4.8	102
-104KS	98	100	110	2.5	9.4	5.7	93
-124KS	99	120	85	0.79	8.0	6.2	89
-154KS	100	150	85	0.79	8.0	6.3	89
-184KS	101	180	85	0.79	6.9	6.4	88
-224KS	102	220	85	0.79	6.1	7.4	82
-274KS	103	270	85	0.79	5.2	8.1	78
-334KS	104	330	100	0.79	4.6	8.8	75
-394KS	105	390	100	0.79	4.0	9.7	72
-474KS	106	470	100	0.79	3.6	10.0	69
-564KS	107	560	100	0.79	2.8	11.0	66
-684KS	108	680	100	0.79	2.3	12.0	64
-824KS	109	820	95	0.79	2.1	17.0	53
-105KS	110	1000	95	0.79	2.0	22.0	47
-125KS	111	1200	75	0.25	1.7	24.0	45
-155KS	112	1500	75	0.25	1.6	25.0	44
-185KS	113	1800	75	0.25	1.5	27.0	43
-225KS	114	2200	75	0.25	1.4	30.0	40
-275KS	115	2700	75	0.25	1.3	34.0	38
-335KS	116	3300	75	0.25	1.2	39.0	35
-395KS	117	3900	75	0.25	1.1	56.0	29
-475KS	118	4700	75	0.25	1.0	70.0	26
-565KS	119	5600	75	0.25	0.9	80.0	25
-685KS	120	6800	75	0.25	0.8	90.0	23
-825KS	121	8200	75	0.25	0.7	100.0	22
-106KS	122	10000	75	0.25	0.7	110.0	21

SERIES**1008R
1008****Shielded Surface Mount Inductors**

Actual Size

**Physical Parameters**

	Inches	Millimeters
A	0.095 to 0.115	2.41 to 2.92
B	0.085 to 0.105	2.16 to 2.66
C	0.075 to 0.095	1.91 to 2.41
D	0.010 to 0.030	0.26 to 0.76
E	0.040 to 0.060	1.02 to 1.52
F	0.060 (Ref. only)	1.52 (Ref. only)
G	0.045 (Ref. only)	1.14 (Ref. only)

Dimensions "A" and "C" are over terminals.

Weight Max. (Grams) 0.1**Operating Temperature Range** -55°C to +125°C**Current Rating at 90°C Ambient** 35°C Rise**Maximum Power Dissipation at 90°C**

Phenolic: 0.169 W

Ferrite: 0.208 W

Marking SMD; Dash number with tolerance letter; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 1008R-181J

SMD

181J

R 0703A

Packaging Tape & reel (8mm): 7" reel, 2000 pieces max.; 13" reel, 7000 pieces max.

Made In the U.S.A. Patent Protected

DASH NUMBER*	INDUCTANCE (μH)	TOLERANCE	TEST FREQUENCY (MHz)	Q MINIMUM	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
SERIES 1008 PHENOLIC CORE							
-018M	0.0018	±20%	40	50	2700	0.050	1562
-022M	0.0022	±20%	40	50	2700	0.050	1562
-027M	0.0027	±20%	40	50	2700	0.050	1562
-033M	0.0033	±20%	40	50	2700	0.050	1562
-039M	0.0039	±20%	40	50	2700	0.050	1562
-047M	0.0047	±20%	40	50	2700	0.050	1562
-056M	0.0056	±20%	40	50	2700	0.050	1562
-068M	0.0068	±20%	40	50	2700	0.050	1562
-082M	0.0082	±20%	40	50	2700	0.050	1562
-100K	0.010	±10%	40	50	2700	0.050	1562
-120K	0.012	±10%	40	50	2450	0.058	1450
-150K	0.015	±10%	40	50	2200	0.064	1381
-180K	0.018	±10%	40	50	2000	0.070	1320
-220K	0.022	±10%	35	50	1800	0.080	1235
-270K	0.027	±10%	35	50	1625	0.090	1164
-330K	0.033	±10%	30	50	1450	0.100	1105
-390K	0.039	±10%	30	50	1335	0.110	1053
-470K	0.047	±10%	30	50	1220	0.120	1008
-560K	0.056	±10%	25	50	1110	0.170	847
-680K	0.068	±10%	25	50	1000	0.180	823
-820K	0.082	±10%	25	50	915	0.190	801
-101K	0.100	±10%	15	25	550	0.230	728
SERIES 1008 FERRITE CORE							
-121K	0.12	±10%	40	25	750	0.100	1225
-151K	0.15	±10%	40	25	650	0.110	1168
-181K	0.18	±10%	40	25	550	0.120	1119
-221K	0.22	±10%	40	25	450	0.135	1055
-271K	0.27	±10%	40	25	375	0.150	1000
-331K	0.33	±10%	40	25	300	0.165	954
-391K	0.39	±10%	40	25	250	0.180	913
-471K	0.47	±10%	40	25	215	0.210	846
-561K	0.56	±10%	40	25	195	0.230	808
-681K	0.68	±10%	40	25	175	0.260	760
-821K	0.82	±10%	40	25	140	0.300	708
-102J	1.0	±5%	30	7.9	125	0.320	685
-122J	1.2	±5%	30	7.9	100	0.430	591
-152J	1.5	±5%	30	7.9	92	0.500	548
-182J	1.8	±5%	30	7.9	76	0.720	457
-222J	2.2	±5%	30	7.9	70	0.800	433
-272J	2.7	±5%	30	7.9	62	0.880	413
-332J	3.3	±5%	30	7.9	60	0.950	398
-392J	3.9	±5%	30	7.9	57	1.20	354
-472J	4.7	±5%	30	7.9	47	1.35	334
-562J	5.6	±5%	30	7.9	44	1.54	312
-682J	6.8	±5%	30	7.9	35	2.00	274
-822J	8.2	±5%	30	7.9	33	2.16	264
-103J	10	±5%	30	7.9	28	2.50	245
-123J	12	±5%	30	2.5	24	3.50	207
-153J	15	±5%	30	2.5	21	4.00	194
-183J	18	±5%	30	2.5	19	5.00	173
-223J	22	±5%	30	2.5	17	6.00	158
-273J	27	±5%	30	2.5	15	7.00	146
-333J	33	±5%	30	2.5	13	8.00	135
-393J	39	±5%	30	2.5	12	9.00	125
-473J	47	±5%	30	2.5	11	10.00	120

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #


For surface finish information,
refer to www.delevanfinishes.com

SERIES


HF1008R
HF1008



Unshielded Surface Mount Inductors



Actual Size



Physical Parameters

	Inches	Millimeters
A	0.095 to 0.115	2.41 to 2.92
B	0.085 to 0.105	2.16 to 2.66
C	0.075 to 0.095	1.91 to 2.41
D	0.010 to 0.030	0.26 to 0.76
E	0.040 to 0.060	1.02 to 1.52
F	0.060 (Ref. only)	1.52 (Ref. only)
G	0.045 (Ref. only)	1.14 (Ref. only)

Dimensions "A" and "C" are over terminals.

Weight Max. (Grams) 0.1

Operating Temperature Range -55°C to +125°C

Current Rating at 90°C Ambient 35°C Rise

Maximum Power Dissipation at 90°C

Non-magnetic: 0.169 W

Ferrite: 0.208 W

Note Consult factory for custom applications

Marking SMD; HF followed by dash number with tolerance letter; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: HF1008-472G

SMD
HF472G
0819B

Packaging Tape & reel (8mm): 7" reel, 2000 pieces max.; 13" reel, 7000 pieces max.

Made In the U.S.A. Patent Protected


DASH NUMBER*	INDUCTANCE (μH)	TOLERANCE	TEST FREQUENCY (MHz)	Q MINIMUM	SRF MINIMUM (MHz)	MAXIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
--------------	-----------------	-----------	----------------------	-----------	-------------------	---------------	------------------------------	-----------------------------

SERIES HF1008 NON-MAGNETIC CORE								
-047M	4.7	±20%	40	50	>3000	0.070	1320	
-082M	8.2	±20%	40	50	>3000	0.075	1275	
-100M	10.0	±20%	30	50	>3000	0.080	1235	
-120M	12.0	±20%	30	50	2700	0.105	1075	
-150M	15.0	±20%	30	50	2400	0.110	1053	
-180M	18.0	±20%	30	50	2250	0.130	965	
-220M	22.0	±20%	30	50	2000	0.135	950	
-270M	27.0	±20%	30	50	1800	0.140	930	
-330M	33.0	±20%	30	50	1600	0.150	900	
-390M	39.0	±20%	30	50	1500	0.160	870	
-470M	47.0	±20%	30	50	1350	0.170	847	
-560K	56.0	±10%	20	50	1200	0.370	570	
-680K	68.0	±10%	20	50	1050	0.400	550	
-820K	82.0	±10%	15	50	1000	0.800	390	
-101K	100	±10%	15	25	900	0.850	375	
SERIES HF1008 FERRITE CORE								
-121K	120	±10%	30	25	850	0.910	405	
-151K	150	±10%	30	25	800	0.950	395	
-181K	180	±10%	30	25	700	1.05	375	
-221K	220	±10%	30	25	600	1.15	360	
-271K	270	±10%	30	25	550	1.25	345	
-331K	330	±10%	30	25	500	1.35	330	
-391K	390	±10%	30	25	465	1.45	320	
-471K	470	±10%	30	25	425	1.55	310	
-561K	560	±10%	30	25	415	1.65	300	
-621K	620	±10%	30	25	375	1.75	290	
-681K	680	±10%	30	25	340	1.85	280	
-751K	750	±10%	30	25	330	1.95	275	
-821K	820	±10%	30	25	325	2.00	273	
-911K	910	±10%	30	25	305	2.05	270	
-102K	1000	±10%	30	25	290	1.40	325	
-122K	1200	±10%	30	7.9	200	1.45	320	
-152K	1500	±10%	30	7.9	165	1.50	315	
-182K	1800	±10%	30	7.9	150	1.60	305	
-222K	2200	±10%	30	7.9	120	1.65	300	
-272K	2700	±10%	30	7.9	110	1.80	285	
-332K	3300	±10%	30	7.9	60	1.90	280	
-392K	3900	±10%	30	7.9	50	1.95	275	
-472K	4700	±10%	30	7.9	40	2.00	273	


Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

SERIES**S1008R
S1008****Shielded Surface Mount Inductors**

Actual Size

**Physical Parameters**

	Inches	Millimeters
A	0.095 to 0.115	2.41 to 2.92
B	0.085 to 0.105	2.16 to 2.66
C	0.075 to 0.095	1.91 to 2.41
D	0.010 to 0.030	0.26 to 0.76
E	0.040 to 0.060	1.02 to 1.52
F	0.060 (Ref. only)	1.52 (Ref. only)
G	0.045 (Ref. only)	1.14 (Ref. only)

Dimensions "A" and "C" are over terminals.

Weight Max. (Grams) 0.1**Operating Temperature Range** -55°C to +125°C**Current Rating at 90°C Ambient** 35°C Rise**Maximum Power Dissipation at 90°C** 0.157 W

Marking SMD; S followed by dash number with tolerance letter; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: S1008-471H

SMD

S471H

0912A

Packaging Tape & reel (8mm): 7" reel, 2000 pieces max.;
13" reel, 7000 pieces max.

Made In the U.S.A. Patent Protected

DASH NUMBER*	INDUCTANCE (μH) ±10%	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
SERIES S1008 FERRITE CORE						
-101K	0.10	40	25	383	0.09	1120
-121K	0.12	40	25	368	0.10	1060
-151K	0.15	40	25	353	0.11	1015
-181K	0.18	40	25	338	0.12	970
-221K	0.22	40	25	323	0.13	930
-271K	0.27	40	25	308	0.14	900
-331K	0.33	40	25	293	0.15	865
-391K	0.39	40	25	278	0.16	840
-471K	0.47	40	25	255	0.17	815
-561K	0.56	40	25	232	0.18	790
-621K	0.62	40	25	200	0.19	770
-681K	0.68	40	25	186	0.20	750
-751K	0.75	40	25	163	0.21	735
-821K	0.82	40	25	140	0.22	715
-911K	0.91	40	25	130	0.24	685
-102K	1.0	30	7.9	120	0.25	670
-122K	1.2	30	7.9	95	0.29	625
-152K	1.5	30	7.9	72	0.42	545
-182K	1.8	30	7.9	66	0.60	435
-222K	2.2	30	7.9	60	0.80	375
-272K	2.7	30	7.9	55	0.85	365
-332K	3.3	30	7.9	50	0.90	355
-392K	3.9	30	7.9	45	1.00	335
-472K	4.7	30	7.9	42	1.20	305
-562K	5.6	30	7.9	40	1.30	295
-682K	6.8	30	7.9	38	1.80	250
-822K	8.2	30	7.9	32	1.90	240
-103K	10	30	7.9	29	2.10	230
-123K	12	30	2.5	28	3.50	220
-153K	15	30	2.5	25	4.00	210
-183K	18	30	2.5	21	5.00	200
-223K	22	30	2.5	18	6.00	170
-273K	27	30	2.5	15	7.00	160
-333K	33	30	2.5	12	7.40	125
-393K	39	30	2.5	10	8.00	120
-473K	47	30	2.5	8	9.00	110

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com


SERIES

4302R 4302




Temperature Stable (1008 size) Surface Mount Inductors

INDUCTANCE (μ H) $\pm 10\%$
DASH NUMBER*
TEST FREQUENCY (MHz)
Q MINIMUM
SRF MINIMUM (MHz)
MAXIMUM (MHz)
DC RESISTANCE
MAXIMUM (OHMS)
CURRENT RATING
MAXIMUM (mA)
RF Inductors



Actual Size



Temperature Stable for critical conditions

Physical Parameters

	Inches	Millimeters
A	0.095 to 0.115	2.41 to 2.92
B	0.085 to 0.105	2.16 to 2.66
C	0.075 to 0.095	1.91 to 2.41
D	0.010 to 0.030	0.26 to 0.76
E	0.040 to 0.060	1.02 to 1.52
F	0.060 (Ref. only)	1.52 (Ref. only)
G	0.045 (Ref. only)	1.14 (Ref. only)

Dimensions "A" and "C" are over terminals.

Weight Max. (Grams) 0.1

Operating Temperature Range -55°C to $+125^{\circ}\text{C}$

Current Rating at 90°C Ambient 35°C Rise

Maximum Power Dissipation at 90°C 0.208 W

Note For applications requiring improved characteristics over typical ferrite core inductors of the same size. See 1008 Series for values lower than $0.12\mu\text{H}$.

Marking SMD; dash number with tolerance letter; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 4302-272K

SMD
272K
0422B

Packaging Tape & reel (8mm): 7" reel, 2000 pieces max.;
13" reel, 7000 pieces max.

Made In the U.S.A. Patent Protected

SERIES 4302 POWDERED IRON CORE


-121K	0.12	40	25.0	400	0.130	1075
-151K	0.15	40	25.0	375	0.150	1000
-181K	0.18	40	25.0	325	0.165	955
-221K	0.22	40	25.0	270	0.175	925
-271K	0.27	40	25.0	240	0.190	890
-331K	0.33	40	25.0	180	0.200	865
-391K	0.39	40	25.0	160	0.220	825
-471K	0.47	40	25.0	130	0.240	790
-561K	0.56	40	25.0	115	0.295	710
-681K	0.68	40	25.0	105	0.320	685
-821K	0.82	40	25.0	95	0.510	540
-102K	1.0	30	7.9	80	0.550	520
-122K	1.2	30	7.9	75	0.600	500
-152K	1.5	30	7.9	70	0.730	455
-182K	1.8	30	7.9	60	0.800	430
-222K	2.2	30	7.9	50	1.25	345
-272K	2.7	30	7.9	45	1.60	305
-332K	3.3	30	7.9	40	1.85	285
-392K	3.9	30	7.9	35	2.10	265
-472K	4.7	30	7.9	30	2.30	255
-562K	5.6	30	7.9	26	3.00	225
-682K	6.8	30	7.9	22	3.50	205
-822K	8.2	30	7.9	20	4.00	195
-103K	10.0	30	7.9	18	4.50	180
-123K	12.0	20	2.5	16	7.50	140
-153K	15.0	20	2.5	14	9.00	125
-183K	18.0	20	2.5	12	11.00	115
-223K	22.0	20	2.5	11	12.00	110
-273K	27.0	20	2.5	10	13.00	105


Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #


For surface finish information, refer to www.delevanfinishes.com

For more detailed graphs, contact factory



SERIES**1210R**
1210**Surface Mount Inductors****RF Inductors**

Actual Size

**Physical Parameters**

	Inches	Millimeters
A	0.118 to 0.138	3.00 to 3.51
B	0.085 to 0.105	2.16 to 2.67
C	0.081 to 0.101	2.06 to 2.57
D	0.016 (Min.)	0.41 (Min.)
E	0.041 to 0.061	1.04 to 1.55
F	0.070 (Ref. only)	1.78 (Ref. only)
G	0.054 (Ref. only)	1.37 (Ref. only)

Dimensions "A" and "C" are over terminals

Weight Max. (Grams) 0.1**Operating Temperature Range** -55°C to +125°C**Current Rating at 90°C Ambient** 35°C Rise**Maximum Power Dissipation at 90°C Ambient**

Phenolic: 0.168 W

Iron: 0.287 W

Ferrite: 0.287 W

****Note** Self Resonant Frequency (SRF) values are calculated and for reference only.**Marking** SMD; dash number with tolerance letter; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 1210-018M

SMD
018M
0642C**Packaging** Tape & reel (8mm): 7" reel, 2000 pieces max.; 13" reel, 7000 pieces max.**Made in the U.S.A. Patent Protected**


Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #


For surface finish information,
refer to www.delevanfinishes.com

DASH NUMBER*	INDUCTANCE (μH)	TOLERANCE	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
SERIES 1210 PHENOLIC CORE							
-018M	0.0018	± 20%	40	50.0	2700**	0.050	1562
-022M	0.0022	± 20%	40	50.0	2700**	0.050	1562
-027M	0.0027	± 20%	40	50.0	2700**	0.050	1562
-033M	0.0033	± 20%	40	50.0	2700**	0.050	1562
-039M	0.0039	± 20%	40	50.0	2700**	0.050	1562
-047M	0.0047	± 20%	40	50.0	2700**	0.050	1562
-056M	0.0056	± 20%	40	50.0	2700**	0.050	1562
-068M	0.0068	± 20%	40	50.0	2700**	0.050	1562
-082M	0.0082	± 20%	40	50.0	2700**	0.050	1562
-100K	0.010	± 10%	30	50.0	2000**	0.13	966
-120K	0.012	± 10%	30	50.0	1850**	0.14	931
-150K	0.015	± 10%	30	50.0	1700**	0.16	871
-180K	0.018	± 10%	30	50.0	1550**	0.18	821
-220K	0.022	± 10%	30	50.0	1300**	0.20	779
-270K	0.027	± 10%	30	50.0	1150**	0.22	743
-330K	0.033	± 10%	30	50.0	1000**	0.24	711
-390K	0.039	± 10%	30	50.0	900**	0.27	670
-470K	0.047	± 10%	30	50.0	800**	0.30	636
-560K	0.056	± 10%	30	50.0	750**	0.33	606
-680K	0.068	± 10%	30	50.0	700**	0.36	580
-820K	0.082	± 10%	30	50.0	625**	0.40	551
SERIES 1210 IRON CORE							
-101K	0.10	± 10%	30	25.0	550	0.20	1018
-121K	0.12	± 10%	30	25.0	500	0.22	971
-151K	0.15	± 10%	30	25.0	450	0.25	910
-181K	0.18	± 10%	30	25.0	400	0.28	860
-221K	0.22	± 10%	30	25.0	350	0.32	805
-271K	0.27	± 10%	30	25.0	320	0.36	759
-331K	0.33	± 10%	30	25.0	300	0.40	720
-391K	0.39	± 10%	30	25.0	250	0.45	679
-471K	0.47	± 10%	30	25.0	220	0.50	644
-561K	0.56	± 10%	30	25.0	180	0.55	614
-681K	0.68	± 10%	30	25.0	160	0.60	588
-821K	0.82	± 10%	30	25.0	140	0.67	556
SERIES 1210 FERRITE CORE							
-102J	1.0	± 5%	30	7.9	120	0.70	515
-122J	1.2	± 5%	30	7.9	100	0.75	497
-152J	1.5	± 5%	30	7.9	85	0.85	467
-182J	1.8	± 5%	30	7.9	75	0.90	454
-222J	2.2	± 5%	30	7.9	70	1.0	431
-272J	2.7	± 5%	30	7.9	65	1.1	411
-332J	3.3	± 5%	30	7.9	58	1.2	393
-392J	3.9	± 5%	30	7.9	50	1.3	378
-472J	4.7	± 5%	30	7.9	45	1.5	352
-562J	5.6	± 5%	30	7.9	42	1.6	341
-682J	6.8	± 5%	30	7.9	40	1.8	321
-822J	8.2	± 5%	30	7.9	35	2.0	305
-103J	10	± 5%	30	7.9	30	2.1	297
-123J	12	± 5%	30	2.5	28	2.5	272
-153J	15	± 5%	30	2.5	25	2.8	257
-183J	18	± 5%	30	2.5	23	3.3	237
-223J	22	± 5%	30	2.5	20	3.7	224
-273J	27	± 5%	30	2.5	18	5.0	193
-333J	33	± 5%	30	2.5	15	5.6	182
-393J	39	± 5%	30	2.5	14	6.4	170
-473J	47	± 5%	30	2.5	13	7.0	163
-563J	56	± 5%	30	2.5	11	8.0	152
-683J	68	± 5%	30	2.5	10	9.0	144
-823J	82	± 5%	30	2.5	9	10.0	136
-104J	100	± 5%	30	2.5	8	13.0	120

Shielded Surface Mount Inductors



Actual Size



Physical Parameters

	Inches	Millimeters
A	0.118 to 0.138	3.00 to 3.51
B	0.085 to 0.105	2.16 to 2.66
C	0.081 to 0.101	2.06 to 2.57
D	0.016 Min.	0.41 Min.
E	0.041 to .061	1.04 to 1.55
F	0.070 (Ref. only)	1.78 (Ref. only)
G	0.054 (Ref. only)	1.37 (Ref. only)

Dimensions "A" and "C" are over terminals.

Weight Max. (Grams) 0.1

Operating Temperature Range -55°C to +125°C

Current Rating at 90°C Ambient 35°C Rise

Maximum Power Dissipation at 90°C

Iron: 0.266 W

Ferrite: 0.224 W

Marking SMD; S followed by dash number with tolerance letter; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: S1210R-471K

SMD
S471K
R 0912B

Packaging Tape & reel (8mm): 7" reel, 2000 pieces max.; 13" reel, 7000 pieces max.

Made In the U.S.A. Patent Protected


Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com

RF Inductor							
DASH NUMBER*	INDUCTANCE (μH) ±10%	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	MAXIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
SERIES S1210 IRON CORE							
-101K	0.10	40	25	375	0.15	1131	
-121K	0.12	40	25	350	0.17	1062	
-151K	0.15	40	25	330	0.20	979	
-181K	0.18	40	25	310	0.22	934	
-221K	0.22	40	25	300	0.25	876	
-271K	0.27	40	25	290	0.30	800	
-331K	0.33	40	25	255	0.35	740	
-391K	0.39	40	25	230	0.40	692	
-471K	0.47	40	25	220	0.45	653	
-561K	0.56	40	25	200	0.50	619	
-681K	0.68	40	25	180	0.55	590	
-821K	0.82	40	25	170	0.60	565	
SERIES S1210 FERRITE CORE							
-102K	1.0	40	7.9	140	0.40	635	
-122K	1.2	40	7.9	120	0.49	574	
-152K	1.5	40	7.9	110	0.57	532	
-182K	1.8	40	7.9	95	0.65	498	
-222K	2.2	40	7.9	80	0.73	470	
-272K	2.7	40	7.9	70	0.75	464	
-332K	3.3	40	7.9	45	0.80	449	
-392K	3.9	40	7.9	42	0.83	441	
-472K	4.7	40	7.9	40	1.00	402	
-562K	5.6	40	7.9	38	1.30	352	
-682K	6.8	40	7.9	35	1.50	328	
-822K	8.2	40	7.9	32	1.70	308	
-103K	10.0	40	2.5	28	1.90	291	
-123K	12.0	40	2.5	25	2.10	277	
-153K	15.0	40	2.5	23	2.50	254	
-183K	18.0	40	2.5	21	2.80	240	
-223K	22.0	40	2.5	19	3.00	232	
-273K	27.0	40	2.5	16	4.00	201	
-333K	33.0	40	2.5	14	4.50	189	
-393K	39.0	40	2.5	12	5.00	179	
-473K	47.0	40	2.5	10	5.50	171	
-563K	56.0	40	2.5	8	6.30	160	
-683K	68.0	40	2.5	8	7.00	152	
-823K	82.0	40	2.5	8	8.50	137	
-104K	100.0	40	2.5	8	10.00	127	

For more detailed graphs, contact factory




SERIES**4232R**
4232

Open Construction Wirewound Surface Mount Inductors



Actual Size



Temperature Stable for critical conditions

Physical Parameters

	Inches	Millimeters
A	0.118 to 0.138	3.00 to 3.51
B	0.085 to 0.105	2.16 to 2.67
C	0.081 to 0.101	2.06 to 2.57
D	0.016 Min.	0.41 Min.
E	0.041 to 0.061	1.04 to 1.55
F	0.070 (Ref. only)	1.78 (Ref. only)
G	0.054 (Ref. only)	1.37 (Ref. only)

Dimensions "A" and "C" are over terminals.

Weight Max. (Grams) 0.1

Operating Temperature -55°C to +125°C

Current Rating at 90°C Ambient 35°C Rise

Maximum Power Dissipation at 90°C Ambient

Phenolic: 0.168 W

Iron: 0.287 W

Note For applications requiring improved characteristics over typical ferrite core inductors of the same size, see 1210 Series for values lower than 0.10μH.

Marking SMD; dash number with tolerance letter; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 4232R-562F

SMD

562F

R 0909A

Packaging Tape & reel (8mm): 7" reel, 2000 pieces max.; 13" reel, 7000 pieces max.

Made In the U.S.A. Patent Protected

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com

INDUCTANCE (μH) ±10%
TEST FREQUENCY (MHz)
SRF MINIMUM (MHz)
DC RESISTANCE MAXIMUM (OHMS)
CURRENT RATING MAXIMUM (mA)
RF Inductors


SERIES 4232 PHENOLIC CORE


-101K	0.10	20	25	250	0.45	519
-121K	0.12	20	25	220	0.50	493
-151K	0.15	20	25	180	0.54	474
-181K	0.18	19	25	165	0.61	446
-221K	0.22	19	25	135	0.68	442
-271K	0.27	17	25	120	0.72	410
-331K	0.33	17	25	200	0.76	400
-391K	0.39	17	25	180	0.84	380
-471K	0.47	17	25	140	0.92	363
-561K	0.56	15	25	120	1.06	338
-681K	0.68	15	25	110	1.25	312
-821K	0.82	10	25	100	1.40	294
-102K	1.0	10	25	90	1.50	284

SERIES 4232 IRON CORE

-122K	1.2	30	7.9	83	0.90	480
-152K	1.5	30	7.9	75	1.00	455
-182K	1.8	30	7.9	65	1.10	434
-222K	2.2	30	7.9	55	1.20	416
-272K	2.7	30	7.9	50	1.25	407
-332K	3.3	30	7.9	47	1.30	399
-392K	3.9	30	7.9	45	1.40	385
-472K	4.7	30	7.9	40	1.80	339
-562K	5.6	30	7.9	36	2.00	322
-682K	6.8	30	7.9	22	2.40	294
-822K	8.2	30	7.9	21	3.00	263
-103K	10.0	30	7.9	20	4.30	220
-123K	12.0	30	2.5	18	5.80	189
-153K	15.0	30	2.5	17	6.50	179
-183K	18.0	30	2.5	16	7.20	170
-223K	22.0	30	2.5	15	8.00	161
-273K	27.0	30	2.5	14	8.80	153
-333K	33.0	30	2.5	13	9.20	150
-393K	39.0	30	2.5	12	10.8	139
-473K	47.0	30	2.5	10	11.4	135

For more detailed graphs, contact factory



SERIES**1330R
1330**RoHS
CompliantTraditional
First Quality**Unshielded Surface Mount Inductors****Physical Parameters**

	Inches	Millimeters
A	0.300 to 0.325	7.62 to 8.26
B	0.105 to 0.125	2.67 to 3.18
C	0.125 to 0.145	3.18 to 3.68
D	0.020 Min.	0.508 Min.
E	0.040 to 0.060	1.02 to 1.52
F	0.190 (Ref. only)	4.83 (Ref. only)
G	0.070 (Ref. only)	1.78 (Ref. only)

Weight Max (Grams) 0.30**Operating Temperature Range**

Phenolic: -55°C to +125°C

Iron and Ferrite: -55°C to +105°C

Current Rating at 90°C Ambient

Phenolic: 35°C Rise

Iron and Ferrite: 15°C Rise

Maximum Power Dissipation at 90°C Ambient

Phenolic: 0.210 W

Iron: 0.090 W

Ferrite: 0.073 W

Marking API/SMD; inductance with units and tolerance;
date code (YYWWL). Note: An R before the date code
indicates a RoHS component.

Example: 1330-42K

API/SMD

8.2uH±10%

0218A

Packaging Tape & reel (16mm): 7" reel, 500 pieces max.;
13" reel, 2200 pieces max.

Made In the U.S.A. Patent Protected

INDUCTANCE (uH) ±10%
TEST FREQUENCY (MHz)
Q MINIMUM
SRF MINIMUM (MHz)
MAXIMUM (MHz)
DC RESISTANCE
MAXIMUM (OHMS)
CURRENT RATING
MAXIMUM (mA)
RF Inductors

SERIES 1330 PHENOLIC CORE

-94K	0.10	40	25.0	680.0	0.08	1380
-96K	0.12	40	25.0	640.0	0.09	1300
-00K	0.15	38	25.0	600.0	0.10	1230
-02K	0.18	35	25.0	550.0	0.12	1120
-04K	0.22	33	25.0	510.0	0.14	1040
-06K	0.27	33	25.0	430.0	0.16	975
-08K	0.33	30	25.0	410.0	0.22	830
-10K	0.39	30	25.0	365.0	0.30	710
-12K	0.47	30	25.0	330.0	0.35	660
-14K	0.56	30	25.0	300.0	0.50	550
-16K	0.68	28	25.0	275.0	0.60	500
-18K	0.82	28	25.0	250.0	0.85	420
-20K	1.00	25	25.0	230.0	1.00	390

SERIES 1330 IRON CORE

-22K	1.20	25	7.9	150.0	0.18	620
-24K	1.50	28	7.9	140.0	0.22	560
-26K	1.80	30	7.9	125.0	0.30	480
-28K	2.20	30	7.9	115.0	0.40	415
-30K	2.70	37	7.9	100.0	0.55	355
-32K	3.30	45	7.9	90.0	0.85	285
-34K	3.90	45	7.9	80.0	1.00	263
-36K	4.70	45	7.9	75.0	1.20	239
-38K	5.60	50	7.9	65.0	1.80	195
-40K	6.80	50	7.9	60.0	2.00	185
-42K	8.20	55	7.9	55.0	2.70	160
-44K	10.00	55	7.9	50.0	3.30	144
-46K	12.0	45	2.5	40.0	2.70	160
-48K	15.0	45	2.5	35.0	2.80	157
-50K	18.0	45	2.5	30.0	3.10	149
-52K	22.0	45	2.5	25.0	3.30	144
-54K	27.0	45	2.5	20.0	3.50	140

SERIES 1330 FERRITE CORE

-56K	33.0	35	2.5	24.0	3.40	130
-58K	39.0	35	2.5	22.0	3.60	125
-60K	47.0	35	2.5	20.0	4.50	110
-62K	56.0	35	2.5	18.0	5.70	100
-64K	68.0	35	2.5	15.0	6.70	92
-66K	82.0	35	2.5	14.0	7.30	88
-68K	100.0	35	2.5	13.0	8.00	84
-70K	120.0	30	0.79	12.0	13.00	66
-72K	150.0	30	0.79	11.0	15.00	61
-74K	180.0	30	0.79	10.0	17.00	57
-76K	220.0	30	0.79	9.0	21.00	52
-78K	270.0	30	0.79	8.0	25.00	47
-80K	330.0	30	0.79	7.0	28.00	45
-82K	390.0	30	0.79	6.5	35.00	40
-84K	470.0	30	0.79	6.0	42.00	36
-86K	560.0	30	0.79	5.0	46.00	35
-88K	680.0	30	0.79	4.2	60.00	30
-90K	820.0	30	0.79	3.8	65.00	29
-92K	1000.0	30	0.79	3.4	72.00	28


Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

SERIES**MIL1330**

Unshielded Surface Mount Inductors



Actual Size

Military QPL Approval

M83446/31 Phenolic Core

M83446/32 Iron Core

M83446/33 Ferrite Core

† **Ordering Note** Military parts must be ordered to the M83446/ part number

Physical Parameters

	Inches	Millimeters
A	0.300 to 0.325	7.62 to 8.26
B	0.105 to 0.125	2.67 to 3.18
C	0.125 to 0.145	3.18 to 3.68
D	0.020 Min.	0.508 Min.
E	0.040 to 0.060	1.02 to 1.52
F	0.190 (Ref. only)	4.83 (Ref. only)
G	0.070 (Ref. only)	1.78 (Ref. only)

Weight Max (Grams) 0.30

Operating Temperature Range

Phenolic: -55°C to +125°C

Iron and Ferrite: -55°C to +105°C

Current Rating at 90°C Ambient

Phenolic: 35°C Rise

Iron and Ferrite: 15°C Rise

Maximum Power Dissipation at 90°C Ambient

Phenolic: 0.210 W

Iron: 0.090 W

Ferrite: 0.073 W

Marking API/SMD; inductance with units and tolerance; date code (YYWWL) followed by an M.

Example: 1330-42K

API/SMD

8.2uH±10%

0601A M

Packaging Tape & reel (16mm): 7" reel, 500 pieces max.; 13" reel, 2200 pieces max.

Made In the U.S.A. Patent Protected

INDUCTANCE (uH) ±10%
TEST FREQUENCY (MHz)
Q MINIMUM
SRF MINIMUM (MHz)
MAXIMUM (MHz)
DC RESISTANCE MAXIMUM (OHMS)
CURRENT RATING MAXIMUM (mA)

RF Inductors

M83446/31 – SERIES MIL1330 PHENOLIC CORE

-94K	01F	0.10	40	25.0	680.0	0.08	1380
-96K	02F	0.12	40	25.0	640.0	0.09	1300
-00K	03F	0.15	38	25.0	600.0	0.10	1230
-02K	04F	0.18	35	25.0	550.0	0.12	1120
-04K	05F	0.22	33	25.0	510.0	0.14	1040
-06K	06F	0.27	33	25.0	430.0	0.16	975
-08K	07F	0.33	30	25.0	410.0	0.22	830
-10K	08F	0.39	30	25.0	365.0	0.30	710
-12K	09F	0.47	30	25.0	330.0	0.35	660
-14K	10F	0.56	30	25.0	300.0	0.50	550
-16K	11F	0.68	28	25.0	275.0	0.60	500
-18K	12F	0.82	28	25.0	250.0	0.85	420
-20K	13F	1.00	25	25.0	230.0	1.00	390

M83446/32 – SERIES MIL1330 IRON CORE

-22K	01F	1.20	25	7.9	150.0	0.18	620
-24K	02F	1.50	28	7.9	140.0	0.22	560
-26K	03F	1.80	30	7.9	125.0	0.30	480
-28K	04F	2.20	30	7.9	115.0	0.40	415
-30K	05F	2.70	37	7.9	100.0	0.55	355
-32K	06F	3.30	45	7.9	90.0	0.85	285
-34K	07F	3.90	45	7.9	80.0	1.00	263
-36K	08F	4.70	45	7.9	75.0	1.20	239
-38K	09F	5.60	50	7.9	65.0	1.80	195
-40K	10F	6.80	50	7.9	60.0	2.00	185
-42K	11F	8.20	55	7.9	55.0	2.70	160
-44K	12F	10.00	55	7.9	50.0	3.30	144
-46K	13F	12.0	45	2.5	40.0	2.70	160
-48K	14F	15.0	45	2.5	35.0	2.80	157
-50K	15F	18.0	45	2.5	30.0	3.10	149
-52K	16F	22.0	45	2.5	25.0	3.30	144
-54K	17F	27.0	45	2.5	20.0	3.50	140


M83446/33 – SERIES MIL1330 FERRITE CORE

-56K	01F	33.0	35	2.5	24.0	3.40	130
-58K	02F	39.0	35	2.5	22.0	3.60	125
-60K	03F	47.0	35	2.5	20.0	4.50	110
-62K	04F	56.0	35	2.5	18.0	5.70	100
-64K	05F	68.0	35	2.5	15.0	6.70	92
-66K	06F	82.0	35	2.5	14.0	7.30	88
-68K	07F	100.0	35	2.5	13.0	8.00	84
-70K	08F	120.0	30	0.79	12.0	13.00	66
-72K	09F	150.0	30	0.79	11.0	15.00	61
-74K	10F	180.0	30	0.79	10.0	17.00	57
-76K	11F	220.0	30	0.79	9.0	21.00	52
-78K	12F	270.0	30	0.79	8.0	25.00	47
-80K	13F	330.0	30	0.79	7.0	28.00	45
-82K	14F	390.0	30	0.79	6.5	35.00	40
-84K	15F	470.0	30	0.79	6.0	42.00	36
-86K	16F	560.0	30	0.79	5.0	46.00	35
-88K	17F	680.0	30	0.79	4.2	60.00	30
-90K	18F	820.0	30	0.79	3.8	65.00	29
-92K	19F	1000.0	30	0.79	3.4	72.00	28

Parts listed above are QPL/MIL qualified

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

SERIES**1331R
1331****Shielded Surface Mount Inductors****Physical Parameters**

	Inches	Millimeters
A	0.300 to 0.325	7.62 to 8.26
B	0.105 to 0.125	2.67 to 3.18
C	0.125 to 0.145	3.18 to 3.68
D	0.020 Min.	0.508 Min.
E	0.040 to 0.060	1.02 to 1.52
F	0.190 (Ref. only)	4.83 (Ref. only)
G	0.070 (Ref. only)	1.78 (Ref. only)

Dimensions "A" and "C" are over terminations

Weight Max (Grams) 0.30**Operating Temperature Range** -55°C to +105°C**Current Rating at 90°C Ambient** 15°C Rise**Maximum Power Dissipation at 90°C** 0.585 W**Incremental Current** Current level which causes a maximum of 5% decrease in inductance.**Coupling** 3% Max.****Note** Self Resonant Frequency (SRF) values for -101K to -331K are calculated and for reference only.**Marking** API/SMD; inductance with units and tolerance followed by an S; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 1331R-683K

API/SMD

68uH±10%S

R 0719B

Packaging Tape & reel (16mm): 7" reel, 500 pieces max.; 13" reel, 2200 pieces max.**Made In the U.S.A. Patent Protected**

INDUCTANCE (uH) ±10%
DASH NUMBER*
TEST FREQUENCY (MHz)
Q MINIMUM
SRF MINIMUM (MHz)
DC RESISTANCE MAXIMUM (OHMS)
CURRENT RATING MAXIMUM (mA)
INCREMENTAL CURRENT (mA)

SERIES 1331 IRON CORE - IRON SLEEVE

-101K	0.10	45	25.0	490.0**	0.10	670	670
-121K	0.12	45	25.0	430.0**	0.11	635	635
-151K	0.15	45	25.0	415.0**	0.12	610	610
-181K	0.18	45	25.0	375.0**	0.13	585	585
-221K	0.22	45	25.0	330.0**	0.15	545	545
-271K	0.27	45	25.0	300.0**	0.16	530	530
-331K	0.33	44	25.0	260.0**	0.18	495	495
-391K	0.39	42	25.0	230.0	0.19	485	485
-471K	0.47	41	25.0	220.0	0.21	460	460
-561K	0.56	41	25.0	210.0	0.23	440	440
-681K	0.68	39	25.0	180.0	0.24	430	430
-821K	0.82	38	25.0	165.0	0.27	405	405
-102K	1.00	37	25.0	150.0	0.30	385	385
-122K	1.20	40	7.9	130.0	0.73	247	247
-152K	1.50	41	7.9	115.0	0.86	228	228
-182K	1.80	43	7.9	105.0	0.95	217	217
-222K	2.20	45	7.9	95.0	1.10	202	202
-272K	2.70	48	7.9	90.0	1.20	193	193
-332K	3.30	49	7.9	80.0	1.30	185	185
-392K	3.90	50	7.9	75.0	1.50	173	173
-472K	4.70	50	7.9	70.0	2.40	136	136
-562K	5.60	50	7.9	60.0	2.90	124	124
-682K	6.80	50	7.9	55.0	3.20	118	118
-822K	8.20	50	7.9	53.0	3.60	111	111
-103K	10.0	50	7.9	50.0	4.00	106	106

SERIES 1331 IRON CORE - FERRITE SLEEVE

-123K	12.0	36	2.5	35.0	3.00	122	122
-153K	15.0	38	2.5	30.0	3.40	115	115
-183K	18.0	40	2.5	26.0	3.80	108	108
-223K	22.0	40	2.5	24.0	4.90	96	96
-273K	27.0	40	2.5	21.0	5.80	88	88
-333K	33.0	41	2.5	20.0	6.50	83	83
-393K	39.0	42	2.5	19.0	7.90	75	75
-473K	47.0	44	2.5	16.0	9.30	69	69
-563K	56.0	44	2.5	15.0	11.0	64	64
-683K	68.0	45	2.5	13.0	12.0	61	61
-823K	82.0	45	2.5	11.0	13.0	59	59
-104K	100.0	40	2.5	10.5	16.8	51	51

SERIES 1331 FERRITE CORE - FERRITE SLEEVE

-124K	120.0	31	0.79	13.0	5.80	88	27
-154K	150.0	33	0.79	12.0	7.90	75	24
-184K	180.0	33	0.79	11.0	9.40	69	22
-224K	220.0	35	0.79	10.0	11.0	64	20
-274K	270.0	35	0.79	9.0	12.0	61	18
-334K	330.0	35	0.79	8.0	16.0	53	16
-394K	390.0	35	0.79	7.8	21.0	46	14
-474K	470.0	35	0.79	7.5	24.0	43	13
-564K	560.0	35	0.79	7.0	28.0	40	12


Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

SERIES**MIL1331**

Shielded Surface Mount Inductors



Actual Size

Military QPL Approval

M83446/34 Iron Core/Iron Sleeve

M83446/34 Iron Core/Ferrite Sleeve

M83446/35 Ferrite Core/Ferrite Sleeve

† **Ordering Note** Military parts must be ordered to the M83446/ part number

Physical Parameters

	Inches	Millimeters
A	0.300 to 0.325	7.62 to 8.26
B	0.105 to 0.125	2.67 to 3.18
C	0.125 to 0.145	3.18 to 3.68
D	0.020 Min.	0.508 Min.
E	0.040 to 0.060	1.02 to 1.52
F	0.190 (Ref. only)	4.83 (Ref. only)
G	0.070 (Ref. only)	1.78 (Ref. only)

Dimensions "A" and "C" are over terminations

Weight Max (Grams) 0.30**Operating Temperature Range** -55°C to +105°C**Current Rating at 90°C Ambient** 15°C Rise**Maximum Power Dissipation at 90°C** 0.585 W

Incremental Current Current level which causes a maximum of 5% decrease in inductance.

Coupling 3% Max.

****Note** Self Resonant Frequency (SRF) values for -101K to -331K are calculated and for reference only.

Marking API/SMD; inductance with units and tolerance followed by an S; date code (YYWWL) followed by an M.
Example: MIL1331-683K

API/SMD
68uH±10%S
0701A M

INDUCTANCE (uH) ±10%
MIL DASH #
DASH NUMBER*
TEST FREQUENCY (MHz)
Q MINIMUM
SRF MINIMUM (MHz)
DC RESISTANCE MAXIMUM (OHMS)
CURRENT RATING MAXIMUM (mA)
INCREMENTAL CURRENT (mA)

RF Inductors

SERIES MIL1331 IRON CORE - IRON SLEEVE

-101K	01F	0.10	45	25.0	490.0**	670	0.10	670
-121K	02F	0.12	45	25.0	430.0**	635	0.11	635
-151K	03F	0.15	45	25.0	415.0**	610	0.12	610
-181K	04F	0.18	45	25.0	375.0**	585	0.13	585
-221K	05F	0.22	45	25.0	330.0**	545	0.15	545
-271K	06F	0.27	45	25.0	300.0**	530	0.16	530
-331K	07F	0.33	44	25.0	260.0**	495	0.18	495
-391K	08F	0.39	42	25.0	230.0	485	0.19	485
-471K	09F	0.47	41	25.0	220.0	460	0.21	460
-561K	10F	0.56	41	25.0	210.0	440	0.23	440
-681K	11F	0.68	39	25.0	180.0	430	0.24	430
-821K	12F	0.82	38	25.0	165.0	405	0.27	405
-102K	13F	1.00	37	25.0	150.0	385	0.30	385
-122K	14F	1.20	40	7.9	130.0	247	0.73	247
-152K	15F	1.50	41	7.9	115.0	228	0.86	228
-182K	16F	1.80	43	7.9	105.0	217	0.95	217
-222K	17F	2.20	45	7.9	95.0	202	1.10	202
-272K	18F	2.70	48	7.9	90.0	193	1.20	193
-332K	19F	3.30	49	7.9	80.0	185	1.30	185
-392K	20F	3.90	50	7.9	75.0	173	1.50	173
-472K	21F	4.70	50	7.9	70.0	136	2.40	136
-562K	22F	5.60	50	7.9	60.0	124	2.90	124
-682K	23F	6.80	50	7.9	55.0	118	3.20	118
-822K	24F	8.20	50	7.9	53.0	111	3.60	111
-103K	25F	10.0	50	7.9	50.0	106	4.00	106

SERIES MIL1331 IRON CORE - FERRITE SLEEVE

-123K	26F	12.0	36	2.5	35.0	122	3.00	122
-153K	27F	15.0	38	2.5	30.0	115	3.40	115
-183K	28F	18.0	40	2.5	26.0	108	3.80	108
-223K	29F	22.0	40	2.5	24.0	96	4.90	96
-273K	30F	27.0	40	2.5	21.0	88	5.80	88
-333K	31F	33.0	41	2.5	20.0	83	6.50	83
-393K	32F	39.0	42	2.5	19.0	75	7.90	75
-473K	33F	47.0	44	2.5	16.0	69	9.30	69
-563K	34F	56.0	44	2.5	15.0	64	11.0	64
-683K	35F	68.0	45	2.5	13.0	61	12.0	61
-823K	36F	82.0	45	2.5	11.0	59	13.0	59
-104K	37F	100.0	40	2.5	10.5	51	16.8	51

SERIES MIL1331 FERRITE CORE - FERRITE SLEEVE

-124K	01F	120.0	31	0.79	13.0	88	5.80	27
-154K	02F	150.0	33	0.79	12.0	75	7.90	24
-184K	03F	180.0	33	0.79	11.0	69	9.40	22
-224K	04F	220.0	35	0.79	10.0	64	11.0	20
-274K	05F	270.0	35	0.79	9.0	61	12.0	18
-334K	06F	330.0	35	0.79	8.0	53	16.0	16
-394K	07F	390.0	35	0.79	7.8	46	21.0	14
-474K	08F	470.0	35	0.79	7.5	43	24.0	13
-564K	09F	560.0	35	0.79	7.0	40	28.0	12

Parts listed above are QPL/MIL qualified

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

Packaging Tape & reel (16mm): 7" reel, 500 pieces max.; 13" reel, 2200 pieces max.

Made In the U.S.A. Patent Protected

SERIES


1812R
1812



Unshielded Surface Mount Inductors



Actual Size



Physical Parameters

	Inches	Millimeters
A	0.166 to 0.190	4.22 to 4.83
B	0.118 to 0.134	3.00 to 3.40
C	0.118 to 0.134	3.00 to 3.40
D	0.015 Min.	0.38 Min.
E	0.054 to 0.078	1.37 to 1.98
F	0.118 (Ref. only)	3.00 (Ref. only)
G	0.066 (Ref. only)	1.68 (Ref. only)

Dimensions "A" and "C" are over terminals

Operating Temperature Range -55°C to +125°C

Current Rating at 90°C Ambient 35°C Rise

Maximum Power Dissipation at 90°C

Iron and Ferrite: 0.278 W

Phenolic: 0.210 W

*** Note** Self Resonant Frequency (SRF) values are calculated and for reference only.

Marking API/SMD; inductance with units and tolerance; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 1812R-105J

API/SMD
1mH±5%
R 0629A

Packaging Tape & reel (12mm): 7" reel, 650 pieces max.; 13" reel, 2500 pieces max.

Made In the U.S.A. Patent Protected

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%


*Complete part # must include series # PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com

DASH NUMBER*	INDUCTANCE (μH) ±10%	TOLERANCE	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
SERIES 1812 PHENOLIC CORE							
-100M	0.010	±20%	40	50	1000*	0.10	1230
-120M	0.012	±20%	40	50	1000*	0.10	1230
-150M	0.015	±20%	40	50	1000*	0.10	1230
-180M	0.018	±20%	40	50	1000*	0.10	1230
-220M	0.022	±20%	40	50	1000*	0.10	1230
-270M	0.027	±20%	40	50	1000*	0.15	1000
-330M	0.033	±20%	40	50	1000*	0.15	1000
-390M	0.039	±20%	30	50	1000*	0.20	870
-470M	0.047	±20%	30	50	1000*	0.20	870
-560M	0.056	±20%	30	50	850*	0.25	770
-680M	0.068	±20%	25	50	750*	0.25	770
-820M	0.082	±20%	25	50	750*	0.25	700
SERIES 1812 IRON CORE							
-101K	0.10	±10%	30	25	650	0.30	818
-121K	0.12	±10%	30	25	600	0.30	818
-151K	0.15	±10%	30	25	500	0.30	818
-181K	0.18	±10%	30	25	400	0.35	757
-221K	0.22	±10%	30	25	350	0.40	708
-271K	0.27	±10%	30	25	300	0.45	668
-331K	0.33	±10%	30	25	250	0.55	604
-391K	0.39	±10%	30	25	220	0.70	535
-471K	0.47	±10%	30	25	190	0.80	501
-561K	0.56	±10%	30	25	170	1.20	409
-681K	0.68	±10%	30	25	150	1.40	379
-821K	0.82	±10%	30	25	140	1.60	354
SERIES 1812 FERRITE CORE							
-102J	1.0	±5%	50	7.9	100	0.50	634
-122J	1.2	±5%	50	7.9	80	0.55	604
-152J	1.5	±5%	50	7.9	70	0.60	578
-182J	1.8	±5%	50	7.9	60	0.65	556
-222J	2.2	±5%	50	7.9	55	0.70	535
-272J	2.7	±5%	50	7.9	50	0.75	517
-332J	3.3	±5%	50	7.9	45	0.80	501
-392J	3.9	±5%	50	7.9	40	0.90	472
-472J	4.7	±5%	50	7.9	35	1.00	448
-562J	5.6	±5%	50	7.9	33	1.10	427
-682J	6.8	±5%	50	7.9	27	1.20	409
-822J	8.2	±5%	50	7.9	25	1.40	375
-103J	10	±5%	50	7.9	20	1.60	354
-123J	12	±5%	50	2.5	18	2.00	317
-153J	15	±5%	50	2.5	17	2.50	283
-183J	18	±5%	50	2.5	15	2.80	268
-223J	22	±5%	50	2.5	13	3.20	250
-273J	27	±5%	50	2.5	12	3.60	236
-333J	33	±5%	50	2.5	11	4.00	224
-393J	39	±5%	50	2.5	10	4.50	211
-473J	47	±5%	50	2.5	10	5.00	200
-563J	56	±5%	50	2.5	9	5.50	191
-683J	68	±5%	50	2.5	9	6.00	183
-823J	82	±5%	50	2.5	8	7.00	169
-104J	100	±5%	50	2.5	8	8.00	158
-124J	120	±5%	40	0.79	6	8.0	158
-154J	150	±5%	40	0.79	6	9.0	149
-184J	180	±5%	40	0.79	5	9.5	145
-224J	220	±5%	40	0.79	4	10.0	142
-274J	270	±5%	40	0.79	4	12.0	129
-334J	330	±5%	40	0.79	3.5	14.0	120
-394J	390	±5%	40	0.79	3.0	20.0	100
-474J	470	±5%	40	0.79	3.0	26.0	88
-564J	560	±5%	30	0.79	3.0	30.0	82
-684J	680	±5%	30	0.79	3.0	30.0	82
-824J	820	±5%	30	0.79	2.5	45.0	67
-105J	1000	±5%	30	0.79	2.5	60.0	55

SERIES**MIL1812R
MIL1812****Unshielded Surface Mount Inductors**

Actual Size

**Military QPL Approvals**

M83446/39

* Suffix F: Tin/Lead Termination

* Suffix P: Tin Termination

Physical Parameters

	Inches	Millimeters
A	0.166 to 0.190	4.22 to 4.83
B	0.118 to 0.134	3.00 to 3.40
C	0.118 to 0.134	3.00 to 3.40
D	0.015 Min.	0.38 Min.
E	0.054 to 0.078	1.37 to 1.98
F	0.118 (Ref. only)	3.00 (Ref. only)
G	0.066 (Ref. only)	1.68 (Ref. only)

Dimensions "A" and "C" are over terminals

Operating Temperature Range -55°C to +125°C**Current Rating at 90°C Ambient** 35°C Rise**Maximum Power Dissipation at 90°C**

Iron and Ferrite: 0.278 W

Phenolic: 0.210 W

****†Note** Self Resonant Frequency (SRF) values are calculated and for reference only.

Packaging Tape & reel (12mm): 7" reel, 650 pieces max.;
13" reel, 2500 pieces max.

*** Termination Finish Options** (Part & Callout)

MIL1812-101K = M83446/30F (Tin/Lead)

MIL1812R-101K = M83446/13P (Lead free)

Marking API/SMD; inductance with units and tolerance;
date code (YYWWL) followed by an M. Note: An R before
the date code indicates a RoHS component.

Example: MIL1812-101K

API/SMD
0.10uH±10%
0808A M

Parts listed above are QPL/MIL qualified

*Complete part # must include series # PLUS the dash #


For surface finish information,
refer to www.delevanfinishes.com

DASH NUMBER*	MIL DASH #	INDUCTANCE (uH) ±10%	TOLERANCE	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
M83446/39 PHENOLIC CORE								
-100M	-01*	0.010	±20%	40	50	1000**†	0.10	1230
	-02*	0.012	±20%	40	50	1000**†	0.10	1230
	-03*	0.015	±20%	40	50	1000**†	0.10	1230
	-04*	0.018	±20%	40	50	1000**†	0.10	1230
	-05*	0.022	±20%	40	50	1000**†	0.10	1230
	-06*	0.027	±20%	40	50	1000**†	0.15	1000
	-07*	0.033	±20%	40	50	1000**†	0.15	1000
	-08*	0.039	±20%	30	50	1000**†	0.20	870
	-09*	0.047	±20%	30	50	1000**†	0.20	870
	-10*	0.056	±20%	30	50	850**†	0.25	770
	-11*	0.068	±20%	25	50	750**†	0.25	770
	-12*	0.082	±20%	25	50	750**†	0.25	700
	-13*	0.10	±10%	30	25	650**†	0.30	818
	-14*	0.12	±10%	30	25	600**†	0.30	818
	-15*	0.15	±10%	30	25	500**†	0.30	818
	-16*	0.18	±10%	30	25	400**†	0.35	757
	-17*	0.22	±10%	30	25	350**†	0.40	708
	-18*	0.27	±10%	30	25	300**†	0.45	668
	-19*	0.33	±10%	30	25	250	0.55	604
	-20*	0.39	±10%	30	25	220	0.70	535
	-21*	0.47	±10%	30	25	190	0.80	501
	-22*	0.56	±10%	30	25	170	1.20	409
	-23*	0.68	±10%	30	25	150	1.40	379
	-24*	0.82	±10%	30	25	140	1.60	354
	-25*	1.0	±5%	50	7.9	100	0.50	634
	-26*	1.2	±5%	50	7.9	80	0.55	604
	-27*	1.5	±5%	50	7.9	70	0.60	578
	-28*	1.8	±5%	50	7.9	60	0.65	556
	-29*	2.2	±5%	50	7.9	55	0.70	535
	-30*	2.7	±5%	50	7.9	50	0.75	517
	-31*	3.3	±5%	50	7.9	45	0.80	501
	-32*	3.9	±5%	50	7.9	40	0.90	472
	-33*	4.7	±5%	50	7.9	35	1.00	448
	-34*	5.6	±5%	50	7.9	33	1.10	427
	-35*	6.8	±5%	50	7.9	27	1.20	409
	-36*	8.2	±5%	50	7.9	25	1.40	375
	-37*	10	±5%	50	7.9	20	1.60	354
	-38*	12	±5%	50	2.5	18	2.00	317
	-39*	15	±5%	50	2.5	17	2.50	283
	-40*	18	±5%	50	2.5	15	2.80	268
	-41*	22	±5%	50	2.5	13	3.20	250
	-42*	27	±5%	50	2.5	12	3.60	236
	-43*	33	±5%	50	2.5	11	4.00	224
	-44*	39	±5%	50	2.5	10	4.50	211
	-45*	47	±5%	50	2.5	10	5.00	200
	-46*	56	±5%	50	2.5	9	5.50	191
	-47*	68	±5%	50	2.5	9	6.00	183
	-48*	82	±5%	50	2.5	8	7.00	169
	-49*	100	±5%	50	2.5	8	8.00	158
	-50*	120	±5%	40	0.79	6	8.0	158
	-51*	150	±5%	40	0.79	6	9.0	149
	-52*	180	±5%	40	0.79	5	9.5	145
	-53*	220	±5%	40	0.79	4	10.0	142
	-54*	270	±5%	40	0.79	4	12.0	129
	-55*	330	±5%	40	0.79	3.5	14.0	120
	-56*	390	±5%	40	0.79	3.0	20.0	100
	-57*	470	±5%	40	0.79	3.0	26.0	88
	-58*	560	±5%	30	0.79	3.0	30.0	82
	-59*	680	±5%	30	0.79	3.0	30.0	82
	-60*	820	±5%	30	0.79	2.5	45.0	67
	-61*	1000	±5%	30	0.79	2.5	60.0	55

Shielded Surface Mount Inductors



Actual Size



Physical Parameters

	Inches	Millimeters
A	0.166 to 0.190	4.2 to 4.8
B	0.118 to 0.134	3.0 to 3.4
C	0.118 to 0.134	3.0 to 3.4
D	0.015 Min.	0.38 Min.
E	0.054 to 0.078	1.37 to 1.98
F	0.118 (Ref. only)	3.0 (Ref. only)
G	0.066 (Ref. only)	1.7 (Ref. only)

Dimensions "A" and "C" are over terminals

Weight Max. (Grams) 0.15


Operating Temperature Range -55°C to +125°C

Current Rating at 90°C Ambient 35°C Rise

Maximum Power Dissipation at 90°C 0.278 W

Marking API/SMD; inductance with units and tolerance followed by an S; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: S1812R-102K
API/SMD
1.0uH±10%S
R 0743A



For more detailed graphs, contact factory

RF Inductor							
DASH NUMBER*	INDUCTANCE (μH) ±10%	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	MAXIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
SERIES S1812 IRON CORE							
-101K	0.10	50	25	460		0.09	1490
-121K	0.12	50	25	400		0.10	1412
-151K	0.15	50	25	390		0.11	1347
-181K	0.18	50	25	350		0.12	1290
-221K	0.22	50	25	310		0.15	1154
-271K	0.27	50	25	280		0.18	1053
-331K	0.33	40	25	240		0.22	952
-391K	0.39	40	25	215		0.26	876
-471K	0.47	40	25	205		0.31	802
-561K	0.56	40	25	185		0.37	735
-681K	0.68	40	25	166		0.44	675
-821K	0.82	40	25	155		0.53	614
SERIES S1812 FERRITE CORE							
-102K	1.0	40	7.9	160		0.35	755
-122K	1.2	40	7.9	140		0.38	725
-152K	1.5	40	7.9	110		0.40	706
-182K	1.8	40	7.9	100		0.43	681
-222K	2.2	40	7.9	90		0.46	658
-272K	2.7	40	7.9	67		0.49	638
-332K	3.3	40	7.9	61		0.70	534
-392K	3.9	40	7.9	56		0.84	487
-472K	4.7	40	7.9	50		0.90	471
-562K	5.6	40	7.9	40		1.00	447
-682K	6.8	40	7.9	32		1.20	408
-822K	8.2	40	7.9	30		1.44	372
-103K	10	50	2.5	25		1.80	333
-123K	12	50	2.5	22		2.00	315
-153K	15	50	2.5	18		2.20	301
-183K	18	50	2.5	15		2.40	288
-223K	22	50	2.5	14		2.60	277
-273K	27	50	2.5	13		2.80	267
-333K	33	50	2.5	12		3.00	258
-393K	39	50	2.5	11		3.20	250
-473K	47	50	2.5	9.0		3.40	242
-563K	56	50	2.5	8.0		3.60	235
-683K	68	50	2.5	7.6		4.30	215
-823K	82	50	2.5	7.2		5.20	196
-104K	100	40	0.79	7.0		7.00	169
-124K	120	40	0.79	6.0		7.50	163
-154K	150	40	0.79	5.0		8.00	158
-184K	180	40	0.79	4.5		8.50	153
-224K	220	40	0.79	4.2		9.00	149
-274K	270	40	0.79	4.0		11.0	135
-334K	330	40	0.79	3.7		12.0	129
-394K	390	40	0.79	3.5		18.0	105
-474K	470	40	0.79	3.3		24.0	91
-564K	560	40	0.79	2.8		28.0	84
-684K	680	40	0.79	2.6		32.0	79
-824K	820	40	0.79	2.2		40.0	71
-105K	1000	40	0.79	2.0		55.0	60

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

Packaging Tape & reel (12mm): 7" reel, 650 pieces max.; 13" reel, 2500 pieces max.

Made In the U.S.A. Patent Protected

SERIES


MILS1812R
MILS1812



Shielded Surface Mount Inductors



Actual Size



Military QPL Approvals

M83446/40

* Suffix F: Tin/Lead Termination

* Suffix P: Tin Termination

Physical Parameters

	Inches	Millimeters
A	0.166 to 0.190	4.2 to 4.8
B	0.118 to 0.134	3.0 to 3.4
C	0.118 to 0.134	3.0 to 3.4
D	0.015 Min.	0.38 Min.
E	0.054 to 0.078	1.37 to 1.98
F	0.118 (Ref. only)	3.0 (Ref. only)
G	0.066 (Ref. only)	1.7 (Ref. only)

Dimensions "A" and "C" are over terminals

Weight Max. (Grams) 0.15

Operating Temperature Range -55°C to +125°C

Current Rating at 90°C Ambient 35°C Rise

Maximum Power Dissipation at 90°C 0.278 W


****†Note** Self Resonant Frequency (SRF) values are calculated and for reference only.

Marking API/SMD; inductance with units and tolerance followed by an S; date code (YYWWL) followed by an M. Note: An R before the date code indicates a RoHS component.

Example: MILS1812-153K

API/SMD
15uH±10%S
0850A M

Made In the U.S.A. Patent Protected



For more detailed graphs, contact factory

M83446/40 IRON CORE							
INDUCTANCE (uH) ±10%	MIL DASH #	TEST FREQUENCY (MHz)	Q MINIMUM	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)	
-101K	-01*	0.10	50	25	460**†	0.09	1490
-121K	-02*	0.12	50	25	400**†	0.10	1412
-151K	-03*	0.15	50	25	390**†	0.11	1347
-181K	-04*	0.18	50	25	350**†	0.12	1290
-221K	-05*	0.22	50	25	310**†	0.15	1154
-271K	-06*	0.27	50	25	280**†	0.18	1053
-331K	-07*	0.33	40	25	240	0.22	952
-391K	-08*	0.39	40	25	215	0.26	876
-471K	-09*	0.47	40	25	205	0.31	802
-561K	-10*	0.56	40	25	185	0.37	735
-681K	-11*	0.68	40	25	166	0.44	675
-821K	-12*	0.82	40	25	155	0.53	614
M83446/40 FERRITE CORE							
-102K	-13*	1.0	40	7.9	160	0.35	755
-122K	-14*	1.2	40	7.9	140	0.38	725
-152K	-15*	1.5	40	7.9	110	0.40	706
-182K	-16*	1.8	40	7.9	100	0.43	681
-222K	-17*	2.2	40	7.9	90	0.46	658
-272K	-18*	2.7	40	7.9	67	0.49	638
-332K	-19*	3.3	40	7.9	61	0.70	534
-392K	-20*	3.9	40	7.9	56	0.84	487
-472K	-21*	4.7	40	7.9	50	0.90	471
-562K	-22*	5.6	40	7.9	40	1.00	447
-682K	-23*	6.8	40	7.9	32	1.20	408
-822K	-24*	8.2	40	7.9	30	1.44	372
-103K	-25*	10	50	2.5	25	1.80	333
-123K	-26*	12	50	2.5	22	2.00	315
-153K	-27*	15	50	2.5	18	2.20	301
-183K	-28*	18	50	2.5	15	2.40	288
-223K	-29*	22	50	2.5	14	2.60	277
-273K	-30*	27	50	2.5	13	2.80	267
-333K	-31*	33	50	2.5	12	3.00	258
-393K	-32*	39	50	2.5	11	3.20	250
-473K	-33*	47	50	2.5	9.0	3.40	242
-563K	-34*	56	50	2.5	8.0	3.60	235
-683K	-35*	68	50	2.5	7.6	4.30	215
-823K	-36*	82	50	2.5	7.2	5.20	196
-104K	-37*	100	40	0.79	7.0	7.00	169
-124K	-38*	120	40	0.79	6.0	7.50	163
-154K	-39*	150	40	0.79	5.0	8.00	158
-184K	-40*	180	40	0.79	4.5	8.50	153
-224K	-41*	220	40	0.79	4.2	9.00	149
-274K	-42*	270	40	0.79	4.0	11.0	135
-334K	-43*	330	40	0.79	3.7	12.0	129
-394K	-44*	390	40	0.79	3.5	18.0	105
-474K	-45*	470	40	0.79	3.3	24.0	91
-564K	-46*	560	40	0.79	2.8	28.0	84
-684K	-47*	680	40	0.79	2.6	32.0	79
-824K	-48*	820	40	0.79	2.2	40.0	71
-105K	-49*	1000	40	0.79	2.0	55.0	60

Parts listed above are QPL/MIL qualified

*Complete part # must include series # PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com

Packaging Tape & reel (12mm): 7" reel, 650 pieces max.; 13" reel, 2500 pieces max.

*** Termination Finish Options** (Part & Callout)

MILS1812 - 101K = M83446/30F (Tin/Lead)


MILS1812R - 101K = M83446/13P (Pb free)

SERIES

2510R 2510



Unshielded Surface Mount Inductors



Actual Size

Physical Parameters

	Inches	Millimeters
A	0.235 to 0.255	5.97 to 6.48
B	0.085 to 0.105	2.16 to 2.67
C	0.090 to 0.110	2.29 to 2.79
D	0.060 to 0.080	1.52 to 2.03
E	0.035 to 0.055	0.89 to 1.40
F	0.100 (Ref. only)	2.54 (Ref. only)
G	0.059 (Ref. only)	1.47 (Ref. only)

Dimensions "A" and "C" are over terminals.

Weight Max. (Grams)

Phenolic: 0.19

Iron & Ferrite: 0.22

Operating Temperature Range

Phenolic: -55°C to +125°C

Iron & Ferrite: -55°C to +105°C

Current Rating at 90°C Ambient

Phenolic: 35°C Rise

Iron & Ferrite: 15°C Rise

Maximum Power Dissipation at 90°C Ambient

Phenolic: 0.145 W

Iron & Ferrite: 0.062 W

Marking API/SMD; inductance with units and tolerance; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 2510R-52K

API/SMD

15uH±10%

R 0614B

Packaging Tape & reel (12mm): 7" reel, 750 pieces max.; 13" reel, 2700 pieces max.

INDUCTANCE (uH) ±10%
TEST FREQUENCY (MHz)
Q MINIMUM
SRF MINIMUM (MHz)
DC RESISTANCE MAXIMUM (OHMS)
CURRENT RATING MAXIMUM (mA)
RF Inductors

SERIES 2510 PHENOLIC CORE

-00K	0.10	25	25.0	640.0	0.14	865
-02K	0.12	25	25.0	610.0	0.17	785
-04K	0.15	25	25.0	530.0	0.20	725
-06K	0.18	25	25.0	510.0	0.22	690
-08K	0.22	25	25.0	480.0	0.26	635
-10K	0.27	25	25.0	440.0	0.40	510
-12K	0.33	25	25.0	410.0	0.50	455
-14K	0.39	25	25.0	380.0	0.60	415
-16K	0.47	25	25.0	340.0	0.63	405

SERIES 2510 IRON CORE

-18K	0.56	35	25.0	240.0	0.19	500
-20K	0.68	35	25.0	210.0	0.21	475
-22K	0.82	35	25.0	200.0	0.24	444
-24K	1.0	35	7.9	180.0	0.27	418
-26K	1.2	25	7.9	160.0	0.32	385
-28K	1.5	30	7.9	140.0	0.53	300
-30K	1.8	30	7.9	125.0	0.59	283
-32K	2.2	30	7.9	120.0	0.76	250
-34K	2.7	30	7.9	100.0	0.90	229
-36K	3.3	35	7.9	90.0	1.35	187
-38K	3.9	35	7.9	85.0	1.70	167
-40K	4.7	35	7.9	80.0	2.30	143
-42K	5.6	35	7.9	75.0	3.10	123
-44K	6.8	35	7.9	64.0	3.60	114
-46K	8.2	35	7.9	50.0	4.8	99
-48K	10.0	35	7.9	45.0	5.7	91
-50K	12.0	25	2.5	29.0	3.3	120
-52K	15.0	25	2.5	24.0	3.8	110
-54K	18.0	25	2.5	21.0	4.2	106
-56K	22.0	25	2.5	18.0	4.7	100
-58K	27.0	25	2.5	17.0	5.7	91
-60K	33.0	25	2.5	15.0	6.2	87
-62K	39.0	25	2.5	13.0	8.1	76
-64K	47.0	25	2.5	12.0	9.8	69
-66K	56.0	25	2.5	11.0	12.0	62
-68K	68.0	25	2.5	10.0	13.8	58
-70K	82.0	25	2.5	9.0	19.0	50
-72K	100.0	25	2.5	8.9	21.0	47

SERIES 2510 FERRITE CORE

-74K	120.0	15	0.79	8.5	17.0	52
-76K	150.0	15	0.79	7.6	19.0	49
-78K	180.0	15	0.79	7.2	21.5	46
-80K	220.0	15	0.79	6.8	32.0	38
-82K	270.0	15	0.79	6.2	37.0	35
-84K	330.0	15	0.79	5.3	47.0	31
-86K	390.0	15	0.79	5.0	53.0	30
-88K	470.0	15	0.79	4.6	60.0	28
-90K	560.0	15	0.79	4.3	71.0	25
-92K	680.0	15	0.79	3.8	83.0	23
-94K	820.0	15	0.79	3.2	95.0	22
-96K	1000.0	15	0.79	2.4	108.0	20

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%


*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

Made In the U.S.A. Patent Protected

SERIES**MIL2510**

Unshielded Surface Mount Inductors



Actual Size

Military QPL Approval

M83446/28 Phenolic Core

M83446/29 Iron Core

M83446/30 Ferrite Core

†**Ordering Note** Military parts must be ordered to the M83446/ part number

Physical Parameters

	Inches	Millimeters
A	0.235 to 0.255	5.97 to 6.48
B	0.085 to 0.105	2.16 to 2.67
C	0.090 to 0.110	2.29 to 2.79
D	0.060 to 0.080	1.52 to 2.03
E	0.035 to 0.055	0.89 to 1.40
F	0.100 (Ref. only)	2.54 (Ref. only)
G	0.059 (Ref. only)	1.47 (Ref. only)

Dimensions "A" and "C" are over terminals.

Weight Max. (Grams)

Phenolic: 0.19

Iron & Ferrite: 0.22

Operating Temperature Range

Phenolic: -55°C to +125°C

Iron & Ferrite: -55°C to +105°C

Current Rating at 90°C Ambient

Phenolic: 35°C Rise

Iron & Ferrite: 15°C Rise

Maximum Power Dissipation at 90°C Ambient

Phenolic: 0.145 W

Iron & Ferrite: 0.062 W

Marking API/SMD; inductance with units and tolerance; date code (YYWWL) followed by an M.

Example: MIL2510-26K

API/SMD
1.2uH±10%
0851A M

Packaging Tape & reel (12mm): 7" reel, 750 pieces max.; 13" reel, 2700 pieces max.

INDUCTANCE (uH) ±10%
TEST FREQUENCY (MHz)
SRF MINIMUM (MHz)
DC RESISTANCE MAXIMUM (OHMS)
CURRENT RATING MAXIMUM (mA)
DASH NUMBER*
MIL DASH #

RF Inductors

M83446/28- SERIES MIL 2510 PHENOLIC CORE

-00K	01F	0.10	25	25.0	640.0	0.14	865
-02K	02F	0.12	25	25.0	610.0	0.17	785
-04K	03F	0.15	25	25.0	530.0	0.20	725
-06K	04F	0.18	25	25.0	510.0	0.22	690
-08K	05F	0.22	25	25.0	480.0	0.26	635
-10K	06F	0.27	25	25.0	440.0	0.40	510
-12K	07F	0.33	25	25.0	410.0	0.50	455
-14K	08F	0.39	25	25.0	380.0	0.60	415
-16K	09F	0.47	25	25.0	340.0	0.63	405

M83446/29- SERIES MIL 2510 IRON CORE

-18K	01F	0.56	35	25.0	240.0	0.19	500
-20K	02F	0.68	35	25.0	210.0	0.21	475
-22K	03F	0.82	35	25.0	200.0	0.24	444
-24K	04F	1.0	35	7.9	180.0	0.27	418
-26K	05F	1.2	25	7.9	160.0	0.32	385
-28K	06F	1.5	30	7.9	140.0	0.53	300
-30K	07F	1.8	30	7.9	125.0	0.59	283
-32K	08F	2.2	30	7.9	120.0	0.76	250
-34K	09F	2.7	30	7.9	100.0	0.90	229
-36K	10F	3.3	35	7.9	90.0	1.35	187
-38K	11F	3.9	35	7.9	85.0	1.70	167
-40K	12F	4.7	35	7.9	80.0	2.30	143
-42K	13F	5.6	35	7.9	75.0	3.10	123
-44K	14F	6.8	35	7.9	64.0	3.60	114
-46K	15F	8.2	35	7.9	50.0	4.8	99
-48K	16F	10.0	35	7.9	45.0	5.7	91
-50K	17F	12.0	25	2.5	29.0	3.3	120
-52K	18F	15.0	25	2.5	24.0	3.8	110
-54K	19F	18.0	25	2.5	21.0	4.2	106
-56K	20F	22.0	25	2.5	18.0	4.7	100
-58K	21F	27.0	25	2.5	17.0	5.7	91
-60K	22F	33.0	25	2.5	15.0	6.2	87
-62K	23F	39.0	25	2.5	13.0	8.1	76
-64K	24F	47.0	25	2.5	12.0	9.8	69
-66K	25F	56.0	25	2.5	11.0	12.0	62
-68K	26F	68.0	25	2.5	10.0	13.8	58
-70K	27F	82.0	25	2.5	9.0	19.0	50
-72K	28F	100.0	25	2.5	8.9	21.0	47

M83446/30- SERIES MIL 2510 FERRITE CORE


-74K	01F	120.0	15	0.79	8.5	17.0	52
-76K	02F	150.0	15	0.79	7.6	19.0	49
-78K	03F	180.0	15	0.79	7.2	21.5	46
-80K	04F	220.0	15	0.79	6.8	32.0	38
-82K	05F	270.0	15	0.79	6.2	37.0	35
-84K	06F	330.0	15	0.79	5.3	47.0	31
-86K	07F	390.0	15	0.79	5.0	53.0	30
-88K	08F	470.0	15	0.79	4.6	60.0	28
-90K	09F	560.0	15	0.79	4.3	71.0	25
-92K	10F	680.0	15	0.79	3.8	83.0	23
-94K	11F	820.0	15	0.79	3.2	95.0	22
-96K	12F	1000.0	15	0.79	2.4	108.0	20

Parts listed above are QPL/MIL qualified

*Complete part # must include series # PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com

Made In the U.S.A. Patent Protected

SERIES**S4924R**
S4924**Shielded Surface Mount Inductors**

Actual Size

Physical Parameters

	Inches	Millimeters
A	0.490 to 0.520	12.44 to 13.21
B	0.230 to 0.250	5.84 to 6.35
C	0.210 to 0.230	5.33 to 5.84
D	0.050 Min.	1.27 Min.
E	0.055 to 0.095	1.397 to 2.413
F	0.330 (Ref. only)	8.38 (Ref. only)
G	0.120 (Ref. only)	3.04 (Ref. only)

Mechanical Configuration

Units are encapsulated in an epoxy molded surface mount package

Operating Temperature Range

-55°C to +125°C

Current Rating at 90°C Ambient 35°C Rise**Maximum Power Dissipation at 90°C 0.385 W**

Incremental Current Current which causes a max. of 5% change in Inductance

Dielectric Withstanding Voltage 1000V RMS Min.

Inductance Tolerance Tolerance is specified by suffixing an alpha character to the part number as follows: H = 3% and J = 5%. Units are normally supplied to the tolerance indicated in table.

Coupling 3% Max.

Marking API/SMD; S4924; inductance with units and tolerance; date code (YYWWL). Note: An R after S4924 indicates a RoHS component.

Example: S4924-184J

API/SMD
S4924
180uH±5%
0226B

Packaging Tape & reel (24mm): 13" reel, 800 pieces max.; 7" reel not available


Made In the U.S.A.

Optional Tolerances: J = 5% H = 3%

*Complete part # must include series # PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com

DASH NUMBER*	INDUCTANCE (μH) ±10%	TEST FREQUENCY (MHz)	Q MINIMUM	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)	INCREMENTAL CURRENT (mA)
SERIES S4924 PHENOLIC CORE - IRON SLEEVE							
-101K	0.10	50	25.0	450	0.025	3900	3900
-121K	0.12	50	25.0	425	0.034	3345	3345
-151K	0.15	50	25.0	400	0.037	3195	3195
-181K	0.18	50	25.0	350	0.047	2835	2835
-221K	0.22	49	25.0	325	0.067	2385	2385
-271K	0.27	47	25.0	300	0.11	1855	1855
-331K	0.33	46	25.0	275	0.13	1705	1705
-391K	0.39	44	25.0	250	0.18	1450	1450
-471K	0.47	44	25.0	235	0.25	1235	1235
-561K	0.56	43	25.0	210	0.33	1075	1075
-681K	0.68	42	25.0	190	0.45	915	915
-821K	0.82	40	25.0	180	0.59	800	800
SERIES S4924 IRON CORE - IRON SLEEVE							
-102K	1.00	44	25.0	140	0.07	2320	2320
-122K	1.20	44	7.9	130	0.10	1920	1920
-152K	1.50	44	7.9	115	0.12	1780	1780
-182K	1.80	44	7.9	105	0.14	1650	1650
-222K	2.20	44	7.9	100	0.19	1420	1420
-272K	2.70	44	7.9	92	0.28	1160	1160
-332K	3.30	44	7.9	85	0.35	1045	1045
-392K	3.90	44	7.9	75	0.40	970	970
-472K	4.70	44	7.9	70	0.55	830	830
-562K	5.60	44	7.9	65	0.72	725	725
-682K	6.80	50	7.9	55	1.02	610	610
-822K	8.20	50	7.9	50	1.32	535	535
-103K	10.0	50	7.9	46	1.62	485	485
-123K	12.0	55	2.5	44	2.0	440	440
SERIES S4924 FERRITE CORE - FERRITE SLEEVE							
-153K	15.0	45	2.5	49	0.8	618	300
-183K	18.0	45	2.5	45	0.89	580	250
-223K	22.0	45	2.5	41	0.96	561	210
-273K	27.0	45	2.5	38	1.19	504	195
-333K	33.0	45	2.5	34	1.37	471	160
-393K	39.0	50	2.5	29	1.93	397	150
-473K	47.0	50	2.5	27	2.11	380	135
-563K	56.0	50	2.5	25	2.23	369	124
-683K	68.0	50	2.5	21	2.70	355	122
-823K	82.0	50	2.5	10.5	2.44	342	120
-104K	100.0	50	2.5	10.0	3.12	312	113
-124K	120.0	55	0.79	9.7	3.6	291	98
-154K	150.0	55	0.79	8.5	4.1	272	84
-184K	180.0	55	0.79	8.0	4.4	263	76
-224K	220.0	55	0.79	7.5	5.0	247	67
-274K	270.0	55	0.79	7.0	5.8	228	60
-334K	330.0	55	0.79	6.5	6.4	218	55
-394K	390.0	60	0.79	6.2	7.4	203	46
-474K	470.0	60	0.79	5.7	9.5	178	43
-564K	560.0	60	0.79	4.7	10.5	171	40
-684K	680.0	60	0.79	4.5	11.8	160	38
-824K	820.0	60	0.79	4.2	13.0	152	33
-105K	1000.0	60	0.79	3.8	17.5	134	29
-125K	1200.0	50	0.25	3.0	22.1	120	28
-155K	1500.0	50	0.25	2.8	26.5	115	27
-185K	1800.0	50	0.25	2.6	29.9	110	24
-225K	2200.0	50	0.25	2.4	33.8	104	22
-275K	2700.0	50	0.25	2.2	47.3	88	20
-335K	3300.0	50	0.25	2.0	53.0	85	19
-395K	3900.0	50	0.25	1.9	73.8	72	17
-475K	4700.0	50	0.25	1.7	81.6	68	15
-565K	5600.0	50	0.25	1.6	98.9	61	14
-685K	6800.0	50	0.25	1.4	111.0	59	13
-825K	8200.0	50	0.25	1.2	119.0	57	12
-106K	10000.0	50	0.25	1.0	137.0	54	11
-126K	12000.0	30	0.079	0.80	143.0	50	9
-156K	15000.0	30	0.079	0.60	157.0	48	8
-186K	18000.0	30	0.079	0.55	225.0	46	7
-226K	22000.0	27	0.079	0.50	274.0	37	7
-276K	27000.0	27	0.079	0.40	308.0	35	7

SERIES**5022R
5022****Surface Mountable Inductors**

Actual Size

Physical Parameters

	Inches	Millimeters
A	0.490 to 0.520	12.44 to 13.21
B	0.230 to 0.250	5.84 to 6.35
C	0.210 to 0.230	5.33 to 5.84
D	0.050 Min.	1.27 Min.
E	0.055 to 0.095	1.397 to 2.413
F	0.330 (Ref. only)	8.38 (Ref. only)
G	0.120 (Ref. only)	3.04 (Ref. only)

Weight Max. (Grams) 1.5**Mechanical Configuration** Units are encapsulated in an epoxy molded surface mount package.**Operating Temperature Range** -55°C to +125°C**Current Rating at 90°C Ambient** 35°C Rise**Maximum Power Dissipation at 90°C** 0.405 W**Marking** API/SMD; 5022; inductance with units and tolerance; date code (YYWWL). Note: An R after 5022 indicates a RoHS component.

Example: 5022R-102G

API/SMD
5022R
1.0uH±2%
0542A

Packaging Tape & reel (24mm): 13" reel, 800 pieces max.; 7" reel not available**Made In the U.S.A. Patent Protected**

RF Inductors

INDUCTANCE (μH) ±5%
DASH NUMBER*
TEST FREQUENCY (MHz)
Q MINIMUM
SRF MINIMUM (MHz)
MAXIMUM (MHz)
DC RESISTANCE MAXIMUM (OHMS)
CURRENT RATING MAXIMUM (mA)

SERIES 5022 PHENOLIC CORE

-151J	0.15	50	25.0	525	0.030	3500
-161J	0.16	50	25.0	525	0.040	3025
-181J	0.18	50	25.0	500	0.043	2915
-201J	0.20	50	25.0	475	0.047	2790
-221J	0.22	50	25.0	450	0.055	2580
-241J	0.24	45	25.0	415	0.060	2470
-271J	0.27	45	25.0	400	0.070	2285
-301J	0.30	45	25.0	380	0.080	2140
-331J	0.33	45	25.0	360	0.090	2015
-361J	0.36	45	25.0	345	0.098	1935
-391J	0.39	45	25.0	330	0.100	1915
-431J	0.43	45	25.0	315	0.110	1825
-471J	0.47	45	25.0	310	0.120	1750
-511J	0.51	45	25.0	300	0.130	1680
-561J	0.56	50	25.0	280	0.135	1645
-621J	0.62	50	25.0	260	0.140	1615
-681J	0.68	50	25.0	250	0.150	1555
-751J	0.75	50	25.0	230	0.180	1425
-821J	0.82	50	25.0	220	0.220	1300
-911J	0.91	50	25.0	210	0.240	1240
-102J	1.00	50	25.0	200	0.290	1125
-112J	1.10	33	7.9	190	0.420	930
-122J	1.20	33	7.9	180	0.420	930
-132J	1.30	33	7.9	170	0.480	875
-152J	1.50	33	7.9	160	0.500	855
-162J	1.60	33	7.9	155	0.600	780
-182J	1.80	33	7.9	150	0.650	755
-202J	2.00	33	7.9	140	0.800	675
-222J	2.20	33	7.9	135	0.950	620
-242J	2.40	33	7.9	130	1.100	575
-272J	2.70	33	7.9	120	1.200	550
-302J	3.00	33	7.9	115	1.800	455
-332J	3.30	33	7.9	110	2.000	430
-362J	3.60	33	7.9	105	2.150	415
-392J	3.90	33	7.9	100	2.300	395
-432J	4.30	33	7.9	95	2.400	390
-472J	4.70	33	7.9	90	2.600	375

Optional Tolerances: H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #


For surface finish information, refer to www.delevanfinishes.com

SERIES

5022R
5022



Surface Mountable Inductors




DASH NUMBER*	INDUCTANCE (μH) ±10%	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
SERIES 5022 IRON CORE						
-512J	5.10	35	7.9	65	0.300	1040
-562J	5.60	45	7.9	60	0.320	1030
-622J	6.20	45	7.9	60	0.470	830
-682J	6.80	50	7.9	55	0.500	820
-752J	7.50	50	7.9	55	0.550	765
-822J	8.20	50	7.9	50	0.600	748
-912J	9.10	55	7.9	50	0.800	638
-103J	10.0	55	7.9	45	0.900	610
-113J	11.0	60	2.5	44	1.050	565
-123J	12.0	65	2.5	42	1.100	555
-133J	13.0	65	2.5	40	1.200	520
-153J	15.0	65	2.5	40	1.400	495
-163J	16.0	70	2.5	38	1.800	420
-183J	18.0	75	2.5	34	2.250	388
-203J	20.0	75	2.5	30	2.500	372
-223J	22.0	75	2.5	30	2.500	368
-243J	24.0	60	2.5	26	2.500	368
-273J	27.0	60	2.5	25	2.600	360
-303J	30.0	65	2.5	21	2.800	348
-333J	33.0	65	2.5	19	3.000	337
-363J	36.0	60	2.5	15.5	2.500	368
-393J	39.0	60	2.5	14.5	2.600	361
-433J	43.0	60	2.5	13.7	2.700	353
-473J	47.0	55	2.5	13.0	2.750	351
-513J	51.0	55	2.5	12.7	2.850	344
-563J	56.0	55	2.5	12.0	3.000	335
-623J	62.0	55	2.5	11.5	3.150	328
-683J	68.0	55	2.5	11.0	3.300	320
-753J	75.0	55	2.5	10.5	3.700	302
-823J	82.0	50	2.5	10.3	3.900	295
-913J	91.0	50	2.5	10.0	4.300	280
-104J	100.0	50	2.5	9.5	4.500	275
-114J	110.0	60	0.79	8.9	4.900	262
-124J	120.0	65	0.79	8.7	5.200	255
-134J	130.0	65	0.79	8.5	5.450	250
-154J	150.0	65	0.79	8.0	6.050	237
-164J	160.0	65	0.79	7.5	6.400	230
-184J	180.0	65	0.79	7.0	6.750	224
-204J	200.0	65	0.79	6.5	7.100	219
-224J	220.0	65	0.79	6.2	7.450	213
-244J	240.0	65	0.79	5.9	7.800	210
-274J	270.0	65	0.79	5.7	11.000	182
-304J	300.0	65	0.79	5.4	11.500	178
-334J	330.0	65	0.79	5.1	12.000	173
-364J	360.0	65	0.79	4.8	12.500	171
-394J	390.0	65	0.79	4.5	16.300	149
-434J	430.0	65	0.79	4.2	17.100	147
-474J	470.0	65	0.79	3.9	17.900	143
-514J	510.0	65	0.79	3.7	18.800	139
-564J	560.0	65	0.79	3.8	19.500	136
-624J	620.0	65	0.79	3.3	25.900	119
-684J	680.0	65	0.79	3.1	27.200	116
-754J	750.0	65	0.79	2.9	28.600	112
-824J	820.0	65	0.79	2.7	30.000	110
-914J	910.0	65	0.79	2.5	31.500	107
-105J	1000.0	65	0.79	2.3	33.000	105

Optional Tolerances: H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

SERIES**4426R**
4426**Air Core Inductors**

Actual Size

	Size A in.	Size A mm	Size B in. in.	Size B mm
A Max	0.120	3.05	0.120	3.05
B Max	0.125	3.18	0.125	3.18
C Max	0.145	3.68	0.270	6.86r
D	0.115±.010	2.92±.25	0.230±.010	5.84±.25
E	0.05±.015	1.27±.38	0.05±.015	1.27±.38
F	0.165	4.19	0.285	7.23
G	0.110	2.79	0.110	2.79
H	0.130	3.30	0.130	3.30
I	0.050	1.27	0.050	1.27
J	0.065	1.65	0.185	4.69

High Q, wire wound air cores Designed to operate over a wide frequency range. Standard flat cap top is suitable for automatic placement.

***Ordering** Suffix the dash number with **RC** to order optional water dissolvable flat top cap for applications requiring hand adjustment. The cap allows the part to be pick and placed onto the PCB, and will dissolve in almost all board cleaning solvents, leaving no residue. Suffix the dash number with **NC** to order option with no cap, for manual placement.

Operating Temperature Range -55°C to +125°C

Packaging Tape & reel


Size A, (12mm): 7" reel, 650 pieces max.; 13" reel, 2500 pieces max.;


Size B, (16mm): 7" reel, 400 pieces max.; 13" reel, 1400 pieces max.

DASH NUMBER*	INDUCTANCE (μH) ±10%	TEST FREQUENCY (MHz)	Q MINIMUM	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)	INCREMENTAL CURRENT (mA)
SERIES 4426							
-1	1	2.5±10%	145	150	>3	3.0	A
-2	2	5.0±10%	140	150	>3	3.0	A
-3	3	8.0±5%	140	150	>3	3.0	A
-4	4	12.5±5%	137	150	>3	3.0	A
-5	5	18.5±5%	132	150	>3	3.0	A
-6	6	17.5±5%	100	150	>3	3.0	B
-7	7	22.0±5%	102	150	>3	3.0	B
-8	8	28.0±5%	105	150	2.6	3.0	B
-9	9	35.5±5%	112	150	1.8	3.0	B
-10	11	43.0±5%	106	150	1.5	3.0	B

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com



SERIES**4726R
4726****Air Core Inductors**


RF Inductors

DASH NUMBER* INDUCTANCE (nH) ±5% Q NOM. TEST FREQUENCY (MHz) SRF MIN. (GHz) CURRENT RATING MAXIMUM (Amps)

SERIES 4726						
-22	4	22	95	150	3.0	3.0
-27	5	27	100	150	2.7	3.0
-33	5	33	115	150	2.5	3.0
-35	5	35	115	150	2.0	3.0
-39	6	39	115	150	2.0	3.0
-47	6	47	120	150	1.7	3.0
-56	7	56	120	150	1.5	3.0
-60	7	60	135	150	1.5	3.0
-68	7	68	135	150	1.4	3.0
-82	8	82	135	150	1.3	3.0
-100	9	100	135	150	1.2	3.0
-120	9	120	135	150	1.2	3.0
-150	10	150	140	150	1.0	3.0

*Complete part # must include series # PLUS the dash #
See Hand Adjustable Note

For surface finish information,
refer to www.delevanfinishes.com

**High Q, wire wound air cores**

Designed to operate over a wide frequency range.

Physical Parameters

	Inches	Millimeters
A	0.175 Max.	4.445 Max.
B	0.165 Max.	4.191 Max.
C	0.220 Max.	5.588 Max.
D	0.170 ± .015	4.318 ± 0.38
E	0.060 ± 0.020	1.524 ± 0.51
F	0.228	5.79
G	0.103	2.62
H	0.203	5.16
I	0.058	1.47
J	0.112	2.84

Operating Temperature Range -55°C to +125°C

Inductance and Q tested on HP4291A


Hand Adjustable when ordered with dissolvable cap or without cap. Removable cap allows for pick and place application and dissolves with board cleaning solvents. Suffix the part number RC to order a removable cap; suffix the part number NC to order without cap.

Ordering Example

4726-150 Capped Air Core (SnPb)
4726-150RC Removable Capped Air Core (SnPb)
4726R-150NC Without Cap Air Core (RoHS)

Packaging Tape & reel (16mm)


7" reel, not available; 13" reel, 1000 pieces max.

SERIES**5526R
5526****Air Core Inductors**

DASH NUMBER*	INDUCTANCE (μ H) $\pm 5\%$	TEST FREQUENCY (MHz)	CURRENT RATING MAXIMUM (mA)	SRF MINIMUM (MHz)
SERIES 5526				
-1	9	90	50	3.5
-2	10	111	87	50
-3	11	130	87	50
-4	12	169	95	50
-5	13	206	95	50
-6	14	222	92	50
-7	15	246	95	50
-8	16	307	95	50
-9	17	380	95	50
-10	18	420	95	50
-11	19	491	95	50
-12	20	538	87	50

*Complete part # must include series # PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com

**High Q, wire wound air cores**

Designed to operate over a wide frequency range.

Physical Parameters

	Inches	Millimeters
A Max	0.250	6.35
B Max	0.235	5.97
C Max	0.420	10.67
D	0.314 $\pm$ 0.020	7.98 $\pm$ 0.510
E	0.032 $\pm$ 0.025	0.813 $\pm$ 0.635
F	0.394	10.00
G	0.095	2.42
H	0.185	4.70
I	0.080	2.03
J	0.234	5.95

Operating Temperature Range -55°C to $+125^{\circ}\text{C}$


Inductance and Q tested on HP4291A using HP16193A test fixture and correlation

Packaging Tape & reel (24mm): 13" reel, 800 pieces max.; 7" reel not available; Intermediate values available upon request.

Made in the U.S.A.

SERIES**0819R**
0819**Molded Unshielded RF Coils**

Actual Size

**Physical Parameters**

	Inches	Millimeters
Length	0.200 ± 0.010	5.08 ± 0.25
Diameter	0.078 ± 0.008	1.98 ± 0.20
Lead Size		
AWG #24 TCW	0.020 ± 0.0015	0.508 ± 0.038
Lead Length	1.5 ± 0.12	38.10 ± 3.05

Current Rating at 90°C Ambient

Phenolic: 35°C Rise

Iron and Ferrite: 15°C Rise

Operating Temperature Range

Phenolic: -55°C to +125°C

Iron and Ferrite: -55°C to +105°C

Maximum Power Dissipation at 90°C

Phenolic: 0.145 W

Iron and Ferrite: 0.062 W

Weight Max. (Grams)

Phenolic: 0.19

Iron and Ferrite: 0.22

Marking DELEVAN; inductance with units and tolerance; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 0819-32K

Front: Reverse:
DELEVAN 0850B
2.2uH±10%

Packaging Tape & reel: 12" reel, 3500 pieces max.; 14" reel, 6000 pieces max.

Made in the U.S.A.

INDUCTANCE (uH) ±10%
DASH NUMBER*
TEST FREQUENCY (MHz)
Q MINIMUM
SRF MINIMUM (MHz)
DC RESISTANCE MAXIMUM (OHMS)
CURRENT RATING MAXIMUM (mA)
RF Inductors

SERIES 0819 PHENOLIC CORE

-00K	0.10	35	25.0	680	0.13	895
-02K	0.12	35	25.0	650	0.15	835
-04K	0.15	35	25.0	560	0.18	760
-06K	0.18	35	25.0	540	0.21	705
-08K	0.22	30	25.0	500	0.25	645
-10K	0.27	30	25.0	440	0.38	525
-12K	0.33	25	25.0	410	0.49	460
-14K	0.39	25	25.0	380	0.59	420
-16K	0.47	25	25.0	340	0.62	410

SERIES 0819 IRON CORE

-18K	0.56	40	25.0	250	0.18	510
-20K	0.68	40	25.0	215	0.20	485
-22K	0.82	40	25.0	200	0.22	465
-24K	1.0	40	25.0	190	0.25	435
-26K	1.2	35	7.9	170	0.28	410
-28K	1.5	40	7.9	150	0.49	310
-30K	1.8	40	7.9	135	0.56	290
-32K	2.2	45	7.9	130	0.72	257
-34K	2.7	45	7.9	110	0.85	236
-36K	3.3	45	7.9	100	1.2	198
-38K	3.9	50	7.9	95	1.5	178
-40K	4.7	55	7.9	88	2.1	150
-42K	5.6	55	7.9	78	2.8	130
-44K	6.8	55	7.9	69	3.2	122
-46K	8.2	45	7.9	52	4.4	104
-48K	10.0	45	7.9	47	5.2	95

SERIES 0819 FERRITE CORE

-50K	12.0	40	2.5	31.0	3.0	126.0
-52K	15.0	40	2.5	26.0	3.4	118.0
-54K	18.0	40	2.5	23.0	3.8	112.0
-56K	22.0	45	2.5	20.0	4.3	105.0
-58K	27.0	45	2.5	17.0	4.7	100.0
-60K	33.0	45	2.5	15.0	5.2	95.0
-62K	39.0	45	2.5	13.5	6.8	83.5
-64K	47.0	45	2.5	12.5	8.2	76.0
-66K	56.0	45	2.5	11.5	10.0	69.0
-68K	68.0	45	2.5	10.5	11.5	64.0
-70K	82.0	45	2.5	10.0	16.0	54.5
-72K	100.0	45	2.5	9.5	17.5	52.0
-74K	120.0	35	0.79	8.9	16.0	54.5
-76K	150.0	35	0.79	7.9	18.0	51.0
-78K	180.0	35	0.79	7.5	20.0	49.0
-80K	220.0	35	0.79	7.1	26.5	42.5
-82K	270.0	35	0.79	6.6	30.5	39.0
-84K	330.0	35	0.79	6.2	40.5	34.0
-86K	390.0	35	0.79	5.9	43.0	33.0
-88K	470.0	35	0.79	5.4	48.0	31.5
-90K	560.0	35	0.79	5.0	60.0	28.0
-92K	680.0	35	0.79	4.5	66.0	27.0
-94K	820.0	35	0.79	3.9	72.0	25.5
-96K	1000.0	35	0.79	3.3	79.0	24.5

Optional Tolerances: J= 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com


SERIES

1025R, 1026R
1025
1026



Molded Unshielded RF Coils

Actual Size



Military Specifications (1025 Series Only)

MS75083 (LT4K); MS75084 (LT10K); MS75085 (LT10K)

Physical Parameters

	Inches	Millimeters
Length	0.250 ± 0.010	6.35 ± 0.25
Diameter	0.095 ± 0.010	2.41 ± 0.25
Lead Size		
AWG #24 TCW	0.020 ± 0.0015	0.508 ± 0.038
Lead Length	1.5 ± 0.12	38.1 ± 3.05

Current Rating at 90°C Ambient

LT4K 35°C Rise
 LT10K 15°C Rise

Operating Temperature Range

LT4K -55°C to +125°C
 LT10K -55°C to +105°C

Maximum Power Dissipation at 90°C

Phenolic: LT4K 0.21 W
 Iron: LT10K 0.09 W
 Ferrite: LT10K 0.073 W

Weight Max. (Grams) 0.3

• For in-between values see Series 1782 (page 41)

Note (1026 Series only) Self Resonant Frequency (SRF) values are calculated and for reference only.

Marking DELEVAN; inductance with units and tolerance; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 1025R-16K

<i>Front:</i>	<i>Reverse:</i>
DELEVAN	2.2uH±10%
2.2uH±10%	R 0850B

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com


RF Inductors									
DASH NUMBER*	MIL DASH #	INDUCTANCE (μH)	TOLERANCE	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	MAXIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
MS75083- SERIES 1025 PHENOLIC CORE (LT4K)									
-94K	1	0.10	±10%	40	25.0	680.0	0.08	1380	
-96K	2	0.12	±10%	40	25.0	640.0	0.09	1300	
-00K	3	0.15	±10%	38	25.0	600.0	0.10	1230	
-02K	4	0.18	±10%	35	25.0	550.0	0.12	1120	
-04K	5	0.22	±10%	33	25.0	510.0	0.14	1040	
-06K	6	0.27	±10%	33	25.0	430.0	0.16	975	
-08K	7	0.33	±10%	30	25.0	410.0	0.22	830	
-10K	8	0.39	±10%	30	25.0	365.0	0.30	710	
-12K	9	0.47	±10%	30	25.0	330.0	0.35	660	
-14K	10	0.56	±10%	30	25.0	300.0	0.50	550	
-16K	11	0.68	±10%	28	25.0	275.0	0.60	500	
-18K	12	0.82	±10%	28	25.0	250.0	0.85	420	
-20K	13	1.0	±10%	25	25.0	230.0	1.00	390	
MS75084- SERIES 1025 IRON CORE (LT10K)									
-22K	1	1.2	±10%	25	7.9	150.0	0.18	620	
-24K	2	1.5	±10%	28	7.9	140.0	0.22	560	
-26K	3	1.8	±10%	30	7.9	125.0	0.30	480	
-28K	4	2.2	±10%	30	7.9	115.0	0.40	415	
-30K	5	2.7	±10%	37	7.9	100.0	0.55	355	
-32K	6	3.3	±10%	45	7.9	90.0	0.85	285	
-34K	7	3.9	±10%	45	7.9	80.0	1.00	263	
-36K	8	4.7	±10%	45	7.9	75.0	1.20	239	
-38K	9	5.6	±10%	50	7.9	65.0	1.80	195	
-40K	10	6.8	±10%	50	7.9	60.0	2.00	185	
-42K	11	8.2	±10%	55	7.9	55.0	2.70	160	
-44K	12	10.0	±10%	55	7.9	50.0	3.30	144	
-46K	13	12.0	±10%	45	2.5	40.0	2.70	160	
-48K	14	15.0	±10%	45	2.5	35.0	2.80	157	
-50K	15	18.0	±10%	50	2.5	30.0	3.10	149	
-52K	16	22.0	±10%	50	2.5	25.0	3.30	144	
-54K	17	27.0	±10%	50	2.5	20.0	3.50	140	
MS75085- SERIES 1025 FERRITE CORE (LT10K)									
-56K	1	33.0	±10%	45	2.5	24.0	3.40	130	
-58K	2	39.0	±10%	45	2.5	22.0	3.60	125	
-60K	3	47.0	±10%	45	2.5	20.0	4.50	110	
-62K	4	56.0	±10%	45	2.5	18.0	5.70	100	
-64K	5	68.0	±10%	50	2.5	15.0	6.70	92	
-66K	6	82.0	±10%	50	2.5	14.0	7.30	88	
-68K	7	100.0	±10%	50	2.5	13.0	8.00	84	
-70K	8	120.0	±10%	30	0.79	12.0	13.00	66	
-72K	9	150.0	±10%	30	0.79	11.0	15.00	61	
-74K	10	180.0	±10%	30	0.79	10.0	17.00	57	
-76K	11	220.0	±10%	30	0.79	9.0	21.00	52	
-78K	12	270.0	±10%	30	0.79	8.0	25.00	47	
-80K	13	330.0	±10%	30	0.79	7.0	28.00	45	
-82K	14	390.0	±10%	30	0.79	6.5	35.00	40	
-84K	15	470.0	±10%	30	0.79	6.0	42.00	36	
-86K	16	560.0	±10%	30	0.79	5.0	46.00	35	
-88K	17	680.0	±10%	30	0.79	4.2	60.00	30	
-90K	18	820.0	±10%	30	0.79	3.8	65.00	29	
-92K	19	1000.0	±10%	30	0.79	3.4	72.00	28	
SERIES 1026 PHENOLIC CORE (LT4K)									
-00M		0.022	±20%	50	50.0	900.0	0.010	3800	
-02K		0.027	±10%	40	25.0	875.0	0.030	2200	
-04K		0.033	±10%	40	25.0	850.0	0.035	2000	
-06K		0.039	±10%	40	25.0	825.0	0.040	1900	
-08K		0.047	±10%	40	25.0	800.0	0.045	1800	
-10K		0.056	±10%	40	25.0	775.0	0.050	1700	
-12K		0.068	±10%	40	25.0	750.0	0.060	1500	
-14K		0.082	±10%	40	25.0	725.0	0.070	1400	

Packaging Tape & reel: 12" reel, 3500 pieces max.; 14" reel, 6000 pieces max.

Made in the U.S.A.

SERIES**1782R**
1782**Molded Unshielded RF Coils**

Actual Size

**Physical Parameters**

	Inches	Millimeters
Length	0.250 ± 0.010	6.35 ± 0.25
Diameter	0.095 ± 0.010	2.41 ± 0.25
Lead Size		
AWG #24 TCW	0.020 ± 0.0015	0.508 ± 0.038
Lead Length	1.5 ± 0.12	38.1 ± 3.05

Current Rating at 90°C Ambient

LT4K 35°C Rise

LT10K 15°C Rise

Operating Temperature Range

LT4K -55°C to + 125°C

LT10K -55°C to + 105°C

Maximum Power Dissipation at 90°C

Phenolic: LT4K 0.21 W

Iron: LT10K 0.09 W

Ferrite: LT10K 0.073 W

Weight Max. (Grams) 0.3

Marking DELEVAN; inductance with units and tolerance; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 1782-49J

<i>Front:</i>	<i>Reverse:</i>
DELEVAN	16uH±5%
16uH±5%	0237A

Packaging Tape & reel: 12" reel, 3500 pieces max.; 14" reel, 6000 pieces max.

Made in the U.S.A.

INDUCTANCE (uH) ±10%
TEST FREQUENCY (MHz)
Q MINIMUM
SRF MINIMUM (MHz)
MAXIMUM (MHz)
DC RESISTANCE MAXIMUM (OHMS)
CURRENT RATING MAXIMUM (mA)

RF Inductors**SERIES 1782 PHENOLIC CORE (LT4K)**

-95J	0.11	40	25.0	640	0.09	1270
-97J	0.13	38	25.0	600	0.10	1200
-02J	0.16	35	25.0	550	0.12	1105
-03J	0.20	33	25.0	510	0.14	1025
-05J	0.24	33	25.0	430	0.16	960
-07J	0.30	30	25.0	410	0.22	815
-09J	0.36	30	25.0	365	0.30	700
-11J	0.43	30	25.0	330	0.35	650
-13J	0.51	30	25.0	300	0.50	545
-15J	0.62	28	25.0	275	0.60	495
-17J	0.75	28	25.0	250	0.85	415
-19J	0.91	25	25.0	230	1.00	385

SERIES 1782 IRON CORE (LT10K)

-21J	1.10	25	7.9	150	0.18	590
-23J	1.30	25	7.9	140	0.22	535
-25J	1.60	28	7.9	125	0.30	455
-27J	2.00	30	7.9	115	0.40	395
-29J	2.40	30	7.9	100	0.55	335
-31J	3.00	37	7.9	90	0.85	270
-33J	3.60	45	7.9	80	1.00	250
-35J	4.30	45	7.9	75	1.20	230
-37J	5.10	45	7.9	65	1.80	185
-39J	6.20	50	7.9	60	2.00	175
-41J	7.50	50	7.9	55	2.70	155
-43J	9.10	55	7.9	50	3.70	130
-45J	11.0	45	2.5	40	2.70	155
-47J	13.0	40	2.5	35	2.80	150
-49J	16.0	40	2.5	30	3.10	145
-51J	20.0	50	2.5	25	3.30	140
-53J	24.0	50	2.5	20	3.50	135

SERIES 1782 FERRITE CORE (LT10K)

-55J	30.0	45	2.5	20	3.40	130
-57J	36.0	45	2.5	22	3.60	125
-59J	43.0	45	2.5	20	4.50	110
-61J	51.0	45	2.5	18	5.70	100
-63J	62.0	45	2.5	15	6.70	92
-65J	75.0	50	2.5	14	7.30	88
-67J	91.0	50	2.5	13	8.00	84
-69J	110.0	30	0.790	12	13.0	66
-71J	130.0	30	0.790	11	15.0	61
-73J	160.0	30	0.790	10	17.0	57
-75J	200.0	30	0.790	9.0	21.0	52
-77J	240.0	30	0.790	8.0	25.0	47
-79J	300.0	30	0.790	7.0	28.0	45
-81J	360.0	30	0.790	6.5	35.0	40
-83J	430.0	30	0.790	6.0	42.0	36
-85J	510.0	30	0.790	5.0	46.0	35
-87J	620.0	30	0.790	4.0	60.0	30
-89J	750.0	30	0.790	3.8	65.0	29
-91J	910.0	30	0.790	3.4	72.0	28


Optional Tolerances: H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

Molded Unshielded RF Coils

Actual Size



Military Specifications MS14046 (LT10K); MS18130 (LT4K); MS90538 (LT10K);
g No MS # Issued

Physical Parameters

	Inches	Millimeters
Length	0.375 ± 0.010	9.53 ± 0.25
Diameter	0.156 ± 0.010	3.96 ± 0.25
Lead Size		
AWG #22 TCW	0.025 ± 0.002	0.635 ± 0.051
Lead Length	1.44 ± 0.12	36.58 ± 3.05

Current Rating at 90°C Ambient

LT4K 35°C Rise
LT10K 15°C Rise

Operating Temperature Range

LT4K -55°C to +125°C;
LT10K -55°C to +105°C

Maximum Power Dissipation at 90°C

LT4K 0.312 W
LT10K 0.134 W

Weight Max. (Grams) 0.9

• **For in-between values**, see Series 511 (page 44)

Marking DELEVAN; inductance with units and tolerance; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 1537-00J

Front:	Reverse:
DELEVAN	.15uH±5%
.15uH±5%	0841A

Packaging Tape & reel: 12" reel, 2500 pieces max.; 14" reel, 4000 pieces max.

Made in the U.S.A.

DASH NUMBER*	MIL DASH #	INDUCTANCE (μH)	TOLERANCE	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
MS18130- SERIES 1537 PHENOLIC CORE (LT4K)								
-00M	1	0.15	± 20%	50	25.0	525.0	0.03	2740
-02M	2	0.22	± 20%	50	25.0	450.0	0.055	2020
-04M	3	0.33	± 20%	45	25.0	360.0	0.09	1580
-06M	4	0.47	± 20%	45	25.0	310.0	0.12	1370
-07K	5	0.56	± 10%	50	25.0	280.0	0.135	1290
-08K	6	0.68	± 10%	50	25.0	250.0	0.15	1220
-10K	7	0.82	± 10%	50	25.0	220.0	0.22	1020
-12K	8	1.00	± 10%	50	25.0	200.0	0.29	880
-14K	9	1.20	± 10%	33	7.9	180.0	0.42	730
-16K	10	1.50	± 10%	33	7.9	160.0	0.50	670
-18K	11	1.80	± 10%	33	7.9	150.0	0.65	590
-20K	12	2.20	± 10%	33	7.9	135.0	0.95	485
-22K	13	2.70	± 10%	33	7.9	120.0	1.20	430
-24K	14	3.30	± 10%	33	7.9	110.0	2.00	335
-26K	15	3.90	± 10%	33	7.9	100.0	2.30	310
-28K	16	4.70	± 10%	33	7.9	90.0	2.60	294
MS14046- SERIES 1537 IRON CORE (LT10K)								
-30K	1	5.60	± 10%	45	7.9	60.0	0.32	565
-32K	2	6.80	± 10%	50	7.9	55.0	0.50	450
-34K	3	8.20	± 10%	50	7.9	50.0	0.60	410
-36K	4	10.0	± 10%	55	7.9	45.0	0.90	335
-38K	5	12.0	± 10%	65	2.5	42.0	1.10	305
-40K	6	15.0	± 10%	65	2.5	40.0	1.40	271
-42K	7	18.0	± 10%	75	2.5	34.0	2.25	213
-44K	8	22.0	± 10%	75	2.5	30.0	2.50	202
-46J	●	24.0	± 5%	60	2.5	26.0	2.50	202
-47K	9	27.0	± 10%	60	2.5	25.0	2.60	198
-48J	●	27.0	± 5%	60	2.5	25.0	2.60	198
-50J	●	30.0	± 5%	65	2.5	21.0	2.80	191
-51K	10	33.0	± 10%	65	2.5	19.0	3.00	185
-52J	●	33.0	± 5%	65	2.5	19.0	3.00	185
MS90538- SERIES 1537 IRON CORE (LT10K)								
-54J	1	36.0	± 5%	60	2.5	15.5	2.50	202
-56J	2	39.0	± 5%	60	2.5	14.5	2.60	198
-58J	3	43.0	± 5%	60	2.5	13.7	2.70	194
-60J	4	47.0	± 5%	55	2.5	13.0	2.75	193
-62J	5	51.0	± 5%	55	2.5	12.7	2.85	189
-64J	6	56.0	± 5%	55	2.5	12.0	3.00	184
-66J	7	62.0	± 5%	55	2.5	11.5	3.15	180
-68J	8	68.0	± 5%	55	2.5	11.0	3.30	176
-70J	9	75.0	± 5%	55	2.5	10.5	3.70	166
-72J	10	82.0	± 5%	50	2.5	10.3	3.90	162
-74J	11	91.0	± 5%	50	2.5	10.0	4.30	154
-76J	12	100.0	± 5%	50	2.5	9.5	4.50	151
-78J	13	110.0	± 5%	60	0.79	8.9	4.90	144
-80J	14	120.0	± 5%	65	0.79	8.7	5.20	140
-82J	15	130.0	± 5%	65	0.79	8.5	5.45	137
-84J	16	150.0	± 5%	65	0.79	8.0	6.05	130
-86J	17	160.0	± 5%	65	0.79	7.5	6.40	126
-88J	18	180.0	± 5%	65	0.79	7.0	6.75	123
-90J	19	200.0	± 5%	65	0.79	6.5	7.10	120
-92J	20	220.0	± 5%	65	0.79	6.2	7.45	117
-94J	21	240.0	± 5%	65	0.79	5.9	7.80	115

Parts listed above are QPL/MIL qualified

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com


SERIES

511R
511



Molded Unshielded RF Coils

Actual Size



Physical Parameters

Inches	Millimeters	
Length	0.375 ± 0.010	9.53 ± 0.25
Diameter	0.156 ± 0.010	3.96 ± 0.25
Lead Size		
AWG #22 TCW	0.025 ± 0.002	0.635 ± 0.051
Lead Length	1.44 ± 0.12	36.58 ± 3.05

Current Rating at 90°C Ambient

Phenolic 35°C Rise
Iron 15°C Rise

Operating Temperature Range

Phenolic -55°C to +125°C;
Iron -55°C to +105°C

Maximum Power Dissipation at 90°C

Phenolic 0.312 W
Iron 0.134 W

Weight Max. (Grams) 0.9

Marking DELEVAN; inductance with units and tolerance;
date code (YYWWL). Note: An R before the date code
indicates a RoHS component.

Example: 511-16J

Front:	Reverse:
DELEVAN	4.3uH±5%
4.3uH±5%	0628C

Packaging Tape & reel: 12" reel, 2500 pieces max.; 14" reel, 4000 pieces max.

Made in the U.S.A.

DASH NUMBER*	INDUCTANCE (μH) ±5%	TEST FREQUENCY (MHz)	Q MINIMUM	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
SERIES 511 PHENOLIC CORE						
-2J	0.16	50	25.0	525	0.040	2370
-3J	0.18	50	25.0	500	0.043	2285
-4J	0.20	50	25.0	475	0.047	2185
-6J	0.24	45	25.0	415	0.060	1935
-7J	0.27	45	25.0	400	0.070	1790
-8J	0.30	45	25.0	380	0.080	1675
-10J	0.36	45	25.0	345	0.098	1515
-11J	0.39	45	25.0	330	0.100	1500
-12J	0.43	45	25.0	315	0.110	1430
-14J	0.51	45	25.0	300	0.130	1315
-16J	0.62	50	25.0	260	0.140	1265
-18J	0.75	50	25.0	230	0.180	1115
-20J	0.91	50	25.0	210	0.240	970
-22J	1.10	33	7.9	190	0.420	730
-24J	1.30	33	7.9	170	0.480	685
-26J	1.60	33	7.9	155	0.600	610
-28J	2.00	33	7.9	140	0.800	530
-30J	2.40	33	7.9	130	1.100	450
-32J	3.00	33	7.9	115	1.800	355
-34J	3.60	33	7.9	105	2.150	325
-36J	4.30	33	7.9	95	2.400	305
SERIES 511 IRON CORE						
-38J	5.10	35	7.9	65	0.360	570
-40J	6.20	45	7.9	60	0.470	455
-42J	7.50	50	7.9	55	0.550	420
-44J	9.10	55	7.9	50	0.800	350
-46J	11.0	60	2.5	44	1.050	310
-48J	13.0	65	2.5	40	1.200	285
-50J	16.0	70	2.5	38	1.800	230
-52J	20.0	75	2.5	30	2.500	195


Optional Tolerances: H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

SERIES**1638R
1638****Molded Unshielded RF Coils****RF Inductors**

Actual Size



DASH NUMBER*	INDUCTANCE (μ H) $\pm 5\%$	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
SERIES 1638 IRON CORE						
-00J	270	65	0.79	5.7	11.0	143
-02J	300	65	0.79	5.4	11.5	140
-04J	330	65	0.79	5.1	12.0	136
-06J	360	65	0.79	4.8	12.5	134
-08J	390	65	0.79	4.5	16.3	117
-10J	430	65	0.79	4.2	17.1	115
-12J	470	65	0.79	3.9	17.9	112
-14J	510	65	0.79	3.7	18.8	109
-16J	560	65	0.79	3.8	19.5	107
-18J	620	65	0.79	3.3	25.9	93
-20J	680	65	0.79	3.1	27.2	91
-22J	750	65	0.79	2.9	28.6	88
-24J	820	65	0.79	2.7	30.0	86
-26J	910	65	0.79	2.5	31.5	84
-28J	1000	65	0.79	2.3	33.0	82

Optional Tolerances: H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com**Physical Parameters**

	Inches	Millimeters
Length	0.375 ± 0.010	9.53 ± 0.25
Diameter	0.156 ± 0.010	3.96 ± 0.25
Lead Size		
AWG #22 TCW	0.025 ± 0.002	0.635 ± 0.051
Lead Length	1.44 ± 0.12	36.58 ± 3.05

Current Rating at 90°C Ambient 35°C Rise**Operating Temperature** -55°C to +125°C**Maximum Power Dissipation at 90°C** 0.312 W**Weight Max.** (Grams) 1.0**Core Material** Iron

Marking DELEVAN; inductance with units and tolerance; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 1638R-16J

Front: DELEVAN
560uH $\pm 5\%$

Reverse: R 0828A

Packaging Tape & reel: 12" reel, 2500 pieces max.; 14" reel, 4000 pieces max.

Made in the U.S.A.


SERIES

1840R
1840



Molded Unshielded RF Coils

Actual Size



Military Specifications

MS75008 (LT4K); MS75101 (LT10K)

Physical Parameters

	Inches	Millimeters
Length	0.437 ± 0.010	11.10 ± 0.25
Diameter	0.187 ± 0.010	4.75 ± 0.25
Lead Size		
AWG #22 TCW	0.025 ± 0.002	0.635 ± 0.051
Lead Length	1.44 ± 0.12	36.58 ± 3.05

Current Rating at 90°C Ambient

LT4K 35°C Rise
LT10K 15°C Rise

Operating Temperature Range

LT4K -55°C to +125°C;
LT10K -55°C to +105°C

Maximum Power Dissipation at 90°C

LT4K 0.385 W
LT10K 0.165 W

Weight Max. (Grams) 0.95

Marking DELEVAN; inductance with units and tolerance; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 1840R-18K

Front:	Reverse:
DELEVAN	3.3uH±10%
3.3uH±10%	R 0910A

Packaging Tape & reel: 12" reel, 2500 pieces max.; 14" reel, 3000 pieces max.

⦿ No MS # Issued

Made in the U.S.A.

DASH NUMBER*	MIL DASH #	INDUCTANCE (μH)	TOLERANCE	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
MS75008- SERIES 1840 PHENOLIC CORE (LT4K)								
-00M	21	0.15	± 20%	55	25.0	510	0.030	3050
-02M	22	0.22	± 20%	55	25.0	415	0.035	2820
-04M	23	0.33	± 20%	55	25.0	350	0.050	2360
-05M	24	0.39	± 20%	55	25.0	300	0.080	1860
-06M	24	0.47	± 20%	55	25.0	300	0.080	1860
-07K	25	0.56	± 10%	55	25.0	270	0.100	1670
-08K	26	0.68	± 10%	55	25.0	250	0.120	1520
-09K	27	0.82	± 10%	55	25.0	220	0.180	1240
-10K	28	1.00	± 10%	55	25.0	200	0.250	1050
-11K	29	1.20	± 10%	35	7.9	180	0.400	835
-12K	30	1.50	± 10%	35	7.9	170	0.485	755
-13K	31	1.80	± 10%	35	7.9	150	0.740	610
-14K	32	2.20	± 10%	35	7.9	140	0.900	555
-16K	33	2.70	± 10%	35	7.9	120	1.100	525
MS75101- SERIES 1840 IRON CORE (LT10K)								
-18K	1	3.30	± 10%	35	7.9	70	0.120	1020
-20K	2	3.90	± 10%	35	7.9	65	0.155	900
-22K	3	4.70	± 10%	35	7.9	60	0.210	775
-24K	4	5.60	± 10%	35	7.9	50	0.280	670
-26K	5	6.80	± 10%	35	7.9	50	0.375	580
-28K	6	8.20	± 10%	35	7.9	48	0.400	560
-30K	7	10.0	± 10%	35	7.9	42	0.600	455
-32K	8	12.0	± 10%	50	2.5	36	0.850	385
-34K	9	15.0	± 10%	55	2.5	30	1.200	324
-35K	10	18.0	± 10%	60	2.5	30	1.800	265
-36K	11	22.0	± 10%	60	2.5	24	2.000	251
-38K	12	27.0	± 10%	65	2.5	22	2.750	214

Parts listed above are QPL/MIL qualified

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com


SERIES

1944R & 1945R
1944 & 1945



Molded Unshielded RF Coils

Actual Size



Test Methods MIL-PRF-15305 test methods, only.
MS21389-01 to MS21389-17, reference - 1944 Series
MS21390-01 to MS21390-39, reference - 1945 Series

Physical Parameters

	Inches	Millimeters
Length	0.420 to 0.447	10.67 to 11.35
Diameter	0.168 to 0.193	4.27 to 4.90
Lead Size		
AWG #22 TCW	0.023 to 0.027	0.584 to 0.686
Lead Length	1.30 Min.	33.02 Min.

Current Rating at 90°C Ambient 35°C Rise

Operating Temperature -55°C to +125°C

Maximum Power Dissipation at 90°C

Series 1944: 0.385 W
Series 1945: 0.330 W

Marking DELEVAN; inductance with units and tolerance; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 1944-14M

Front: Reverse:
DELEVAN 0704A
1.2uH±20%

Packaging Tape & reel: 12" reel, 2500 pieces max.; 14" reel, 3000 pieces max.

Made in the U.S.A.

DASH NUMBER*	MIL DASH # (Ref.)	INDUCTANCE (uH)	TOLERANCE	Q TEST FREQUENCY (MHz)	INDUCTANCE TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	Q MINIMUM	MAXIMUM (MHz)	DC RESISTANCE (OHMS)	CURRENT RATING MAXIMUM (mA)
--------------	-------------------	-----------------	-----------	------------------------	---------------------------------	-------------------	-----------	---------------	----------------------	-----------------------------

MS21389 (Reference) – SERIES 1944 PHENOLIC CORE										
-01M	1	0.10	± 20%	25	50	75	400	0.020	4000	
-02M	2	0.12	± 20%	25	50	75	400	0.025	3500	
-03M	3	0.15	± 20%	25	50	75	400	0.030	3000	
-04M	4	0.18	± 20%	25	50	65	400	0.030	3000	
-05M	5	0.22	± 20%	25	50	65	400	0.030	3000	
-06M	6	0.27	± 20%	25	45	65	376	0.040	2700	
-07M	7	0.33	± 20%	25	40	65	352	0.045	2500	
-08M	8	0.39	± 20%	25	40	60	320	0.070	2000	
-09M	9	0.47	± 20%	25	25	55	288	0.070	2000	
-10M	10	0.56	± 20%	25	25	50	264	0.100	1700	
-11M	11	0.68	± 20%	25	25	50	240	0.120	1500	
-12M	12	0.82	± 20%	25	25	45	220	0.160	1300	
-13M	13	1.00	± 20%	25	20	45	200	0.230	1100	
-14M	14	1.20	± 20%	7.9	20	45	176	0.280	1000	
-15K	15	1.50	± 10%	7.9	15	45	160	0.380	850	
-16K	16	1.80	± 10%	7.9	15	45	144	0.540	720	
-17K	17	2.20	± 10%	7.9	15	45	132	0.750	610	

MS21390 (Reference) – SERIES 1945 IRON CORE										
-01K	1	2.70	± 10%	7.9	10	55	88	0.11	1600	
-02K	2	3.30	± 10%	7.9	10	55	80	0.14	1400	
-03K	3	3.90	± 10%	7.9	10	60	76	0.19	1200	
-04K	4	4.70	± 10%	7.9	7.9	70	72	0.28	1000	
-05K	5	5.60	± 10%	7.9	7.9	65	64	0.34	900	
-06K	6	6.80	± 10%	7.9	7.9	65	56	0.43	800	
-07K	7	8.20	± 10%	7.9	7.9	60	52	0.56	720	
-08K	8	10.0	± 10%	7.9	5.0	60	48	0.67	650	
-09K	9	12.0	± 10%	2.5	5.0	65	42.4	0.81	590	
-10K	10	15.0	± 10%	2.5	2.5	80	37.6	1.15	500	
-11K	11	18.0	± 10%	2.5	2.5	75	34.4	1.40	460	
-12K	12	22.0	± 10%	2.5	2.5	75	32.0	1.60	430	
-13J	13	27.0	± 5%	2.5	2.5	75	28.8	2.30	360	
-14J	14	33.0	± 5%	2.5	2.5	85	25.6	3.30	300	
-15J	15	39.0	± 5%	2.5	2.5	80	20.8	3.32	290	
-16J	16	47.0	± 5%	2.5	2.5	80	17.6	3.70	275	
-17J	17	56.0	± 5%	2.5	2.5	75	15.2	3.99	265	
-18J	18	68.0	± 5%	2.5	2.5	75	12.8	4.48	250	
-19J	19	82.0	± 5%	2.5	2.5	75	10.4	5.07	235	
-20J	20	100	± 5%	2.5	1.5	75	8.00	5.78	220	
-21J	21	120	± 5%	0.79	0.79	65	5.76	5.00	170	
-22J	22	150	± 5%	0.79	0.79	65	5.36	5.80	164	
-23J	23	180	± 5%	0.79	0.79	65	5.04	6.60	158	
-24J	24	220	± 5%	0.79	0.79	65	4.72	7.40	155	
-25J	25	270	± 5%	0.79	0.79	65	4.48	8.00	150	
-26J	26	300	± 5%	0.79	0.79	65	4.24	8.60	145	
-27J	27	330	± 5%	0.79	0.79	65	4.00	8.90	142	
-28J	28	360	± 5%	0.79	0.79	65	3.76	9.60	137	
-29J	29	390	± 5%	0.79	0.79	65	3.60	9.90	135	
-30J	30	430	± 5%	0.79	0.79	65	3.44	10.4	131	
-31J	31	470	± 5%	0.79	0.79	65	3.20	10.9	128	
-32J	32	510	± 5%	0.79	0.79	65	3.04	11.6	124	
-33J	33	560	± 5%	0.79	0.79	60	2.88	11.8	123	
-34J	34	620	± 5%	0.79	0.79	60	2.80	12.5	120	
-35J	35	680	± 5%	0.79	0.79	60	2.72	13.5	115	
-36J	36	750	± 5%	0.79	0.79	60	2.64	14.0	113	
-37J	37	820	± 5%	0.79	0.79	60	2.48	15.0	110	
-38J	38	910	± 5%	0.79	0.79	60	2.40	15.5	107	
-39J	39	1000	± 5%	0.79	0.79	60	2.24	16.5	104	

Optional Tolerances: K = 10% J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com


SERIES

**2150R
2150**



Molded Unshielded RF Coils

Actual Size



Military Specifications

MS90542 (LT4K); MS14052(LT10K)

Physical Parameters

	Inches	Millimeters
Length	0.560 ± .0010	14.22 ± 0.25
Diameter	0.220 ± 0.010	5.59 ± 0.25
Lead Size		
AWG #22 TCW	0.025 ± 0.002	0.635 ± 0.051
Lead Length	1.44 ± 0.12	36.58 ± 3.05

Current Rating at 90°C Ambient

LT4K 35°C Rise
LT10K 15°C Rise

Operating Temperature

LT4K -55°C to +125°C
LT10K -55°C to +105°C

Maximum Power Dissipation at 90°C

LT4K .427 W
LT10K .183 W

Weight Max. (Grams) 1.5

Marking DELEVAN; inductance with units and tolerance; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 2150R-28K

<i>Front:</i>	<i>Reverse:</i>
DELEVAN	15uH±10%
15uH±10%	R 0904A

DASH NUMBER*	MIL DASH #	INDUCTANCE (μH) ±10%	TEST FREQUENCY (MHz)	Q MINIMUM	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
MS90542- SERIES 2150 PHENOLIC CORE (LT4K)							
-00K	1	0.47	65	25.0	300	0.06	2270
-01K	2	0.56	65	25.0	270	0.07	2100
-02K	3	0.68	65	25.0	240	0.08	1960
-03K	4	0.82	65	25.0	220	0.11	1670
-04K	5	1.00	65	25.0	200	0.14	1480
-05K	6	1.20	40	7.9	180	0.19	1270
-06K	7	1.50	40	7.9	160	0.28	1050
-07K	8	1.80	40	7.9	150	0.37	915
-08K	9	2.20	40	7.9	135	0.50	785
-10K	10	2.70	40	7.9	120	0.65	690
-12K	11	3.30	40	7.9	105	1.00	555
-14K	12	3.90	40	7.9	100	1.20	505
-16K	13	4.70	40	7.9	90	1.80	415
MS14052- SERIES 2150 IRON CORE (LT10K)							
-18K	1	5.60	35	7.9	55	0.13	1040
-20K	2	6.80	35	7.9	50	0.20	835
-22K	3	8.20	35	7.9	44	0.22	795
-24K	4	10.0	35	7.9	42	0.26	735
-26K	5	12.0	45	2.5	34	0.45	560
-28K	6	15.0	45	2.5	32	0.52	520
-30K	7	18.0	50	2.5	28	0.70	445
-32K	8	22.0	60	2.5	24	1.00	375
-34K	9	27.0	60	2.5	22	1.30	330
-36K	10	33.0	60	2.5	20	1.50	305
-38K	11	39.0	70	2.5	18	2.00	264

Parts listed above are QPL/MIL qualified

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #


For surface finish information, refer to www.delevanfinishes.com

Packaging Tape & reel: 12" reel, 1000 pieces max.; 14" reel, 1500 pieces max.

Made in the U.S.A.

Molded Unshielded RF Coils

Actual Size
(Mold Size B)



Military Specifications MS90539 (LT10K);
MS90540 (LT10K); MS90541 (LT10K);
g No MS # Issued

Physical Parameters

Mold Size	A	B	C
Length			
Inches ± .010	0.440	0.560	0.740
mm ± .25	11.18	14.22	18.80
Diameter			
Inches ± .010	0.190	0.215	0.240
mm ± .25	4.83	5.46	6.10
Lead Type & Size			
AWG #	#22	#21	#20
TCW ± .002 Inches	0.025	0.028	0.032
[TCW ± .051 mm]	0.635	0.711	0.813
Lead Length			
Inches ± .12	1.44	1.44	1.44
mm ± 3.05	36.58	36.58	36.58
Maximum Power Dissipation			
at 90°C W	0.166	0.182	0.213
Weight Max.			
(Grams)	0.95	1.5	2.5

Current Rating at 90°C Ambient 15°C Rise

Operating Temperature Range -55°C to +105°C
Core Material Iron (LT10K)

Marking DELEVAN; inductance with units and tolerance;
date code (YYWWL). Note: An R before the date code
indicates a RoHS component.
Example: 2500-16J

Front: DELEVAN 560uH±5%
Reverse: 560uH±5% 0824C

DASH NUMBER*	MIL DASH #	INDUCTANCE (μH) ±5%	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)	MOLD SIZE
MS90539 • SERIES 2500 IRON CORE (LT10K)							
-00J	1	270	65	0.790	5.60	8.2	126 A
-02J	2	300	65	0.790	5.3	8.7	122 A
-04J	3	330	65	0.790	5.0	9.1	120 A
-06J	4	360	65	0.790	4.7	9.6	115 A
-08J	5	390	65	0.790	4.5	10.0	114 A
-10J	6	430	65	0.790	4.3	10.6	111 A
-12J	7	470	65	0.790	4.0	11.0	108 A
-14J	8	500	65	0.790	3.7	11.3	106 A
-15J	8	510	65	0.790	3.8	11.6	105 A
-16J	9	560	65	0.790	3.6	12.3	104 A
-18J	10	620	60	0.790	3.5	13.0	101 A
-20J	11	680	60	0.790	3.4	13.7	97 A
-22J	12	750	60	0.790	3.3	14.4	95 A
-24J	13	820	60	0.790	3.1	15.1	92 A
-26J	14	910	60	0.790	2.9	15.8	91 A
-28J	15	1000	60	0.790	2.8	16.5	88 A
MS90540 • SERIES 2500 IRON CORE (LT10K)							
-30J	1	1100	60	0.250	2.8	21.0	81 B
-32J	2	1200	60	0.250	2.7	22.0	79 B
-34J	3	1300	60	0.250	2.6	23.0	78 B
-36J	4	1500	65	0.250	2.4	25.0	76 B
-38J	5	1600	65	0.250	2.3	26.0	74 B
-40J	6	1800	65	0.250	2.2	28.0	71 B
-42J	7	2000	65	0.250	2.1	29.0	69 B
-44J	8	2200	70	0.250	2.0	30.0	68 B
-46J	9	2400	70	0.250	1.9	31.0	67 B
-48J	10	2700	70	0.250	1.8	33.0	65 B
-50J	11	3000	70	0.250	1.7	35.0	63 B
-52J	12	3300	70	0.250	1.6	38.0	61 B
-54J	13	3600	70	0.250	1.5	40.0	59 B
MS90541 • SERIES 2500 IRON CORE (LT10K)							
-56J	1	3900	80	0.250	1.45	44.0	62 C
-58J	2	4300	80	0.250	1.40	46.0	60 C
-60J	3	4700	80	0.250	1.35	48.0	59 C
-62J	4	5000	80	0.250	1.30	50.0	58 C
-63J	5	5100	80	0.250	1.30	50.0	58 C
-64J	5	5600	80	0.250	1.25	53.0	56 C
-66J	6	6200	80	0.250	1.20	56.0	55 C
-68J	7	6800	80	0.250	1.15	59.0	54 C
-70J	8	7500	80	0.250	1.10	62.0	52 C
-72J	9	8200	80	0.250	1.05	65.0	51 C
-74J	10	9100	80	0.250	1.0	68.0	49 C
-76J	11	10000	80	0.250	0.95	72.0	48 C

Parts listed above are QPL/MIL qualified

Optional Tolerances: H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com


Packaging Tape & reel: Mold sizes "A" and "C": 12" reel, 2500 pieces max.; 14" reel, 3000 pieces max.
Mold size "B": 12" reel, 1000 pieces max.; 14" reel, 1500 pieces max.
Made in the U.S.A.

SERIES

**2890R
2890**



Molded Unshielded RF Coils



Military Specifications

MS91189 (LT4K); MS75103(LT10K)

Physical Parameters

	Inches	Millimeters
Length	0.900 ± 0.010	22.86 ± 0.25
Diameter	0.280 ± 0.010	7.11 ± 0.25
Lead Size		
AWG #21 TCW	0.028 ± 0.002	0.711 ± 0.051
Lead Length	1.44 ± 0.12	36.58 ± 3.05

Current Rating at 90°C Ambient

LT4K 35°C Rise
LT10K 15°C Rise

Operating Temperature Range

LT4K -55°C to +125°C
LT10K -55°C to +105°C

Maximum Power Dissipation at 90°C

LT4K 0.598 W
LT10K 0.256 W

Weight Max. (Grams) 3.9

Marking DELEVAN; inductance with units and tolerance;
date code (YYWWL). Note: An R before the date code
indicates a RoHS component.

Example: 2890R-16F

<i>Front:</i>	<i>Reverse:</i>
DELEVAN	6.8uH±1%
6.8uH±1%	R 0518B

Packaging Tape & reel: 12" reel, 800 pieces max.; 14"
reel, 1300 pieces max.

Made in the U.S.A.

DASH NUMBER*	MIL DASH #	INDUCTANCE (μH) ±10%	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
MS91189- SERIES 2890 PHENOLIC CORE (LT4K)							
-00K	14	1.2	60	7.9	170	0.075	2400
-02K	15	1.5	60	7.9	160	0.090	2190
-03K	16	1.8	60	7.9	140	0.135	1790
-04K	17	2.2	60	7.9	125	0.160	1640
-06K	18	2.7	60	7.9	115	0.220	1400
-08K	19	3.3	60	7.9	100	0.305	1190
-10K	20	3.9	60	7.9	95	0.450	980
-12K	21	4.7	60	7.9	90	0.560	880
-14K	22	5.6	60	7.9	80	0.745	760
-16K	23	6.8	60	7.9	75	1.05	640
-18K	24	8.2	60	7.9	68	1.40	555
-20K	25	10.0	60	7.9	60	1.90	475
-22K	26	12.0	40	2.5	53	2.65	405
-24K	27	15.0	40	2.5	50	3.25	365
-26K	28	18.0	40	2.5	45	4.15	320
MS75103- SERIES 2890 IRON CORE (LT10K)							
-28K	1	22.0	50	2.5	24	0.295	815
-30K	2	27.0	45	2.5	22	0.35	750
-32K	3	33.0	60	2.5	19	0.55	595
-34K	4	39.0	55	2.5	18	0.65	550
-36K	5	47.0	65	2.5	16	1.00	445
-38K	6	56.0	65	2.5	14	1.15	410
-39K	7	68.0	75	2.5	13	1.85	325
-40K	8	82.0	75	2.5	12	2.10	305
-42K	9	100.0	75	2.5	12	2.50	279
-44K	10	120.0	95	0.79	10	4.10	219

Parts listed above are QPL/MIL qualified

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #


For surface finish information, refer to www.delevanfinishes.com

SERIES

4470R
4470



Molded Unshielded RF Coils



Physical Parameters

	Inches	Millimeters
Length	0.880 to 0.910	22.35 to 23.11
Diameter	0.270 to 0.310	6.86 to 7.87
Lead Size		
AWG #21 TCW	0.0260 to .0305	0.66 to 0.77
Lead Length	1.30 Min.	33.02 Min.

Operating Temperature -55°C to +125°C

Current Rating at 90°C Ambient 35°C Rise

Maximum Power Dissipation at 90°C 0.540 W

Test Methods MIL-PRF-15305 test methods, only.
MS21380-01 to MS21380-49, reference.

Marking DELEVAN; inductance with units and tolerance;
date code (YYWWL). Note: An R before the date code
indicates a RoHS component.

Example: 4470-49J

<i>Front:</i>	<i>Reverse:</i>
DELEVAN	0915B
10mH±5%	

Packaging Tape & reel: 12" reel, 800 pieces max.; 14" reel, 1300 pieces max.

Made in the U.S.A.

DASH NUMBER*	MIL DASH # (Ref.)	INDUCTANCE (μH)	TOLERANCE	Q TEST FREQUENCY (MHz)	INDUCTANCE TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	Q MINIMUM	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
--------------	-------------------	-----------------	-----------	------------------------	---------------------------------	-------------------	-----------	------------------------------	-----------------------------

MS21380 (Reference) – SERIES 4470 IRON CORE									
-01K	1	1.0	± 10%	25.0	15.0	130	136.0	0.03	4000
-02K	2	1.2	± 10%	7.9	15.0	130	124.0	0.03	4000
-03K	3	1.5	± 10%	7.9	10.0	130	112.0	0.03	4000
-04K	4	1.8	± 10%	7.9	10.0	130	100.0	0.03	4000
-05K	5	2.2	± 10%	7.9	10.0	130	92.0	0.04	3500
-06K	6	2.7	± 10%	7.9	10.0	100	81.6	0.04	3500
-07K	7	3.3	± 10%	7.9	7.9	100	72.0	0.04	3500
-08K	8	3.9	± 10%	7.9	7.9	80	68.0	0.05	3100
-09K	9	4.7	± 10%	7.9	7.9	75	64.0	0.05	3100
-10K	10	5.6	± 10%	7.9	7.9	65	57.6	0.06	3000
-11K	11	6.8	± 10%	7.9	7.9	65	52.0	0.06	3000
-12K	12	8.2	± 10%	7.9	7.9	65	45.6	0.09	2400
-13K	13	10.0	± 10%	7.9	5.0	75	40.0	0.15	1800
-14K	14	12.0	± 10%	2.5	5.0	75	36.0	0.20	1600
-15J	15	15.0	± 5%	2.5	5.0	75	32.0	0.30	1300
-16J	16	18.0	± 5%	2.5	5.0	75	28.8	0.40	1150
-17J	17	22.0	± 5%	2.5	2.5	75	25.6	0.50	1000
-18J	18	27.0	± 5%	2.5	2.5	70	24.0	0.60	900
-19J	19	33.0	± 5%	2.5	2.5	70	22.4	0.70	850
-20J	20	39.0	± 5%	2.5	2.5	70	20.8	1.00	720
-21J	21	47.0	± 5%	2.5	2.5	75	20.0	1.30	620
-22J	22	56.0	± 5%	2.5	2.5	80	17.6	1.80	540
-23J	23	68.0	± 5%	2.5	2.5	100	16.0	2.40	450
-24J	24	82.0	± 5%	2.5	2.5	100	14.4	2.80	425
-25J	25	100.0	± 5%	2.5	1.5	100	13.6	3.20	400
-26J	26	120.0	± 5%	0.79	1.5	100	12.0	4.10	360
-27J	27	150.0	± 5%	0.79	1.0	100	11.2	6.40	280
-28J	28	180.0	± 5%	0.79	1.0	95	9.60	9.50	240
-29J	29	220.0	± 5%	0.79	1.0	95	8.80	12.0	200
-30J	30	270.0	± 5%	0.79	1.0	70	7.20	13.0	195
-31J	31	330.0	± 5%	0.79	0.79	65	6.00	14.0	190
-32J	32	390.0	± 5%	0.79	0.79	65	5.20	15.5	180
-33J	33	470.0	± 5%	0.79	0.79	60	4.40	17.0	170
-34J	34	560.0	± 5%	0.79	0.50	75	3.20	18.5	165
-35J	35	680.0	± 5%	0.79	0.50	75	2.56	20.0	155
-36J	36	820.0	± 5%	0.79	0.50	75	2.24	22.0	150
-37J	37	1000.0	± 5%	0.79	0.50	75	1.92	24.0	145
-38J	38	1200.0	± 5%	0.79	0.50	75	1.68	27.0	137
-39J	39	1500.0	± 5%	0.79	0.40	75	1.52	29.0	130
-40J	40	1800.0	± 5%	0.79	0.40	65	1.36	32.0	125
-41J	41	2200.0	± 5%	0.25	0.25	65	1.20	35.0	120
-42J	42	2700.0	± 5%	0.25	0.25	65	1.04	40.0	112
-43J	43	3300.0	± 5%	0.25	0.25	65	0.96	45.0	105
-44J	44	3900.0	± 5%	0.25	0.25	65	0.80	49.0	100
-45J	45	4700.0	± 5%	0.25	0.25	65	0.76	53.0	95
-46J	46	5600.0	± 5%	0.25	0.25	65	0.68	60.0	90
-47J	47	6800.0	± 5%	0.25	0.25	65	0.60	67.0	85
-48J	48	8200.0	± 5%	0.25	0.25	65	0.52	75.0	82
-49J	49	10000.0	± 5%	0.25	0.15	65	0.47	80.0	80


Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

Molded Shielded RF Coils

Actual Size



Military Specifications

MS21426 (LT10K); MS21427 (LT10K)

Physical Parameters

	Inches	Millimeters
Length	0.250 ± 0.010	6.35 ± 0.25
Diameter	0.095 ± 0.010	2.41 ± 0.25
Lead Size		
AWG #24 TCW	0.020 ± 0.0015	0.508 ± 0.038
Lead Length	1.5 ± 0.12	38.10 ± 3.05

Current Rating at 90°C Ambient 15°C Rise

Operating Temperature Range -55°C to +105°C

Maximum Power Dissipation at 90°C 0.0585 W

Weight Max. (Grams) 0.25

Incremental Current Current level which causes a Max. of 5% change in inductance.

Coupling 3% Max.

† Self Resonant Frequency (SRF) values are calculated and to be used for reference only.

Marking DELEVAN; inductance with units and tolerance; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 0925R-472K

<i>Front:</i>	<i>Reverse:</i>
DELEVAN	4.7uH±10%
4.7uH±10%	R 0902A

Packaging Tape & reel: 12" reel, 3500 pieces max.; 14" reel, 6000 pieces max.

Made in the U.S.A.

DASH NUMBER*	MIL DASH #	INDUCTANCE (uH) ±10%	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)	INCREMENTAL CURRENT (mA)
MS21426- SERIES 0925 IRON CORE & SLEEVE (LT10K)								
-101K	1	0.10	54	25.0	490.0†	0.10	670	670
-121K	2	0.12	52	25.0	430.0†	0.11	635	635
-151K	3	0.15	50	25.0	415.0†	0.12	610	610
-181K	4	0.18	49	25.0	375.0†	0.13	585	585
-221K	5	0.22	47	25.0	330.0†	0.15	545	545
-271K	6	0.27	46	25.0	300.0†	0.16	530	530
-331K	7	0.33	44	25.0	260.0†	0.18	495	495
-391K	8	0.39	42	25.0	230.0	0.19	485	485
-471K	9	0.47	41	25.0	220.0	0.21	460	460
-561K	10	0.56	41	25.0	210.0	0.23	440	440
-681K	11	0.68	39	25.0	180.0	0.24	430	430
-821K	12	0.82	38	25.0	165.0	0.27	405	405
-102K	13	1.00	37	25.0	150.0	0.30	385	385
-122K	14	1.20	40	7.9	130.0	0.73	247	247
-152K	15	1.50	41	7.9	115.0	0.86	228	228
-182K	16	1.80	43	7.9	105.0	0.95	217	217
-222K	17	2.20	45	7.9	95.0	1.10	202	202
-272K	18	2.70	48	7.9	90.0	1.20	193	193
-332K	19	3.30	49	7.9	80.0	1.30	185	185
-392K	20	3.90	50	7.9	75.0	1.50	173	173
-472K	21	4.70	53	7.9	70.0	2.40	136	136
-562K	22	5.60	54	7.9	60.0	2.90	124	124
-682K	23	6.80	55	7.9	55.0	3.20	118	118
-822K	24	8.20	55	7.9	53.0	3.60	111	111
-103K	25	10.0	57	7.9	50.0	4.00	106	106
-123K	26	12.0	36	2.5	35.0	3.00	122	122
-153K	27	15.0	38	2.5	30.0	3.40	115	115
-183K	28	18.0	40	2.5	26.0	3.80	108	108
-223K	29	22.0	40	2.5	24.0	4.90	96	96
-273K	30	27.0	40	2.5	21.0	5.80	88	88
-333K	31	33.0	41	2.5	20.0	6.50	83	83
-393K	32	39.0	42	2.5	19.0	7.90	75	75
-473K	33	47.0	44	2.5	16.0	9.30	69	69
-563K	34	56.0	44	2.5	15.0	11.0	64	64
-683K	35	68.0	45	2.5	13.0	12.0	61	61
-823K	36	82.0	45	2.5	11.0	13.0	59	59
-104K	37	100.0	40	2.5	10.5	16.8	51	51
MS21427- SERIES 0925 FERRITE CORE & SLEEVE (LT10K)								
-124K	1	120.0	31	0.79	13.0	5.80	88	27
-154K	2	150.0	33	0.79	12.0	7.90	75	24
-184K	3	180.0	33	0.79	11.0	9.40	69	22
-224K	4	220.0	35	0.79	10.0	11.0	64	20
-274K	5	270.0	37	0.79	9.0	12.0	61	18
-334K	6	330.0	40	0.79	8.0	16.0	53	16
-394K	7	390.0	38	0.79	7.8	21.0	46	14
-474K	8	470.0	36	0.79	7.5	24.0	43	13
-564K	9	560.0	36	0.79	7.0	28.0	40	12

Parts listed above are QPL/MIL qualified

Optional Tolerances: J = 5% H = 3%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com


SERIES

1641R
1641



Molded Shielded RF Coils

Actual Size



Military Specifications

MS75087 (LT10K); MS75088 (LT10K);
MS75089 (15μH to 1000μH only) (LT10K)

Physical Parameters

	Inches	Millimeters
Length	0.410 ± 0.020	10.41 ± 0.51
Diameter	0.162 ± 0.010	4.11 ± 0.25
Lead Size		
AWG #22 TCW	0.025 ± 0.002	0.635 ± 0.05
Lead Length	1.44 ± 0.12	36.58 ± 3.05

Current Rating at 90°C Ambient 15°C Rise

Operating Temperature Range -55°C to +105°C

Maximum Power Dissipation at 90°C 0.11 W

Weight Max. (Grams) 1.0

Incremental Current Current level which causes a Max. of 5% change in inductance.

Coupling 3% Max.

Marking DELEVAN; inductance with units and tolerance; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 1641-103H

Front:	Reverse:
DELEVAN	10uH±3%
10uH±3%	0907A

Packaging Tape & reel: 12" reel, 2500 pieces max.; 14" reel, 4000 pieces max.

Made in the U.S.A.

DASH NUMBER*	MIL DASH #	INDUCTANCE (μH) ±10%	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)	INCREMENTAL CURRENT (mA)
MS75087- SERIES 1641 PHENOLIC CORE/IRON SLEEVE (LT10K)								
-101K	1	0.10	50	25.0	250.0	0.025	1830	1830
-121K	2	0.12	51	25.0	250.0	0.034	1570	1570
-151K	3	0.15	51	25.0	250.0	0.037	1500	1500
-181K	4	0.18	50	25.0	250.0	0.047	1330	1330
-221K	5	0.22	49	25.0	250.0	0.067	1120	1120
-271K	6	0.27	47	25.0	250.0	0.11	870	870
-331K	7	0.33	46	25.0	250.0	0.13	800	800
-391K	8	0.39	44	25.0	250.0	0.18	680	680
-471K	9	0.47	44	25.0	235.0	0.25	580	580
-561K	10	0.56	43	25.0	210.0	0.33	505	505
-681K	11	0.68	42	25.0	190.0	0.45	430	430
-821K	12	0.82	40	25.0	180.0	0.59	375	375
MS75088- SERIES 1641 IRON CORE & SLEEVE (LT10K)								
-102K	1	1.0	44	25.0	140.0	0.07	1090	1090
-122K	2	1.2	44	7.9	130.0	0.10	900	900
-152K	3	1.5	44	7.9	115.0	0.12	835	835
-182K	4	1.8	44	7.9	105.0	0.14	775	775
-222K	5	2.2	44	7.9	100.0	0.19	665	665
-272K	6	2.7	44	7.9	92.0	0.28	545	545
-332K	7	3.3	44	7.9	85.0	0.35	490	490
-392K	8	3.9	44	7.9	75.0	0.40	455	455
-472K	9	4.7	44	7.9	70.0	0.55	390	390
-562K	10	5.6	44	7.9	65.0	0.72	340	340
-682K	11	6.8	50	7.9	55.0	1.02	285	285
-822K	12	8.2	50	7.9	50.0	1.32	250	250
-103K	13	10.0	50	7.9	46.0	1.62	228	228
-123K	14	12.0	55	2.5	44.0	2.00	205	205
MS75089- SERIES 1641 FERRITE CORE & SLEEVE (LT10K)								
-153K	1	15.0	45	2.5	49.0	0.80	325	250
-183K	2	18.0	45	2.5	45.0	0.89	305	235
-223K	3	22.0	45	2.5	41.0	0.96	295	220
-273K	4	27.0	45	2.5	38.0	1.19	265	200
-333K	5	33.0	45	2.5	34.0	1.37	248	190
-393K	6	39.0	50	2.5	29.0	1.93	209	180
	7	47.0	50	2.5	27.0	2.11	200	175
	8	56.0	50	2.5	25.0	2.23	194	160
	9	68.0	50	2.5	21.0	2.70	176	150
	10	82.0	50	2.5	10.5	2.44	186	140
	11	100.0	50	2.5	10.0	3.12	164	120
	12	120.0	55	0.79	9.7	3.60	153	95
	13	150.0	55	0.79	8.5	4.10	143	90
	14	180.0	55	0.79	8.0	4.40	138	85
	15	220.0	55	0.79	7.5	5.00	130	80
	16	270.0	55	0.79	7.0	5.80	120	70
	17	330.0	55	0.79	6.5	6.40	115	65
	18	390.0	60	0.79	6.2	7.40	107	60
	19	470.0	60	0.79	5.7	9.50	94	58
	20	560.0	60	0.79	4.7	10.5	90	55
	21	680.0	60	0.79	4.5	11.8	84	50
	22	820.0	60	0.79	4.2	13.0	80	45
	23	1000.0	60	0.79	3.8	17.5	70	40

See 4307 Series for values above 1000μH.
Parts listed above are QPL/MIL qualified

Optional Tolerances: J = 5% H = 3%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

SERIES

4307R
4307



Molded Shielded RF Coils

INDUCTANCE (μ H) $\pm 10\%$	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)	INCREMENTAL CURRENT (mA)**
DASH NUMBER*	Q MINIMUM				


SERIES 4307 FERRITE CORE AND SLEEVE

-125K	1200	50	0.250	3.00	22.1	115	35
-155K	1500	50	0.250	2.80	26.5	110	33
-185K	1800	50	0.250	2.60	29.9	105	30
-225K	2200	50	0.250	2.40	33.8	99	27
-275K	2700	50	0.250	2.20	47.3	83	25
-335K	3300	50	0.250	2.00	53.0	80	22
-395K	3900	50	0.250	1.90	73.8	67	20
-475K	4700	50	0.250	1.70	81.6	63	19
-565K	5600	50	0.250	1.60	98.9	56	17
-685K	6800	50	0.250	1.40	111.0	54	16
-825K	8200	50	0.250	1.20	119.0	52	15
-106K	10000	50	0.250	1.00	137.0	49	14
-126K	12000	30	0.079	0.80	143.0	46	13
-156K	15000	30	0.079	0.60	157.0	45	12
-186K	18000	30	0.079	0.55	225.0	41	10
-226K	22000	27	0.079	0.50	274.0	33	9
-276K	27000	27	0.079	0.40	308.0	31	8
-336K	33000	27	0.079	0.40	343.0	29	7.5

Optional Tolerances: J = 5% H = 3%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com



Test Methods MIL-PRF-15305 test methods only.
MS75089-24 to MS75089-40, reference;
MS90537-50 to MS90537-66, reference.

Mechanical Configuration Units are axial leaded, encapsulated in an epoxy molded case. Core and sleeve are both of ferrite material.

Physical Parameters

	Inches	Millimeters
Length	0.427 to 0.447	10.85 to 11.35
Diameter	0.177 to 0.197	4.496 to 5.004
Lead Size		
AWG #22 TCW	0.023 to 0.027	0.584 to 0.686
Lead Length	1.320 to 1.560	33.53 to 39.62

Current Rating at 90°C Ambient 35°C Rise

Operating Temperature -55°C to +125°C

Power Dissipation at 90°C 0.385 W

Coupling 3% Max.

**** Note** Incremental Current is the D.C. current required to decrease the inductance a maximum of 5%.

Marking DELEVAN; inductance with units and tolerance; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 4307-336J

<i>Front:</i>	<i>Reverse:</i>
DELEVAN	33mH $\pm 5\%$
33mH $\pm 5\%$	0839A


Packaging Tape & reel: 12" reel, 2500 pieces max.; 14" reel, 3000 pieces max.

Made in the U.S.A.

Established Reliability Inductors

Physical Parameters and Environmental Characteristics	ER1641			ER1840		ER1537		ER1025		
	MIL-PRF-39010/01	MIL-PRF-39010/02	MIL-PRF-39010/03	MIL-PRF-39010/04	MIL-PRF-39010/05	MIL-PRF-39010/06	MIL-PRF-39010/07	MIL-PRF-39010/08	MIL-PRF-39010/09	MIL-PRF-39010/10
Inductance Range, μH	0.10 to 0.82	0.91 to 12.0	15 to 1000	0.15 to 2.7	3.0 to 27.0	0.15 to 4.7	5.1 to 240.0	0.10 to 1.00	1.1 to 27.0	30 to 1000
Core Material	Phenolic	Iron	Ferrite	Phenolic	Iron	Phenolic	Iron	Phenolic	Iron	Ferrite
Sleeve	Iron	Iron	Ferrite	—	—	—	—	—	—	—
Length, Inches	0.410 ± 0.020	0.410 ± 0.020	0.410 ± 0.020	0.437 ± 0.01	0.437 ± 0.01	0.375 ± 0.010	0.375 ± 0.010	0.250 ± 0.010	0.250 ± 0.010	0.250 ± 0.010
Millimeters	10.41 ± 0.51	10.41 ± 0.51	10.41 ± 0.51	11.10 ± 0.25	11.10 ± 0.25	9.53 ± 0.25	9.53 ± 0.25	6.35 ± 0.25	6.35 ± 0.25	6.35 ± 0.25
Diameter, Inches	0.162 ± 0.010	0.162 ± 0.010	0.162 ± 0.010	0.187 ± 0.010	0.187 ± 0.010	0.156 ± 0.010	0.156 ± 0.010	0.095 ± 0.010	0.095 ± 0.010	0.095 ± 0.010
Millimeters	4.11 ± 0.25	4.11 ± 0.25	4.11 ± 0.25	4.75 ± 0.25	4.75 ± 0.25	3.96 ± 0.25	3.96 ± 0.25	2.41 ± 0.25	2.41 ± 0.25	2.41 ± 0.25
Lead Size — AWG #	#22 TCW	#22 TCW	#22 TCW	#22 TCW	#22 TCW	#22 TCW	#22 TCW	#24 TCW	#24 TCW	#24 TCW
Inches	0.025 ± 0.002	0.025 ± 0.002	0.025 ± 0.002	0.025 ± 0.002	0.025 ± 0.002	0.025 ± 0.002	0.025 ± 0.002	0.020 ± 0.0015	0.020 ± 0.0015	0.020 ± 0.0015
Millimeters	0.635 ± 0.051	0.635 ± 0.051	0.635 ± 0.051	0.635 ± 0.051	0.635 ± 0.051	0.635 ± 0.051	0.635 ± 0.051	0.51 ± 0.04	0.51 ± 0.04	0.51 ± 0.04
Lead Length, Inches	1.438 ± 0.188	1.438 ± 0.188	1.438 ± 0.188	1.438 ± 0.188	1.438 ± 0.188	1.438 ± 0.188	1.438 ± 0.188	1.438 ± 0.188	1.438 ± 0.188	1.438 ± 0.188
Millimeters	36.53 ± 4.77	36.53 ± 4.77	36.53 ± 4.77	36.58 ± 3.05	36.58 ± 3.05	36.53 ± 4.77	36.53 ± 4.77	36.53 ± 4.77	36.53 ± 4.77	36.53 ± 4.77
Weight Max. (Grams)	0.85	1.0	1.0	0.95	0.95	0.9	0.9	0.3	0.3	0.3
Current Rating at 90°C, Max. Rise °C	15	15	15	35	15	35	15	35	15	15
Operating Temp. °C	-55 to +105	-55 to +105	-55 to +105	-55 to +125	-55 to +105	-55 to +125	-55 to +105	-55 to +125	-55 to +105	-55 to +105
Max. Power Dissipation at 90°C, Watts	0.11	0.11	0.11	0.385	0.385	0.312	0.134	0.21	0.09	0.073
Coupling	3% Max.	3% Max.	3% Max.	—	—	—	—	—	—	—
Body Color	Black	Black	Black	Tan	Tan	Tan	Tan	Tan	Tan	Tan

MARKING EXAMPLE & ORDERING INFORMATION



MIL-PRF-39010 Molded RF Coils with Sn10 high-temperature solder for internal connections.

Approved Through Failure Rate Level S

Note The complete Military dash numbers will include two additional letters, indicated in the tables on the following three pages by **. The first additional letter will indicate tolerance: J indicates $\pm 5\%$; K indicates $\pm 10\%$; L indicates $\pm 20\%$.

The second letter will indicate the failure rate (e.g., M, P, R, S).

Packaging Tape & reel

ER1025: 12" reel, 3500 pieces max.; 14" reel, 6000 pieces max.
ER1537 and ER1641: 12" reel, 2500 pieces max.; 14" reel, 4000 pieces max.
ER1840: 12" reel, 2500 pieces max.; 14" reel, 3000 pieces max. For additional packaging options, see technical section.

Made in the U.S.A.

CONTINUED ON NEXT PAGE

ER SERIES (continued)

DELEVAN PART NUMBER	DASH NUMBER	MILITARY	INDUCTANCE (μH)	IND. TOLERANCE (%)	TEST FREQUENCY (MHz)	Q MINIMUM	SRF MINIMUM (MHz)	DC RESISTANCE (OHMS @ 25°C)	CURRENT (mA)	RATED DC
MIL-PRF-39010/01										
ER1641-101**	AR10**	0.10	5.10	50	25.0	250	0.025	1,790		
ER1641-111**	AR11**	0.11	5	50	25.0	250	0.034	1,530		
ER1641-121**	AR12**	0.12	5.10	50	25.0	250	0.034	1,530		
ER1641-131**	AR13**	0.13	5	50	25.0	250	0.037	1,470		
ER1641-151**	AR15**	0.15	5.10	50	25.0	250	0.037	1,470		
ER1641-161**	AR16**	0.16	5	50	25.0	250	0.047	1,300		
ER1641-181**	AR18**	0.18	5.10	50	25.0	250	0.047	1,300		
ER1641-201**	AR20**	0.20	5	49	25.0	250	0.067	1,100		
ER1641-221**	AR22**	0.22	5.10	49	25.0	250	0.067	1,100		
ER1641-241**	AR24**	0.24	5	47	25.0	250	0.110	853		
ER1641-271**	AR27**	0.27	5.10	47	25.0	250	0.110	853		
ER1641-301**	AR30**	0.30	5	46	25.0	250	0.130	780		
ER1641-331**	AR33**	0.33	5.10	46	25.0	250	0.130	780		
ER1641-361**	AR36**	0.36	5	44	25.0	250	0.180	670		
ER1641-391**	AR39**	0.39	5.10	44	25.0	250	0.180	670		
ER1641-431**	AR43**	0.43	5	44	25.0	235	0.250	565		
ER1641-471**	AR47**	0.47	5.10	44	25.0	235	0.250	565		
ER1641-511**	AR51**	0.51	5	43	25.0	210	0.330	490		
ER1641-561**	AR56**	0.56	5.10	43	25.0	210	0.330	490		
ER1641-621**	AR62**	0.62	5	42	25.0	190	0.450	420		
ER1641-681**	AR68**	0.68	5.10	42	25.0	190	0.450	420		
ER1641-751**	AR75**	0.75	5	40	25.0	180	0.590	370		
ER1641-821**	AR82**	0.82	5.10	40	25.0	180	0.590	370		
MIL-PRF-39010/02										
ER1641-911**	AR91**	0.91	5	44	25.0	140	0.070	1,070		
ER1641-102**	A1R0**	1.00	5.10	44	25.0	140	0.070	1,070		
ER1641-112**	A1R1**	1.10	5	44	7.9	130	0.100	895		
ER1641-122**	A1R2**	1.20	5.10	44	7.9	130	0.100	895		
ER1641-132**	A1R3**	1.30	5	44	7.9	115	0.120	815		
ER1641-152**	A1R5**	1.50	5.10	44	7.9	115	0.120	815		
ER1641-162**	A1R6**	1.60	5	44	7.9	105	0.140	755		
ER1641-182**	A1R8**	1.80	5.10	44	7.9	105	0.140	755		
ER1641-202**	A2R0**	2.00	5	44	7.9	100	0.190	650		
ER1641-222**	A2R2**	2.20	5.10	44	7.9	100	0.190	650		
ER1641-242**	A2R4**	2.40	5	44	7.9	92	0.280	535		
ER1641-272**	A2R7**	2.70	5.10	44	7.9	92	0.280	535		
ER1641-302**	A3R0**	3.00	5	44	7.9	85	0.350	480		
ER1641-332**	A3R3**	3.30	5.10	44	7.9	85	0.350	480		
ER1641-362**	A3R6**	3.60	5	44	7.9	75	0.400	450		
ER1641-392**	A3R9**	3.90	5.10	44	7.9	75	0.400	450		
ER1641-432**	A4R3**	4.30	5	44	7.9	70	0.550	380		
ER1641-472**	A4R7**	4.70	5.10	44	7.9	70	0.550	380		
ER1641-512**	A5R1**	5.10	5	44	7.9	65	0.720	335		
ER1641-562**	A5R6**	5.60	5.10	44	7.9	65	0.720	335		
ER1641-622**	A6R2**	6.20	5	44	7.9	55	1.020	280		
ER1641-682**	A6R8**	6.80	5.10	50	7.9	55	1.020	280		
ER1641-752**	A7R5**	7.50	5	50	7.9	50	1.320	245		
ER1641-822**	A8R2**	8.20	5.10	50	7.9	50	1.320	245		
ER1641-912**	A9R1**	9.10	5	50	7.9	46	1.620	220		
ER1641-103**	A100**	10.00	5.10	50	7.9	46	1.620	220		
ER1641-113**	A110**	11.00	5	50	2.5	44	2.000	200		
ER1641-123**	A120**	12.00	5.10	50	2.5	44	2.000	200		
MIL-PRF-39010/03										
ER1641-153**	A150**	15	5.10	45	2.50	49.0	0.80	315		
ER1641-163**	A160**	16	5	45	2.50	45.0	0.89	300		
ER1641-183**	A180**	18	5.10	45	2.50	45.0	0.89	300		
ER1641-203**	A200**	20	5	45	2.50	41.0	0.96	290		
ER1641-223**	A220**	22	5.10	45	2.50	41.0	0.96	290		
ER1641-243**	A240**	24	5	45	2.50	38.0	1.19	260		
ER1641-273**	A270**	27	5.10	45	2.50	38.0	1.19	260		
ER1641-303**	A300**	30	5	45	2.50	34.0	1.37	240		
ER1641-333**	A330**	33	5.10	45	2.50	34.0	1.37	240		
ER1641-363**	A360**	36	5	45	2.50	29.0	1.93	205		
ER1641-393**	A390**	39	5.10	50	2.50	29.0	1.93	205		
ER1641-433**	A430**	43	5	50	2.50	27.0	2.11	195		
ER1641-473**	A470**	47	5.10	50	2.50	27.0	2.11	195		
ER1641-513**	A510**	51	5	50	2.50	25.0	2.23	190		
ER1641-563**	A560**	56	5.10	50	2.50	25.0	2.23	190		

MIL-PRF-39010/03 (continued)								
ER1641-623**	A620**	62	5	50	2.50	21.0	2.44	180
ER1641-683**	A680**	68	5,10	50	2.50	21.0	2.44	180
ER1641-753**	A750**	75	5	50	2.50	10.5	2.70	170
ER1641-823**	A820**	82	5,10	50	2.50	10.5	2.70	170
ER1641-913**	A910**	91	5	50	2.50	10.0	3.12	160
ER1641-104**	A101**	100	5,10	50	2.50	10.0	3.12	160
ER1641-114**	A111**	110	5	50	0.79	9.7	3.60	150
ER1641-124**	A121**	120	5,10	55	0.79	9.7	3.60	150
ER1641-134**	A131**	130	5	55	0.79	8.5	4.10	140
ER1641-154**	A151**	150	5,10	55	0.79	8.5	4.10	140
ER1641-164**	A161**	160	5	55	0.79	8.0	4.40	135
ER1641-184**	A181**	180	5,10	55	0.79	8.0	4.40	135
ER1641-204**	A201**	200	5	55	0.79	7.5	5.00	125
ER1641-224**	A221**	220	5,10	55	0.79	7.5	5.00	125
ER1641-244**	A241**	240	5	55	0.79	7.0	5.80	115
ER1641-274**	A271**	270	5,10	55	0.79	7.0	5.80	115
ER1641-304**	A301**	300	5	55	0.79	6.5	6.40	110
ER1641-334**	A331**	330	5,10	55	0.79	6.5	6.40	110
ER1641-364**	A361**	360	5	55	0.79	6.2	7.40	105
ER1641-394**	A391**	390	5,10	60	0.79	6.2	7.40	105
ER1641-434**	A431**	430	5	60	0.79	5.7	9.50	92
ER1641-474**	A471**	470	5,10	60	0.79	5.7	9.50	92
ER1641-514**	A511**	510	5	60	0.79	4.7	10.50	90
ER1641-564**	A561**	560	5,10	60	0.79	4.7	10.50	90
ER1641-624**	A621**	620	5	60	0.79	4.5	11.80	80
ER1641-684**	A681**	680	5,10	60	0.79	4.5	11.80	80
ER1641-754**	A751**	750	5	60	0.79	4.2	13.00	80
ER1641-824**	A821**	820	5,10	60	0.79	4.2	13.00	80
ER1641-914**	A911**	910	5	60	0.79	3.8	17.50	70
ER1641-105**	A102**	1,000	5,10	60	0.79	3.8	17.50	70
MIL-PRF-39010/04								
ER1840-00**	BR15**	0.15	5,10,20	55	25.0	510	0.030	2,900
ER1840-101**	BR16**	0.16	5	50	25.0	415	0.035	2,700
ER1840-01**	BR18**	0.18	5,10	50	25.0	415	0.035	2,700
ER1840-102**	BR20**	0.20	5	50	25.0	415	0.035	2,700
ER1840-02**	BR22**	0.22	5,10,20	50	25.0	415	0.035	2,700
ER1840-103**	BR24**	0.24	5	50	25.0	350	0.065	2,000
ER1840-03**	BR27**	0.27	5,10	50	25.0	350	0.065	2,000
ER1840-104**	BR30**	0.30	5	50	25.0	350	0.065	2,000
ER1840-04**	BR33**	0.33	5,10,20	50	25.0	350	0.065	2,000
ER1840-105**	BR36**	0.36	5	50	25.0	300	0.085	1,700
ER1840-05**	BR39**	0.39	5,10	50	25.0	300	0.085	1,700
ER1840-106**	BR43**	0.43	5	50	25.0	300	0.085	1,700
ER1840-06**	BR47**	0.47	5,10,20	50	25.0	300	0.085	1,700
ER1840-107**	BR51**	0.51	5	50	25.0	270	0.125	1,450
ER1840-07**	BR56**	0.56	5,10	50	25.0	270	0.125	1,450
ER1840-108**	BR62**	0.62	5	45	25.0	250	0.150	1,300
ER1840-08**	BR68**	0.68	5,10	45	25.0	250	0.150	1,300
ER1840-109**	BR75**	0.75	5	40	25.0	210	0.205	1,100
ER1840-09**	BR82**	0.82	5,10	40	25.0	210	0.205	1,100
ER1840-110**	BR91**	0.91	5	40	25.0	200	0.290	930
ER1840-10**	B1R0**	1.00	5,10	40	25.0	200	0.290	930
ER1840-111**	B1R1**	1.10	5	30	7.9	180	0.400	785
ER1840-11**	B1R2**	1.20	5,10	30	7.9	180	0.400	785
ER1840-112**	B1R3**	1.30	5	30	7.9	170	0.485	720
ER1840-12**	B1R5**	1.50	5,10	30	7.9	170	0.485	720
ER1840-113**	B1R6**	1.60	5	30	7.9	150	0.740	580
ER1840-13**	B1R8**	1.80	5,10	30	7.9	150	0.740	580
ER1840-114**	B2R0**	2.00	5	30	7.9	140	0.970	505
ER1840-14**	B2R2**	2.20	5,10	30	7.9	140	0.970	505
ER1840-15**	B2R4**	2.40	5	30	7.9	120	1.200	460
ER1840-16**	B2R7**	2.70	5,10	30	7.9	120	1.200	460

ER SERIES (continued)



DELEVAN PART NUMBER	DASH NUMBER	MILITARY	INDUCTANCE (μH)	IND. TOLERANCE (%)	TEST FREQUENCY (MHz)	Q MINIMUM	SRF MINIMUM (MHz)	MAXIMUM (OHMS @ 25°C)	DC RESISTANCE (mΩ @ 25°C)	CURRENT (mA)	RATED DC
MIL-PRF-39010/05											
ER1840-17**	A3R0**		3.00	5	30	7.9	70	0.140	945		
ER1840-18**	A3R3**		3.30	5,10	30	7.9	70	0.140	945		
ER1840-19**	A3R6**		3.60	5	30	7.9	65	0.155	870		
ER1840-20**	A3R9**		3.90	5,10	30	7.9	65	0.155	870		
ER1840-21**	A4R3**		4.30	5	30	7.9	60	0.210	745		
ER1840-22**	A4R7**		4.70	5,10	30	7.9	60	0.210	745		
ER1840-23**	A5R1**		5.10	5	30	7.9	50	0.280	645		
ER1840-24**	A5R6**		5.60	5,10	30	7.9	50	0.280	645		
ER1840-25**	A6R2**		6.20	5	30	7.9	50	0.375	560		
ER1840-26**	A6R8**		6.80	5,10	30	7.9	50	0.375	560		
ER1840-27**	A7R5**		7.50	5	30	7.9	48	0.440	520		
ER1840-28**	A8R2**		8.20	5,10	30	7.9	48	0.440	520		
ER1840-29**	A9R1**		9.10	5	30	7.9	42	0.605	440		
ER1840-30**	A100**		10.0	5,10	30	7.9	42	0.605	440		
ER1840-31**	A110**		11.0	5	30	2.5	36	1.05	335		
ER1840-32**	A120**		12.0	5,10	50	2.5	36	1.05	335		
ER1840-33**	A130**		13.0	5	50	2.5	30	1.20	310		
ER1840-34**	A150**		15.0	5,10	55	2.5	30	1.20	310		
ER1840-135**	A160**		16.0	5	55	2.5	30	1.95	245		
ER1840-35**	A180**		18.0	5,10	60	2.5	30	1.95	245		
ER1840-136**	A200**		20.0	5	60	2.5	24	2.20	230		
ER1840-36**	A220**		22.0	5,10	60	2.5	24	2.20	230		
ER1840-37**	A240**		24.0	5	60	2.5	22	2.75	205		
ER1840-38**	A270**		27.0	5,10	65	2.5	22	2.75	205		
MIL-PRF-39010/06											
ER1537-00**	BR15**		0.15	5,10,20	50	25.0	525	0.030	2,450		
ER1537-101**	BR16**		0.16	5	50	25.0	460	0.055	1,810		
ER1537-01**	BR18**		0.18	5,10	50	25.0	460	0.055	1,810		
ER1537-102**	BR20**		0.20	5	50	25.0	460	0.055	1,810		
ER1537-02**	BR22**		0.22	5,10,20	50	25.0	460	0.055	1,810		
ER1537-103**	BR24**		0.24	5	45	25.0	360	0.090	1,400		
ER1537-03**	BR27**		0.27	5,10	45	25.0	360	0.090	1,400		
ER1537-104**	BR30**		0.30	5	45	25.0	360	0.090	1,400		
ER1537-04**	BR33**		0.33	5,10,20	45	25.0	360	0.090	1,400		
ER1537-105**	BR36**		0.36	5	45	25.0	310	0.12	1,225		
ER1537-05**	BR39**		0.39	5,10	45	25.0	310	0.12	1,225		
ER1537-106**	BR43**		0.43	5	45	25.0	310	0.12	1,225		
ER1537-06**	BR47**		0.47	5,10,20	45	25.0	310	0.12	1,225		
ER1537-107**	BR51**		0.51	5	45	25.0	280	0.135	1,150		
ER1537-07**	BR56**		0.56	5,10	50	25.0	280	0.135	1,150		
ER1537-108**	BR62**		0.62	5	50	25.0	250	0.150	1,100		
ER1537-08**	BR68**		0.68	5,10	50	25.0	250	0.150	1,100		
ER1537-09**	BR75**		0.75	5	50	25.0	220	0.220	900		
ER1537-10**	BR82**		0.82	5,10	50	25.0	220	0.220	900		
ER1537-11**	BR91**		0.91	5	50	25.0	200	0.290	785		
ER1537-12**	B1R0**		1.00	5,10	50	25.0	200	0.290	785		
ER1537-13**	B1R1**		1.10	5	33	7.9	180	0.420	650		
ER1537-14**	B1R2**		1.20	5,10	33	7.9	180	0.420	650		
ER1537-15**	B1R3**		1.30	5	33	7.9	160	0.500	600		
ER1537-16**	B1R5**		1.50	5,10	33	7.9	160	0.500	600		
ER1537-17**	B1R6**		1.60	5	33	7.9	150	0.650	525		
ER1537-18**	B1R8**		1.80	5,10	33	7.9	150	0.650	525		
ER1537-19**	B2R0**		2.00	5	33	7.9	135	0.950	435		
ER1537-20**	B2R2**		2.20	5,10	33	7.9	135	0.950	435		
ER1537-21**	B2R4**		2.40	5	33	7.9	120	1.20	385		
ER1537-22**	B2R7**		2.70	5,10	33	7.9	120	1.20	385		
ER1537-23**	B3R0**		3.00	5	33	7.9	110	2.00	300		
ER1537-24**	B3R3**		3.30	5,10	33	7.9	110	2.00	300		
ER1537-25**	B3R6**		3.60	5	33	7.9	100	2.30	280		
ER1537-26**	B3R9**		3.90	5,10	33	7.9	100	2.30	280		
ER1537-27**	B4R3**		4.30	5	33	7.9	90	2.60	260		
ER1537-28**	B4R7**		4.70	5,10	33	7.9	90	2.60	260		

MIL-PRF-39010/07										
ER1537-29**	A5R1**	5.1	5	45	7.90	60.0	0.32	495		
ER1537-30**	A5R6**	5.6	5,10	45	7.90	60.0	0.32	495		
ER1537-31**	A6R2**	6.2	5	45	7.90	55.0	0.50	395		
ER1537-32**	A6R8**	6.8	5,10	50	7.90	55.0	0.50	395		
ER1537-33**	A7R5**	7.5	5	50	7.90	50.0	0.60	360		
ER1537-34**	A8R2**	8.2	5,10	50	7.90	50.0	0.60	360		
ER1537-35**	A9R1**	9.1	5	50	7.90	45.0	0.90	290		
ER1537-36**	A100**	10.0	5,10	55	7.90	45.0	0.90	290		
ER1537-37**	A110**	11.0	5	55	2.50	42.0	1.10	265		
ER1537-38**	A120**	12.0	5,10	65	2.50	42.0	1.10	265		
ER1537-39**	A130**	13.0	5	65	2.50	40.0	1.40	240		
ER1537-40**	A150**	15.0	5,10	65	2.50	40.0	1.40	240		
ER1537-41**	A160**	16.0	5	65	2.50	34.0	2.25	185		
ER1537-42**	A180**	18.0	5,10	75	2.50	34.0	2.25	185		
ER1537-43**	A200**	20.0	5	75	2.50	30.0	2.50	175		
ER1537-44**	A220**	22.0	5,10	75	2.50	30.0	2.50	175		
ER1537-46**	A240**	24.0	5	60	2.50	25.0	2.60	170		
ER1537-48**	A270**	27.0	5,10	60	2.50	25.0	2.60	170		
ER1537-50**	A300**	30.0	5	60	2.50	19.0	3.00	165		
ER1537-52**	A330**	33.0	5,10	65	2.50	19.0	3.00	165		
ER1537-54**	A360**	36.0	5	60	2.50	15.5	2.50	180		
ER1537-56**	A390**	39.0	5	60	2.50	14.5	2.60	176		
ER1537-58**	A430**	43.0	5	60	2.50	13.7	2.70	172		
ER1537-60**	A470**	47.0	5	55	2.50	13.0	2.75	170		
ER1537-62**	A510**	51.0	5	55	2.50	12.7	2.85	167		
ER1537-64**	A560**	56.0	5	55	2.50	12.0	3.00	164		
ER1537-66**	A620**	62.0	5	55	2.50	11.5	3.15	160		
ER1537-68**	A680**	68.0	5	55	2.50	11.0	3.30	156		
ER1537-70**	A750**	75.0	5	55	2.50	10.5	3.70	147		
ER1537-72**	A820**	82.0	5	50	2.50	10.3	3.90	143		
ER1537-74**	A910**	91.0	5	50	2.50	10.0	4.30	136		
ER1537-76**	A101**	100.0	5	50	2.50	9.50	4.50	133		
ER1537-78**	A111**	110.0	5	60	0.79	8.90	4.90	128		
ER1537-80**	A121**	120.0	5	65	0.79	8.70	5.20	124		
ER1537-82**	A131**	130.0	5	65	0.79	8.50	5.45	121		
ER1537-84**	A151**	150.0	5	65	0.79	8.00	6.05	114		
ER1537-86**	A161**	160.0	5	65	0.79	7.50	6.40	111		
ER1537-88**	A181**	180.0	5	65	0.79	7.00	6.75	108		
ER1537-90**	A201**	200.0	5	65	0.79	6.50	7.10	106		
ER1537-92**	A221**	220.0	5	65	0.79	6.20	7.45	103		
ER1537-94**	A241**	240.0	5	65	0.79	5.90	7.80	101		
MIL-PRF-39010/08										
ER1025-94**	BR10**	0.10	5,10	40	25.0	680	0.08	1,350		
ER1025-95**	BR11**	0.11	5	40	25.0	640	0.09	1,270		
ER1025-96**	BR12**	0.12	5,10	40	25.0	640	0.09	1,270		
ER1025-97**	BR13**	0.13	5	38	25.0	600	0.10	1,200		
ER1025-00**	BR15**	0.15	5,10	38	25.0	600	0.10	1,200		
ER1025-01**	BR16**	0.16	5	35	25.0	550	0.12	1,105		
ER1025-02**	BR18**	0.18	5,10	35	25.0	550	0.12	1,105		
ER1025-03**	BR20**	0.20	5	33	25.0	510	0.14	1,025		
ER1025-04**	BR22**	0.22	5,10	33	25.0	510	0.14	1,025		
ER1025-05**	BR24**	0.24	5	33	25.0	430	0.16	960		
ER1025-06**	BR27**	0.27	5,10	33	25.0	430	0.16	960		
ER1025-07**	BR30**	0.30	5	30	25.0	410	0.22	815		
ER1025-08**	BR33**	0.33	5,10	30	25.0	410	0.22	815		
ER1025-09**	BR36**	0.36	5	30	25.0	365	0.30	700		
ER1025-10**	BR39**	0.39	5,10	30	25.0	365	0.30	700		
ER1025-11**	BR43**	0.43	5	30	25.0	330	0.35	650		
ER1025-12**	BR47**	0.47	5,10	30	25.0	330	0.35	650		
ER1025-13**	BR51**	0.51	5	30	25.0	300	0.50	545		
ER1025-14**	BR56**	0.56	5,10	30	25.0	300	0.50	545		
ER1025-15**	BR62**	0.62	5	28	25.0	275	0.60	495		
ER1025-16**	BR68**	0.68	5,10	28	25.0	275	0.60	495		
ER1025-17**	BR75**	0.75	5	28	25.0	250	0.85	415		
ER1025-18**	BR82**	0.82	5,10	28	25.0	250	0.85	415		
ER1025-19**	BR91**	0.91	5	25	25.0	230	1.00	385		
ER1025-20**	B1R0**	1.00	5,10	25	25.0	230	1.00	385		

ER SERIES (continued)

DELEVAN PART NUMBER	MILITARY DASH NUMBER	INDUCTANCE (μH)	IND. TOLERANCE (%)	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE (OHMS @ 25°C)	CURRENT (mA)	RATED DC
MIL-PRF-39010/09								
ER1025-21**	A1R1**	1.1	5	25	7.9	150	0.18	590
ER1025-22**	A1R2**	1.2	5,10	25	7.9	150	0.18	590
ER1025-23**	A1R3**	1.3	5	25	7.9	140	0.22	535
ER1025-24**	A1R5**	1.5	5,10	28	7.9	140	0.22	535
ER1025-25**	A1R6**	1.6	5	28	7.9	125	0.30	455
ER1025-26**	A1R8**	1.8	5,10	30	7.9	125	0.30	455
ER1025-27**	A2R0**	2.0	5	30	7.9	115	0.40	395
ER1025-28**	A2R2**	2.2	5,10	30	7.9	115	0.40	395
ER1025-29**	A2R4**	2.4	5	30	7.9	100	0.55	335
ER1025-30**	A2R7**	2.7	5,10	37	7.9	100	0.55	335
ER1025-31**	A3R0**	3.0	5	37	7.9	90	0.85	270
ER1025-32**	A3R3**	3.3	5,10	45	7.9	90	0.85	270
ER1025-33**	A3R6**	3.6	5	45	7.9	80	1.00	250
ER1025-34**	A3R9**	3.9	5,10	45	7.9	80	1.00	250
ER1025-35**	A4R3**	4.3	5	45	7.9	75	1.20	230
ER1025-36**	A4R7**	4.7	5,10	45	7.9	75	1.20	230
ER1025-37**	A5R1**	5.1	5	45	7.9	65	1.80	185
ER1025-38**	A5R6**	5.6	5,10	50	7.9	65	1.80	185
ER1025-39**	A6R2**	6.2	5	50	7.9	60	2.00	175
ER1025-40**	A6R8**	6.8	5,10	50	7.9	60	2.00	175
ER1025-41**	A7R5**	7.5	5	50	7.9	55	2.70	155
ER1025-42**	A8R2**	8.2	5,10	55	7.9	55	2.70	155
ER1025-43**	A9R1**	9.1	5	55	7.9	50	3.70	130
ER1025-44**	A100**	10.0	5,10	55	7.9	50	3.70	130
ER1025-45**	A110**	11.0	5	45	2.5	40	2.70	130
ER1025-46**	A120**	12.0	5,10	45	2.5	40	2.70	155
ER1025-47**	A130**	13.0	5	40	2.5	35	2.80	150
ER1025-48**	A150**	15.0	5,10	40	2.5	35	2.80	150
ER1025-49**	A160**	16.0	5	40	2.5	30	3.10	145
ER1025-50**	A180**	18.0	5,10	50	2.5	30	3.10	145
ER1025-51**	A200**	20.0	5	50	2.5	25	3.30	140
ER1025-52**	A220**	22.0	5,10	50	2.5	25	3.30	140
ER1025-53**	A240**	24.0	5	50	2.5	20	3.50	135
ER1025-54**	A270**	27.0	5,10	50	2.5	20	3.50	135

DELEVAN PART NUMBER	MILITARY DASH NUMBER	INDUCTANCE (μH)	IND. TOLERANCE (%)	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE (OHMS @ 25°C)	CURRENT (mA)	RATED DC
MIL-PRF-39010/10								
ER1025-55**	A300**	30.0	5	45	2.50	24	3.4	130
ER1025-56**	A330**	33.0	5,10	45	2.50	24	3.4	130
ER1025-57**	A360**	36.0	5	45	2.50	22	3.6	125
ER1025-58**	A390**	39.0	5,10	45	2.50	22	3.6	125
ER1025-59**	A430**	43.0	5	45	2.50	20	4.5	110
ER1025-60**	A470**	47.0	5,10	45	2.50	20	4.5	110
ER1025-61**	A510**	51.0	5	45	2.50	18	5.7	100
ER1025-62**	A560**	56.0	5,10	45	2.50	18	5.7	100
ER1025-63**	A620**	62.0	5	45	2.50	15	6.7	92
ER1025-64**	A680**	68.0	5,10	50	2.50	15	6.7	92
ER1025-65**	A750**	75.0	5	50	2.50	14	7.3	88
ER1025-66**	A820**	82.0	5,10	50	2.50	14	7.3	88
ER1025-67**	A910**	91.0	5	50	2.50	13	8.0	84
ER1025-68**	A101**	100	5,10	50	2.50	13	8.0	84
ER1025-69**	A111**	110	5	30	0.79	12	13.0	66
ER1025-70**	A121**	120	5,10	30	0.79	12	13.0	66
ER1025-71**	A131**	130	5	30	0.79	11	15.0	61
ER1025-72**	A151**	150	5,10	30	0.79	11	15.0	61
ER1025-73**	A161**	160	5	30	0.79	10	17.0	57
ER1025-74**	A181**	180	5,10	30	0.79	10	17.0	57
ER1025-75**	A201**	200	5	30	0.79	9.0	21.0	52
ER1025-76**	A221**	220	5,10	30	0.79	9.0	21.0	52
ER1025-77**	A241**	240	5	30	0.79	8.0	25.0	47
ER1025-78**	A271**	270	5,10	30	0.79	8.0	25.0	47
ER1025-79**	A301**	300	5	30	0.79	7.0	28.0	45
ER1025-80**	A331**	330	5,10	30	0.79	7.0	28.0	45
ER1025-81**	A361**	360	5	30	0.79	6.5	35.0	40
ER1025-82**	A391**	390	5,10	30	0.79	6.5	35.0	40
ER1025-83**	A431**	430	5	30	0.79	6.0	42.0	36
ER1025-84**	A471**	470	5,10	30	0.79	6.0	42.0	36
ER1025-85**	A511**	510	5	30	0.79	5.0	46.0	35
ER1025-86**	A561**	560	5,10	30	0.79	5.0	46.0	35
ER1025-87**	A621**	620	5	30	0.79	4.0	60.0	30
ER1025-88**	A681**	680	5,10	30	0.79	4.0	60.0	30
ER1025-89**	A751**	750	5	30	0.79	3.8	65.0	29
ER1025-90**	A821**	820	5,10	30	0.79	3.8	65.0	29
ER1025-91**	A911**	910	5	30	0.79	3.4	72.0	28
ER1025-92**	A102**	1,000	5,10	30	0.79	3.4	72.0	28

SERIES**2020R
2020****Radial Toroidal Inductors****RF Inductors****Military Specifications MS21422 (LT4K)****Physical Parameters**

	Inches	Millimeters
A	0.200 to 0.230	5.08 to 5.84
B	0.190 to 0.210	4.83 to 5.33
C	0.090 to 0.110	2.29 to 2.79
D	0.090 to 0.110	2.29 to 2.79
E	1.00 Min.	25.40 Min.
F	0.0185 to 0.0215	0.47 to 0.55

Current Rating at 90°C Ambient 35°C Rise**Operating Temperature Range** -55°C to +125°C**Maximum Power Dissipation at 90°C** 0.2 W**Weight Max.** (Grams) 0.5**Core Material** Iron**Lead Size** AWG #24 TCW**Note** Inductance measured .25" from body**Packaging** Bulk only**Made In the U.S.A.**

DASH NUMBER*	MIL DASH #	INDUCTANCE (μH)	TOLERANCE	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
MS21422- SERIES 2020 IRON CORE (LT4K)								
-00K	1	0.10	±10%	55	25.0	450	0.04	2200
-02K	2	0.12	±10%	60	25.0	400	0.05	2000
-04K	3	0.15	±10%	60	25.0	350	0.06	1800
-06K	4	0.18	±10%	60	25.0	320	0.07	1600
-08K	5	0.22	±10%	65	25.0	300	0.08	1500
-10K	6	0.27	±10%	65	25.0	280	0.10	1400
-12K	7	0.33	±10%	65	25.0	260	0.11	1300
-14K	8	0.39	±10%	65	25.0	240	0.14	1200
-16K	9	0.47	±10%	65	25.0	220	0.17	1100
-18K	10	0.56	±10%	70	25.0	200	0.22	1000
-20K	11	0.68	±10%	70	25.0	180	0.27	900
-22K	12	0.82	±10%	70	25.0	160	0.30	800
-24J	13	1.0	±5%	70	25.0	150	0.35	750
-26J	14	1.2	±5%	60	7.9	130	0.40	700
-28J	15	1.5	±5%	60	7.9	120	0.50	630
-30J	16	1.8	±5%	60	7.9	110	0.70	530
-32J	17	2.2	±5%	60	7.9	100	0.90	470
-34J	18	2.7	±5%	60	7.9	90	1.1	420
-36J	19	3.3	±5%	60	7.9	70	1.3	390
-38J	20	3.9	±5%	60	7.9	60	1.5	360
-40J	21	4.7	±5%	60	7.9	50	1.8	330
-42J	22	5.6	±5%	60	7.9	45	2.0	310
-44J	23	6.8	±5%	60	7.9	40	2.2	300
-46J	24	8.2	±5%	60	7.9	37	2.4	290
-48J	25	10.0	±5%	60	7.9	35	2.6	280

Parts listed above are QPL/MIL qualified

Optional Tolerances: J = 5% H = 3%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com**QPL Marking** MS214;22- followed by the military dash number; Delevan cage code (99800); date code (YYWWL).**Non QPL Marking** DELEVAN; 2020; dash number; date code (YYWWL).

Note: An R after 2020 indicates a RoHS component.

QPL Example: 2020-00K (MS21422-01)

MS214

22-01

99800

0213A


RoHS/Tight Tolerance Example: 2020R-00J

DELEVAN


2020R

-02J

0827A

SERIES**2727R**
2727**Radial Toroidal Inductors**

Actual Size

**Military Specification** MS21424 (Ref.)**Physical Parameters**

	Inches	Millimeters
A	0.270 to 0.300	6.86 to 7.62
B	0.260 to 0.280	6.60 to 7.11
C	0.140 to 0.160	3.56 to 4.06
D	0.190 to 0.210	4.83 to 5.33
E	1.00 Min.	25.40 Min.
F	0.023 to 0.027	0.584 to 0.686

Current Rating at 90°C Ambient 35°C Rise**Operating Temperature** -55°C to +125°C**Maximum Power Dissipation at 90°C** 0.33 W**Core Material** Iron**Weight Max.** (Grams) 1.0**Lead Size** AWG #22 TCW

Marking 2727; dash number with tolerance letter; Delevan cage code (99800); date code (YYWWL). Note: An R after 2727 indicates a RoHS component.

Example: 2727-25J

2727

-25J

99800

0908A

Packaging Bulk only**Made in the U.S.A.**

INDUCTANCE (μH) ±5%
DASH NUMBER*
TEST FREQUENCY (MHz)
Q MINIMUM
SRF MINIMUM (MHz)
DC RESISTANCE MAXIMUM (OHMS)
CURRENT RATING MAXIMUM (mA)

SERIES 2727 IRON CORE

-01J	10.0	75	2.5	35	1.1	420
-02J	12.0	75	2.5	31	1.3	385
-03J	15.0	75	2.5	27	1.5	360
-04J	18.0	80	2.5	24	1.9	320
-05J	22.0	80	2.5	22	2.3	290
-06J	27.0	80	2.5	20	2.7	265
-07J	33.0	80	2.5	18	3.3	240
-08J	39.0	80	2.5	16	3.9	220
-09J	47.0	80	2.5	14	4.7	200
-10J	56.0	80	2.5	12	5.6	185
-11J	68.0	80	2.5	11	6.8	165
-12J	82.0	80	2.5	10	8.1	155
-13J	100.0	80	2.5	9.1	9.7	140
-14J	120.0	45	0.79	8.2	12	125
-15J	150.0	45	0.79	7.3	14	115
-16J	180.0	45	0.79	6.4	17	105
-17J	220.0	50	0.79	5.6	20	96
-18J	270.0	55	0.79	5.0	24	90
-19J	330.0	55	0.79	4.4	19	100
-20J	390.0	55	0.79	3.9	22	93
-21J	470.0	55	0.79	3.5	27	84
-22J	560.0	55	0.79	3.1	32	77
-23J	680.0	55	0.79	2.8	19	100
-24J	820.0	50	0.79	2.5	23	92
-25J	1000.0	50	0.79	2.2	27	84

*Complete part # must include series # PLUS the dash #



For surface finish information,
refer to www.delevanfinishes.com

SERIES

4445R
4445



Radial Toroidal Inductors



MIL DASH # (Ref.)
INDUCTANCE (μH)
TOLERANCE
Q MINIMUM
TEST FREQUENCY (MHz)
SRF MINIMUM (MHz)
MAXIMUM (MHz)**
DC RESISTANCE MAXIMUM (OHMS)
CURRENT RATING MAXIMUM (mA)

MS21423 (Ref.) – SERIES 4445								
-01M	1	0.010	± 20%	60	150	1000	0.020	3000
-02M	2	0.012	± 20%	60	150	1000	0.020	3000
-03M	3	0.015	± 20%	60	150	1000	0.020	3000
-04M	4	0.018	± 20%	60	150	1000	0.020	3000
-05M	5	0.022	± 20%	60	100	900	0.020	3000
-06M	6	0.027	± 20%	60	100	800	0.020	3000
-07M	7	0.033	± 20%	60	100	750	0.020	3000
-08M	8	0.039	± 20%	60	100	700	0.020	3000
-09M	9	0.047	± 20%	60	100	650	0.020	3000
-10M	10	0.056	± 20%	60	100	600	0.020	3000
-11M	11	0.068	± 20%	60	100	550	0.030	2500
-12M	12	0.082	± 20%	60	100	500	0.040	2200
-13K	13	0.100	± 10%	80	50	450	0.040	2200
-14K	14	0.120	± 10%	80	50	400	0.050	2000
-15K	15	0.150	± 10%	80	50	350	0.060	1800
-16K	16	0.180	± 10%	80	50	320	0.070	1600
-17K	17	0.220	± 10%	80	50	300	0.080	1500
-18K	18	0.270	± 10%	80	50	280	0.100	1400
-19K	19	0.330	± 10%	80	50	260	0.120	1300
-20K	20	0.390	± 10%	80	50	240	0.150	1150
-21K	21	0.470	± 10%	80	50	220	0.200	1000
-22K	22	0.560	± 10%	70	50	200	0.250	900
-23K	23	0.680	± 10%	70	50	180	0.300	800
-24K	24	0.820	± 10%	70	50	160	0.350	750
-25K	25	1.000	± 10%	70	50	150	0.400	700

Military Specification MS21423 (Ref.)

Mechanical Configuration Units are radial leaded and encapsulated in an epoxy molded package.

Physical Parameters

	Inches	Millimeters
A	0.200 to 0.230	5.08 to 5.84
B	0.190 to 0.210	4.83 to 5.33
C	0.090 to 0.110	2.29 to 2.79
D	0.090 to 0.110	2.29 to 2.79
E	1.00 Min.	25.4 Min.
F	0.0185 to 0.0215	0.470 to 0.546

Operating Temperature -55°C to +125°C

Current Rating at 90°C Ambient 35°C Rise

Maximum Power Dissipation at 90°C 0.200 W

Note Inductance measured 0.25" from body.

Weight Max. (Grams) 0.5

**** Note** Self Resonant Frequency (SRF) values above 250 MHz are calculated and for reference only.
Marking 4445; dash number with tolerance letter; Delevan cage code (99800); date code (YYWWL). Note: An R after 4445 indicates a RoHS component.

Example: 4445-01M
4445
-01M
99800
0828A

Packaging Bulk only

Made in the U.S.A.


Optional Tolerances: J = 5% H = 3% G
(Dash 01-12 Min. Tolerance is ±5%)
*Complete part # must include series # PLUS the dash #
For surface finish information, refer to www.delevanfinishes.com

SERIES

2534R
2534



Molded Unshielded RF Coils



Physical Parameters

	Inches	Millimeters
Height	0.345 Max.	8.76 Max.
Diameter	0.25 ± 0.010	6.35 ± 0.25
Lead Size		
AWG #24 TCW	0.020 ± 0.0015	0.508 ± .0038
Lead Length	1.62 ± 0.12	41.15 ± 3.05
Lead Spacing	0.170 to 0.210	4.32 to 5.33

Current Rating at 90°C Ambient 35°C Rise

Operating Temperature Range -55°C to +125°C

Maximum Power Dissipation at 90°C 0.23 W

Weight Max. (Grams) 1.0

Core Material Ferrite

Marking Delevan cage code (99800); 2534; dash number with tolerance letter. Note: An R after 2534 indicates a RoHS component.

Example: 2534R-24K

99800
2534R
-24K

Packaging Bulk only

Made in the U.S.A.

DASH NUMBER*	INDUCTANCE (mH)	TOLERANCE	Q MINIMUM	TEST FREQUENCY (kHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
--------------	-----------------	-----------	-----------	----------------------	-------------------	------------------------------	-----------------------------

SERIES 2534 FERRITE CORE							
-00K	0.10	± 10%	100	790	4.0	1.5	330
-02K	0.12	± 10%	95	790	3.3	1.8	300
-04K	0.15	± 10%	90	790	3.2	2.0	285
-06K	0.18	± 10%	85	790	2.8	2.2	277
-08K	0.22	± 10%	90	790	2.5	2.4	265
-10K	0.27	± 10%	95	790	2.3	3.2	229
-12K	0.33	± 10%	90	790	2.2	3.4	220
-14K	0.39	± 10%	80	790	2.0	4.1	203
-16K	0.47	± 10%	70	790	1.9	4.5	193
-18K	0.56	± 10%	65	790	1.8	4.8	187
-20K	0.68	± 10%	65	790	1.7	5.4	175
-22K	0.82	± 10%	65	790	1.6	5.8	170
-24K	1.00	± 10%	65	790	1.4	6.4	160
-26K	1.20	± 10%	95	250	1.2	10.0	130
-28K	1.50	± 10%	90	250	1.15	12.0	118
-30K	1.80	± 10%	90	250	1.10	14.0	110
-32K	2.20	± 10%	90	250	0.95	17.0	100
-34K	2.70	± 10%	90	250	0.86	20.0	90
-36K	3.30	± 10%	90	250	0.80	24.0	85
-38K	3.90	± 10%	85	250	0.68	27.0	80
-40K	4.70	± 10%	85	250	0.64	34.0	70
-42K	5.60	± 10%	80	250	0.60	37.0	68
-44K	6.80	± 10%	75	250	0.50	45.0	61
-46K	8.20	± 10%	65	250	0.47	48.0	59
-48K	10.0	± 10%	45	250	0.42	51.0	58
-50L	12.0	± 15%	40	79	0.41	100.0	41
-52L	15.0	± 15%	45	79	0.32	105.0	40
-54L	18.0	± 15%	45	79	0.30	120.0	37
-56L	22.0	± 15%	45	79	0.25	145.0	34
-58L	27.0	± 15%	45	79	0.24	195.0	29
-60L	33.0	± 15%	45	79	0.21	250.0	26
-62L	39.0	± 15%	40	79	0.20	295.0	23
-64L	47.0	± 15%	40	79	0.18	365.0	21.5
-66L	56.0	± 15%	40	79	0.17	430.0	19.5
-68L	68.0	± 15%	30	79	0.15	510.0	18.0
-70L	82.0	± 15%	30	79	0.14	605.0	16.6
-72L	100.0	± 15%	30	79	0.12	670.0	15.8
-74L	120.0	± 15%	30	50	0.11	900.0	13.5
-76L	150.0	± 15%	25	50	0.10	1100.0	12.0

Optional Tolerances: J = 5% H = 3%

*Complete part # must include series # PLUS the dash #


For surface finish information, refer to www.delevanfinishes.com

SERIES

4554R & 4564R
4554 & 4564



Radial Lead Inductors



Actual Size (Max.)

Physical Parameters

Series 4554

	Inches	Millimeters
A	0.34 Max.	8.64 Max.
B	0.433 Max.	11 Max.
C	0.200 Nom.	5.0 Nom.
D	0.200 Nom.	5.0 Nom.
E	0.024 Nom.	0.61 Nom.

Series 4564

	Inches	Millimeters
A	0.315 Max.	8.0 Max.
B	0.440 Max.	11.2 Max.
C	0.200 Nom.	5.0 Nom.
D	0.200 Nom.	5.0 Nom.
E	0.028 Nom.	0.71 Nom.

Operating Temperature Range

Series 4554 -40°C to +85°C

Series 4564 -20°C to +80°C

Storage Temperature Range

Series 4554 -40°C to +85°C

Series 4564 -40°C to +80°C

The Rated DC Current The amperage where the inductance value decreases 10%.

****Note: Series 4554 Inductance Tolerance** Available in J = 5% in values ≥ 100µH only

Packaging Bulk

Series 4564 Optional Tolerances: J = 5%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

DASH NUMBER*	INDUCTANCE**	TOLERANCE (%)	Q MINIMUM	TEST FREQUENCY (MHz)	SRF MINIMUM (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (A)
--------------	--------------	---------------	-----------	----------------------	-------------------	------------------------------	----------------------------


SERIES 4554 FERRITE CORE							
-1R0M	1.0 µH	±20%	20	7.96	150.0	0.013	10.0
-1R5M	1.5 µH	±20%	20	7.96	130.0	0.016	8.5
-2R2M	2.2 µH	±20%	20	7.96	100.0	0.021	6.5
-3R3M	3.3 µH	±20%	20	7.96	79.0	0.025	5.5
-4R7M	4.7 µH	±20%	20	7.96	51.0	0.030	4.3
-6R8M	6.8 µH	±20%	20	7.96	29.0	0.035	3.7
-100K	10 µH	±10%	50	2.52	14.0	0.055	3.0
-120K	12 µH	±10%	50	2.52	13.0	0.060	2.6
-150K	15 µH	±10%	50	2.52	12.0	0.065	2.2
-180K	18 µH	±10%	40	2.52	11.0	0.085	2.0
-220K	22 µH	±10%	40	2.52	9.2	0.095	1.7
-270K	27 µH	±10%	40	2.52	8.5	0.120	1.6
-330K	33 µH	±10%	30	2.52	7.8	0.140	1.5
-390K	39 µH	±10%	30	2.52	6.9	0.160	1.4
-470K	47 µH	±10%	30	2.52	6.5	0.200	1.3
-560K	56 µH	±10%	30	2.52	5.4	0.210	1.2
-680K	68 µH	±10%	30	2.52	4.9	0.210	1.2
-820K	82 µH	±10%	30	2.52	4.1	0.230	1.1
-101K	100 µH**	±10%	20	0.796	3.7	0.290	0.91
-121K	120 µH**	±10%	20	0.796	3.4	0.320	0.84
-151K	150 µH**	±10%	20	0.796	3.2	0.450	0.75
-181K	180 µH**	±10%	20	0.796	2.8	0.580	0.69
-221K	220 µH**	±10%	20	0.796	2.7	0.650	0.64
-271K	270 µH**	±10%	20	0.796	2.4	0.800	0.57
-331K	330 µH**	±10%	20	0.796	2.3	0.900	0.54
-391K	390 µH**	±10%	20	0.796	2.1	1.0	0.48
-471K	470 µH**	±10%	20	0.796	1.9	1.1	0.46
-561K	560 µH**	±10%	20	0.796	1.8	1.4	0.41
-681K	680 µH**	±10%	20	0.796	1.6	1.6	0.38
-821K	820 µH**	±10%	20	0.796	1.5	1.8	0.35
-102K	1000 µH**	±10%	50	0.252	1.3	2.9	0.29
SERIES 4564 FERRITE CORE							
-101K	0.10 mH	±10%	80	0.796	5.3	2.0	0.20
-121K	0.12 mH	±10%	80	0.796	4.5	2.0	0.20
-151K	0.15 mH	±10%	80	0.796	3.8	2.0	0.20
-181K	0.18 mH	±10%	80	0.796	3.3	3.0	0.20
-221K	0.22 mH	±10%	80	0.796	2.9	3.0	0.20
-271K	0.27 mH	±10%	80	0.796	2.6	3.0	0.20
-331K	0.33 mH	±10%	80	0.796	2.3	4.0	0.20
-391K	0.39 mH	±10%	80	0.796	2.1	4.0	0.20
-471K	0.47 mH	±10%	80	0.796	1.9	4.0	0.20
-561K	0.56 mH	±10%	80	0.796	1.7	4.0	0.20
-681K	0.68 mH	±10%	80	0.796	1.6	4.0	0.20
-821K	0.82 mH	±10%	80	0.796	1.4	6.0	0.20
-102K	1.00 mH	±10%	90	0.252	1.3	6.0	0.15
-122K	1.20 mH	±10%	90	0.252	1.2	9.0	0.15
-152K	1.50 mH	±10%	90	0.252	1.1	9.0	0.15
-182K	1.80 mH	±10%	90	0.252	1.0	9.0	0.10
-222K	2.20 mH	±10%	90	0.252	0.9	13.0	0.10
-272K	2.70 mH	±10%	90	0.252	0.8	13.0	0.10
-332K	3.30 mH	±10%	90	0.252	0.7	13.0	0.10
-392K	3.90 mH	±10%	90	0.252	0.7	13.0	0.05
-472K	4.70 mH	±10%	90	0.252	0.6	18.0	0.05
-562K	5.60 mH	±10%	90	0.252	0.6	18.0	0.05
-682K	6.80 mH	±10%	90	0.252	0.5	26.0	0.05
-822K	8.20 mH	±10%	90	0.252	0.5	26.0	0.05
-103K	10.0 mH	±10%	100	0.0796	0.4	40.0	0.04
-123K	12.0 mH	±10%	100	0.0796	0.4	40.0	0.04
-153K	15.0 mH	±10%	100	0.0796	0.4	60.0	0.04
-183K	18.0 mH	±10%	100	0.0796	0.3	60.0	0.03
-223K	22.0 mH	±10%	100	0.0796	0.3	80.0	0.03
-273K	27.0 mH	±10%	100	0.0796	0.2	80.0	0.03
-333K	33.0 mH	±10%	100	0.0796	0.2	80.0	0.03

SERIES


5400R
5400



Filter Inductors



Actual Size



DASH NUMBER*	INDUCTANCE (μH) ±10%	TEST FREQUENCY (kHz)	SRF MINIMUM (kHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT 5% INCREMENTAL	CURRENT 10% INCREMENTAL
SERIES 5400 POWDER CORE						
-106K	10	1.0	269	1.53	131	204
-126K	12	1.0	235	1.67	120	186
-156K	15	1.0	200	1.88	107	167
-186K	18	1.0	175	2.55	98	152
-226K	22	1.0	150	2.83	88	138
-276K	27	1.0	127	3.15	80	124
-336K	33	1.0	107	3.50	72	113
-396K	39	1.0	92	4.80	66	104
-476K	47	1.0	76	5.31	60	94
-566K	56	1.0	62	5.83	55	86
-686K	68	1.0	48	6.47	50	78
-826K	82	1.0	35	8.89	46	71
-107K	100	1.0	21	9.89	41	65

Optional Tolerances: J = 5% H = 3% G = 2%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

Physical Parameters

	Inches	Millimeters
A	1.30 ± 0.010	33.020 ± 0.254
B	0.73 ± 0.010	18.542 ± 0.254
C	0.150 ± 0.005	3.810 ± 0.127
D	1.00 Min.	25.4 Min.
E	0.032 Typ.	0.813 Typ.

Marking DELEVAN; 5400 followed by the dash number and tolerance letter; date code (YYWWL). Note an R after 5400 indicates a RoHS component.

Example: 5400R-396G

DELEVAN
5400R-396G
0913A

Operating Temperature Range -55°C to +125°C

Inductance Measured at 1kHz, 100mV with no DC Current

Incremental Current The current at which the inductance will be decreased by a maximum of 5% or 10% from its initial 0 DC value

Packaging Bulk Only

Contact the Factory for additional sizes and electrical configurations.



SERIES

9405R & 9406R
9405 & 9406



Tunable Variable RF Coils

Leads AWG #24 Tinned Copperweld
Tuning Torque 0.1 to 3.5 oz. in.
Pin #1 is identified by white dot on 9406 only.
Current Rating at 90°C Ambient 35°C Rise
Operating Temperature Range
-55°C to +125°C

Max. Power Dissipation at 90°C - 0.3 W
Weight Max. (Grams) 4.0

Units are electro-magnetically shielded

Core and Shield Material Ferrite

Ordering Information

Vertical Coil = Dash No. prefixed by 9405; Horizontal Coil = Dash No. prefixed by 9406. Additionally – an electrostatic shield for 9405 is available on a custom basis; order as 9415-XX

9405 Marking DEC; part number

9406 Marking Part number; DEC

Example: 9405R-10

DEC
9405R-10


Packaging Bulk only

Made in the U.S.A.

RF Inductor										
DASH NUMBER*	NOMINAL INDUCTANCE (μH)	INDUCTANCE MINIMUM (μH)	INDUCTANCE MAXIMUM (μH)	TEST FREQUENCY (MHz)	Q MINIMUM @ L MIN.	SRF MINIMUM @ L MIN.	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)		
										INDUCTANCE MAXIMUM (μH)
Horizontal Inductor – an Automated	-1	0.10	0.080	0.120	25.0	45	43	250.0	0.030	2690.0
	-2	0.15	0.120	0.180	25.0	53	50	198.0	0.035	2490.0
	-4	0.22	0.154	0.286	25.0	55	52	195.0	0.056	1970.0
	-6	0.33	0.231	0.429	25.0	51	49	142.0	0.060	1900.0
	-8	0.47	0.329	0.611	25.0	53	51	110.0	0.064	1840.0
	-10	0.68	0.476	0.884	25.0	51	48	130.0	0.073	1720.0
	-12	1.00	0.700	1.30	25/7.9	51	67	95.0	0.600	600.0
	-14	1.50	1.05	1.95	7.9	55	82	76.0	0.620	590.0
	-16	2.20	1.54	2.86	7.9	65	103	57.0	0.720	550.0
	-18	3.30	2.31	4.29	7.9	70	91	39.0	1.05	455.0
	-20	4.70	3.29	6.11	7.9	74	87	37.0	1.15	435.0
	-22	6.80	4.76	8.84	7.9	72	88	27.0	1.30	410.0
	-24	10.0	7.00	13.0	7.9/2.5	72	87	18.0	1.50	380.0
	-26	15.0	10.5	19.5	2.5	66	93	16.0	2.35	305.0
	-28	22.0	15.4	28.6	2.5	74	102	12.0	2.80	278.0
	-30	33.0	23.1	42.9	2.5	83	110	11.0	3.00	269.0
	-32	47.0	32.9	61.1	2.5	76	96	8.0	3.70	242.0
	-34	68.0	47.6	88.4	2.5	70	73	7.0	4.35	223.0
	-36	100.0	70.0	130.0	2.5/0.79	65	67	6.5	5.50	198.0
	-38	150.0	105.0	195.0	0.79	53	81	4.5	9.20	153.0
	-40	220.0	154.0	286.0	0.79	61	83	3.5	9.70	149.0
	-42	330.0	231.0	429.0	0.79	42	57	3.2	14.0	124.0
	-44	470.0	329.0	611.0	0.79	48	67	3.1	15.0	120.0
	-46	680.0	476.0	884.0	0.79	45	57	2.4	20.0	104.0
-48	1000.0	700.0	1300.0	0.79/0.25	48	52	1.9	24.5	94.0	
-50	1500.0	1050.0	1950.0	0.25	38	53	1.3	30.0	85.0	
-52	2200.0	1540.0	2860.0	0.25	42	65	1.2	38.0	75.5	
-54	3300.0	2310.0	4290.0	0.25	42	57	0.85	45.0	69.5	
-56	4700.0	3290.0	6110.0	0.25	38	51	0.68	70.0	55.5	
-58	6800.0	4760.0	8840.0	0.25	38	49	0.60	100.0	46.5	
-60	10000.0	7000.0	13000.0	0.25/0.079	40	40	0.50	115.0	43.5	

*Complete part # must include series # PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com





Physical Parameters	Dimension A	B	C	D	E	F	G	H	J	K, L
In.	0.200 ± 0.010	0.020 ± 0.0015	0.187 ± 0.020	0.500 max.	0.380 max.	0.400 ± 0.020	0.500 max.	0.300 ± 0.010	0.187 ± 0.020	0.375 max.
mm	5.08 ± 0.25	0.508 ± 0.038	4.75 ± 0.51	12.7 max.	9.65 max.	10.16 ± 0.51	12.7 max.	7.62 ± 0.25	4.75 ± 0.51	9.53 max.

SERIES

**P160R
P160**



Power Micro i® Chip Inductors



Actual Size

Physical Parameters

	Inches	Millimeters
A	0.100 Max.	2.54 Max.
B	0.145 to 0.155	3.68 to 3.94
C	0.115 to 0.125	2.92 to 3.18
D	0.070 Min.	1.78 Min.
E	0.020 to 0.030	0.508 to 0.762
F	0.020 Max. (Typ.)	0.51 Max.

Operating Temperature Range -55°C to +125°C

Current Rating at 90°C Ambient 35°C Rise

Maximum Power Dissipation at 90°C 0.170 W

Termination Standard-Tin/Lead. For RoHS, order P160R-XXXKS. Consult the factory for additional finish options.

Inductance Measured at 0.100VAC with no DC Current

Incremental Current The current at which the inductance will be decreased by a maximum of 5% from its initial 0 ADC value

Packaging Bulk only

DASH NUMBER*

INDUCTANCE (μH)
±10% @ 100 kHz

DC RESISTANCE
MAXIMUM (OHMS)

CURRENT RATING
MAXIMUM (mA)

INCREMENTAL
CURRENT (mA)

SERIES P160 FERRITE CORE				
-331KS	0.330	0.033	1929	2636
-391KS	0.390	0.035	1873	2417
-471KS	0.470	0.038	1797	2231
-561KS	0.560	0.041	1730	2071
-681KS	0.680	0.044	1670	1933
-821KS	0.820	0.050	1567	1706
-102KS	1.00	0.056	1480	1526
-122KS	1.20	0.078	1254	1381
-152KS	1.50	0.086	1195	1261
-182KS	1.80	0.093	1149	1160
-222KS	2.20	0.11	1056	1036
-272KS	2.70	0.12	1011	935
-332KS	3.30	0.16	876	829
-392KS	3.90	0.17	850	784
-472KS	4.70	0.24	715	707
-562KS	5.60	0.26	687	644
-682KS	6.80	0.28	662	592
-822KS	8.20	0.40	554	537
-103KS	10.0	0.57	464	483
-123KS	12.0	0.63	441	439
-153KS	15.0	0.70	419	397
-183KS	18.0	1.0	350	358
-223KS	22.0	1.1	334	326
-273KS	27.0	1.2	320	293
-333KS	33.0	1.6	277	266
-393KS	39.0	1.8	261	244
-473KS	47.0	1.9	254	223
-563KS	56.0	2.7	213	204
-683KS	68.0	2.9	206	185
-823KS	82.0	3.2	196	169
-104KS	100	4.6	163	153
-124KS	120	5.0	157	139
-154KS	150	6.8	134	124
-184KS	180	7.5	128	114
-224KS	220	9.8	112	103
-274KS	270	10.8	107	93
-334KS	330	12.0	101	84




Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

SERIES SP1008R SP1008

Shielded Surface Mount Power Inductors



Physical Parameters

	Inches	Millimeters
A	0.095 to 0.115	2.41 to 2.92
B	0.085 to 0.105	2.16 to 2.66
C	0.0755 to 0.095	1.91 to 2.41
D	0.010 to 0.030	0.26 to 0.76
E	0.040 to 0.060	1.02 to 1.52
F	0.060 (Ref. only)	1.52 (Ref. only)
G	0.045 (Ref. only)	1.14 (Ref. only)

Dimensions "A" and "C" are over terminals.

Operating Temperature Range -55°C to +125°C

Current Rating at 90°C Ambient 35°C Rise

Inductance Measured at 1V with no DC current

Incremental Current The current at which the inductance will be decreased by a maximum of 5% from its initial 0 ADC value.

Marking SMD; dash number with tolerance letter followed by a P; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: SP1008-104K

SMD
104KP
0925A

Packaging Tape & reel (8mm): 7" reel, 2000 pieces max.; 13" reel, 7000 pieces max.

Coupling 5% Typical (Ref. M83446, 1mm spacing)


Made In the U.S.A.

DASH NUMBER*	INDUCTANCE (μH) ±10% @ 100 KHz	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
SERIES SP1008 FERRITE CORE			
-271K	0.270	0.099	1070
-331K	0.330	0.108	1030
-391K	0.390	0.118	980
-471K	0.470	0.128	941
-561K	0.560	0.147	878
-681K	0.680	0.157	850
-821K	0.820	0.167	824
-102K	1.00	0.228	705
-122K	1.20	0.252	671
-152K	1.50	0.288	627
-182K	1.80	0.392	538
-222K	2.20	0.437	509
-272K	2.70	0.482	485
-332K	3.30	0.527	465
-392K	3.90	0.739	392
-472K	4.70	0.817	372
-562K	5.60	0.895	356
-682K	6.80	1.43	282
-822K	8.20	1.54	271
-103K	10.0	1.70	258
-123K	12.0	1.87	246
-153K	15.0	2.10	232
-183K	18.0	2.88	198
-223K	22.0	4.02	168
-273K	27.0	4.50	159
-333K	33.0	4.90	152
-393K	39.0	5.30	146
-473K	47.0	5.90	139
-563K	56.0	6.40	133
-683K	68.0	9.00	112
-823K	82.0	9.90	107
-104K	100	10.9	102

Optional Tolerances: J = 5% H = 3% G = 2%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com




SERIES**SP1210R
SP1210****Shielded Surface Mount Power Inductors**

DASH NUMBER*

INDUCTANCE (μH)
±10% @100 kHzDC RESISTANCE
MAXIMUM (OHMS)CURRENT RATING
MAXIMUM (mA DC)INCREMENTAL
CURRENT (mA DC)

Actual Size

**Physical Parameters**

	Inches	Millimeters
A	0.118 to 0.138	3.00 to 3.51
B	0.085 to 0.105	2.16 to 2.66
C	0.081 to 0.101	2.06 to 2.57
D	0.016 Min.	0.41 Min.
E	0.041 to 0.061	1.04 to 1.55
F	0.070 (Ref. Only)	1.78 (Ref. Only)
G	0.054 (Ref. Only)	1.37 (Ref. Only)

Dimensions "A" and "C" are over terminals.

Operating Temperature Range -55°C to +125°C**Current Rating at 90°C Ambient** 35°C Rise**Maximum Power Dissipation at 90°C** 0.287 W**Inductance** Measured at 1V with no DC current**Incremental Current** The current at which the inductance will be decreased by a maximum of 5% from its initial DC value**Marking** API, dash number with tolerance letter followed by a P, date code/lot (YYWWL). Note: An R before the date code/lot symbol indicates a RoHS component.

Example: SP1210R-102J

API

102JP

R 1028A

Packaging Tape & reel (12mm): 7" reel, 650 pieces max.; 13" reel, 2500 pieces max.**Coupling** 5% Typical (Ref. M83446, 1mm spacing)**Made In the U.S.A.****SERIES SP1210 FERRITE CORE**


-471K	0.470	0.100	1440	1870
-561K	0.560	0.109	1380	1720
-681K	0.680	0.119	1320	1580
-821K	0.820	0.133	1250	1420
-102K	1.00	0.147	1190	1290
-122K	1.20	0.160	1140	1180
-152K	1.5	0.175	1080	1060
-182K	1.80	0.195	1030	965
-222K	2.20	0.211	992	892
-272K	2.70	0.305	826	784
-332K	3.30	0.440	692	718
-392K	3.90	0.470	665	665
-472K	4.70	0.520	633	601
-562K	5.60	0.570	606	550
-682K	6.80	0.630	576	497
-822K	8.20	0.880	487	454
-103K	10.0	0.960	464	410
-123K	12.0	1.3	400	375
-153K	15.0	1.8	338	336
-183K	18.0	2.0	322	304
-223K	22.0	2.2	306	275
-273K	27.0	2.5	291	249
-333K	33.0	3.5	243	225
-393K	39.0	4.6	212	207
-473K	47.0	5.0	203	189
-563K	56.0	5.5	194	174
-683K	68.0	6.1	185	157
-823K	82.0	7.9	162	143
-104K	100	8.7	154	129
-124K	120	9.6	147	118
-154K	150	13.5	124	106
-184K	180	14.7	119	96
-224K	220	20.7	100	87
-274K	270	23.0	95	79
-334K	330	26.8	88	71
-394K	390	32.4	80	65

Optional Tolerances: J = 5% H = 3% G = 2%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

Surface Mount Power Inductors



Physical Parameters

	Inches	Millimeters
A	0.300 to 0.325	7.62 to 8.26
B	0.105 to 0.125	2.67 to 3.18
C	0.125 to 0.145	3.18 to 3.68
D	0.020 Min.	0.508 Min.
E	0.040 to 0.060	1.02 to 1.52
F	0.190 (Ref. only)	4.83 (Ref. only)
G	0.070 (Ref. only)	1.78 (Ref. only)

Weight Max (Grams) 0.30

Operating Temperature Range -55°C to +125°C

Current Rating at 90°C Ambient 35°C Rise

Maximum Power Dissipation at 90°C 0.210 W

Inductance Measured at 1V with no DC current

Incremental Current The current at which the inductance will be decreased by a maximum of 5% from its initial zero DC value.

Marking API/SMD; inductance with units and tolerance followed by a P; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: P1330-104J

API/SMD
8.2uH±10%P
0719A

Packaging Tape & reel (16mm): 7" reel, 500 pieces max.; 13" reel, 2200 pieces max.

Made In the U.S.A. Patent Protected


DASH NUMBER*	INDUCTANCE (uH) ±10% @ 1 kHz	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA DC)	INCREMENTAL CURRENT (mA DC)
SERIES P1330 FERRITE CORE				
-102K	1.0	0.035	2780	1526
-122K	1.2	0.041	2690	1400
-152K	1.5	0.043	2030	1291
-182K	1.8	0.048	1950	1180
-222K	2.2	0.075	1690	1104
-272K	2.7	0.080	1550	936
-332K	3.3	0.108	1460	840
-392K	3.9	0.118	1390	732
-472K	4.7	0.125	1330	720
-562K	5.6	0.145	1110	612
-682K	6.8	0.165	1080	600
-822K	8.2	0.180	1020	600
-103K	10	0.216	946	564
-123K	12	0.252	912	516
-153K	15	0.288	858	432
-183K	18	0.328	817	420
-223K	22	0.384	694	348
-273K	27	0.425	657	324
-333K	33	0.538	568	270
-393K	39	0.600	488	270
-473K	47	0.792	467	246
-563K	56	0.900	442	216
-683K	68	1.020	384	174
-823K	82	1.380	362	150
-104K	100	1.680	347	132
-124K	120	1.800	327	111
-154K	150	2.040	272	106
-184K	180	2.400	261	89
-224K	220	2.648	223	72
-274K	270	4.320	191	60
-334K	330	4.800	179	57
-394K	390	5.640	171	48
-474K	470	6.000	161	41
-564K	560	6.960	138	35
-684K	680	8.760	130	30
-824K	820	9.960	113	26
-105K	1000	11.160	105	22

Optional Tolerances: J = 5% H = 3% G = 2%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

Surface Mount Power Inductors



Physical Parameters

	Inches	Millimeters
A	0.166 to 0.190	4.22 to 4.83
B	0.118 to 0.134	3.00 to 3.40
C	0.118 to 0.134	3.00 to 3.40
D	0.015 Min.	0.38 Min.
E	0.054 to 0.078	1.37 to 1.98
F	0.118 (Ref. only)	3.00 (Ref. only)
G	0.066 (Ref. only)	1.68 (Ref. only)

Dimensions "A" and "C" are over terminals

Operating Temperature Range -55°C to +125°C

Current Rating at 90°C Ambient 35°C Rise

Maximum Power Dissipation at 90°C 0.278 W

Inductance Measured at 1V with no DC current

Incremental Current The current at which the inductance will be decreased by a maximum of 5% from its initial zero DC value.

Marking API/SMD; inductance with units and tolerance followed by an SP; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: P1812-182K

API/SMD
1.8uH±10%P
0808B

Packaging Tape & reel (12mm): 7" reel, 650 pieces max.; 13" reel, 2500 pieces max.

Made In the U.S.A. Patent Protected

DASH NUMBER*	INDUCTANCE (uH) ±10% @ 1 kHz	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA DC)	INCREMENTAL CURRENT (mA DC)
SERIES P1812 FERRITE CORE				
-102K	1.0	0.113	1050	2400
-122K	1.2	0.199	1000	2158
-152K	1.5	0.222	950	1980
-182K	1.8	0.240	900	1828
-222K	2.2	0.268	850	1697
-272K	2.7	0.288	800	1513
-332K	3.3	0.323	750	1397
-392K	3.9	0.347	700	1250
-472K	4.7	0.401	650	1131
-562K	5.6	0.437	650	1060
-682K	6.8	0.472	600	990
-822K	8.2	0.548	600	871
-103K	10	0.608	550	772
-123K	12	0.670	550	752
-153K	15	0.780	450	693
-183K	18	0.875	400	614
-223K	22	1.200	370	515
-273K	27	1.404	330	465
-333K	33	1.578	300	425
-393K	39	1.848	280	376
-473K	47	2.064	260	366
-563K	56	2.268	240	336
-683K	68	3.408	220	297
-823K	82	3.648	200	267
-104K	100	4.320	180	238
-124K	120	6.000	160	208
-154K	150	6.432	140	183
-184K	180	8.400	120	158
-224K	220	9.680	120	143
-274K	270	12.720	100	129
-334K	330	15.240	90	118


Optional Tolerances: J = 5% H = 3% G = 2%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

SERIES**MILP1812**
**MIL-PRF-27/368 Qualified
Surface Mount Power Inductors**
Power Inductors


Actual Size


Physical Parameters

	Inches	Millimeters
A	0.166 to 0.190	4.22 to 4.83
B	0.118 to 0.134	3.00 to 3.40
C	0.118 to 0.134	3.00 to 3.40
D	0.015 Min.	0.38 Min.
E	0.054 to 0.078	1.37 to 1.98
F	0.118 (Ref. only)	3.00 (Ref. only)
G	0.066 (Ref. only)	1.68 (Ref. only)

Dimensions "A" and "C" are over terminals

Operating Temperature Range -55°C to +130°C

Current Rating at 90°C Ambient 40°C Rise

Maximum Power Dissipation at 90°C 0.278 W

Inductance Measured at 1V with no DC current

Incremental Current The current at which the inductance will decrease by a maximum of 5% from its inductance at zero DC current.

Marking Military Part Number; MP1812 followed by the dash number with tolerance letter; date code (YYWWL).

Example: MILP1812-103K

 M27/368-13
 MP1812-103K
 0905A

Packaging Tape & reel (12mm): 7" reel, 650 pieces max.; 13" reel, 2500 pieces max.

Lead Finish Sn63Pb37
 (Tin-Lead) Hot Solder Dipped

Made In the U.S.A.

DASH NUMBER*

MIL DASH

 INDUCTANCE (μH)
 ±10% @ 1KHz

 DC RESISTANCE
 MAXIMUM (OHMS)

 CURRENT RATING
 MAXIMUM (mA DC)

 INCREMENTAL
 CURRENT (mA DC)


M27/368 - SERIES MILP1812 FERRITE CORE

-102K	-01	1.0	0.113	1050	2400
-122K	-02	1.2	0.199	1000	2158
-152K	-03	1.5	0.222	950	1980
-182K	-04	1.8	0.240	900	1828
-222K	-05	2.2	0.268	850	1697
-272K	-06	2.7	0.288	800	1513
-332K	-07	3.3	0.323	750	1397
-392K	-08	3.9	0.347	700	1250
-472K	-09	4.7	0.401	650	1131
-562K	-10	5.6	0.437	650	1060
-682K	-11	6.8	0.472	600	990
-822K	-12	8.2	0.548	600	871
-103K	-13	10	0.608	550	772
-123K	-14	12	0.670	550	752
-153K	-15	15	0.780	450	693
-183K	-16	18	0.875	400	614
-223K	-17	22	1.200	370	515
-273K	-18	27	1.404	330	465
-333K	-19	33	1.578	300	425
-393K	-20	39	1.848	280	376
-473K	-21	47	2.064	260	366
-563K	-22	56	2.268	240	336
-683K	-23	68	3.408	220	297
-823K	-24	82	3.648	200	267
-104K	-25	100	4.320	180	238
-124K	-26	120	6.000	160	208
-154K	-27	150	6.432	140	183
-184K	-28	180	8.400	120	158
-224K	-29	220	9.680	120	143
-274K	-30	270	12.720	100	129
-334K	-31	330	15.240	90	118

*Complete part # must include series # PLUS the dash #

SERIES**SP1812R
SP1812****Shielded Surface Mount Power Inductors**

DASH NUMBER*

INDUCTANCE (μ H)
 $\pm 10\%$ @ 1 kHzDC RESISTANCE
MAXIMUM (OHMS)CURRENT RATING
MAXIMUM (mA DC)INCREMENTAL
CURRENT (mA DC)**Physical Parameters**

	Inches	Millimeters
A	0.166 to 0.190	4.22 to 4.83
B	0.118 to 1.34	3.00 to 3.40
C	0.118 to 1.34	3.00 to 3.40
D	0.015 Min.	0.38 Min.
E	0.054 to 0.078	1.37 to 1.98
F	0.118 (Ref. only)	3.00 (Ref. only)
G	0.066 (Ref. only)	1.68 (Ref. only)

Dimensions "A" and "C" are over terminals.

Operating Temperature Range -55°C to $+125^{\circ}\text{C}$ **Current Rating at 90°C Ambient** 35°C Rise**Maximum Power Dissipation at 90°C** 0.287 W**Inductance** Measured at 1V with no DC current

Incremental Current The current at which the inductance will be decreased by a maximum of 10% from its initial DC value

Marking API/SMD; inductance with units and tolerance followed by an SP; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: SP1812R-182K

API/SMD

1.8 μ H $\pm 10\%$ SP

R 0904A

Packaging Tape & reel (12mm): 7" reel, 650 pieces max.; 13" reel, 2500 pieces max.


Coupling 5% Typical (Ref. M83446, 1mm spacing)**Made In the U.S.A.****SERIES SP1812 FERRITE CORE**

-102K	1.00	0.081	1580	2060
-122K	1.20	0.088	1510	1890
-152K	1.50	0.098	1430	1690
-182K	1.80	0.11	1360	1540
-222K	2.20	0.15	1170	1390
-272K	2.70	0.16	1110	1270
-332K	3.30	0.18	1060	1150
-392K	3.90	0.20	1000	1000
-472K	4.70	0.21	969	959
-562K	5.60	0.24	920	866
-682K	6.80	0.26	878	789
-822K	8.20	0.28	842	724
-103K	10.0	0.31	802	657
-123K	12.0	0.34	767	602
-153K	15.0	0.49	640	530
-183K	18.0	0.68	613	486
-223K	22.0	0.75	509	438
-273K	27.0	1.0	430	400
-333K	33.0	1.2	408	359
-393K	39.0	1.6	354	332
-473K	47.0	1.8	335	296
-563K	56.0	1.9	323	275
-683K	68.0	2.7	275	250
-823K	82.0	2.9	262	228
-104K	100	3.2	250	206
-124K	120	4.6	210	188
-154K	150	5.1	198	168
-184K	180	6.7	172	154
-224K	220	7.5	164	139
-274K	270	9.8	143	125
-334K	330	10.9	136	113

Optional Tolerances: J = 5% H = 3% G = 2%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

**SERIES 2512R
2512****Surface Mount Power Inductors****Physical Parameters**

	Inches	Millimeters
A	0.235 to 0.255	5.97 to 6.48
B	0.085 to 0.105	2.16 to 2.67
C	0.090 to 0.110	2.29 to 2.79
D	0.060 to 0.080	1.52 to 2.03
E	0.035 to 0.055	0.89 to 1.40
F	0.100 (Ref. only)	2.54 (Ref. only)
G	0.058 (Ref. only)	1.47 (Ref. only)

Dimensions "A" and "C" are over terminals

Operating Temperature Range -55°C to +125°C**Maximum Power Dissipation at 60°C** 0.56 W

Note Current rating is based on 60°C ambient and 125°C max. operating temperature. The Incremental Current is the current which causes a maximum change of inductance of 10%.

Marking API/SMD; HC followed by the dash number with tolerance letter; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 2512-102K

API/SMD
HC102K
0845A

Packaging Tape & reel (12mm):

7" reel, 750 pieces max.; 13" reel, 2700 pieces max.

Made In the U.S.A. Patent Protected

DASH NUMBER*	INDUCTANCE (μH) ±10%	TEST FREQUENCY (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)	INCREMENTAL CURRENT DC (mA)
SERIES 2512 FERRITE CORE					
-102K	1.0	7.9	0.15	1640	1230
-122K	1.2	7.9	0.21	1390	1040
-152K	1.5	7.9	0.27	1220	920
-182K	1.8	7.9	0.29	1180	890
-222K	2.2	7.9	0.40	1000	750
-272K	2.7	7.9	0.54	865	649
-332K	3.3	7.9	0.75	734	551
-392K	3.9	7.9	0.82	702	527
-472K	4.7	7.9	1.0	636	477
-562K	5.6	7.9	1.1	606	455
-682K	6.8	7.9	1.2	580	435
-822K	8.2	7.9	1.3	557	418
-103K	10.0	7.9	1.5	519	389
-123K	12.0	2.5	1.6	503	377
-153K	15.0	2.5	1.8	474	355
-183K	18.0	2.5	2.6	394	296
-223K	22.0	2.5	3.5	340	255
-273K	27.0	2.5	3.7	330	248
-333K	33.0	2.5	3.8	326	245
-393K	39.0	2.5	3.9	322	242
-473K	47.0	2.5	4.2	310	233
-563K	56.0	2.5	4.6	296	222
-683K	68.0	2.5	5.1	281	211
-823K	82.0	2.5	5.6	278	209
-104K	100.0	2.5	6.0	260	195

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #


For surface finish information, refer to www.delevanfinishes.com

SERIES 3483R S3483R

Surface Mount Power Inductors



Actual Size



Physical Parameters

	Inches	Millimeters
A	0.276 to 0.299	7.0 to 7.6
B	0.114 to 0.138	2.9 to 3.5
C	0.276 to 0.299	7.0 to 7.6
D	0.067 to 0.091	1.7 to 2.3
E	0.201 to 0.224	5.1 to 5.7
F	0.033 Nom.	0.85 Nom.

F = Electrode Thickness

Current Rating

The DC where inductance value decreases 10% or where the temperature rise is 40°C max.

Operating Temperature Range -20°C to +80°C

Marking Printed with the last three numbers of the Delevan Part Number (i.e. 101)

Electrical Characteristics (Initial) @ 25°C

Marking Components are marked with three characters. In the instance of two digits and a letter R, the R indicates a decimal point and the remaining digits indicates the inductance in H. When three digits are present, the first two digits indicate the inductance in H and the third digit indicates the number of trailing zeros where a zero indicates that there are no trailing zeros.

Example: 3483R-1R5M (1.5 H)

1R5

Example: S3483R-101M (100 H)

101

Packaging Tape and Reel

(16mm): 13" reel, 1000 pieces max.; 7" reel not available.

DASH NUMBER*	INDUCTANCE (μH) ±20% @ 100 kHz	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (Amps)
SERIES 3483 - UNSHIELDED FERRITE CORE			
-1R0M	1.0	0.022	2.88
-1R5M	1.5	0.026	2.67
-2R2M	2.2	0.032	2.40
-3R3M	3.3	0.041	2.08
-4R7M	4.7	0.049	1.92
-6R8M	6.8	0.067	1.60
-100M	10.0	0.085	1.41
-120M	12.0	0.100	1.28
-150M	15.0	0.130	1.12
-180M	18.0	0.160	1.00
-220M	22.0	0.180	0.93
-270M	27.0	0.240	0.80
-330M	33.0	0.290	0.72
-390M	39.0	0.340	0.66
-470M	47.0	0.410	0.59
-560M	56.0	0.480	0.55
-680M	68.0	0.600	0.49
-820M	82.0	0.710	0.44
-101M	100.0	0.950	0.38
SERIES S3483 - SHIELDED FERRITE CORE & SLEEVE			
-1R0M	1.0	0.019	3.12
-1R5M	1.5	0.023	2.85
-2R2M	2.2	0.028	2.66
-3R3M	3.3	0.035	2.26
-4R7M	4.7	0.043	1.96
-6R8M	6.8	0.055	1.76
-100M	10.0	0.080	1.34
-120M	12.0	0.090	1.23
-150M	15.0	0.120	1.09
-180M	18.0	0.130	0.99
-220M	22.0	0.150	0.90
-270M	27.0	0.210	0.81
-330M	33.0	0.250	0.72
-390M	39.0	0.310	0.67
-470M	47.0	0.350	0.60
-560M	56.0	0.430	0.55
-680M	68.0	0.520	0.50
-820M	82.0	0.600	0.46
-101M	100.0	0.790	0.41

*Complete part # must include series # PLUS the dash #


For surface finish information, refer to www.delevanfinishes.com

SERIES

SDS130R

RoHS
Compliant

Surface Mount Shielded Power Choke



Actual Size

Physical Parameters

	Inches	Millimeters
A	0.500 ±0.008	12.7 ±0.2
B	0.398 ±0.008	10.1 ±0.2
C	0.118 Max.	3.0 Max.
D	0.094 ±0.008	2.4 ±0.2
E	0.087 ±0.008	2.2 ±0.2
F	0.303 ±0.015	7.7 ±0.4
G	0.287 Ref.	7.3 Ref.
H	0.118 Ref.	3.0 Ref.
I	0.110 Ref.	2.8 Ref.

Current rating at 25°C Ambient

40°C Max. Rise

Operating Temperature Range

-40°C to +85°C

Weight Maximum

0.85 grams

Marking For values lower than 10 H the R indicates a decimal point and the remaining digits indicate the inductance in H. For values 10 H and above, the first two digits indicate the inductance in H and the third digit indicates the number of trailing zeros where a zero indicates that there are no trailing zeros.

Example: SDS130R-222N (2.2 H)
2R2

Example: SDS130R-473M (47 H)
470


Packaging

Tape & Reel (24mm): 13" reel
1000 pieces max.

DASH NUMBER*	INDUCTANCE (μH)	TOLERANCE	TEST FREQUENCY (MHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
SERIES SDS130 FERRITE CORE & SLEEVE					
-222N	2.2	±30%	100	0.045	3500
-302N	3.0	±30%	100	0.062	3000
-392N	3.9	±30%	100	0.070	2800
-472N	4.7	±30%	100	0.078	2500
-682N	6.8	±30%	100	0.100	2200
-103M	10	±20%	1	0.145	2000
-123M	12	±20%	1	0.185	1750
-153M	15	±20%	1	0.20	1500
-183M	18	±20%	1	0.27	1400
-223M	22	±20%	1	0.30	1300
-273M	27	±20%	1	0.40	1200
-333M	33	±20%	1	0.45	1100
-393M	39	±20%	1	0.56	950
-473M	47	±20%	1	0.65	800
-563M	56	±20%	1	0.68	750
-683M	68	±20%	1	0.80	700
-823M	82	±20%	1	1.20	650
-104M	100	±20%	1	1.40	600
-124M	120	±20%	1	1.52	550
-154M	150	±20%	1	1.80	500
-184M	180	±20%	1	2.20	450
-224M	220	±20%	1	2.70	400
-274M	270	±20%	1	3.10	350
-334M	330	±20%	1	3.60	300
-394M	390	±20%	1	4.60	250
-474M	470	±20%	1	5.10	200

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com



SERIES

SDS680R

RoHS
Compliant

Surface Mount Shielded Power Choke



Physical Parameters

	Inches	Millimeters
A	0.260 Max.	6.60 Max.
B	0.175 Max.	4.45 Max.
C	0.115 Max.	2.92 Max.
D	0.040 ±0.010	1.02 ±0.25
E	0.050 Max.	1.27 Max.
F	0.170 ±0.015	4.32 ±0.38
G	0.120 Ref.	3.05 Ref.
H	0.055 Ref.	1.40 Ref.
I	0.140 Ref.	3.56 Ref.
J	0.160 Ref.	4.06 Ref.

Current rating at 25°C Ambient

40°C Max. Rise

Operating Temperature Range

-40°C to +85°C

Weight Maximum

0.20 grams

Marking For values lower than 10 H the R indicates a decimal point and the remaining digits indicate the inductance in H. For values 10 H and above, the first two digits indicate the inductance in H and the third digit indicates the number of trailing zeros where a zero indicates that there are no trailing zeros.

Example: SDS680R-102M (1.0 H)
1R0

Example: SDS680R-106M (10,000 H)
103


Packaging

Tape & Reel (16mm): 13" reel
2000 pieces max.

DASH NUMBER*	INDUCTANCE (μH) C 100 kHz	TOLERANCE	SRF (MHz) REF. ONLY	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
SERIES SDS680 FERRITE CORE & SLEEVE					
-102M	1.0	±20%	250	0.040	3000
-152M	1.5	±20%	125	0.045	2800
-222M	2.2	±20%	120	0.050	1800
-332M	3.3	±20%	120	0.055	1600
-472M	4.7	±20%	105	0.060	1400
-682M	6.8	±20%	50	0.065	1200
-103M	10	±20%	38	0.075	1000
-153M	15	±20%	33	0.090	800
-223M	22	±20%	25	0.110	700
-333M	33	±20%	20	0.190	600
-473M	47	±20%	20	0.230	500
-683M	68	±20%	15	0.290	400
-104M	100	±20%	10	0.480	300
-154M	150	±20%	9	0.590	260
-224M	220	±20%	6	0.770	220
-334M	330	±20%	5	1.40	200
-474M	470	±20%	4	1.80	190
-684M	680	±20%	3	2.20	180
-105M	1000	±20%	2	3.40	150
-155M	1500	±20%	2	4.20	120
-225M	2200	±20%	2	8.50	100
-335M	3300	±20%	1	11.0	80
-475M	4700	±20%	1	13.9	60
-685M	6800	±20%	1	25.0	40
-106M	10000	±20%	0.8	32.8	20

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com




SERIES

SDS850R

RoHS
Compliant

Surface Mount Shielded Power Choke



Physical Parameters

	Inches	Millimeters
A	0.413 ±0.008	10.5 ±0.2
B	0.315 ±0.008	8.0 ±0.2
C	0.190 Max.	4.8 Max.
D	0.083 ±0.008	2.1 ±0.2
E	0.079 ±0.008	2.0 ±0.2
F	0.236 ±0.012	6.0 ±0.3
G	0.224 Ref.	5.7 Ref.
H	0.094 Ref.	2.4 Ref.
I	0.087 Ref.	2.2 Ref.

Current rating at 25°C Ambient

40°C Max. Rise

Operating Temperature Range

-40°C to +85°C

Weight Maximum

0.95 grams

Marking For values lower than 10 H the R indicates a decimal point and the remaining digits indicate the inductance in H. For values 10 H and above, the first two digits indicate the inductance in H and the third digit indicates the number of trailing zeros where a zero indicates that there are no trailing zeros.

Example: SDS850R-392N (3.9 H)
3R9

Example: SDS850R-105M (1,000 H)
102


Packaging

Tape & Reel (16mm): 13" reel
1000 pieces max.

DASH NUMBER*	INDUCTANCE (μH)	TOLERANCE	TEST FREQUENCY (kHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
SERIES SDS850 FERRITE CORE & SLEEVE					
-222N	2.2	±30%	100	0.040	2500
-392N	3.9	±30%	100	0.055	2100
-562N	5.6	±30%	100	0.065	1950
-822N	8.2	±30%	100	0.080	1750
-103M	10	±20%	1	0.100	1500
-123M	12	±20%	1	0.120	1400
-153M	15	±20%	1	0.140	1300
-183M	18	±20%	1	0.160	1200
-223M	22	±20%	1	0.180	1100
-273M	27	±20%	1	0.200	1000
-333M	33	±20%	1	0.240	920
-393M	39	±20%	1	0.260	840
-473M	47	±20%	1	0.280	750
-563M	56	±20%	1	0.380	680
-683M	68	±20%	1	0.440	600
-823M	82	±20%	1	0.550	540
-104M	100	±20%	1	0.600	500
-124M	120	±20%	1	0.750	450
-154M	150	±20%	1	0.900	400
-184M	180	±20%	1	1.050	350
-224M	220	±20%	1	1.180	300
-274M	270	±20%	1	1.40	270
-334M	330	±20%	1	1.80	240
-394M	390	±20%	1	2.10	220
-474M	470	±20%	1	2.25	200
-564M	560	±20%	1	3.00	180
-684M	680	±20%	1	3.40	170
-824M	820	±20%	1	4.00	160
-105M	1000	±20%	1	5.00	150

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com




SERIES


4501R 4501



Surface Mount Low-Profile Power Toroids



SCHEMATIC



Actual Size



Test Methods Solderability per MIL-STD-202, Method 208. Inductance tested @ 10 kHz and zero Amps DC. Tested at 25°C.

Mechanical Configuration A flat top surface mount case with excellent coplanarity of terminals.

Physical Parameters

	Inches	Millimeters
A	0.285 ± 0.010	7.24 ± 0.25
B	0.360 ± 0.010	9.14 ± 0.25
C	0.060 ± 0.010	1.52 ± 0.25
D	0.350 ± 0.010	8.90 ± 0.25
E	0.200 ± 0.010	5.08 ± 0.25
F	0.025 ± 0.010	0.64 ± 0.25
G	0.040 (Ref.)	1.02 (Ref.)

Electrical Configuration Two inductors per unit; internal terminals: #1 (start) – #2 (finish) & #4 (start) – #3 (finish).

Series Externally connect #2 to #4.

Parallel Externally connect #1 to #4 and #2 to #3.

Operating Temperature Range –55°C to +125°C

Rated DC Current Based upon 20°C temperature rise from 25°C ambient.

Maximum Power Dissipation at 25°C 0.230 Watts

Inductance Tolerance Tolerance is specified by suffixing an alpha character to the part number as follows: K = 10%, L = 15%, M = 20%. Units are normally supplied to the tolerance indicated in the tables.

Marking Delevan; inductance and tolerance. A white dot indicates the location of pin 1. Note: RoHS component components will be marked with 4501R.

Example: 4501-102

DELEVAN
.47uH±20%

0 AMPS DC INDUCTANCE
±20% (μH @ 10 kHz)

DCR (OHMS) MAXIMUM

RATED DC CURRENT
(Amps) MAXIMUM

INDUCTANCE (μH) MINIMUM
@ Rated DC Current

Power Inductors


SERIES 4501 FERROUS ALLOY CORE

Parallel Connected Specifications

-102M	0.47	0.005	6.50	0.30
-104M	0.68	0.006	5.50	0.40
-106M	1.00	0.008	5.00	0.60
-108M	2.00	0.010	4.50	1.20
-110M	5.00	0.020	3.00	3.00
-112M	8.00	0.025	2.70	4.80
-114M	10.0	0.030	2.50	6.00
-116M	15.0	0.060	1.70	9.50
-118M	20.0	0.080	1.50	12.0
-120M	25.0	0.090	1.40	15.0
-122M	33.0	0.105	1.40	20.0
-124M	50.0	0.200	0.95	30.0
-126M	68.0	0.300	0.80	40.0
-128M	100.0	0.400	0.65	60.0
-130M	150.0	0.550	0.60	90.0
-132M	200.0	0.750	0.45	120.0
-134M	300.0	1.100	0.40	180.0

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com



Series Connected Specifications

Inductance Four (4) times parallel inductance specifications.

DCR Four (4) times parallel DCR specifications.

Rated DC Current minimum One-half of parallel Rated DC Current specifications.

Packaging Tape & reel (24mm):
13" reel, 600 pieces max.; 7" reel not available



Weight (Grams) 1.0 (Ref.)

SERIES

4448R
4448



Surface Mount High Current Power Toroids



Actual Size



Test Methods Solderability per MIL-STD-202, Method 208. Inductance tested at 10 kHz and zero Amp DC. Tested at 25°C

Mechanical Configuration A flat top surface mount case with excellent coplanarity of terminals.

Physical Parameters

	Inches	Millimeters
A	0.390 to 0.410	9.91 to 10.41
B	0.520 to 0.540	13.21 to 13.71
C	0.115 to 0.135	2.92 to 3.43
D	0.480 to 0.500	12.19 to 12.70
E	0.310 Max.	7.87 Max.
F	0.020 to 0.040	0.51 to 1.02
G	0.060 (Ref. only)	1.52 (Ref. only)

Electrical Configuration Two inductors per unit; internal terminals: #1(start) – #2(finish) & #4(start) – #3 (finish).

Series Externally connect #2 to #4.

Parallel Externally connect #1 to # 4 and # 2 to # 3.

Operating Temperature Range –55°C to +125°C

Rated DC Current Based upon 20°C temperature rise from 25°C ambient.

Maximum Power Dissipation at 25°C 0.313 Watts

Inductance Tolerance Tolerance is specified by suffixing an alpha character to the part number as follows: K = 10%, L = 15%. M = 20%. Units are normally supplied to the tolerance indicated in the tables.

Marking Delevan; inductance and tolerance. A white dot indicates the location of pin 1.

Example: 4448-102M
DELEVAN
.47uH±20%

Weight (Grams) 2.5 (Ref.)

Inductance at Rated DC Current Minimum percent of measured zero Amp DC Inductance.
-02M to -34L = 60%; -102M to 134L = 50%

Packaging Tape & reel (24mm):
13" reel, 350 pieces max.; 7" reel not available


0 AMPS DC PARALLEL INDUCTANCE (uH)	RATED PARALLEL DC CURRENT MAXIMUM	TOLERANCE	0 AMPS DC SERIES INDUCTANCE (uH)	TOLERANCE	RATED SERIES DC MAXIMUM (AMPS)	SERIES DC RESISTANCE MAXIMUM (OHMS)
---------------------------------------	--------------------------------------	-----------	-------------------------------------	-----------	-----------------------------------	--

SERIES 4448 POWDERED IRON CORE							
-02M	0.47	± 20%	7.90	0.005	2.00	± 20%	3.95
-04M	0.68	± 20%	7.20	0.006	3.00	± 20%	3.60
-06M	1.00	± 20%	5.90	0.009	4.00	± 20%	2.95
-08M	2.00	± 20%	4.60	0.014	8.00	± 20%	2.30
-10M	5.00	± 20%	3.30	0.027	20.0	± 20%	1.65
-12M	8.00	± 20%	3.00	0.033	32.0	± 20%	1.50
-14L	10.0	± 15%	2.50	0.047	40.0	± 15%	1.25
-16L	15.0	± 15%	2.30	0.057	60.0	± 15%	1.15
-18L	20.0	± 15%	1.90	0.085	80.0	± 15%	0.95
-20L	25.0	± 15%	1.60	0.116	100	± 15%	0.80
-22L	33.0	± 15%	1.30	0.166	132	± 15%	0.65
-24L	50.0	± 15%	1.20	0.202	200	± 15%	0.60
-26L	68.0	± 15%	1.10	0.238	272	± 15%	0.55
-28L	100	± 15%	0.72	0.565	400	± 15%	0.36
-30L	150	± 15%	0.64	0.696	600	± 15%	0.32
-32L	200	± 15%	0.60	0.810	800	± 15%	0.30
-34L	300	± 15%	0.54	1.003	1200	± 15%	0.27

SERIES 4448 FERROUS ALLOY CORE							
-102M	0.47	± 20%	7.90	0.004	2.00	± 20%	3.95
-104M	0.68	± 20%	7.00	0.005	3.00	± 20%	3.50
-106M	1.00	± 20%	6.50	0.006	4.00	± 20%	3.25
-108M	2.00	± 20%	5.90	0.007	8.00	± 20%	2.95
-110M	5.00	± 20%	4.40	0.014	20.0	± 20%	2.20
-112M	8.00	± 20%	3.50	0.019	32.0	± 20%	1.75
-114L	10.0	± 15%	3.40	0.020	40.0	± 15%	1.70
-116L	15.0	± 15%	3.00	0.024	60.0	± 15%	1.50
-118L	20.0	± 15%	2.10	0.055	80.0	± 15%	1.05
-120L	25.0	± 15%	2.00	0.064	100	± 15%	1.00
-122L	33.0	± 15%	1.80	0.072	132	± 15%	0.90
-124L	50.0	± 15%	1.50	0.111	200	± 15%	0.75
-126L	68.0	± 15%	1.20	0.158	272	± 15%	0.60
-128L	100	± 15%	0.92	0.303	400	± 15%	0.46
-130L	150	± 15%	0.82	0.372	600	± 15%	0.41
-132L	200	± 15%	0.64	0.545	800	± 15%	0.32
-134L	300	± 15%	0.62	0.672	1200	± 15%	0.31

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com




SERIES

4922R 4922



Surface Mount High Current Power Inductors



Actual Size

Mechanical Configuration Units are encapsulated in a Surface Mount package, using an epoxy molded case. Leads are pre-tinned. A high resistivity ferrite core allows for high inductance with low DC resistance.

Physical Parameters

	Inches	Millimeters
A	0.490 to 0.520	12.44 to 13.21
B	0.230 to 0.250	5.84 to 6.35
C	0.210 to 0.230	5.33 to 5.84
D	0.050 Min.	1.27 Min.
E	0.055 to 0.075	1.40 to 1.91
F	0.330 (Ref. only)	8.38 (Ref. only)
G	0.120 (Ref. only)	3.04 (Ref. only)

Operating Temperature Range -55°C to +125°C

Current Rating at 85°C Ambient 40°C Rise

Maximum Power Dissipation at 85°C 0.55 Watts

Inductance

Measured at 1 VAC open circuit with no DC current.

Incremental Current The current at which the inductance will be decreased by a maximum of 5% from its initial zero DC value.

Weight (Grams Max.) 1.5

Marking API/SMD; inductance with units and tolerance; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 4922-01L

API/SMD
1.0uH±15%
0918A

Packaging Tape & reel (24mm): 13" reel, 800 pieces max.; 7" reel not available

Made In the U.S.A. Patent Protected

Optional Tolerances: Values < 10µH: K = 10% J = 5%
Values ≥ 10µH: K = 10% J = 5% H = 3%

*Complete part # must include series # PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com

0 AMPS DC INDUCTANCE
±20% (µH @ 10 kHz)

DCR (OHMS) MAXIMUM

RATED DC CURRENT
(Amps) MAXIMUM


INDUCTANCE (µH) MINIMUM
@ Rated DC Current

Power Inductors

SERIES 4922 FERRITE CORE				
-221L	0.22	0.0080	7.00	7.00
-271L	0.27	0.0085	6.75	6.75
-331L	0.33	0.0090	6.50	6.50
-391L	0.39	0.0095	6.25	6.25
-471L	0.47	0.0100	6.00	6.00
-561L	0.56	0.0105	5.80	5.80
-681L	0.68	0.0110	5.70	5.70
-821L	0.82	0.0120	5.60	5.60
-01L	1.00	0.013	5.50	5.50
-02L	1.20	0.018	4.69	4.69
-03L	1.50	0.020	4.45	4.45
-04L	1.80	0.021	4.34	4.34
-05L	2.20	0.029	3.70	3.70
-06L	2.70	0.034	3.41	3.41
-07L	3.30	0.038	3.23	3.23
-08L	3.90	0.042	3.07	3.07
-09L	4.70	0.047	2.90	2.90
-10L	5.60	0.051	2.79	2.79
-11L	6.80	0.058	2.61	2.61
-12L	8.20	0.063	2.51	2.51
-13L	10.0	0.071	2.36	2.36
-14L	12.0	0.079	2.24	2.24
-15L	15.0	0.089	2.11	2.11
-16L	18.0	0.119	1.82	1.82
-17L	22.0	0.152	1.61	1.61
-18L	27.0	0.179	1.48	1.48
-19L	33.0	0.222	1.33	1.33
-20L	39.0	0.315	1.12	1.12
-21L	47.0	0.362	1.04	1.04
-22L	56.0	0.397	1.00	1.00
-23L	68.0	0.418	0.97	0.97
-24L	82.0	0.604	0.81	0.81
-25L	100	0.672	0.76	0.76
-26L	120	0.735	0.73	0.73
-27L	150	0.998	0.63	0.63
-28L	180	1.370	0.53	0.53
-29L	220	1.580	0.50	0.50
-30L	270	1.770	0.47	0.47
-31L	330	2.510	0.39	0.39
-32L	390	2.730	0.38	0.38
-33L	470	3.250	0.35	0.35
-34L	560	3.750	0.33	0.33
-35L	680	4.310	0.30	0.30
-36L	820	6.040	0.26	0.26
-37L	1000	6.900	0.24	0.24
-38L	1200	10.00	0.200	0.200
-39L	1500	12.50	0.178	0.178
-40L	1800	16.00	0.157	0.157
-41L	2200	20.00	0.141	0.141
-42L	2700	23.00	0.131	0.131
-43L	3300	25.00	0.126	0.126
-44L	3900	33.00	0.110	0.110
-45L	4700	37.00	0.103	0.103
-46L	5600	40.00	0.100	0.100
-47L	6800	62.00	0.080	0.080
-48L	8200	66.00	0.077	0.077
-49L	10000	74.00	0.071	0.071
-50L	12000	93.00	0.065	0.065
-51L	15000	105.0	0.061	0.061
-52L	18000	143.0	0.052	0.052
-53L	22000	160.0	0.050	0.050

SERIES**MIL4922**

High Current, MIL-PRF-27/367 Qualified Surface Mount Power Inductors



Mechanical Configuration

Units are encapsulated in a Surface Mount package, using an epoxy molded case. Leads are pre-tinned. A high resistivity ferrite core allows for high inductance with low DC resistance.

Physical Parameters

	Inches	Millimeters
A	0.490 to 0.520	12.44 to 13.21
B	0.230 to 0.250	5.84 to 6.35
C	0.210 to 0.230	5.33 to 5.84
D	0.050 Min.	1.27 Min.
E	0.055 to .075	1.40 to 1.91
F	0.330 (Ref. only)	8.38 (Ref. only)
G	0.120 (Ref. only)	3.04 (Ref. only)

Operating Temperature Range -55°C to +130°C

Current Rating at 85°C Ambient 45°C Rise

Maximum Power Dissipation at 85°C 0.55 W

Inductance

Measured at 1 VAC open circuit with no DC current
Incremental Current The current at which the inductance will decrease by a maximum of 5% from its inductance at zero DC current.

Weight (Grams Max.) 1.5

Packaging Tape & reel (24mm): 13" reel, 800 pieces max.; 7" reel not available


Lead Finish Sn63Pb37
(Tin-Lead) Hot Solder Dipped

Made In the U.S.A.

*Complete part # must include series # PLUS the dash #

DASH NUMBER*	INDUCTANCE (μH)	TOLERANCE	TEST FREQUENCY (kHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (mA)
M27/367 - SERIES MIL4922 FERRITE CORE					
-221L	-01	0.22	0.0080	7.00	7.00
-271L	-02	0.27	0.0085	6.75	6.75
-331L	-03	0.33	0.0090	6.50	6.50
-391L	-04	0.39	0.0095	6.25	6.25
-471L	-05	0.47	0.0100	6.00	6.00
-561L	-06	0.56	0.0105	5.80	5.80
-681L	-07	0.68	0.0110	5.70	5.70
-821L	-08	0.82	0.0120	5.60	5.60
-01L	-09	1.00	0.013	5.50	5.50
-02L	-10	1.20	0.018	4.69	4.69
-03L	-11	1.50	0.020	4.45	4.45
-04L	-12	1.80	0.021	4.34	4.34
-05L	-13	2.20	0.029	3.70	3.70
-06L	-14	2.70	0.034	3.41	3.41
-07L	-15	3.30	0.038	3.23	3.23
-08L	-16	3.90	0.042	3.07	3.07
-09L	-17	4.70	0.047	2.90	2.90
-10L	-18	5.60	0.051	2.79	2.79
-11L	-19	6.80	0.058	2.61	2.61
-12L	-20	8.20	0.063	2.51	2.51
-13L	-21	10.0	0.071	2.36	2.36
-14L	-22	12.0	0.079	2.24	2.24
-15L	-23	15.0	0.089	2.11	2.11
-16L	-24	18.0	0.119	1.82	1.82
-17L	-25	22.0	0.152	1.61	1.61
-18L	-26	27.0	0.179	1.48	1.48
-19L	-27	33.0	0.222	1.33	1.33
-20L	-28	39.0	0.315	1.12	1.12
-21L	-29	47.0	0.362	1.04	1.04
-22L	-30	56.0	0.397	1.00	1.00
-23L	-31	68.0	0.418	0.97	0.97
-24L	-32	82.0	0.604	0.81	0.81
-25L	-33	100	0.672	0.76	0.76
-26L	-34	120	0.735	0.73	0.73
-27L	-35	150	0.998	0.63	0.63
-28L	-36	180	1.370	0.53	0.53
-29L	-37	220	1.580	0.50	0.50
-30L	-38	270	1.770	0.47	0.47
-31L	-39	330	2.510	0.39	0.39
-32L	-40	390	2.730	0.38	0.38
-33L	-41	470	3.250	0.35	0.35
-34L	-42	560	3.750	0.33	0.33
-35L	-43	680	4.310	0.30	0.30
-36L	-44	820	6.040	0.26	0.26
-37L	-45	1000	6.900	0.24	0.24
-38L	-46	1200	10.00	0.200	0.200
-39L	-47	1500	12.50	0.178	0.178
-40L	-48	1800	16.00	0.157	0.157
-41L	-49	2200	20.00	0.141	0.141
-42L	-50	2700	23.00	0.131	0.131
-43L	-51	3300	25.00	0.126	0.126
-44L	-52	3900	33.00	0.110	0.110
-45L	-53	4700	37.00	0.103	0.103
-46L	-54	5600	40.00	0.100	0.100
-47L	-55	6800	62.00	0.080	0.080
-48L	-56	8200	66.00	0.077	0.077
-49L	-57	10000	74.00	0.071	0.071
-50L	-58	12000	93.00	0.065	0.065
-51L	-59	15000	105.0	0.061	0.061
-52L	-60	18000	143.0	0.052	0.052
-53L	-61	22000	160.0	0.050	0.050

High Current Surface Mount Power Inductors



Mechanical Configuration

Units are encapsulated in a Surface Mount package, using an epoxy molded case. High resistivity ferrite core, allows for high inductance with low DC resistance.

Physical Parameters

	Inches	Millimeters
A	0.840 to 0.880	21.34 to 22.35
B	0.310 to 0.330	7.87 to 8.38
C	0.266 to 0.286	6.76 to 7.26
D	0.050 Min.	1.27 Min.
E	0.070 to 0.110	1.78 to 2.79
F	0.750 (Ref. only)	19.05 (Ref. only)
G	0.120 (Ref. only)	3.05 (Ref. only)

Dimensions "A" and "C" are over terminals.

Operating Temperature Range -55°C to +125°C

Current Rating 40°C Rise over 85°C Ambient

Maximum Power Dissipation at 85°C 0.50 Watts

Inductance

Measured at 1 VAC open circuit with no DC current.
Incremental Current The current at which the inductance will decrease by a maximum of 5% from its initial zero DC value.

Weight Max. (Grams) 2.5

Marking API/SMD; inductance with units and tolerance; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 8532R-52L

API/SMD
18mH±15%
R 0901B

Packaging Tape & reel (44mm):
13" reel, 480 pieces max.; 7" reel not available

Made In the U.S.A. Patent Protected

DASH NUMBER*	INDUCTANCE (μH) ±15% @ 1 kHz	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (Amps)	INCREMENTAL CURRENT (Amps)
SERIES 8532 FERRITE CORE				
-01L	1.0	0.009	6.27	6.4
-02L	1.2	0.010	5.95	5.8
-03L	1.5	0.011	5.67	5.2
-04L	1.8	0.012	5.43	4.8
-05L	2.2	0.013	5.22	4.3
-06L	2.7	0.014	5.03	3.9
-07L	3.3	0.016	4.70	3.5
-08L	3.9	0.017	4.56	3.2
-09L	4.7	0.022	4.01	2.9
-10L	5.6	0.024	3.84	2.7
-11L	6.8	0.026	3.69	2.5
-12L	8.2	0.028	3.55	2.2
-13L	10.0	0.033	3.27	2.0
-14L	12.0	0.037	3.09	1.8
-15L	15.0	0.040	2.97	1.6
-16L	18.0	0.044	2.84	1.5
-17L	22.0	0.050	2.66	1.4
-18L	27.0	0.070	2.25	1.2
-19L	33.0	0.075	2.17	1.1
-20L	39.0	0.084	2.05	1.0
-21L	47.0	0.104	1.84	0.93
-22L	56.0	0.130	1.65	0.85
-23L	68.0	0.145	1.56	0.77
-24L	82.0	0.152	1.53	0.71
-25L	100.0	0.208	1.30	0.64
-26L	120.0	0.283	1.12	0.58
-27L	150.0	0.330	1.04	0.52
-28L	180.0	0.362	0.99	0.48
-29L	220.0	0.505	0.84	0.43
-30L	270.0	0.557	0.80	0.39
-31L	330.0	0.650	0.74	0.35
-32L	390.0	0.770	0.68	0.32
-33L	470.0	1.03	0.59	0.29
-34L	560.0	1.14	0.56	0.27
-35L	680.0	1.50	0.49	0.25
-36L	820.0	1.98	0.42	0.22
-37L	1000.0	2.30	0.39	0.20
-38L	1200.0	2.55	0.37	0.18
-39L	1500.0	3.00	0.34	0.16
-40L	1800.0	4.00	0.30	0.15
-41L	2200.0	4.40	0.28	0.14
-42L	2700.0	5.80	0.25	0.12
-43L	3300.0	6.56	0.23	0.11
-44L	3900.0	8.63	0.20	0.10
-45L	4700.0	10.1	0.19	0.09
-46L	5600.0	11.2	0.18	0.09
-47L	6800.0	15.0	0.15	0.08
-48L	8200.0	20.8	0.13	0.07
-49L	10000.0	23.4	0.12	0.06
-50L	12000.0	26.0	0.12	0.06
-51L	15000.0	36.0	0.10	0.05
-52L	18000.0	40.0	0.09	0.05


Optional Tolerances: Values < 10μH: K = 10% J = 5%
Values ≥ 10μH: K = 10% J = 5% H = 3%

*Complete part # must include series # PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com

SERIES**MIL8532**

High Current, MIL-PRF-27/370 Qualified Surface Mount Power Inductors



Actual Size

Mechanical Configuration

Units are encapsulated in a Surface Mount package, using an epoxy molded case. High resistivity ferrite core, allows for high inductance with low DC resistance.

Physical Parameters

	Inches	Millimeters
A	0.840 to 0.880	21.34 to 22.35
B	0.310 to 0.330	7.87 to 8.38
C	0.266 to 0.286	6.76 to 7.26
D	0.050 Min.	1.27 Min.
E	0.070 to 0.110	1.78 to 2.79
F	0.750 (Ref. only)	19.05 (Ref. only)
G	0.120 (Ref. only)	3.05 (Ref. only)

Dimensions "A" and "C" are over terminals.

Operating Temperature Range -55°C to +130°C

Current Rating at 85°C Ambient 45°C Rise

Maximum Power Dissipation at 85°C 0.50 W

Inductance

Measured at 1 VAC open circuit with no DC current

Incremental Current The current at which the inductance will decrease by a maximum of 5% from its inductance at zero DC current.

Weight (Grams Max.) 2.5

Packaging Tape & reel (44mm):

13" reel, 480 pieces max.; 7" reel not available

Lead Finish Sn63Pb37

(Tin-Lead) Hot Solder Dipped

Made In the U.S.A.


Power Inductors

DASH NUMBER*
MIL DASH #
INDUCTANCE @ 1 kHz
(μH) ±15%
DC RESISTANCE
MAXIMUM (OHMS)
CURRENT RATING
MAXIMUM (Amps)
CURRENT DC (Amps)
INCREMENTAL

M27/370 - SERIES MIL8532 FERRITE CORE

-01L	-01	1.0	0.009	6.27	6.4
-02L	-02	1.2	0.010	5.95	5.8
-03L	-03	1.5	0.011	5.67	5.2
-04L	-04	1.8	0.012	5.43	4.8
-05L	-05	2.2	0.013	5.22	4.3
-06L	-06	2.7	0.014	5.03	3.9
-07L	-07	3.3	0.016	4.70	3.5
-08L	-08	3.9	0.017	4.56	3.2
-09L	-09	4.7	0.022	4.01	2.9
-10L	-10	5.6	0.024	3.84	2.7
-11L	-11	6.8	0.026	3.69	2.5
-12L	-12	8.2	0.028	3.55	2.2
-13L	-13	10.0	0.033	3.27	2.0
-14L	-14	12.0	0.037	3.09	1.8
-15L	-15	15.0	0.040	2.97	1.6
-16L	-16	18.0	0.044	2.84	1.5
-17L	-17	22.0	0.050	2.66	1.4
-18L	-18	27.0	0.070	2.25	1.2
-19L	-19	33.0	0.075	2.17	1.1
-20L	-20	39.0	0.084	2.05	1.0
-21L	-21	47.0	0.104	1.84	0.93
-22L	-22	56.0	0.130	1.65	0.85
-23L	-23	68.0	0.145	1.56	0.77
-24L	-24	82.0	0.152	1.53	0.71
-25L	-25	100.0	0.208	1.30	0.64
-26L	-26	120.0	0.283	1.12	0.58
-27L	-27	150.0	0.330	1.04	0.52
-28L	-28	180.0	0.362	0.99	0.48
-29L	-29	220.0	0.505	0.84	0.43
-30L	-30	270.0	0.557	0.80	0.39
-31L	-31	330.0	0.650	0.74	0.35
-32L	-32	390.0	0.770	0.68	0.32
-33L	-33	470.0	1.03	0.59	0.29
-34L	-34	560.0	1.14	0.56	0.27
-35L	-35	680.0	1.50	0.49	0.25
-36L	-36	820.0	1.98	0.42	0.22
-37L	-37	1000.0	2.30	0.39	0.20
-38L	-38	1200.0	2.55	0.37	0.18
-39L	-39	1500.0	3.00	0.34	0.16
-40L	-40	1800.0	4.00	0.30	0.15
-41L	-41	2200.0	4.40	0.28	0.14
-42L	-42	2700.0	5.80	0.25	0.12
-43L	-43	3300.0	6.56	0.23	0.11
-44L	-44	3900.0	8.63	0.20	0.10
-45L	-45	4700.0	10.1	0.19	0.09
-46L	-46	5600.0	11.2	0.18	0.09
-47L	-47	6800.0	15.0	0.15	0.08
-48L	-48	8200.0	20.8	0.13	0.07
-49L	-49	10000.0	23.4	0.12	0.06
-50L	-50	12000.0	26.0	0.12	0.06
-51L	-51	15000.0	36.0	0.10	0.05
-52L	-52	18000.0	40.0	0.09	0.05

*Complete part # must include series # PLUS the dash #

SERIES**5500R
5500****High Current Power Chokes**

Actual Size

Physical Parameters

	Inches	Millimeters
A	1.020 to 1.080	25.91 to 27.44
B	0.480 to 0.510	12.20 to 12.96
C	0.520 Maximum	13.21 Maximum
D	0.240 Minimum	6.10 Minimum
E	0.120 to 0.160	3.05 to 4.07
F	0.500 (Ref. Only)	12.70 (Ref. Only)
G	0.250 (Ref. Only)	6.35 (Ref. Only)

Dimensions "A" and "C" and "G" are over the terminals.**Operating Temperature Range** -55°C to +130°C**Current Rating at 85°C Ambient** 45°C Temperature Rise**Maximum Power Dissipation** at +85°C: 1.166 Watts Maximum**Inductance** Measured @ 1 kHz with 0 ADC on Wayne Kerr 3245A, or equivalent.**Incremental Current** The amount of DC that decreases the Inductance by 5% maximum relative to the 0 ADC.**Dielectric Withstanding Voltage** Meets MIL-STD-202, Method 301, 1000 Vrms Minimum**Marking** DELEVAN, INDUCTANCE VALUE and DATE CODE/LOT SYMBOL (YYWWL). Note: An "R" before the date code/lot symbol indicates a RoHS Compliant choke.

DELEVAN

3.9uH

R YYWWL

Thermal Shock Meets MIL-STD-202, Method 107, Test Condition A-1 (-55°C to +130°C).**Mechanical Shock** Meets MIL-STD-202, Method 213, Test Condition I.**Vibration** Meets MIL-STD-202, Method 204, Test Condition D**Solderability** Meets MIL-STD-202, Method 208**Terminal Material and Final Finish**Series 5500R: (Tin - Silver - Copper) Sn96.5Ag3.0Cu0.5 over Copper (Cu)
Series 5500: (Tin - Lead) Sn63Pb37 over Copper (Cu)**Weight** 13 Grams Maximum**Packaging** Tape and Reel (44mm): 13" reel,
200 pieces max: 7" reel not available**Made In The U.S.A.**

DASH NUMBER*
±10% (uH @ 1.00 kHz)
INDUCTANCE
MAXIMUM (OHMS)
DC RESISTANCE
MAXIMUM (A DC)
CURRENT RATING
MAXIMUM (A DC)
INCREMENTAL
CURRENT (A DC)


SERIES 5500R AND 5500

-392K	3.9	0.007	11.91	9.13
-472K	4.7	0.008	11.14	8.30
-562K	5.6	0.011	9.50	7.61
-682K	6.8	0.012	9.10	7.02
-822K	8.2	0.013	8.74	6.52
-103K	10	0.016	7.88	5.71
-123K	12	0.018	7.43	5.07
-153K	15	0.020	7.05	4.57
-183K	18	0.022	6.72	4.15
-223K	22	0.024	6.43	3.65
-273K	27	0.025	6.30	3.38
-333K	33	0.028	5.96	3.04
-393K	39	0.031	5.66	2.85
-473K	47	0.034	5.41	2.61
-563K	56	0.043	4.81	2.34
-683K	68	0.060	4.08	2.12
-823K	82	0.066	3.88	1.94
-104K	100	0.084	3.44	1.76
-124K	120	0.113	2.96	1.60
-154K	150	0.129	2.78	1.43
-184K	180	0.150	2.57	1.30
-224K	220	0.162	2.48	1.19
-274K	270	0.226	2.10	1.07
-334K	330	0.257	1.97	0.96
-394K	390	0.288	1.86	0.88
-474K	470	0.393	1.59	0.81
-564K	560	0.504	1.40	0.74
-684K	680	0.570	1.32	0.68
-824K	820	0.643	1.24	0.63
-105K	1,000	0.844	1.08	0.56
-125K	1,200	0.977	1.01	0.51
-155K	1,500	1.18	0.92	0.45
-185K	1,800	1.50	0.81	0.41
-225K	2,200	1.76	0.75	0.37
-275K	2,700	2.13	0.68	0.32
-335K	3,300	2.53	0.63	0.30
-395K	3,900	2.84	0.59	0.28
-475K	4,700	3.79	0.51	0.25
-565K	5,600	4.24	0.48	0.23
-685K	6,800	5.75	0.42	0.21
-825K	8,200	6.44	0.39	0.19
-106K	10,000	7.30	0.37	0.17
-126K	12,000	9.34	0.33	0.16
-156K	15,000	10.7	0.30	0.14
-186K	18,000	14.8	0.26	0.13
-226K	22,000	18.0	0.23	0.12
-276K	27,000	22.7	0.21	0.10
-336K	33,000	25.7	0.20	0.09
-396K	39,000	29.7	0.18	0.09
-476K	47,000	33.7	0.17	0.08
-566K	56,000	38.0	0.16	0.07
-686K	68,000	52.8	0.14	0.07
-826K	82,000	67.3	0.12	0.06
-107K	100,000	76.0	0.11	0.05

OPTIONAL TOLERANCES: J = +/- 5% L = +/- 15%

The Suffix (Optional Tolerance "J" or "L") should replace the "K", in the dash number.

*Complete part # must include series # PLUS the dash #

SERIES**HCTR
HCT**RoHS
CompliantTraditional
First Quality**High Current Toroidal Inductors**Actual Size
(HCT-44X)**Physical Parameters:**

Package	A Max.	B Max.	C Max.	D	E	F
HCT-37X	0.615	0.600	0.370	0.500	0.440	0.500
HCT-44X	0.665	0.665	0.400	0.560	0.490	0.560
HCT-50X	0.740	0.740	0.400	0.630	0.560	0.630
HCT-68X	0.945	0.940	0.400	0.820	0.700	0.820

Above dimensions in inches and unless otherwise stated all tolerances are ± 0.010 **Mechanical Configuration**

Units are surface mount, low profile, self-leaded devices

Frequency Range 1kHz up to 1 MHz**Operating Temperature Range** -30°C to $+130^{\circ}\text{C}$ **Leads** Solder tinned**Materials** Meet UL94V-0**Optional Tolerances** As low as 10% available on some values.
Consult factory for details.**Maximum Power Dissipation at 25°C Ambient**

HCT-37x, 0.9 W

HCT-44x, 1.0 W

HCT-50x, 1.1 W

HCT-68x, 1.2 W

Marking API; part number.

Example: HCT-504

API

HCT-504


Packaging Bulk; contact factory for tape & reel options.**ELECTRICAL SPECIFICATIONS @ 25°C****DC AMPS TO PRODUCE A MAXIMUM
TEMPERATURE RISE FROM 25°C AMBIENT**

DASH NUMBER*	INDUCTANCE (μH) $\pm 25\%$	Q TYPICAL	L & Q TEST FREQUENCY (kHz)	SRF (MHz, TYPICAL)	DC RESISTANCE MAXIMUM (m Ω)	DC RESISTANCE TYPICAL (m Ω)	5°C	15°C	25°C	35°C	45°C	55°C
-371	1.25	32	100	260	2.5	2.2	5.73	9.75	12.30	14.30	16.00	17.40
-372	2.1	27	100	160	4.0	3.4	4.58	7.78	9.87	11.40	12.80	13.90
-373	2.8	27	100	110	6.3	5.4	3.62	6.17	7.82	9.10	10.10	11.00
-374	4.2	24	100	100	7.9	6.8	3.23	5.49	6.97	8.10	9.04	9.83
-441	2.8	33	100	110	3.6	3.2	5.13	8.73	11.00	12.80	14.30	15.60
-442	4.2	29	100	85	5.4	4.7	4.23	7.20	9.14	10.60	11.80	12.80
-443	5.7	29	100	65	7.5	6.4	3.60	6.13	7.78	9.05	10.00	10.90
-444	9.0	26	100	55	11.4	9.8	2.91	4.95	6.28	7.31	8.15	8.87
-501	6.5	25	100	55	6.6	5.8	3.97	6.75	8.56	9.96	11.10	12.00
-502	8.4	23	100	45	8.3	7.2	3.55	6.04	7.66	8.91	9.94	10.80
-503	12.5	23	100	35	11.4	9.8	3.04	5.17	6.56	7.63	8.50	9.25
-504	17.0	22	100	29	17.0	14.6	2.49	4.23	5.37	6.25	6.97	7.58
-681	10.5	35	100	30	6.2	5.3	4.35	7.40	9.39	10.90	12.10	13.20
-682	17.6	35	100	24	12.3	10.7	3.06	5.21	6.60	7.68	8.57	9.32
-683	22.0	30	100	21	17.5	15.0	2.58	4.40	5.58	6.49	7.24	7.87
-684	29.0	30	100	16	25.0	21.5	2.16	3.67	4.66	5.42	6.04	6.57

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

High Current Toroidal Inductors



For frequencies ≤ 10 kHz

(mW/cm³) Hz Gauss
Core loss = $1.47 \times 10^{-8} f^{0.971} B^{2.11}$

For frequencies ≥ 10 kHz

(mW/cm³) Hz Gauss
Core loss = $9.07 \times 10^{-10} f^{1.26} B^{2.11}$

$$B_{pk} = \frac{E_{rms} 10^8}{4.44 A n f}$$


A:

T37 = 0.064 cm²; T44 = 0.099 cm²;
T50 = 0.112 cm²; T68 = 0.179 cm²

This information is intended to be used in assisting the designer in part selection. Each application may contain other variables which must be considered in part selection, such as temperature effects, waveform distortion, etc. API Delevan Sales/Engineering is available to provide information as needed to fit each application.

Data is representative of a DC current with less than 1% ripple and an AC waveform less than: 50 gauss on the HCT-37X, 25 gauss on the HCT-44X, 15 gauss on the HCT-50X and 10 gauss on the HCT-68X. The effect of AC or ripple flux can be significant in many DC inductor applications. When significantly greater AC flux density is present, it becomes necessary to consider its effect on both core loss and permeability (inductance).

All data points, on the above graphs, that exceed the rated DC current specified for a 55°C rise from a 25°C ambient are for design reference only and are not intended to imply continuous use at those DC current levels.




SERIES

LLSTR LLST



Low Loss Surface Mount Power Toroid



Actual Size

Physical Parameters

	Inches	Millimeters
A	0.475 ± 0.020	12.07 ± 0.50
B	0.420 ± 0.020	10.67 ± 0.50
C	0.290 Max.	7.37 Max.
D	0.400 Ref.	7.62 Ref.
E	0.075 Ref.	1.91 Max.
F	0.375 ± 0.020	9.53 ± 0.50

Operating Temperature Range -40°C to +125°C

Power Dissipation 0.285 Max. (Watts)

Weight Max. (Grams) 2.00

Packaging Bulk only

Current Rating Based on a 35° C max. rise from 90°C ambient.

Power Inductors

DASH NUMBER*

INDUCTANCE @ 1 kHz
(μH) ±15%

INCREMENTAL CURRENT
ADC, 10% Inductance Loss

INCREMENTAL CURRENT
ADC, 20% Inductance Loss

SRF MINIMUM (MHz)

DCR (OHMS) MAXIMUM

CURRENT RATING
ADC MAXIMUM

SERIES LLST HIGH SATURATION CORE

LLST4R7	4.7	4.00	6.10	50.0	0.035	2.600
LLST10	10	2.80	4.10	45.0	0.050	2.250
LLST15	15	2.10	3.20	40.0	0.055	2.150
LLST18	18	1.90	3.00	35.0	0.060	2.050
LLST22	22	1.70	2.80	25.0	0.070	1.900
LLST25	25	1.60	2.60	20.0	0.080	1.780
LLST27	27	1.40	2.30	15.0	0.080	1.780
LLST33	33	1.30	2.20	12.0	0.080	1.780
LLST47	47	1.00	1.80	10.0	0.120	1.450
LLST75	75	0.80	1.40	8.0	0.180	1.190
LLST100	100	0.80	1.40	7.0	0.250	1.000
LLST125	125	0.64	1.10	6.0	0.250	1.000
LLST140	140	0.56	0.98	5.0	0.250	1.000
LLST150	150	0.56	0.98	4.0	0.260	0.985
LLST175	175	0.54	0.90	3.5	0.325	0.890
LLST200	200	0.46	0.80	3.2	0.400	0.795
LLST220	220	0.46	0.80	3.0	0.400	0.795
LLST270	270	0.46	0.78	2.5	0.500	0.710
LLST300	300	0.38	0.68	2.0	0.500	0.710
LLST350	350	0.36	0.62	1.9	0.625	0.650
LLST400	400	0.28	0.50	1.8	0.700	0.600
LLST450	450	0.28	0.50	1.7	0.850	0.550
LLST500	500	0.26	0.50	1.5	1.000	0.500

*Insert 'R' Designator for RoHS

For surface finish information, refer to www.delevanfinishes.com


Material High Saturation Nickel/Iron Core.

Inductance Tested at an AC drive level which does not affect the initial permeability of the core, the DC drive level was 0 amps.

Incremental Current The DC current which reduces the inductance value to the percentage drop tabulated.

Inductor Base Formed from a high temperature thermoplastic capable of withstanding approx. 600°F for short periods of time.

Marking API, Inductance, and Date Code.



For more detailed graphs, contact factory

SERIES

PTHFxxxR-SM
PTKMxxxR-SM
PTHF-SM
PTKM-SM



Surface Mount Toroidal Power Chokes



Actual Size (Max.)
 (PTHF 100-50SM)

- **Excellent electromagnetic shielding** performance for commercial and industrial applications
- **For higher saturation levels** use Series PTHF-SM
- Current rating from 0.92 to 7.36 amps
- Inductance values from 10 μ H to 330 μ H

Marking API; ether PTHF or PTKM; remainder of part number.

Example: PTKM50R-50SM

API
 PTHF
 50R-50SM

Notes 1) Rated current is based on a 35°C temperature rise at an ambient temperature of 90°C. 2) Incremental current is the approximate value that will cause a percentage drop in inductance as indicated in the table.

DASH NUMBER*	INDUCTANCE @ 1 kHz (μ H) $\pm 10\%$	CURRENT RATING ADC	Inc-I ADC $\Delta L 10\%$	Inc-I ADC $\Delta L 20\%$	DC RESISTANCE MAXIMUM (OHMS)	SRF MINIMUM (MHz)
SERIES PTHF-SM HIGH SATURATION CORE						
PTHF10-50SM	10	7.36	6.00	8.70	0.01	35.0
PTHF25-50SM	25	5.20	3.60	5.30	0.02	10.0
PTHF50-50SM	50	3.93	2.00	3.10	0.04	7.0
PTHF75-50SM	75	3.47	1.60	2.50	0.05	5.0
PTHF100-50SM	100	3.14	1.50	2.20	0.06	4.0
PTHF150-50SM	150	2.33	1.20	1.80	0.10	3.0
PTHF200-50SM	200	1.97	1.00	1.60	0.14	2.0
PTHF250-50SM	250	1.84	0.90	1.40	0.16	1.5
PTHF330-50SM	330	1.69	0.80	1.20	0.19	1.0
PTHF10-40SM	10	4.84	3.80	5.70	0.02	35.0
PTHF25-40SM	25	3.38	2.20	3.50	0.04	20.0
PTHF50-40SM	50	1.90	1.70	2.50	0.11	13.0
PTHF75-40SM	75	1.69	1.30	2.00	0.14	9.0
PTHF100-40SM	100	1.60	1.10	1.70	0.16	6.0
PTHF150-40SM	150	1.45	0.90	1.40	0.19	3.5
PTHF200-40SM	200	1.12	0.70	1.10	0.32	3.0
PTHF250-40SM	250	1.05	0.70	1.10	0.36	2.5
PTHF10-30SM	10	2.56	2.20	3.40	0.05	35.0
PTHF25-30SM	25	2.16	1.40	2.10	0.07	25.0
PTHF50-30SM	50	1.81	1.20	1.30	0.10	10.0
PTHF75-30SM	75	1.62	0.80	1.20	0.13	7.0
PTHF100-30SM	100	1.50	0.60	1.00	0.15	6.0
PTHF150-30SM	150	1.33	0.60	1.00	0.19	3.5
PTHF200-30SM	200	1.04	0.50	0.70	0.30	3.0
PTHF250-30SM	250	0.96	0.50	0.70	0.36	3.0
PTHF10-180SM	10	1.60	0.90	1.40	0.10	35.0
PTHF25-180SM	25	1.33	0.60	0.90	0.15	30.0
PTHF50-180SM	50	1.12	0.40	0.60	0.21	10.0
PTHF75-180SM	75	0.99	0.30	0.50	0.26	8.0
PTHF100-180SM	100	0.92	0.30	0.40	0.30	6.0
SERIES PTKM-SM FERROUS ALLOY CORE						
PTKM10-50SM	10	7.36	1.70	3.30	0.01	35.0
PTKM25-50SM	25	5.20	1.00	1.90	0.02	10.0
PTKM50-50SM	50	3.93	0.70	1.30	0.04	7.0
PTKM75-50SM	75	3.47	0.60	1.10	0.05	5.0
PTKM100-50SM	100	3.14	0.50	0.96	0.06	4.0
PTKM150-50SM	150	2.33	0.40	0.78	0.10	3.0
PTKM200-50SM	200	1.97	0.35	0.65	0.14	2.0
PTKM250-50SM	250	1.84	0.31	0.59	0.16	1.5
PTKM330-50SM	330	1.69	0.27	0.50	0.19	1.0
PTKM10-40SM	10	4.84	1.30	2.50	0.02	35.0
PTKM25-40SM	25	3.38	0.70	1.30	0.04	20.0
PTKM50-40SM	50	1.90	0.56	1.00	0.11	13.0
PTKM75-40SM	75	1.69	0.45	0.86	0.14	9.0
PTKM100-40SM	100	1.60	0.40	0.76	0.16	6.0
PTKM150-40SM	150	1.45	0.33	0.60	0.19	3.5
PTKM200-40SM	200	1.12	0.30	0.56	0.32	3.0
PTKM250-40SM	250	1.05	0.25	0.48	0.36	2.5
PTKM10-30SM	10	2.56	0.80	1.60	0.05	35.0
PTKM25-30SM	25	2.16	0.50	0.96	0.07	25.0
PTKM50-30SM	50	1.81	0.35	0.68	0.10	10.0
PTKM75-30SM	75	1.62	0.28	0.54	0.13	7.0
PTKM100-30SM	100	1.50	0.23	0.50	0.15	6.0
PTKM150-30SM	150	1.33	0.20	0.40	0.19	3.5
PTKM200-30SM	200	1.04	0.17	0.34	0.30	3.0
PTKM250-30SM	250	0.96	0.15	0.30	0.36	3.0
PTKM10-180SM	10	1.60	0.43	0.86	0.10	35.0
PTKM25-180SM	25	1.33	0.25	0.50	0.15	30.0
PTKM50-180SM	50	1.12	0.18	0.35	0.21	10.0
PTKM75-180SM	75	0.99	0.15	0.28	0.26	8.0
PTKM100-180SM	100	0.92	0.13	0.25	0.30	6.0

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com


SERIES

PTHFxxxR-SM & PTKMxxxR-SM
PTHF-SM & PTKM-SM

RoHS
Compliant

Traditional
First Quality

Surface Mount Toroidal Power Chokes





PHYSICAL PARAMETERS

PART NUMBER*	A Max.		B Max.		C Max.		D Nom.		E Nom.	
	Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
PT**10-50SM	0.700	17.78	0.670	17.02	0.400	10.16	0.600	15.24	0.600	15.24
PT**25-50SM	0.700	17.78	0.670	17.02	0.400	10.16	0.600	15.24	0.600	15.24
PT**50-50SM	0.700	17.78	0.670	17.02	0.400	10.16	0.600	15.24	0.600	15.24
PT**75-50SM	0.700	17.78	0.670	17.02	0.400	10.16	0.600	15.24	0.600	15.24
PT**100-50SM	0.700	17.78	0.670	17.02	0.400	10.16	0.600	15.24	0.600	15.24
PT**150-50SM	0.700	17.78	0.670	17.02	0.400	10.16	0.600	15.24	0.600	15.24
PT**200-50SM	0.700	17.78	0.670	17.02	0.400	10.16	0.600	15.24	0.600	15.24
PT**250-50SM	0.700	17.78	0.670	17.02	0.400	10.16	0.600	15.24	0.600	15.24
PT**330-50SM	0.700	17.78	0.670	17.02	0.400	10.16	0.600	15.24	0.600	15.24
PT**10-40SM	0.570	14.48	0.560	14.22	0.400	10.16	0.500	12.70	0.500	12.70
PT**25-40SM	0.570	14.48	0.560	14.22	0.400	10.16	0.500	12.70	0.500	12.70
PT**50-40SM	0.570	14.48	0.560	14.22	0.400	10.16	0.500	12.70	0.500	12.70
PT**75-40SM	0.570	14.48	0.560	14.22	0.400	10.16	0.500	12.70	0.500	12.70
PT**100-40SM	0.570	14.48	0.560	14.22	0.400	10.16	0.500	12.70	0.500	12.70
PT**150-40SM	0.570	14.48	0.560	14.22	0.400	10.16	0.500	12.70	0.500	12.70
PT**200-40SM	0.570	14.48	0.560	14.22	0.400	10.16	0.500	12.70	0.500	12.70
PT**250-40SM	0.570	14.48	0.560	14.22	0.400	10.16	0.500	12.70	0.500	12.70
PT**10-30SM	0.440	11.18	0.440	11.18	0.400	10.16	0.400	10.16	0.400	10.16
PT**25-30SM	0.440	11.18	0.440	11.18	0.400	10.16	0.400	10.16	0.400	10.16
PT**50-30SM	0.440	11.18	0.440	11.18	0.400	10.16	0.400	10.16	0.400	10.16
PT**75-30SM	0.440	11.18	0.440	11.18	0.400	10.16	0.400	10.16	0.400	10.16
PT**100-30SM	0.440	11.18	0.440	11.18	0.400	10.16	0.400	10.16	0.400	10.16
PT**150-30SM	0.440	11.18	0.440	11.18	0.400	10.16	0.400	10.16	0.400	10.16
PT**200-30SM	0.440	11.18	0.440	11.18	0.400	10.16	0.400	10.16	0.400	10.16
PT**250-30SM	0.440	11.18	0.440	11.18	0.400	10.16	0.400	10.16	0.400	10.16
PT**10-180SM	0.340	8.636	0.340	8.64	0.300	7.62	0.300	7.62	0.300	7.62
PT**25-180SM	0.340	8.636	0.340	8.64	0.300	7.62	0.300	7.62	0.300	7.62
PT**50-180SM	0.340	8.636	0.340	8.64	0.300	7.62	0.300	7.62	0.300	7.62
PT**75-180SM	0.340	8.636	0.340	8.64	0.300	7.62	0.300	7.62	0.300	7.62
PT**100-180SM	0.340	8.636	0.340	8.64	0.300	7.62	0.300	7.62	0.300	7.62

**Insert HF or KM for complete Part Number

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

SERIES**PDxxxR**RoHS
Compliant**SMT Power Choke Core****TERMINATIONS**

Actual Size (PD105R)

**** Test Measurement Frequency**Values < 10 μ H tested @ 7.96 MHz;Values $\geq$ 10 μ H tested @ 1.0 kHz**Mechanical Configuration**

Units designed for Surface Mounting

Terminals Solder Coated**Core Construction** High Resistivity Ferrite**Operating Temperature Range** -55°C to +125°C**Current Rating at 25°C Ambient** The maximum DC Current that will cause a 40°C maximum temperature rise and where the inductance will not decrease by more than 10% from the zero DC value.**Inductance Tolerance** Tolerance is indicated by the suffix to API part number. Standard tolerance per part number is as shown in table.M = $\pm$ 20%; K = $\pm$ 10%.**Marking** For values lower than 10 H the R indicates a decimal point and the remaining digits indicate the inductance in H. For values 10 H and above, the first two digits indicate the inductance in H and the third digit indicates the number of trailing zeros where a zero indicates that there are no trailing zeros.

Example: PD43R-102M (1.0 H)

1R0

Example: PD73R-224K (220 H)

221

Physical Parameters**Dimensions**

Inches	PD43R	PD54R	PD73R	PD75R	PD104R	PD105R
A	0.165 $\pm$ 0.024	0.224 $\pm$ 0.008	0.303 $\pm$ 0.008	0.303 $\pm$ 0.008	0.386 $\pm$ 0.016	0.386 $\pm$ 0.016
B	0.137 MAX.	0.177 MAX.	0.138 MAX.	0.197 MAX.	0.157 MAX.	0.213 MAX.
C	0.153 $\pm$ 0.012	0.201 $\pm$ 0.008	0.272 $\pm$ 0.008	0.272 $\pm$ 0.008	0.346 $\pm$ 0.016	0.346 $\pm$ 0.016
D	0.060 REF.	0.051 REF.	0.063 REF.	0.063 REF.	0.083 REF.	0.083 REF.

Millimeters	PD43R	PD54R	PD73R	PD75R	PD104R	PD105R
A	4.2 $\pm$ 0.6	5.7 $\pm$ 0.2	7.7 $\pm$ 0.2	7.7 $\pm$ 0.2	9.8 $\pm$ 0.4	9.8 $\pm$ 0.4
B	3.5 MAX.	4.5 MAX.	3.5 MAX.	5.0 MAX.	4.0 MAX.	5.4 MAX.
C	3.9 $\pm$ 0.3	5.1 $\pm$ 0.2	6.9 $\pm$ 0.2	6.9 $\pm$ 0.2	8.8 $\pm$ 0.4	8.8 $\pm$ 0.4
D	1.52 REF.	1.30 REF.	1.60 REF.	1.60 REF.	2.10 REF.	2.10 REF.

Packaging Tape & reel: 7" reel not available; maximum pieces per 13" reel as follows

	PD43R	PD54R	PD73R	PD75R	PD104R	PD105R
mm	12	16	16	16	24	24
Pieces	1500	1000	1000	500	1000	500

****Additional Information on Next Page**

PD SERIES (continued)

Power Inductors

DASH NUMBER*
INDUCTANCE (μH)**
DC RESISTANCE
MAXIMUM (OHMS)
CURRENT RATING
MAXIMUM (AMPS)

DASH NUMBER*
INDUCTANCE (μH)**
DC RESISTANCE
MAXIMUM (OHMS)
CURRENT RATING
MAXIMUM (AMPS)

DASH NUMBER*
INDUCTANCE (μH)**
DC RESISTANCE
MAXIMUM (OHMS)
CURRENT RATING
MAXIMUM (AMPS)

SERIES PD43R			
-102M	1.0	0.049	2.56
-152M	1.5	0.056	2.52
-182M	1.8	0.064	1.95
-222M	2.2	0.071	1.75
-272M	2.7	0.079	1.58
-332M	3.3	0.086	1.44
-392M	3.9	0.094	1.33
-472M	4.7	0.109	1.15
-562M	5.6	0.126	0.99
-682M	6.8	0.131	0.95
-822M	8.2	0.146	0.84
-103M	10	0.182	0.83
-123M	12	0.210	0.80
-153M	15	0.235	0.77
-183M	18	0.338	0.74
-223M	22	0.378	0.66
-273M	27	0.522	0.62
-333K	33	0.540	0.56
-393K	39	0.587	0.52
-473K	47	0.844	0.44
-563K	56	0.937	0.42
-683K	68	1.120	0.37
SERIES PD54R			
-102M	1.0	0.050	2.90
-152M	1.5	0.055	2.70
-182M	1.8	0.060	2.60
-222M	2.2	0.064	2.40
-272M	2.7	0.067	2.20
-332M	3.3	0.070	2.00
-392M	3.9	0.075	1.90
-472M	4.7	0.080	1.80
-562M	5.6	0.085	1.70
-682M	6.8	0.090	1.60
-822M	8.2	0.095	1.50
-103K	10	0.100	1.44
-123K	12	0.130	1.35
-153K	15	0.160	1.27
-183K	18	0.180	1.19
-223K	22	0.210	1.11
-273K	27	0.240	1.00
-333K	33	0.280	0.90
-393K	39	0.320	0.80
-473K	47	0.370	0.72
-563K	56	0.420	0.68
-683K	68	0.500	0.63
-823K	82	0.600	0.58
-104K	100	0.700	0.52
-124K	120	0.850	0.46
-154K	150	1.100	0.40
-184K	180	1.330	0.37
-224K	220	1.570	0.35

** Test Measurement Frequency

Values < 10μH tested @ 7.96 MHz
Values ≥ 10μH tested @ 1.0 kHz

SERIES PD73R			
-332M	3.3	0.050	2.50
-392M	3.9	0.055	2.30
-472M	4.7	0.060	2.10
-562M	5.6	0.065	1.90
-682M	6.8	0.070	1.75
-822M	8.2	0.075	1.60
-103K	10	0.080	1.44
-123K	12	0.090	1.35
-153K	15	0.100	1.30
-183K	18	0.115	1.20
-223K	22	0.130	1.07
-273K	27	0.170	0.98
-333K	33	0.205	0.90
-393K	39	0.230	0.80
-473K	47	0.250	0.68
-563K	56	0.280	0.64
-683K	68	0.350	0.59
-823K	82	0.410	0.54
-104K	100	0.480	0.51
-124K	120	0.570	0.45
-154K	150	0.750	0.40
-184K	180	1.000	0.35
-224K	220	1.200	0.31
SERIES PD75R			
-103K	10	0.080	2.00
-123K	12	0.085	1.90
-153K	15	0.085	1.75
-183K	18	0.090	1.60
-223K	22	0.090	1.50
-273K	27	0.120	1.40
-333K	33	0.150	1.30
-393K	39	0.180	1.20
-473K	47	0.210	1.10
-563K	56	0.240	0.94
-683K	68	0.300	0.85
-823K	82	0.370	0.78
-104K	100	0.500	0.74
-124K	120	0.570	0.68
-154K	150	0.640	0.58
-184K	180	0.680	0.54
-224K	220	0.720	0.49

** Test Measurement Frequency

Values < 10μH tested @ 7.96 MHz
Values ≥ 10μH tested @ 1.0 kHz

*Complete part # must include series #
PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com

SERIES PD104R			
-472M	4.7	0.040	3.00
-562M	5.6	0.045	2.85
-682M	6.8	0.045	2.70
-822M	8.2	0.050	2.55
-103K	10	0.050	2.38
-123K	12	0.060	2.20
-153K	15	0.070	2.00
-183K	18	0.080	1.80
-223K	22	0.090	1.60
-273K	27	0.110	1.45
-333K	33	0.130	1.30
-393K	39	0.150	1.20
-473K	47	0.170	1.10
-563K	56	0.200	1.01
-683K	68	0.220	0.94
-823K	82	0.250	0.85
-104K	100	0.340	0.74
-124K	120	0.450	0.67
-154K	150	0.540	0.61
-184K	180	0.630	0.57
-224K	220	0.720	0.53
-274K	270	0.900	0.48
-334K	330	1.100	0.42
-394K	390	1.300	0.39
-474K	470	1.530	0.35
-564K	560	1.900	0.32
-684K	680	2.300	0.28
SERIES PD105R			
-103K	10	0.060	2.60
-123K	12	0.070	2.45
-153K	15	0.080	2.30
-183K	18	0.090	2.15
-223K	22	0.100	1.95
-273K	27	0.115	1.80
-333K	33	0.125	1.65
-393K	39	0.145	1.40
-473K	47	0.170	1.28
-563K	56	0.190	1.17
-683K	68	0.230	1.08
-823K	82	0.250	1.00
-104K	100	0.350	0.97
-124K	120	0.420	0.88
-154K	150	0.470	0.80
-184K	180	0.560	0.72
-224K	220	0.730	0.66
-274K	270	0.950	0.60
-334K	330	1.150	0.52
-394K	390	1.350	0.48
-474K	470	1.480	0.42
-564K	560	1.900	0.33
-684K	680	2.250	0.28
-824K	820	2.550	0.24


** Test Measurement Frequency

Values < 10μH tested @ 7.96 MHz
Values ≥ 10μH tested @ 1.0 kHz

Shielded Surface Mount Inductors



Actual Size



Mechanical Configuration

Magnetically shielded surface mount power inductor ferrite core & shield.

Physical Parameters

	Inches	Millimeters
A	0.185 ± 0.012	4.7 ± 0.3
B	0.185 ± 0.012	4.7 ± 0.3
C	0.115 Max.	2.92 Max.
D	0.015 Ref.	0.38 Ref.
E	0.100 Ref.	2.54 Ref.
F	0.065 Ref.	1.65 Ref.
G	0.270 Ref.	6.86 Ref.
H	0.075 Ref.	1.90 Ref.
I	0.210 Ref.	5.30 Ref.
J	0.059 Ref.	1.50 Ref.

Operating Temperature Range -55°C to +125°C

Current Rating at 25°C Ambient 40°C maximum temperature rise and 10% maximum decrease in inductance

Application Frequency Range

18 Inductance values from 1.2 H to 100 H

Core Material Ferrite


Weight (Grams Max.) 0.85


Packaging Tape & reel (12mm):
7" reel, 500 pieces max.

DASH NUMBER*	INDUCTANCE (μH) ±20%	TEST FREQUENCY (kHz)	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (Amps)	SRF TYPICAL (MHz)
SERIES SPD42R					
-122M	1.2	100	0.019	1.80	120
-222M	2.2	100	0.023	1.35	77
-332M	3.3	100	0.032	1.10	65
-472M	4.7	100	0.045	0.90	55
-682M	6.8	100	0.060	0.73	45
-103M	10	100	0.083	0.58	37
-123M	12	1.0	0.100	0.53	34
-153M	15	1.0	0.115	0.46	30
-183M	18	1.0	0.150	0.42	28
-223M	22	1.0	0.160	0.38	25
-273M	27	1.0	0.190	0.35	21
-333M	33	1.0	0.215	0.32	18
-393M	39	1.0	0.290	0.30	17
-473M	47	1.0	0.320	0.28	16
-563M	56	1.0	0.365	0.25	15
-683M	68	1.0	0.480	0.22	14
-823M	82	1.0	0.520	0.20	12
-104M	100	1.0	0.700	0.12	11

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com



SERIES**SPD62R**RoHS
Compliant**Shielded Surface Mount Inductors**

Actual Size

**Physical Parameters**

	Inches	Millimeters
A	0.244 ± 0.012	6.2 ± 0.3
B	0.260 ± .012	6.6 ± 0.3
C	0.118 Max.	3.0 Max.
D	0.181 Ref. only	4.60 Ref. only
E	0.059 ± 0.007	1.5 ± 0.2
F	0.050 ± 0.007	1.27 ± 0.2
G	0.015 Ref. only	0.38 Ref. only

Mechanical Configuration Units designed for surface mounting; ferrite core and ferrite sleeve

Operating temperature range -55°C to +125°C

Application Frequency Range

Values 1.2μH to 12μH to 1.0 MHz Min.

Values above 12μH to 300 kHz Min.

Current Rating at 25°C Ambient The maximum DC current that will cause a 40°C maximum temperature rise and where the inductance will not decrease by more than 10% from its zero DC value

Packaging Tape & reel (16mm):

13" reel, 1500 pieces max.; 7" reel not available

DASH NUMBER*

INDUCTANCE (μH) ±20%

TEST FREQUENCY (kHz)

DC RESISTANCE
MAXIMUM (OHMS)CURRENT RATING
TYPICAL (AMPS)

Power Inductors

SERIES SPD62 FERRITE CORE & SLEEVE

-122M	1.2	100	0.08	3.50
-242M	2.4	100	0.10	2.80
-352M	3.5	100	0.12	2.50
-472M	4.7	100	0.15	2.00
-682M	6.8	100	0.17	1.80
-103M	10	100	0.18	1.40
-123M	12	100	0.20	1.30
-153M	15	1.0	0.30	1.20
-183M	18	1.0	0.35	1.10
-223M	22	1.0	0.40	1.00
-273M	27	1.0	0.45	0.94
-333M	33	1.0	0.50	0.82
-393M	39	1.0	0.70	0.78
-473M	47	1.0	0.75	0.70
-563M	56	1.0	0.85	0.68
-683M	68	1.0	1.20	0.56
-823M	82	1.0	1.45	0.50
-104M	100	1.0	1.60	0.41
-124M	120	1.0	1.70	0.39
-154M	150	1.0	1.80	0.37
-184M	180	1.0	2.10	0.35
-224M	220	1.0	2.20	0.32
-274M	270	1.0	3.00	0.29
-334M	330	1.0	3.30	0.22

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

Marking For values lower than 10 H the R indicates a decimal point and the remaining digits indicate the inductance in H. For values 10 H and above, the first two digits indicate the inductance in H and the third digit indicates the number of trailing zeros where a zero indicates that there are no trailing zeros.

Example: SPD62R-122M (1.2 H)

1R2

Example: SPD62R-334M (330 H)


331

SERIES**SPD73R & SPD74R
SPD73 & SPD74**RoHS
CompliantTraditional
First Quality

DASH NUMBER*

INDUCTANCE (μ H) $\pm 20\%$

TEST FREQUENCY (kHz)

DC RESISTANCE
MAXIMUM (OHMS)CURRENT RATING
TYPICAL (AMPS)**Shielded Surface Mount Inductors**

Actual Size

Physical Parameters

	Inches	Millimeters
A	0.287 $\pm$.020	7.3 $\pm$ 0.5
B	0.287 $\pm$.020	7.3 $\pm$ 0.5
C	0.185 Max.	4.7 Max. (Series SPD74)
C	0.153 Max.	3.9 Max. (Series SPD73)
D	0.200 $\pm$ 0.020	5.0 $\pm$ 0.5
E	0.088 $\pm$ 0.020	2.2 $\pm$ 0.5
F	0.042 $\pm$ 0.020	1.0 $\pm$ 0.5
G	0.015 Ref. only	0.38 Ref. only

Mechanical Configuration Units designed for surface mounting; ferrite core and ferrite sleeve

Operating temperature range -55°C to $+125^{\circ}\text{C}$

Application Frequency Range

Values 1.2 μ H to 10 μ H to 1.0 MHz Min.

Values above 10 μ H to 300 kHz Min.

Current Rating at 25°C Ambient The maximum DC current that will cause a 40°C maximum temperature rise and where the inductance will not decrease by more than 10% from its zero DC value

Marking For values lower than 10 H the R indicates a decimal point and the remaining digits indicate the inductance in H. For values 10 H and above, the first two digits indicate the inductance in H and the third digit indicates the number of trailing zeros where a zero indicates that there are no trailing zeros.

Example: SPD73R-122M (1.2 H)

1R2

Example: SPD74R-105M (1,000 H)

102

Packaging Tape & reel (16mm):

13" reel, 1000 pieces max.; 7" reel not available

SERIES SPD73 FERRITE CORE & SLEEVE

-122M	1.2	100	0.020	3.40
-242M	2.4	100	0.032	2.69
-352M	3.5	100	0.035	2.60
-472M	4.7	100	0.050	2.15
-682M	6.8	100	0.065	1.90
-103M	10	100	0.067	1.90
-123M	12	1.0	0.080	1.70
-153M	15	1.0	0.091	1.59
-183M	18	1.0	0.14	1.28
-223M	22	1.0	0.19	1.10
-273M	27	1.0	0.21	1.05
-333M	33	1.0	0.24	0.981
-393M	39	1.0	0.32	0.850
-473M	47	1.0	0.36	0.801
-563M	56	1.0	0.47	0.701
-683M	68	1.0	0.52	0.667
-823M	82	1.0	0.69	0.579
-104M	100	1.0	0.79	0.541
-124M	120	1.0	0.84	0.524
-154M	150	1.0	0.89	0.510
-184M	180	1.0	1.45	0.399
-224M	220	1.0	1.65	0.374
-274M	270	1.0	2.31	0.316
-334M	330	1.0	2.62	0.297
-394M	390	1.0	2.94	0.280
-474M	470	1.0	4.18	0.235
-564M	560	1.0	4.67	0.222
-684M	680	1.0	5.73	0.201
-824M	820	1.0	6.54	0.188
-105M	1000	1.0	9.44	0.156

SERIES SPD74 FERRITE CORE & SLEEVE

-122M	1.2	100	0.025	4.40
-242M	2.4	100	0.03	4.00
-352M	3.5	100	0.034	3.70
-472M	4.7	100	0.038	3.50
-682M	6.8	100	0.042	3.40
-103M	10	100	0.049	2.50
-123M	12	1.0	0.058	2.40
-153M	15	1.0	0.081	2.30
-183M	18	1.0	0.091	2.15
-223M	22	1.0	0.11	2.00
-273M	27	1.0	0.15	1.70
-333M	33	1.0	0.17	1.50
-393M	39	1.0	0.23	1.35
-473M	47	1.0	0.26	1.30
-563M	56	1.0	0.35	1.10
-683M	68	1.0	0.38	1.05
-823M	82	1.0	0.43	1.00
-104M	100	1.0	0.61	0.86
-124M	120	1.0	0.66	0.84
-154M	150	1.0	0.88	0.70
-184M	180	1.0	0.98	0.68
-224M	220	1.0	1.17	0.60
-274M	270	1.0	1.64	0.53
-334M	330	1.0	1.86	0.50
-394M	390	1.0	2.85	0.40
-474M	470	1.0	3.01	0.39
-564M	560	1.0	3.62	0.36
-684M	680	1.0	4.63	0.32
-824M	820	1.0	5.2	0.30
-105M	1000	1.0	6.0	0.28

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

SERIES

SPD125R & SPD127R
SPD125 & SPD127

Shielded Surface Mount Inductors

RoHS
Compliant

Traditional
First Quality


DASH NUMBER*

INDUCTANCE (μH) ±20%

TEST FREQUENCY (kHz)

DC RESISTANCE
MAXIMUM (OHMS)

CURRENT RATING
TYPICAL (AMPS)



SERIES SPD125 FERRITE CORE & SLEEVE				
-222M	2.2	100	0.020	7.00
-332M	3.3	100	0.030	5.50
-472M	4.7	100	0.040	5.00
-682M	6.8	100	0.050	4.50
-103M	10	100	0.055	4.00
-123M	12	1.0	0.060	3.50
-153M	15	1.0	0.065	3.30
-183M	18	1.0	0.070	3.00
-223M	22	1.0	0.075	2.80
-273M	27	1.0	0.085	2.30
-333M	33	1.0	0.095	2.10
-393M	39	1.0	0.105	2.00
-473M	47	1.0	0.115	1.80
-563M	56	1.0	0.135	1.60
-683M	68	1.0	0.170	1.50
-823M	82	1.0	0.190	1.40
-104M	100	1.0	0.210	1.30
-124M	120	1.0	0.250	1.10
-154M	150	1.0	0.300	1.00
-184M	180	1.0	0.350	0.90
-224M	220	1.0	0.420	0.80
-274M	270	1.0	0.510	0.75
-334M	330	1.0	0.600	0.70
-394M	390	1.0	0.750	0.65
-474M	470	1.0	0.820	0.60
-564M	560	1.0	1.000	0.55
-684M	680	1.0	1.300	0.50
-824M	820	1.0	1.650	0.45
-105M	1000	1.0	2.000	0.40

SERIES SPD127 FERRITE CORE & SLEEVE				
-222M	2.2	100	0.015	8.50
-332M	3.3	100	0.018	7.50
-472M	4.7	100	0.022	6.80
-682M	6.8	100	0.030	6.20
-103M	10	100	0.040	5.40
-123M	12	1.0	0.045	4.90
-153M	15	1.0	0.048	4.50
-183M	18	1.0	0.052	3.90
-223M	22	1.0	0.055	3.60
-273M	27	1.0	0.060	3.40
-333M	33	1.0	0.065	3.00
-393M	39	1.0	0.080	2.80
-473M	47	1.0	0.100	2.50
-563M	56	1.0	0.120	2.30
-683M	68	1.0	0.140	2.10
-823M	82	1.0	0.170	1.90
-104M	100	1.0	0.220	1.70
-124M	120	1.0	0.250	1.60
-154M	150	1.0	0.320	1.40
-184M	180	1.0	0.360	1.30
-224M	220	1.0	0.390	1.20
-274M	270	1.0	0.520	1.10
-334M	330	1.0	0.620	1.00
-394M	390	1.0	0.750	0.90
-474M	470	1.0	0.980	0.80
-564M	560	1.0	1.150	0.75
-684M	680	1.0	1.220	0.70
-824M	820	1.0	1.400	0.65
-105M	1000	1.0	1.540	0.62

Physical Parameters

	Inches	Millimeters
A	0.472 ± 0.032	12.0 ± 0.8
B	0.472 ± 0.032	12.0 ± 0.8
C	0.236 Max.	6.0 Max. (Series SPD125)
	0.315 Max.	8.0 Max. (Series SPD127)
D	0.300 ± 0.020	7.6 ± 0.5
E	0.198 ± 0.020	5.0 ± 0.5
F	0.086 ± 0.020	2.18 ± 0.5
G	0.015 Ref. only	0.38 Ref. only
H	0.075 Ref. only	1.91 Ref. only
I	0.198 Ref. only	5.03 Ref. only

Mechanical Configuration Units designed for surface mounting; ferrite core and ferrite sleeve

Operating temperature range -55°C to +125°C

Application Frequency Range

Values 2.2μH to 10μH to 1.0 MHz Min.
Values above 10μH to 300 kHz Min.

Current Rating at 25°C Ambient The maximum DC current that will cause a 40°C maximum temperature rise and where the inductance will not decrease by more than 10% from its zero DC value

Marking For values lower than 10 H the R indicates a decimal point and the remaining digits indicate the inductance in H. For values 10 H and above, the first two digits indicate the inductance in H and the third digit indicates the number of trailing zeros where a zero indicates that there are no trailing zeros.

Example: SPD125R-222M (2.2 H)
2R2


Example: SPD127R-105M (1,000 H)
102

Packaging Tape & reel (24mm):
13" reel, 500 pieces max.; 7" reel not available

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

Axial Lead Power Choke



Mechanical Configuration Units are axial leaded encapsulated in an epoxy molded case.

Physical Parameters

	Inches	Millimeters
Length	0.550 to 0.570	14.00 to 14.48
Diameter	0.205 to 0.225	5.21 to 5.72
Lead Size		
AWG #21 TCW		0.026 to 0.030 0.66 to 0.76
Lead Length		1.25 Min. 31.75 Min.

Operating Temperature -55°C to +125°C

Current Rating at 80°C Ambient 45°C Rise

Maximum Power Dissipation at 80°C 0.44 W

Incremental Current The current at which the inductance will be decreased by a maximum of 5% from its initial zero DC value.

Marking DELEVAN; inductance with units and tolerance; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 2256-16J

Front:	Reverse:
DELEVAN	0920B
18uH±5%	

Packaging Tape & reel: 12" reel, 1000 pieces max.; 14" reel, 1500 pieces max.

Made in the U.S.A.


Optional Tolerances: K = 10% J = 5%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

DASH NUMBER*	INDUCTANCE @ 1 kHz (μH) ±15%	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (AMPS)	INCREMENTAL CURRENT (AMPS)
SERIES 2256 FERRITE CORE				
-221L	0.22	0.0080	7.00	7.00
-271L	0.27	0.0085	6.75	6.75
-331L	0.33	0.0090	6.50	6.50
-391L	0.39	0.0095	6.25	6.25
-471L	0.47	0.0100	6.00	6.00
-561L	0.56	0.0105	5.80	5.80
-681L	0.68	0.0110	5.70	5.70
-821L	0.82	0.0120	5.60	5.60
-01L	1.00	0.013	5.50	5.50
-02L	1.20	0.018	4.69	4.69
-03L	1.50	0.020	4.45	4.45
-04L	1.80	0.021	4.34	4.34
-05L	2.20	0.029	3.70	3.70
-06L	2.70	0.034	3.41	3.41
-07L	3.30	0.038	3.23	3.23
-08L	3.90	0.042	3.07	3.07
-09L	4.70	0.047	2.90	2.90
-10L	5.60	0.051	2.79	2.79
-11L	6.80	0.058	2.61	2.61
-12L	8.20	0.063	2.51	2.51
-13L	10.0	0.071	2.36	2.36
-14L	12.0	0.079	2.24	2.24
-15L	15.0	0.089	2.11	2.11
-16L	18.0	0.119	1.82	1.82
-17L	22.0	0.152	1.61	1.61
-18L	27.0	0.179	1.48	1.48
-19L	33.0	0.222	1.33	1.33
-20L	39.0	0.315	1.12	1.12
-21L	47.0	0.362	1.04	1.04
-22L	56.0	0.397	1.00	1.00
-23L	68.0	0.418	0.97	0.97
-24L	82.0	0.604	0.81	0.81
-25L	100	0.672	0.76	0.76
-26L	120	0.735	0.73	0.73
-27L	150	0.913	0.63	0.63
-28L	180	1.370	0.53	0.53
-29L	220	1.580	0.50	0.50
-30L	270	1.770	0.47	0.47
-31L	330	2.510	0.39	0.39
-32L	390	2.730	0.38	0.38
-33L	470	3.250	0.35	0.35
-34L	560	3.750	0.33	0.33
-35L	680	4.310	0.30	0.30
-36L	820	6.040	0.26	0.26
-37L	1000	6.900	0.24	0.24
-38L	1200	10.00	0.200	0.200
-39L	1500	12.50	0.178	0.178
-40L	1800	16.00	0.157	0.157
-41L	2200	20.00	0.141	0.141
-42L	2700	23.00	0.131	0.131
-43L	3300	25.00	0.126	0.126
-44L	3900	33.00	0.110	0.110
-45L	4700	37.00	0.103	0.103
-46L	5600	40.00	0.100	0.100
-47L	6800	62.00	0.080	0.080
-48L	8200	66.00	0.077	0.077
-49L	10000	74.00	0.071	0.071
-50L	12000	93.00	0.065	0.065
-51L	15000	105.0	0.061	0.061
-52L	18000	143.0	0.052	0.052
-53L	22000	160.0	0.050	0.050

Axial Lead Power Inductors



Mechanical Configuration Units are axial leaded for thru-hole mounting, encapsulated in an epoxy molded case. High resistivity ferrite core, allows for high inductance with low DC resistance.

Physical Parameters

	Inches	Millimeters
Length	0.740 ± 0.010	18.80 ± 0.25
Diameter	0.240 ± 0.010	6.10 ± 0.25
Lead Size		
AWG #20 TCW	0.032 ± 0.002	0.813 ± 0.051
Lead Length	1.44 ± 0.12	36.58 ± 3.05

Operating Temperature Range -55°C to +125°C

Current Rating 40°C Rise over 85°C Ambient

Maximum Power Dissipation at 85°C 0.50 W

Inductance Measured at 1 V with no DC current

Incremental Current The current at which the inductance will be decreased by a maximum of 5% from its initial zero DC value.

Weight Max. (Grams) 2.5

Marking DELEVAN; inductance with units and tolerance; date code (YYWWL). Note: An R before the date code indicates a RoHS component.

Example: 2474R-02K

Front: DELEVAN 1.2uH±10%
Reverse: 0902A

Packaging Tape & reel: 12" reel, 1000 pieces max.; 14" reel, 1500 pieces max. For additional packaging options, see technical section.

Made in the U.S.A.

DASH NUMBER*	INDUCTANCE @ 1 kHz (μH) ±15%	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (AMPS)	INCREMENTAL CURRENT (AMPS)
SERIES 2474 FERRITE CORE				
-01L	1.0	0.009	6.27	6.4
-02L	1.2	0.010	5.95	5.8
-03L	1.5	0.011	5.67	5.2
-04L	1.8	0.012	5.43	4.8
-05L	2.2	0.013	5.22	4.3
-06L	2.7	0.014	5.03	3.9
-07L	3.3	0.016	4.70	3.5
-08L	3.9	0.017	4.56	3.2
-09L	4.7	0.022	4.01	2.9
-10L	5.6	0.024	3.84	2.7
-11L	6.8	0.026	3.69	2.5
-12L	8.2	0.028	3.55	2.2
-13L	10.0	0.033	3.27	2.0
-14L	12.0	0.037	3.09	1.8
-15L	15.0	0.040	2.97	1.6
-16L	18.0	0.044	2.84	1.5
-17L	22.0	0.050	2.66	1.4
-18L	27.0	0.070	2.25	1.2
-19L	33.0	0.075	2.17	1.1
-20L	39.0	0.084	2.05	1.0
-21L	47.0	0.104	1.84	0.93
-22L	56.0	0.130	1.65	0.85
-23L	68.0	0.145	1.56	0.77
-24L	82.0	0.152	1.53	0.71
-25L	100.0	0.208	1.30	0.64
-26L	120.0	0.283	1.12	0.58
-27L	150.0	0.330	1.04	0.52
-28L	180.0	0.362	0.99	0.48
-29L	220.0	0.505	0.84	0.43
-30L	270.0	0.557	0.80	0.39
-31L	330.0	0.650	0.74	0.35
-32L	390.0	0.770	0.68	0.32
-33L	470.0	1.03	0.59	0.29
-34L	560.0	1.14	0.56	0.27
-35L	680.0	1.50	0.49	0.25
-36L	820.0	1.98	0.42	0.22
-37L	1000.0	2.30	0.39	0.20
-38L	1200.0	2.55	0.37	0.18
-39L	1500.0	3.00	0.34	0.16
-40L	1800.0	4.00	0.30	0.15
-41L	2200.0	4.40	0.28	0.14
-42L	2700.0	5.80	0.25	0.12
-43L	3300.0	6.56	0.23	0.11
-44L	3900.0	8.63	0.20	0.10
-45L	4700.0	10.1	0.19	0.09
-46L	5600.0	11.2	0.18	0.09
-47L	6800.0	15.0	0.15	0.08
-48L	8200.0	20.8	0.13	0.07
-49L	10000.0	23.4	0.12	0.06
-50L	12000.0	26.0	0.12	0.06
-51L	15000.0	36.0	0.10	0.05
-52L	18000.0	40.0	0.09	0.05

Optional Tolerances: J = 5% H = 3% G = 2% F = 1%

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com


SERIES

4590R 4590



High Current Filter Inductors

Actual Size (Max.)



Physical Parameters

	Inches	Millimeters
Length	0.900 Max.	22.86 Max.
Diameter	0.455 Max.	11.55 Max.
Lead Size		
AWG #20 TCW	0.032 ± 0.002	0.813 ± 0.05
Lead Length	1.10 Min.	27.94 Min.

Operating Temperature

-55°C to +125°C
-55°C to +85°C @ full rated current

Current Rating at 85°C Ambient 40°C Rise

Maximum Power Dissipation at 85°C 0.70 W

Dielectric Withstanding Voltage 2500 V RMS

Incremental Current The current which will decrease the inductance by approximately 5%.

Inductance Measurement Inductance is measured @ 1 kHz with 1 VAC open circuit and 0 dc bias.

Inductance Tolerance Tolerance is specified by suffixing an alpha character to the part number as follows: J = 5%, K = 10%, and L = 15%. Units are normally supplied to the tolerance indicated in table.

High Saturation Bobbin allows for high inductance with low DCR.

High Resistivity Core offers very high parallel resistance, resulting in maximum coil performance.

4590 Marking DELEVAN; inductance; tolerance.

4590R Marking DELEVAN; 4590R; dash number with tolerance letter.

Example: 4590-393K

DELEVAN
39 uH
±10%

Example: 4590R-393K

DELEVAN
4590R
393K

Packaging Bulk only

DASH NUMBER*
NOMINAL INDUCTANCE
(μH) ±10%
DC RESISTANCE
MAXIMUM (OHMS)
CURRENT RATING
MAXIMUM (AMPS)
CURRENT DC (AMPS)
INCREMENTAL

Power Inductors

SERIES 4590 FERRITE CORE				
-392K	3.9	0.007	9.75	8.2
-472K	4.7	0.008	9.11	7.5
-562K	5.6	0.011	7.77	6.9
-682K	6.8	0.011	7.60	6.3
-822K	8.2	0.013	7.15	5.7
-103K	10.0	0.016	6.44	5.2
-123K	12.0	0.018	6.07	4.7
-153K	15.0	0.020	5.76	4.3
-183K	18.0	0.022	5.49	3.9
-223K	22.0	0.024	5.26	3.5
-273K	27.0	0.025	5.15	3.2
-333K	33.0	0.028	4.87	2.9
-393K	39.0	0.031	4.63	2.7
-473K	47.0	0.034	4.45	2.5
-563K	56.0	0.043	3.93	2.3
-683K	68.0	0.059	3.355	2.1
-823K	82.0	0.066	3.175	1.9
-104K	100	0.084	2.815	1.7
-124K	120	0.113	2.43	1.6
-154K	150	0.129	2.27	1.4
-184K	180	0.150	2.105	1.3
-224K	220	0.162	2.025	1.2
-274K	270	0.226	1.715	1.1
-334K	330	0.257	1.61	0.95
-394K	390	0.288	1.52	0.88
-474K	470	0.393	1.30	0.80
-564K	560	0.504	1.15	0.74
-684K	680	0.570	1.08	0.67
-824K	820	0.643	1.015	0.61
-105K	1000	0.844	0.89	0.56
-125K	1200	0.977	0.825	0.51
-155K	1500	1.18	0.75	0.46
-185K	1800	1.50	0.665	0.42
-225K	2200	1.76	0.615	0.38
-275K	2700	2.13	0.56	0.34
-335K	3300	2.53	0.51	0.31
-395K	3900	2.84	0.48	0.29
-475K	4700	3.79	0.415	0.26
-565K	5600	4.24	0.395	0.24
-685K	6800	5.75	0.34	0.22
-825K	8200	6.44	0.32	0.20
-106K	10000	7.30	0.30	0.18
-126K	12000	9.34	0.265	0.17
-156K	15000	10.7	0.25	0.15
-186K	18000	14.8	0.21	0.14
-226K	22000	18.0	0.19	0.12
-276K	27000	22.7	0.17	0.11
-336K	33000	25.7	0.16	0.10
-396K	39000	29.7	0.15	0.09
-476K	47000	33.7	0.14	0.09
-566K	56000	38.0	0.13	0.08
-686K	68000	52.8	0.11	0.07
-826K	82000	67.3	0.10	0.07
-107K	100000	76.0	0.09	0.06

Optional Tolerances: J = 5% L = 15%

*Complete part # must include series # PLUS the dash #


For surface finish information, refer to www.delevanfinishes.com

SERIES

3443R
3443



Radial Lead Power Chokes



Actual Size (Max.)



Physical Parameters

	Inches	Millimeters
A	0.500 ± 0.015	12.72 ± 0.38
B	0.600 Max.	15.27 Max.
C	0.375 Min.	9.54 Min.
D	0.870 Max.	22.14 Max.
E	0.515 Max.	13.10 Max.
F**	0.040 ± 0.005	1.02 ± 0.13
G	0.030 Min.	0.76 Min.

**F= AWG #18 TCW

Current Rating Based on continuous operation at room temperature. Derating is required at elevated ambient temperatures in accordance with the derating curve.

Operating Temperature Range -55°C to +125°C

Maximum Power Dissipation at 25°C 2.2 W

Weight Max. (Grams) 12.0

Incremental Current 1) Current Level which causes a maximum of 10% decrease in inductance. **2)** The Incremental Current at ambient temperatures other than 25°C will be 70% of the adjusted current rating.

Marking DELEVAN; part number without the tolerance letter, inductance with units. Note: An R after 3443 indicates a RoHS component.


Example: 3443-00K
DELEVAN
3443-00
1uH

Packaging Bulk only

DASH NUMBER*	INDUCTANCE (μH) ±10%	DC RESISTANCE MAXIMUM (OHMS)	CURRENT RATING MAXIMUM (AMPS)	INCREMENTAL CURRENT DC (AMPS)
SERIES 3443 FERRITE CORE				
-00K	1.0	0.005	17.8	17.8
-04K	1.5	0.006	16.2	16.2
-08K	2.2	0.007	15.0	15.0
-12K	3.3	0.008	14.0	12.4
-16K	4.7	0.009	13.0	10.3
-20K	6.8	0.010	12.5	8.9
-24K	10.0	0.015	10.0	7.3
-28K	15.0	0.022	8.5	5.9
-32K	22.0	0.033	6.5	4.9
-36K	33.0	0.052	5.5	4.0
-40K	47.0	0.078	4.5	3.3
-44K	68.0	0.092	4.0	2.8
-48K	100.0	0.140	3.3	2.3
-50K	120.0	0.175	3.0	2.1
-52K	150.0	0.210	2.7	1.9
-56K	220.0	0.330	2.2	1.5
-58K	270.0	0.420	1.95	1.35
-60K	330.0	0.510	1.70	1.20
-64K	470.0	0.610	1.60	1.00
-68K	680.0	0.910	1.30	0.90
-72K	1000.0	1.40	1.00	0.73
-76K	1500.0	2.20	0.84	0.60
-80K	2200.0	3.30	0.69	0.49
-84K	3300.0	5.10	0.55	0.40
-88K	4700.0	7.70	0.45	0.34
-92K	6800.0	11.7	0.36	0.28
-94K	10000.0	14.2	0.33	0.23
-98K	15000.0	21.9	0.26	0.19

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com




For more detailed graphs, contact factory

SERIES

DC630R DC630



High Current Power Line Chokes



Actual Size

Physical Parameters

	Inches	Millimeters
A	0.630 ± 0.030	16.0 ± 0.762
B (C/L to C/L)	See Characteristics table	
C	0.750 Min.	19.05 Min.
D	0.810 ± 0.020	20.57 ± 0.508
E (Ref. only)	0.195 Max.	4.95 Max.
F	Clearance Hole for 4/40 Screw	

Leads Tinned to within 1/16" of Body

Inductance

Measured @ 10 KHz, 25mAdc and 0 Adc @ 25°C

Mechanical Configuration Center hole allows for mechanical mounting

Operating Temperature

-55°C to +125°C;

-55°C to +80°C @ full rated current

Current Rating at 80°C Ambient 45°C Rise

Incremental Current Minimum current which causes a 5% max. change in Inductance

Power Dissipation at 80°C 1.00 Watts Max.

Dielectric Withstanding Voltage 1000 V RMS Min.

Marking DELEVAN; DC630; dash number with tolerance letter. Note: An R after DC630 indicates a RoHS component.

Example: DC630-102M

DELEVAN
DC630
102M

Packaging Bulk only

Power Inductors

LEAD DIAMETER
(Inches, Reference)

DIMENSION B
(Inches, Reference)

INCREMENTAL
CURRENT (A DC)

CURRENT RATING
MAXIMUM (A DC)

DC RESISTANCE
MAXIMUM (OHMS) @ 25°C

TOLERANCE

NOMINAL
INDUCTANCE (μH)

DASH NUMBER*

SERIES DC630							
-102M	1.0	± 20%	0.003	14.00	68.0	0.490	0.051
-152M	1.5	± 20%	0.004	13.50	55.5	0.490	0.051
-222M	2.2	± 20%	0.005	12.80	46.0	0.490	0.051
-272M	2.7	± 20%	0.005	12.80	42.0	0.490	0.051
-332M	3.3	± 20%	0.005	12.80	38.0	0.490	0.051
-392M	3.9	± 20%	0.006	12.30	34.5	0.490	0.051
-472M	4.7	± 20%	0.007	11.70	31.5	0.490	0.051
-562M	5.6	± 20%	0.007	11.70	29.0	0.490	0.051
-682M	6.8	± 20%	0.008	10.50	26.0	0.490	0.051
-822M	8.2	± 20%	0.009	10.00	24.0	0.490	0.051
-103K	10.0	± 10%	0.010	9.50	21.5	0.490	0.051
-123K	12.0	± 10%	0.011	9.10	19.5	0.490	0.051
-153K	15.0	± 10%	0.015	8.09	17.5	0.470	0.045
-183K	18.0	± 10%	0.020	7.00	16.0	0.460	0.040
-223K	22.0	± 10%	0.025	6.26	14.5	0.460	0.040
-273K	27.0	± 10%	0.030	5.72	13.2	0.440	0.036
-333K	33.0	± 10%	0.040	4.95	11.9	0.430	0.032
-393K	39.0	± 10%	0.050	4.43	10.9	0.420	0.029
-473K	47.0	± 10%	0.062	3.98	10.0	0.480	0.029
-563K	56.0	± 10%	0.069	3.77	9.20	0.480	0.029
-683K	68.0	± 10%	0.077	3.57	8.30	0.480	0.029
-823K	82.0	± 10%	0.083	3.44	7.60	0.480	0.029
-104K	100	± 10%	0.095	3.21	6.80	0.480	0.029
-124K	120	± 10%	0.100	3.12	6.20	0.480	0.029
-154K	150	± 10%	0.111	2.97	5.60	0.480	0.029
-184K	180	± 10%	0.125	2.80	5.10	0.480	0.029
-224K	220	± 10%	0.168	2.42	4.60	0.470	0.025
-274K	270	± 10%	0.225	2.09	4.20	0.450	0.023
-334K	330	± 10%	0.315	1.72	3.80	0.450	0.020
-394K	390	± 10%	0.342	1.66	3.40	0.480	0.020
-474K	470	± 10%	0.377	1.58	3.10	0.480	0.020
-564K	560	± 10%	0.408	1.52	2.90	0.480	0.020
-684K	680	± 10%	0.468	1.42	2.60	0.480	0.020

*Complete part # must include series # PLUS the dash #


For surface finish information, refer to www.delevanfinishes.com

SERIES

DC780R DC780



High Current Power Line Chokes



Actual Size

Physical Parameters

	Inches	Millimeters
A	0.775 ± 0.025	19.6 ± 0.6
B (C/L to C/L)	See Characteristics table	
C	0.750 Min.	19.05 Min.
D	0.815 ± 0.015	20.7 ± .4
E (Ref. only)	0.195 Max.	4.95 Max.
F	Clearance Hole for 4/40 Screw	

Leads Tinned to within 1/16" of Body

Inductance Measured @ 1 KHz with 0 Amps dc

Mechanical Configuration Center hole allows for mechanical mounting; insulated bobbins.

Operating Temperature

-55°C to +125°C;

-55°C to +80°C @ full rated current

Current Rating at 80°C Ambient 45°C Rise

Incremental Current Minimum current which causes a 5% max. change in Inductance

Power Dissipation at 80°C 1.400 Watts Max.

Dielectric Withstanding Voltage 1000 V RMS Min.

Marking DELEVAN; DC780; dash number with tolerance letter. Note: An R after DC780 indicates a RoHS component.

Example: DC780R-103K

DELEVAN
DC780R
103K

Packaging Bulk only

Power Inductors

LEAD DIAMETER
(Inches, Reference)

DIMENSION B
(Inches, Reference)

INCREMENTAL
CURRENT (A DC)

CURRENT RATING
MAXIMUM (A DC)

DC RESISTANCE
MAXIMUM (OHMS) @ 25°C

TOLERANCE

NOMINAL
INDUCTANCE (µH)

DASH NUMBER*

SERIES DC780							
-102L	1.0	± 15%	0.003	11.4	110.0	0.620	0.051
-122L	1.2	± 15%	0.003	11.4	108.0	0.620	0.051
-152L	1.5	± 15%	0.003	11.4	89.0	0.620	0.051
-182L	1.8	± 15%	0.003	11.4	81.0	0.620	0.051
-222L	2.2	± 15%	0.004	11.4	73.0	0.620	0.051
-272L	2.7	± 15%	0.005	11.4	66.0	0.620	0.051
-332L	3.3	± 15%	0.005	11.4	60.0	0.620	0.051
-392L	3.9	± 15%	0.005	11.4	55.0	0.620	0.051
-472L	4.7	± 15%	0.005	11.4	50.0	0.620	0.051
-562L	5.6	± 15%	0.006	11.4	46.0	0.620	0.051
-682L	6.8	± 15%	0.007	11.4	42.0	0.620	0.051
-822L	8.2	± 15%	0.007	11.4	38.0	0.620	0.051
-103K	10.0	± 10%	0.009	11.4	34.5	0.620	0.051
-123K	12.0	± 10%	0.009	11.4	31.5	0.620	0.051
-153K	15.0	± 10%	0.013	9.0	28.2	0.625	0.045
-183K	18.0	± 10%	0.018	7.2	25.7	0.630	0.045
-223K	22.0	± 10%	0.019	7.2	23.3	0.630	0.045
-273K	27.0	± 10%	0.026	5.5	21.0	0.546	0.040
-333K	33.0	± 10%	0.029	5.5	19.0	0.546	0.036
-393K	39.0	± 10%	0.030	5.5	17.5	0.594	0.036
-473K	47.0	± 10%	0.035	5.5	15.9	0.625	0.036
-563K	56.0	± 10%	0.039	5.5	14.6	0.625	0.036
-683K	68.0	± 10%	0.053	4.8	13.2	0.656	0.036
-823K	82.0	± 10%	0.060	4.8	12.1	0.656	0.036
-104K	100	± 10%	0.080	4.0	10.9	0.593	0.036
-124K	120	± 10%	0.090	4.0	10.0	0.593	0.036
-154K	150	± 10%	0.098	4.0	8.9	0.593	0.032
-184K	180	± 10%	0.110	4.0	8.1	0.593	0.032
-224K	220	± 10%	0.150	2.8	7.4	0.593	0.029
-274K	270	± 10%	0.213	2.0	6.6	0.562	0.025
-334K	330	± 10%	0.305	1.6	6.0	0.590	0.025
-394K	390	± 10%	0.320	1.6	5.5	0.590	0.025
-474K	470	± 10%	0.355	1.6	5.0	0.590	0.025
-564K	560	± 10%	0.388	1.6	4.6	0.590	0.023
-684K	680	± 10%	0.430	1.6	4.2	0.590	0.023
-824K	820	± 10%	0.590	1.3	3.8	0.590	0.023
-105K	1,000	± 10%	0.818	1.0	3.5	0.590	0.020
-125K	1,200	± 10%	1.140	0.8	3.2	0.590	0.018
-155K	1,500	± 10%	1.260	0.8	2.8	0.590	0.018
-185K	1,800	± 10%	1.390	0.8	2.6	0.590	0.018
-225K	2,200	± 10%	1.540	0.8	2.3	0.590	0.018

*Complete part # must include series # PLUS the dash #


For surface finish information, refer to www.delevanfinishes.com

SERIES

DC1050R
DC1050

RoHS
Compliant
Traditional
First Quality

High Current Power Line Chokes



Actual Size (Max.)

DASH NUMBER*
INDUCTANCE (μH)
NOMINAL
TOLERANCE
MAXIMUM (OHMS) @ 25°C
DC RESISTANCE
CURRENT RATING
MAXIMUM (A DC)
INCREMENTAL
CURRENT (A DC)
(Inches, Reference)
DIMENSION B
(Inches, Reference)
LEAD DIAMETER
(Inches, Reference)

SERIES DC1050 FERRITE CORE							
-104K	100	±10%	0.034	7.5	9.0	0.81	0.046
-124K	120	±10%	0.046	6.5	8.0	0.77	0.040
-154K	150	±10%	0.064	5.5	7.0	0.77	0.040
-184K	180	±10%	0.072	5.1	6.5	0.77	0.040
-224K	220	±10%	0.080	4.8	6.0	0.77	0.040
-274K	270	±10%	0.110	4.2	5.0	0.77	0.036
-334K	330	±10%	0.122	4.0	4.5	0.77	0.036
-394K	390	±10%	0.169	3.4	4.0	0.77	0.032
-474K	470	±10%	0.187	3.2	3.8	0.77	0.032
-564K	560	±10%	0.205	3.0	3.5	0.77	0.032
-684K	680	±10%	0.256	2.7	3.0	0.77	0.029
-824K	820	±10%	0.288	2.5	2.8	0.77	0.029
-105K	1000	±10%	0.426	2.1	2.5	0.77	0.029
-125K	1200	±10%	0.462	2.0	2.2	0.77	0.026
-155K	1500	±10%	0.518	1.9	2.0	0.77	0.026
-185K	1800	±10%	0.705	1.6	1.8	0.77	0.026
-225K	2200	±10%	1.020	1.4	1.5	0.77	0.023
-275K	2700	±10%	1.140	1.3	1.4	0.77	0.023
-335K	3300	±10%	1.270	1.2	1.3	0.77	0.023
-395K	3900	±10%	1.670	1.1	1.2	0.77	0.020
-475K	4700	±10%	1.860	1.0	1.0	0.77	0.020

Physical Parameters

	Inches	Millimeters
A	1.050 ± 0.050	26.670 ± 1.270
B	See Characteristics Table	
C	0.750 Min.	19.050 Min.
D	0.840 Max.	21.336 Max.
E (Ref. only)	0.240 Max.	6.096 Max.
F	Clearance Hole for 4/40 Screw	
G	See Characteristics Table	

Leads Tinned to within 1/16" of Body

Inductance Measured @ 1 kHz within 0 A DC on a GenRad 1658A Digibridge, or equivalent

Mechanical Configuration Center hole allows for mechanical mounting; insulated bobbins

Operating Temperature

-55°C to +125°C;
-55°C to +80°C @ full rated current

Current Rating at 80°C Ambient 45°C Rise

Incremental Current Minimum current which causes a 5% maximum decrease in Inductance

Power Dissipation at 80°C 2.20 Watts Max.

Dielectric Withstanding Voltage 1000 V RMS Min.

Marking DELEVAN; DC1050; dash number with tolerance letter. Note: An R after DC1050 indicates a RoHS component.

Example: DC1050-684K
DELEVAN
DC1050
684K

Packaging Bulk only


*Complete part # must include series # PLUS the dash #
For surface finish information, refer to www.delevanfinishes.com

SERIES

DC1390R
DC1390



High Current Power Line Chokes



Actual Size

Physical Parameters

	Inches	Millimeters
A	1.338 to 1.418	34.0 to 36.0
B	See Characteristics Table	
C	0.750 Min.	19.05 Min.
D	0.925 to 1.043	23.5 to 26.5
E	0.189 to 0.191	4.80 to 4.86
F	0.189 to 0.191	4.80 to 4.86
G	See Characteristics Table	

Leads Tinned to within 1/16" of Body

Inductance Measured @ 1 kHz within 0 A DC on a GenRad 1658A Digibridge, or equivalent

Mechanical Configuration Center hole allows for mechanical mounting; insulated bobbins

Operating Temperature

-55°C to +125°C;
-55°C to +80°C @ full rated current

Incremental Current Minimum current which causes a 5% maximum decrease in Inductance

Power Dissipation at 80°C 3.30 Watts Max.

Dielectric Withstanding Voltage 1000 V RMS Min.

Marking DELEVAN; DC1390; dash number with tolerance letter; date code (YYWWL). Note: An R after DC1390 indicates a RoHS component.

Example: DC1390R-154K

DELEVAN
DC1390R
154K
0850

Packaging Bulk only

DASH NUMBER*	INDUCTANCE (μH)	NOMINAL TOLERANCE	DC RESISTANCE (OHMS) @ 25°C	CURRENT RATING MAXIMUM (A DC)	INCREMENTAL CURRENT (A DC)	DIMENSION B (Inches, Reference)	LEAD DIAMETER (Inches, Reference)
--------------	-----------------	-------------------	-----------------------------	-------------------------------	----------------------------	---------------------------------	-----------------------------------

SERIES DC1390 FERRITE CORE							
-153K	15.0	±10%	0.006	19.9	33.3	1.12	0.082
-183K	18.0	±10%	0.008	17.3	30.4	1.20	0.082
-223K	22.0	±10%	0.009	16.3	28.0	1.20	0.082
-273K	27.0	±10%	0.010	15.4	25.9	1.20	0.082
-333K	33.0	±10%	0.011	14.7	22.6	1.20	0.082
-393K	39.0	±10%	0.012	14.1	21.2	1.20	0.082
-473K	47.0	±10%	0.018	11.5	20.0	1.20	0.073
-563K	56.0	±10%	0.019	11.2	27.9	1.17	0.073
-683K	68.0	±10%	0.021	10.7	16.3	1.17	0.065
-823K	82.0	±10%	0.023	10.2	14.9	1.22	0.065
-104K	100	±10%	0.025	9.76	13.2	1.22	0.065
-124K	120	±10%	0.028	9.23	12.3	1.22	0.065
-154K	150	±10%	0.040	7.72	10.8	1.22	0.058
-184K	180	±10%	0.045	7.28	9.86	1.19	0.058
-224K	220	±10%	0.050	6.90	9.09	1.19	0.058
-274K	270	±10%	0.056	6.52	8.05	1.25	0.058
-334K	330	±10%	0.074	5.67	7.37	1.25	0.051
-394K	390	±10%	0.082	5.39	6.80	1.22	0.051
-474K	470	±10%	0.114	4.57	6.20	1.22	0.046
-564K	560	±10%	0.125	4.37	5.69	1.24	0.046
-684K	680	±10%	0.139	4.14	5.11	1.24	0.046
-824K	820	±10%	0.154	3.93	4.70	1.24	0.046
-105K	1000	±10%	0.216	3.32	4.24	1.24	0.041
-125K	1200	±10%	0.232	3.21	3.87	1.25	0.041
-155K	1500	±10%	0.324	2.71	3.45	1.25	0.036
-185K	1800	±10%	0.360	2.57	3.14	1.22	0.036
-225K	2200	±10%	0.494	2.20	2.86	1.26	0.031
-275K	2700	±10%	0.555	2.07	2.58	1.23	0.031
-335K	3300	±10%	0.773	1.76	2.33	1.26	0.029
-395K	3900	±10%	0.845	1.68	2.14	1.23	0.029

*Complete part # must include series # PLUS the dash #



For surface finish information, refer to www.delevanfinishes.com

SERIES


HCR
HC



High Current Filter Chokes



Actual Size (Max.)



Current Rating based on continuous operation at room temperature ambient. Derating is required at elevated ambient temperatures in accordance with the derating curve. For more detailed graphs, contact factory

					DIMENSIONS Inches [Millimeters]			
PART NUMBER*	INDUCTANCE (μH) ±10% @ 1kHz**	CURRENT RATING MAXIMUM (Amps)	DC RESISTANCE MAX. (OHMS)	INCREMENTAL CURRENT (AMPS) ***	A (Max.)	B (Max.)	C ± 0.062 inches [± 1.59mm]	D ± 0.005 inches [± 0.13mm]
SERIES HC FERRITE CORE								
3HC-5	5	3	0.015	19	0.875 [22.23]	0.625 [15.88]	0.500 [12.70]	0.042 [1.07]
3HC-10	10	3	0.018	17	1.125 [28.58]	0.625 [15.88]	0.687 [17.45]	0.042 [1.07]
3HC-27	27	3	0.035	15	0.875 [22.23]	0.812 [20.62]	0.437 [11.10]	0.042 [1.07]
3HC-50	50	3	0.050	12	1.125 [28.58]	0.812 [20.62]	0.750 [19.05]	0.042 [1.07]
3HC-100	100	3	0.065	8	1.125 [28.58]	0.812 [20.62]	0.937 [23.80]	0.042 [1.07]
3HC-150	150	3	0.075	5	1.375 [34.93]	0.812 [20.62]	1.062 [26.97]	0.042 [1.07]
3HC-200	200	3	0.080	4	1.625 [41.28]	0.812 [20.62]	1.050 [26.67]	0.042 [1.07]
3HC-250	250	3	0.090	3	1.625 [41.28]	0.812 [20.62]	1.312 [33.32]	0.042 [1.07]
3HC-500	500	3	0.130	1	1.625 [41.28]	0.950 [24.13]	0.990 [25.15]	0.042 [1.07]
5HC-5	5	5	0.012	20	0.875 [22.23]	0.640 [16.26]	0.750 [19.05]	0.053 [1.35]
5HC-10	10	5	0.015	18	1.125 [28.58]	0.640 [16.26]	1.000 [25.40]	0.053 [1.35]
5HC-27	27	5	0.025	15	0.875 [22.23]	0.875 [22.23]	0.562 [14.27]	0.053 [1.35]
5HC-50	50	5	0.030	10	1.125 [28.58]	0.875 [22.23]	0.750 [19.05]	0.053 [1.35]
5HC-68	68	5	0.035	9	1.125 [28.58]	0.875 [22.23]	0.875 [22.23]	0.053 [1.35]
5HC-100	100	5	0.050	7	1.375 [34.93]	0.875 [22.23]	1.000 [25.40]	0.053 [1.35]
5HC-150	150	5	0.060	5	1.625 [41.28]	0.875 [22.23]	1.250 [31.75]	0.053 [1.35]
5HC-250	250	5	0.075	3	1.625 [41.28]	1.100 [27.94]	0.900 [22.86]	0.053 [1.35]
10HC-5	5	10	0.010	19	1.125 [28.58]	0.687 [17.45]	0.812 [20.62]	0.065 [1.65]
10HC-10	10	10	0.012	17	1.375 [34.93]	0.687 [17.45]	1.218 [30.94]	0.065 [1.65]
10HC-15	15	10	0.015	16	1.625 [41.28]	0.687 [17.45]	1.415 [35.94]	0.065 [1.65]
10HC-27	27	10	0.018	15	1.125 [28.58]	0.937 [23.80]	0.687 [17.45]	0.065 [1.65]
10HC-50	50	10	0.025	9	1.375 [34.93]	0.937 [23.80]	0.937 [23.80]	0.065 [1.65]
10HC-68	68	10	0.027	9	1.375 [34.93]	0.937 [23.80]	1.125 [28.58]	0.065 [1.65]
10HC-100	100	10	0.030	6	1.625 [41.28]	0.937 [23.80]	1.312 [33.32]	0.065 [1.65]
15HC-5	5	15	0.008	20	1.375 [34.93]	0.725 [18.42]	0.937 [23.80]	0.082 [2.08]
15HC-10	10	15	0.010	17	1.687 [42.85]	0.725 [18.42]	1.500 [38.10]	0.082 [2.08]
15HC-27	27	15	0.015	14	1.375 [34.93]	1.000 [25.40]	0.937 [23.80]	0.082 [2.08]
15HC-50	50	15	0.020	9	1.625 [41.28]	1.000 [25.40]	1.125 [28.58]	0.082 [2.08]
15HC-100	100	15	0.030	5	1.625 [41.28]	1.500 [38.10]	1.312 [33.32]	0.082 [2.08]

Dimension E
1.0 inches ± 1/16 inches;
25.4mm ± 1.59mm

Notes
** Inductance measured with zero DC current.
*** Incremental current reduces inductance by 10% or less. Average current must not exceed specified rated current.
Packaging Bulk only

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com


SERIES

**HTPT66R
HTPT66**

RoHS
Compliant
Traditional
First Quality

High Temperature Power Toroids

DASH NUMBER*
INDUCTANCE (μH)
±10% @ 1 KHz
DC RESISTANCE
MAXIMUM (OHMS)
CURRENT RATING
MAXIMUM (A DC)
INCREMENTAL
CURRENT (A DC)
NOMINAL
DIMENSION E
(Inches)



Actual Size (Max.)

Physical Parameters

	Inches	Millimeters
A	0.660 Max.	16.76 Max.
B	0.360 Max.	9.14 Max.
C	0.280 (Ref. only)	7.11 (Ref. only)
D	1.00 Min.	25.4 Min.
E	See Characteristics Table	

Operating Temperature Range

-55°C to +200°C
-55°C to +160°C @ full rated current. All Materials are rated to +200°C.

Current Rating at 160°C Ambient 40°C Rise

Inductance Measured @ 1 V, 100mA AC with no DC current. Inductance at +200°C is typically 5.5% lower than inductance measured at +25°C.



Incremental Current The current at which the inductance will be decreased by a maximum of 10% from its initial 0 DC value. At elevated temperatures incremental current is unaffected.

Packaging Bulk only

Contact the Factory for additional sizes, mounting, and electrical configurations.

SERIES HTPT66 IRON CORE					
-391	0.390	0.0020	18.3	26.6	0.053
-122	1.20	0.0029	15.3	14.8	0.053
-152	1.50	0.0036	13.7	13.3	0.053
-472	4.70	0.0086	8.8	7.4	0.042
-103	10.0	0.019	5.9	5.1	0.034
-153	15.0	0.030	4.6	4.3	0.031
-223	22.0	0.036	4.0	4.0	0.031
-393	39.0	0.073	2.8	3.0	0.025
-683	68.0	0.122	2.1	2.3	0.022
-104	100	0.145	1.9	1.8	0.022

*Complete part # must include series # PLUS the dash #
For surface finish information, refer to www.delevanfinishes.com



Charts are for reference only. Operation should be verified under actual operating conditions to avoid component operation above +200°C.

SERIES**PTxxxR
PT**

Power Toroids - Horizontal or Vertical Mount

Inductance tested at 1 kHz, <10 gauss and 0 ADC

DC Resistance at 25°C

Rated Idc based on 40°C maximum rise from 25°C ambient with 0 Arms

Windings single layered to maximize operating frequency and minimize board space

Self leads solder coated to within 0.050" of seating plane

Other values available on request

Packaging Bulk only

Mounting Standard mounting is self-lead radial per Figure "1". Optional mounting methods are self-leaded horizontal per Figure "2" or vertical base mounted per Figures "3" and "4".

**FIGURE
1**



**STANDARD
VERTICAL**

**FIGURE
2**




HORIZONTAL

**FIGURE
3**



**VERTICAL
2-LEAD**

**FIGURE
4**



**VERTICAL
4-LEAD**

*Complete part # must include series # PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com

Power Inductors

MOUNTING AVAILABLE

IND. (μH) ±15% @ 1 kHz

DCR MAXIMUM (OHMS)

RATED IDC (AMPS)

FIG. "1" STANDARD VERTICAL

HORIZONTAL

FIG. "3" 2-LEAD VERTICAL

FIG. "2" VERTICAL

FIG. "4" 4-LEAD VERTICAL

PT SERIES POWER TOROIDS							
Part #	Inductance (μH)	DCR (Ω)	Rated IDC (A)	Fig. 1	Horizontal	Fig. 3	Fig. 4
PT5-530	5	0.015	6.1	•	•	•	•
PT5-700	5	0.012	7.4	•	•	•	•
PT5-800	5	0.010	10.6	•	•	•	•
PT5-1000	5	0.008	12.8	•	•	•	•
PT10-530	10	0.020	4.9	•	•	•	•
PT10-680	10	0.015	6.8	•	•	•	•
PT10-820	10	0.010	9.3	•	•	•	•
PT10-990	10	0.008	13.2	•	•	•	•
PT25-680	25	0.035	4.4	•	•	•	•
PT25-800	25	0.025	6.6	•	•	•	•
PT25-900	25	0.020	7.0	•	•	•	•
PT25-1000	25	0.014	10.4	•	•	•	•
PT50-780	50	0.050	3.8	•	•	•	•
PT50-900	50	0.030	5.6	•	•	•	•
PT50-1020	50	0.025	7.0	•	•	•	•
PT50-1320	50	0.020	11.0	•	•	•	•
PT75-900	75	0.060	3.9	•	•	•	•
PT75-980	75	0.040	5.2	•	•	•	•
PT75-1260	75	0.035	7.4	•	•	•	•
PT75-1550	75	0.025	10.6	•	•	•	•
PT100-1000	100	0.080	3.5	•	•	•	•
PT100-1100	100	0.050	5.1	•	•	•	•
PT100-1260	100	0.035	7.8	•	•	•	•
PT100-1550	100	0.028	10.3	•	•	•	•
PT150-1040	150	0.100	3.4	•	•	•	•
PT150-1250	150	0.060	5.7	•	•	•	•
PT150-1500	150	0.050	7.7	•	•	•	•
PT150-2050	150	0.040	12.3	•	•	•	•
PT250-1200	250	0.130	3.8	•	•	•	•
PT250-1500	250	0.080	6.1	•	•	•	•
PT250-1800	250	0.055	9.1	•	•	•	•
PT300-1200	300	0.150	3.3	•	•	•	•
PT300-1500	300	0.100	5.5	•	•	•	•
PT300-1750	300	0.075	7.3	•	•	•	•
PT400-1200	400	0.250	2.4	•	•	•	•
PT400-1500	400	0.180	4.7	•	•	•	•
PT400-1750	400	0.110	6.0	•	•	•	•
PT500-1450	500	0.220	3.4	•	•	•	•
PT500-1750	500	0.160	5.0	•	•	•	•
PT500-2000	500	0.090	8.0	•	•	•	•
PT750-1400	750	0.350	2.6	•	•	•	•
PT750-1700	750	0.280	3.7	•	•	•	•
PT750-2050	750	0.150	6.4	•	•	•	•
PT1000-1400	1000	0.620	1.8	•	•	•	•
PT1000-1750	1000	0.420	3.1	•	•	•	•
PT1000-2050	1000	0.200	5.9	•	•	•	•

Notes to Figure 5 (Page 100) The PT Toroid Series inductance is specified at AC and DC signal levels which have no significant effect on the permeability of the powdered iron toroidal core. Superimposed AC and DC voltages will change the permeability and therefore the inductance, under operating conditions. Typically, DC currents will reduce the inductance, while AC signals will increase the inductance up to a point, before beginning to decrease. Supporting information is provided, detailing the AC or DC effects upon each part. Saturation resulting from DC currents is specified with waveform having less than a 1% ripple content. When considering the AC waveform, both the frequency and voltage level must be taken into account. As an aid in defining what effect the alternating sine wave signal will have, the voltage/frequency factor curve can be used. To determine what change of inductance can be expected at a given voltage level and frequency, simply divide the sinusoidal RMS voltage by the frequency. The voltage is in volts and the frequency is in hertz. As an example, if using part number PT25-680 at a 1VRMS signal level, and a frequency of 25KHz, the voltage/frequency factor is calculated to be: 1VRMS/25,000Hz = 40 x 10⁻⁶. Referring to the graph, a 39% increase in inductance would be expected.

Notes to Figure 6 (Page 100) Typical saturation effects as a function of DC flowing through the part. Data is representative of a DC waveform with less than 1% ripple, and an AC waveform less than 10 gauss.

Note This information is intended to be used in assisting the designer in part selection. Each operating application may contain other variables which must be considered in part selection; such as temperature effects, waveform distortion, etc.... Delevan Sales/Engineering staff is available to provide information as needed to fit each application.

PT SERIES (continued)

Power Inductors

Power Toroids

ELECTRICAL PHYSICAL PARAMETERS

IND. (μH) ± 15% @ 1 kHz
DCR MAX. (OHMS)
RATED IDC (Amps)
A Max. Inches mm
B Max. Inches mm
C Nominal Inches mm
D Min. Inches mm
E Nominal Inches mm
F Nominal Inches mm

SERIES PT IRON CORE														
PT5-530	5	0.015	6.1	0.53	13.46	0.23	5.84	0.17	4.32	0.50	12.7	0.025	0.64	0.450
PT5-700	5	0.012	7.4	0.70	17.78	0.33	8.38	0.24	6.10	0.50	12.7	0.032	0.81	0.600
PT5-800	5	0.010	10.6	0.80	20.32	0.36	9.14	0.31	7.87	0.50	12.7	0.040	1.02	0.720
PT5-1000	5	0.008	12.8	1.00	25.40	0.40	10.16	0.34	8.64	0.50	12.7	0.051	1.30	0.950
PT10-530	10	0.020	4.9	0.53	13.46	0.23	5.84	0.17	4.32	0.50	12.7	0.025	0.64	0.450
PT10-680	10	0.015	6.8	0.68	17.27	0.33	8.38	0.24	6.10	0.50	12.7	0.032	0.81	0.600
PT10-820	10	0.010	9.3	0.82	20.83	0.37	9.40	0.29	7.37	0.50	12.7	0.040	1.02	0.720
PT10-990	10	0.008	13.2	0.99	25.15	0.40	10.16	0.34	8.64	0.50	12.7	0.051	1.30	0.950
PT25-680	25	0.035	4.4	0.68	17.27	0.37	9.40	0.29	7.37	0.50	12.7	0.025	0.64	0.580
PT25-800	25	0.025	6.6	0.80	20.32	0.35	8.89	0.28	7.11	0.50	12.7	0.032	0.81	0.700
PT25-900	25	0.020	7.0	0.90	22.86	0.40	10.16	0.30	7.62	0.50	12.7	0.040	1.02	0.820
PT25-1000	25	0.014	10.4	1.00	25.40	0.40	10.16	0.37	9.40	0.50	12.7	0.051	1.30	0.950
PT50-780	50	0.050	3.8	0.78	19.81	0.36	9.14	0.27	6.86	0.50	12.7	0.025	0.64	0.680
PT50-900	50	0.030	5.6	0.90	22.86	0.38	9.65	0.30	7.62	0.50	12.7	0.032	0.81	0.790
PT50-1020	50	0.025	7.0	1.02	25.91	0.62	15.75	0.43	10.92	0.50	12.7	0.040	1.02	0.920
PT50-1320	50	0.020	11.0	1.32	33.53	0.63	16.00	0.53	13.46	0.50	12.7	0.051	1.30	1.220
PT75-900	75	0.060	3.9	0.90	22.86	0.36	9.14	0.29	7.37	0.50	12.7	0.025	0.64	0.770
PT75-980	75	0.040	5.2	0.98	24.89	0.38	9.65	0.30	7.62	0.50	12.7	0.032	0.81	0.890
PT75-1260	75	0.035	7.4	1.26	32.00	0.60	15.24	0.49	12.45	0.50	12.7	0.040	1.02	1.200
PT75-1550	75	0.025	10.6	1.55	39.37	0.64	16.26	0.53	13.46	0.50	12.7	0.051	1.30	1.500
PT100-1000	100	0.080	3.5	1.00	25.40	0.36	9.14	0.29	7.37	0.50	12.7	0.025	0.64	0.880
PT100-1100	100	0.050	5.1	1.10	27.94	0.50	12.70	0.42	10.67	0.50	12.7	0.032	0.81	0.890
PT100-1260	100	0.035	7.8	1.26	32.00	0.60	15.24	0.49	12.45	0.50	12.7	0.040	1.02	1.200
PT100-1550	100	0.028	10.3	1.55	39.37	0.64	16.26	0.53	13.46	0.50	12.7	0.051	1.30	1.500
PT150-1040	150	0.100	3.4	1.04	26.42	0.50	12.70	0.41	10.41	0.50	12.7	0.025	0.64	0.880
PT150-1250	150	0.060	5.7	1.25	31.75	0.58	14.73	0.48	12.19	0.50	12.7	0.032	0.81	1.160
PT150-1500	150	0.050	7.7	1.50	38.10	0.62	15.75	0.50	12.70	0.50	12.7	0.040	1.02	1.420
PT150-2050	150	0.040	12.3	2.05	52.07	0.92	23.37	0.80	20.32	0.50	12.7	0.051	1.30	2.000
PT250-1200	250	0.130	3.8	1.20	30.48	0.55	13.97	0.49	12.45	0.50	12.7	0.025	0.64	1.200
PT250-1500	250	0.080	6.1	1.50	38.10	0.60	15.24	0.50	12.70	0.50	12.7	0.036	0.91	1.450
PT250-1800	250	0.055	9.1	1.80	45.72	0.77	19.56	0.69	17.53	0.50	12.7	0.051	1.30	1.750
PT300-1200	300	0.150	3.3	1.20	30.48	0.55	13.97	0.48	12.19	0.50	12.7	0.025	0.64	1.200
PT300-1500	300	0.100	5.5	1.50	38.10	0.60	15.24	0.51	12.95	0.50	12.7	0.032	0.81	1.400
PT300-1750	300	0.075	7.3	1.75	44.45	0.76	19.30	0.65	16.51	0.50	12.7	0.045	1.14	1.750
PT400-1200	400	0.250	2.4	1.20	30.48	0.55	13.97	0.48	12.19	0.50	12.7	0.020	0.51	1.150
PT400-1500	400	0.180	4.7	1.50	38.10	0.60	15.24	0.50	12.70	0.50	12.7	0.025	0.64	1.400
PT400-1750	400	0.110	6.0	1.75	44.45	0.78	19.81	0.70	17.78	0.50	12.7	0.040	1.02	1.750
PT500-1450	500	0.220	3.4	1.45	36.83	0.58	14.73	0.50	12.70	0.50	12.7	0.025	0.64	1.400
PT500-1750	500	0.160	5.0	1.75	44.45	0.75	19.05	0.62	15.75	0.50	12.7	0.036	0.91	1.700
PT500-2000	500	0.090	8.0	2.05	52.07	0.88	22.35	0.76	19.30	0.50	12.7	0.045	1.14	2.000
PT750-1400	750	0.350	2.6	1.40	35.56	0.55	13.97	0.48	12.19	0.50	12.7	0.020	0.51	1.400
PT750-1700	750	0.280	3.7	1.70	43.18	0.70	17.78	0.62	15.75	0.50	12.7	0.025	0.64	1.660
PT750-2050	750	0.150	6.4	2.05	52.07	0.85	21.59	0.78	19.81	0.50	12.7	0.036	0.91	2.000
PT1000-1400	1000	0.620	1.8	1.40	35.56	0.55	13.97	0.48	12.19	0.50	12.7	0.016	0.41	1.360
PT1000-1750	1000	0.420	3.1	1.75	44.45	0.70	17.78	0.62	15.75	0.50	12.7	0.025	0.64	1.660
PT1000-2050	1000	0.200	5.9	2.05	52.07	0.85	21.59	0.78	19.81	0.50	12.7	0.032	0.81	2.000

Note: Vertical configuration is standard; add suffix "HM" for horizontal mounting

FIGURE 1: STANDARD VERTICAL MOUNT





FIGURE 2: HORIZONTAL MOUNT



PT SERIES (continued)

Power Inductors

Power Toroids

PART NUMBER	IND. (μH) ± 15% @ 1 kHz	DCR MAX. (OHMS)	RATED IDC (Amps)	FIGURE#	PHYSICAL PARAMETERS									
					A Max.	B Max.	C Typical	D Typical	E Max.	F Typical				
					Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
SERIES PT VERTICAL MOUNT IRON CORE														
PT5-530-VM	5	0.015	6.1	3	0.580	14.73	0.340	8.64	0.220	5.59	0.025	0.63	0.640	16.26
PT5-700-VM	5	0.012	7.4	3	0.650	16.51	0.450	11.43	0.300	7.62	0.032	0.81	0.810	20.57
PT5-800-VM	5	0.010	10.6	3	0.830	21.08	0.450	11.43	0.300	7.62	0.040	1.02	0.910	23.11
PT10-530-VM	10	0.020	4.9	3	0.580	14.73	0.340	8.64	0.220	5.59	0.025	0.63	0.640	16.26
PT10-680-VM	10	0.015	6.8	3	0.650	16.51	0.450	11.43	0.300	7.62	0.032	0.81	0.790	20.07
PT10-820-VM	10	0.010	9.3	3	0.830	21.08	0.450	11.43	0.300	7.62	0.040	1.02	0.930	23.62
PT25-680-VM	25	0.035	4.4	3	0.650	16.51	0.450	11.43	0.300	7.62	0.025	0.63	0.790	20.07
PT25-800-VM	25	0.025	6.6	3	0.830	21.08	0.450	11.43	0.300	7.62	0.032	0.81	0.910	23.11
PT25-900-VM	25	0.020	7.0	3	0.950	24.13	0.600	15.24	0.450	11.43	0.040	1.02	1.010	25.65
PT50-780-VM	50	0.050	3.8	3	0.830	21.08	0.450	11.43	0.300	7.62	0.025	0.63	0.890	22.61
PT50-900-VM	50	0.030	5.6	3	0.830	21.08	0.450	11.43	0.300	7.62	0.032	0.81	1.110	28.19
PT50-1020-VM	50	0.025	7.0	3	1.250	31.75	0.700	17.78	0.500	12.70	0.040	1.02	1.130	28.70
PT75-900-VM	75	0.060	3.9	3	0.950	24.13	0.600	15.24	0.450	11.43	0.025	0.63	1.010	25.65
PT75-980-VM	75	0.040	5.2	3	0.950	24.13	0.600	15.24	0.450	11.43	0.032	0.81	1.090	27.69
PT75-1260-VM	75	0.035	7.4	3	1.250	31.75	0.700	17.78	0.500	12.70	0.040	1.02	1.390	35.31
PT100-1000-VM	100	0.080	3.5	3	0.950	24.13	0.600	15.24	0.450	11.43	0.025	0.63	1.130	28.70
PT100-1100-VM	100	0.050	5.1	3	0.950	24.13	0.600	15.24	0.450	11.43	0.032	0.81	1.230	31.24
PT100-1260-VM	100	0.035	7.8	3	1.250	31.75	0.700	17.78	0.500	12.70	0.040	1.02	1.390	35.31
PT150-1040-VM	150	0.100	3.4	3	0.950	24.13	0.600	15.24	0.450	11.43	0.025	0.63	1.170	29.72
PT150-1250-VM	150	0.060	5.7	3	1.250	31.75	0.700	17.78	0.500	12.70	0.032	0.81	1.380	35.05
PT150-1500-VM	150	0.050	7.7	4	1.500	38.10	0.800	20.32	0.600	15.24	0.050	1.27	1.630	41.40
PT250-1200-VM	250	0.130	3.8	3	1.250	31.75	0.700	17.78	0.500	12.70	0.025	0.63	1.330	33.78
PT250-1500-VM	250	0.080	6.1	4	1.500	38.10	0.800	20.32	0.600	15.24	0.050	1.27	1.630	41.40
PT300-1200-VM	300	0.150	3.3	3	1.250	31.75	0.700	17.78	0.500	12.70	0.025	0.63	1.330	33.78
PT300-1500-VM	300	0.100	5.5	4	1.500	38.10	0.800	20.32	0.600	15.24	0.050	1.27	1.630	41.40
PT400-1200-VM	400	0.250	2.4	3	1.250	31.75	0.700	17.78	0.500	12.70	0.020	0.51	1.330	33.78
PT400-1500-VM	400	0.180	4.7	4	1.500	38.10	0.800	20.32	0.600	15.24	0.050	1.27	1.630	41.40
PT400-1750-VM	400	0.110	6.0	4	1.750	44.45	0.900	22.86	0.700	17.78	0.050	1.27	1.880	47.75
PT500-1450-VM	500	0.220	3.4	4	1.450	36.83	0.800	20.32	0.600	15.24	0.050	1.27	1.580	40.13
PT500-1750-VM	500	0.160	5.0	4	1.750	44.45	0.900	22.86	0.700	17.78	0.050	1.27	1.880	47.75
PT750-1400-VM	750	0.350	2.6	4	1.400	35.56	0.800	20.32	0.600	15.24	0.050	1.27	1.530	38.86
PT750-1700-VM	750	0.280	3.7	4	1.700	43.18	0.900	22.86	0.700	17.78	0.050	1.27	1.830	46.48
PT750-2050-VM	750	0.150	6.4	4	2.050	52.07	0.900	22.86	0.700	17.78	0.050	1.27	2.180	55.37
PT1000-1400-VM	1000	0.620	1.8	4	1.400	35.56	0.800	20.32	0.600	15.24	0.050	1.27	1.530	38.86
PT1000-1750-VM	1000	0.420	3.1	4	1.750	44.45	0.900	22.86	0.700	17.78	0.050	1.27	1.980	50.29
PT1000-2050-VM	1000	0.200	5.9	4	2.050	52.07	0.900	22.86	0.700	17.78	0.050	1.27	2.180	55.37

FIGURE 3: 2-LEAD VERTICAL BASE MOUNT






FIGURE 4: 4-LEAD VERTICAL BASE MOUNT




Power Toroids - Horizontal or Vertical Mount



KEY TO FIGURE 5 CURVE NUMBERS Graphs apply to all mounting styles. For more detailed graphs, contact factory.

1) PT5-530	7) PT10-820	13) PT50-780	19) PT100-1100	25) PT100-1550	31) PT400-1200	37) PT500-1450	43) PT500-2000
2) PT10-530	8) PT10-990	14) PT50-900	20) PT50-1320	26) PT150-1250	32) PT300-1500	38) PT400-1750	44) PT1000-1750
3) PT5-700	9) PT25-680	15) PT75-900	21) PT150-1040	27) PT150-1500	33) PT400-1500	39) PT750-1400	45) PT750-2050
4) PT5-800	10) PT25-800	16) PT75-980	22) PT75-1260	28) PT250-1200	34) PT250-1800	40) PT500-1750	46) PT1000-2050
5) PT10-680	11) PT25-900	17) PT50-1020	23) PT100-1260	29) PT300-1200	35) PT150-2050	41) PT1000-1400	
6) PT5-1000	12) PT25-1000	18) PT100-1000	24) PT75-1550	30) PT250-1500	36) PT300-1750	42) PT750-1750	



For more detailed graphs, contact factory

SERIES

PTHFxxxxR
PTKMxxxxR
PTHF
PTKM



Toroidal Power Chokes



Actual Size

Horizontal or Vertical Mounting

Excellent electromagnetic shielding

Applications Use Series PTHF for high DC saturation applications; use Series PTKM for low AC core loss applications.

DC Resistance at 25°C

Rated Idc based upon 40°C maximum rise from 90°C ambient with 0 Arms

Self Leads Solder coated along entire length

Mounting Toroids can be provided in a vertical or horizontal mount style. Suffix Part Number with "H" for horizontal mount.

dl Incremental Current is the value indicated in the table that will cause an approximate percentage drop in inductance

Marking DELEVAN and part number.

Example: PTHF50R-121

DELEVAN PTHF50R-121

Physical Parameters on Next Page

*Complete part # must include series # PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com

PART NUMBER	INDUCTANCE (μH) @ 1 kHz ±10%	RATED IDC (AMPS)	ΔL 10% dl ADC	ΔL 20% dl ADC	DC RESISTANCE MAXIMUM (OHMS)	SRF MINIMUM (MHz)
SERIES PTHF HIGH SATURATION CORE						
PTHF10-50	10	7.36	6.0	8.7	0.010	35.0
PTHF25-50	25	5.20	3.6	5.3	0.020	10.0
PTHF50-50	50	3.93	2.0	3.1	0.035	7.0
PTHF75-50	75	3.47	1.6	2.5	0.045	5.0
PTHF100-50	100	3.14	1.5	2.2	0.055	4.0
PTHF150-50	150	2.33	1.2	1.8	0.100	2.0
PTHF200-50	200	1.97	1.0	1.6	0.140	1.7
PTHF250-50	250	1.84	0.9	1.4	0.160	1.5
PTHF330-50	330	1.69	0.8	1.2	0.190	1.0
PTHF10-121	10	8.27	9.0	14.0	0.010	20.0
PTHF25-121	25	6.34	7.0	10.5	0.017	8.0
PTHF50-121	50	4.77	3.9	6.0	0.030	4.0
PTHF75-121	75	3.90	3.9	5.8	0.045	3.0
PTHF100-121	100	3.24	3.4	4.7	0.065	2.0
PTHF150-121	150	2.68	3.3	4.8	0.095	1.5
PTHF250-121	250	2.07	2.2	3.2	0.160	1.0
PTHF10-59	10	14.50	15.0	20.0	0.008	20.0
PTHF25-59	25	9.80	11.0	16.0	0.011	8.0
PTHF50-59	50	6.90	8.3	12.0	0.022	4.0
PTHF75-59	75	5.90	6.7	9.1	0.030	3.0
PTHF100-59	100	4.90	6.5	8.2	0.044	2.0
PTHF150-59	150	4.50	4.2	6.0	0.052	1.0
PTHF250-59	250	3.50	4.0	5.6	0.088	1.0
PTHF500-59	500	2.60	2.7	3.8	0.160	0.8
PTHF750-59	750	2.10	1.8	2.7	0.240	0.6
PTHF25-894	25	12.80	13.5	20.0	0.008	8.0
PTHF50-894	50	9.90	10.8	15.2	0.016	4.0
PTHF75-894	75	8.00	8.0	12.0	0.023	3.0
PTHF100-894	100	8.00	7.1	10.6	0.023	2.0
PTHF150-894	150	6.50	6.0	9.0	0.035	1.0
PTHF250-894	250	5.00	4.6	6.8	0.060	1.0
PTHF500-894	500	3.40	3.1	4.6	0.131	0.8
PTHF750-894	750	3.00	2.7	4.0	0.160	0.6
PTHF1000-894	1000	2.40	2.3	3.5	0.235	0.4
SERIES PTKM FERROUS ALLOY CORE						
PTKM10-50	10	7.36	1.70	3.30	0.010	35.0
PTKM25-50	25	5.20	1.00	1.90	0.020	10.0
PTKM50-50	50	3.93	0.70	1.30	0.035	7.0
PTKM75-50	75	3.47	0.60	1.10	0.045	5.0
PTKM100-50	100	3.14	0.50	0.96	0.055	4.0
PTKM150-50	150	2.33	0.40	0.78	0.100	2.0
PTKM200-50	200	1.97	0.35	0.65	0.140	1.7
PTKM250-50	250	1.84	0.31	0.59	0.160	1.5
PTKM330-50	330	1.69	0.27	0.50	0.190	1.0
PTKM10-121	10	8.27	5.30	9.10	0.010	20.0
PTKM25-121	25	6.34	3.30	5.70	0.017	8.0
PTKM50-121	50	4.77	2.30	4.00	0.030	4.0
PTKM75-121	75	3.90	1.80	3.10	0.045	3.0
PTKM100-121	100	3.24	1.60	2.80	0.065	2.0
PTKM150-121	150	2.68	1.30	2.20	0.095	1.5
PTKM250-121	250	2.07	0.90	1.70	0.160	1.0
PTKM10-59	10	14.50	7.60	13.00	0.008	20.0
PTKM25-59	25	9.80	4.70	8.30	0.011	8.0
PTKM50-59	50	6.90	3.30	5.70	0.022	4.0
PTKM75-59	75	5.90	3.00	4.90	0.030	3.0
PTKM100-59	100	4.90	2.40	4.20	0.044	2.0
PTKM150-59	150	4.50	1.90	3.40	0.052	1.0
PTKM250-59	250	3.50	1.50	2.70	0.088	1.0
PTKM500-59	500	2.60	1.10	1.80	0.160	0.8
PTKM750-59	750	2.10	0.90	1.60	0.240	0.6
PTKM25-894	25	12.80	6.60	11.00	0.008	8.0
PTKM50-894	50	9.90	4.20	7.40	0.016	4.0
PTKM75-894	75	8.00	3.70	6.40	0.023	3.0
PTKM100-894	100	8.00	3.50	6.00	0.023	2.0
PTKM150-894	150	6.50	2.30	4.30	0.035	1.0
PTKM250-894	250	5.00	1.90	3.20	0.060	1.0
PTKM500-894	500	3.40	1.40	2.50	0.131	0.8
PTKM750-894	750	3.00	1.20	2.10	0.160	0.6
PTKM1000-894	1000	2.40	1.00	1.80	0.235	0.4

SERIES

PTHFxxxxR-VM
PTKMxxxxR-VM
PTHF-VM
PTKM-VM



Vertical Toroidal Power Chokes



Actual Size
(PT**25-894VM)

- **Excellent electromagnetic shielding** performance for commercial and industrial applications
- **Cost-effective** design
- **For higher saturation levels**
use Series PTHF-VM
- Current rating from 1.69 to 14.5 amps
- Inductance values from 10 μ H to 1000 μ H

Physical Parameters on Next Page

Notes

- 1) Rated current is based on a 35°C temperature rise at an ambient temperature of 90°C.
- 2) Incremental current is the approximate value that will cause a percentage drop in inductance as indicated in the table.

*Complete part # must include series # PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com

PART NUMBER	INDUCTANCE (μ H) @ 1 kHz $\pm$ 10%	RATED IDC (AMPS)	Δ L 10% dI ADC	Δ L 20% dI ADC	DC RESISTANCE MAXIMUM (OHMS)	SRF MINIMUM (MHz)
SERIES PTHF-VM HIGH SATURATION CORE						
PTHF10-50VM	10	7.36	6.00	8.70	0.010	35.0
PTHF25-50VM	25	5.20	3.60	5.30	0.020	10.0
PTHF50-50VM	50	3.93	2.00	3.10	0.035	4.0
PTHF75-50VM	75	3.47	1.60	2.50	0.045	3.5
PTHF100-50VM	100	3.14	1.50	2.20	0.055	2.5
PTHF150-50VM	150	2.33	1.20	1.80	0.100	1.5
PTHF200-50VM	200	1.97	1.00	1.60	0.140	1.3
PTHF250-50VM	250	1.84	0.90	1.40	0.160	1.0
PTHF330-50VM	330	1.69	0.80	1.20	0.190	0.8
PTHF10-121VM	10	8.27	9.00	14.00	0.010	20.0
PTHF25-121VM	25	6.34	7.00	10.50	0.017	6.5
PTHF50-121VM	50	4.77	3.90	6.00	0.030	3.5
PTHF75-121VM	75	3.90	3.90	5.80	0.045	2.5
PTHF100-121VM	100	3.24	3.40	4.70	0.065	2.0
PTHF150-121VM	150	2.68	3.30	4.80	0.095	1.5
PTHF250-121VM	250	2.07	2.20	3.20	0.160	1.0
PTHF10-59VM	10	14.50	15.00	20.00	0.008	10.0
PTHF25-59VM	25	9.80	11.00	16.00	0.011	8.0
PTHF50-59VM	50	6.90	8.30	12.00	0.022	3.5
PTHF75-59VM	75	5.90	6.70	9.10	0.030	2.5
PTHF100-59VM	100	4.90	6.50	8.20	0.044	2.0
PTHF150-59VM	150	4.50	4.20	6.00	0.052	1.0
PTHF250-59VM	250	3.50	4.00	5.60	0.088	0.9
PTHF500-59VM	500	2.60	2.70	3.80	0.160	0.7
PTHF750-59VM	750	2.10	1.80	2.70	0.240	0.5
PTHF25-894VM	25	12.80	13.50	20.00	0.012	8.0
PTHF50-894VM	50	9.90	10.80	15.20	0.016	4.0
PTHF75-894VM	75	8.00	8.00	12.00	0.023	2.5
PTHF100-894VM	100	8.00	7.10	10.60	0.023	2.0
PTHF150-894VM	150	6.50	6.00	9.00	0.035	1.0
PTHF250-894VM	250	5.00	4.60	6.80	0.060	0.9
PTHF500-894VM	500	3.40	3.10	4.60	0.131	0.7
PTHF750-894VM	750	3.00	2.70	4.00	0.160	0.6
PTHF1000-894VM	1000	2.40	2.30	3.50	0.235	0.4
SERIES PTKM-VM FERROUS ALLOY CORE						
PTKM10-50VM	10	7.36	1.70	3.30	0.010	35.0
PTKM25-50VM	25	5.20	1.00	1.90	0.020	10.0
PTKM50-50VM	50	3.93	0.70	1.30	0.035	4.0
PTKM75-50VM	75	3.47	0.60	1.10	0.045	3.5
PTKM100-50VM	100	3.14	0.50	0.96	0.055	2.5
PTKM150-50VM	150	2.33	0.40	0.78	0.100	1.5
PTKM200-50VM	200	1.97	0.35	0.65	0.140	1.3
PTKM250-50VM	250	1.84	0.31	0.59	0.160	1.0
PTKM330-50VM	330	1.69	0.27	0.50	0.190	0.8
PTKM10-121VM	10	8.27	5.30	9.10	0.010	20.0
PTKM25-121VM	25	6.34	3.30	5.70	0.017	6.5
PTKM50-121VM	50	4.77	2.30	4.00	0.030	3.5
PTKM75-121VM	75	3.90	1.80	3.10	0.045	2.5
PTKM100-121VM	100	3.24	1.60	2.80	0.065	2.0
PTKM150-121VM	150	2.68	1.30	2.20	0.095	1.5
PTKM250-121VM	250	2.07	0.90	1.70	0.160	1.0
PTKM10-59VM	10	14.50	7.60	13.00	0.008	10.0
PTKM25-59VM	25	9.80	4.70	8.30	0.011	8.0
PTKM50-59VM	50	6.90	3.30	5.70	0.022	3.5
PTKM75-59VM	75	5.90	3.00	4.90	0.030	2.5
PTKM100-59VM	100	4.90	2.40	4.20	0.044	2.0
PTKM150-59VM	150	4.50	1.90	3.40	0.052	1.0
PTKM250-59VM	250	3.50	1.50	2.70	0.088	0.9
PTKM500-59VM	500	2.60	1.10	1.80	0.160	0.7
PTKM750-59VM	750	2.10	0.90	1.60	0.240	0.5
PTKM25-894VM	25	12.80	6.60	11.00	0.012	8.0
PTKM50-894VM	50	9.90	4.20	7.40	0.016	4.0
PTKM75-894VM	75	8.00	3.70	6.40	0.023	2.5
PTKM100-894VM	100	8.00	3.50	6.00	0.023	2.0
PTKM150-894VM	150	6.50	2.30	4.30	0.035	1.0
PTKM250-894VM	250	5.00	1.90	3.20	0.060	0.9
PTKM500-894VM	500	3.40	1.40	2.50	0.131	0.7
PTKM750-894VM	750	3.00	1.20	2.10	0.160	0.6
PTKM1000-894VM	1000	2.40	1.00	1.80	0.235	0.4


SERIES

PTHFxxxxR & PTKMxxxxR
PTHF & PTKM


RoHS
Compliant

Traditional
First Quality

Toroidal Power Chokes – Horizontal or Vertical Mount



Vertical Configuration



Horizontal Configuration


PHYSICAL PARAMETERS

* **Nominal Dimensions** Allow up to 10% of nominal for maximum size

** **Part Number** Insert HF of KM for complete part number, and suffix "H" for horizontal mounting

Electrical Information on Preceding Page

PART NUMBER	A Nominal*		B Nominal*		C Typical		D Nominal*		E Nominal*		F Nominal*	
	Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
PT**10-50	0.625	15.88	0.300	7.62	0.250	6.35	0.500	12.70	0.036	0.91	0.600	15.24
PT**25-50	0.625	15.88	0.300	7.62	0.250	6.35	0.500	12.70	0.032	0.81	0.600	15.24
PT**50-50	0.625	15.87	0.300	7.62	0.250	6.35	0.500	12.70	0.028	0.71	0.600	15.24
PT**75-50	0.625	15.87	0.300	7.62	0.250	6.35	0.500	12.70	0.025	0.63	0.600	15.24
PT**100-50	0.625	15.87	0.300	7.62	0.250	6.35	0.500	12.70	0.025	0.63	0.600	15.24
PT**150-50	0.625	15.87	0.300	7.62	0.250	6.35	0.500	12.70	0.020	0.51	0.600	15.24
PT**200-50	0.625	15.87	0.300	7.62	0.250	6.35	0.500	12.70	0.018	0.46	0.600	15.24
PT**250-50	0.625	15.87	0.300	7.62	0.250	6.35	0.500	12.70	0.018	0.46	0.600	15.24
PT**330-50	0.625	15.87	0.300	7.62	0.250	6.35	0.500	12.70	0.018	0.46	0.600	15.24
PT**10-121	0.820	20.83	0.400	10.16	0.320	8.13	0.500	12.70	0.040	1.02	0.780	19.81
PT**25-121	0.820	20.83	0.400	10.16	0.320	8.13	0.500	12.70	0.040	1.02	0.780	19.81
PT**50-121	0.820	20.83	0.400	10.16	0.320	8.13	0.500	12.70	0.036	0.91	0.780	19.81
PT**75-121	0.820	20.83	0.400	10.16	0.320	8.13	0.500	12.70	0.032	0.81	0.780	19.81
PT**100-121	0.820	20.83	0.400	10.16	0.320	8.13	0.500	12.70	0.028	0.71	0.780	19.81
PT**150-121	0.850	21.59	0.400	10.16	0.320	8.13	0.500	12.70	0.025	0.63	0.780	19.81
PT**250-121	0.850	21.59	0.400	10.16	0.320	8.13	0.500	12.70	0.023	0.58	0.780	19.81
PT**10-59	1.100	27.94	0.475	12.06	0.370	9.40	0.500	12.70	0.051	1.30	1.050	26.67
PT**25-59	1.100	27.94	0.475	12.06	0.370	9.40	0.500	12.70	0.051	1.30	1.050	26.67
PT**50-59	1.100	27.94	0.475	12.06	0.370	9.40	0.500	12.70	0.045	1.14	1.050	26.67
PT**75-59	1.100	27.94	0.475	12.06	0.370	9.40	0.500	12.70	0.040	1.02	1.050	26.67
PT**100-59	1.100	27.94	0.475	12.06	0.370	9.40	0.500	12.70	0.036	0.91	1.050	26.67
PT**150-59	1.100	27.94	0.475	12.06	0.450	11.43	0.500	12.70	0.036	0.91	1.050	26.67
PT**250-59	1.150	29.21	0.475	12.06	0.450	11.43	0.500	12.70	0.032	0.81	1.050	26.67
PT**500-59	1.150	29.21	0.475	12.06	0.450	11.43	0.500	12.70	0.028	0.71	1.050	26.67
PT**750-59	1.150	29.21	0.475	12.06	0.450	11.43	0.500	12.70	0.025	0.63	1.050	26.67
PT**25-894	1.300	33.02	0.650	16.51	0.600	15.24	0.750	19.05	0.064	1.3	1.250	31.75
PT**50-894	1.300	33.02	0.650	16.51	0.600	15.24	0.750	19.05	0.051	1.30	1.250	31.75
PT**75-894	1.300	33.02	0.650	16.51	0.600	15.24	0.750	19.05	0.051	1.30	1.250	31.75
PT**100-894	1.300	33.02	0.650	16.51	0.600	15.24	0.750	19.05	0.051	1.30	1.250	31.75
PT**150-894	1.300	33.02	0.650	16.51	0.600	15.24	0.750	19.05	0.045	1.14	1.250	31.75
PT**250-894	1.300	33.02	0.650	16.51	0.600	15.24	0.750	19.05	0.040	1.02	1.250	31.75
PT**500-894	1.300	33.02	0.650	16.51	0.600	15.24	0.750	19.05	0.032	0.81	1.250	31.75
PT**750-894	1.300	33.02	0.650	16.51	0.600	15.24	0.750	19.05	0.032	0.81	1.250	31.75
PT**1000-894	1.300	33.02	0.650	16.51	0.600	15.24	0.750	19.05	0.028	0.71	1.250	31.75

SERIES**PTHFxxxxR-VM & PTKMxxxxR-VM
PTHF-VM & PTKM-VM**RoHS
CompliantTraditional
First Quality**Vertical Toroidal Power Chokes****Physical Parameters**

	Inches	Millimeters
F (Standoffs)	0.025	0.635
G (Lead length below standoff)	0.250 ± 0.062	6.35 ± 1.57

Other dimensions in table below

Electrical Information on Preceding Page

PART NUMBER	A Nominal		B Nominal		C Nominal		D Nominal		E Nominal	
	Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
PT**10-50VM	0.750	19.05	0.400	10.16	0.775	19.68	0.250	6.350	0.036	0.914
PT**25-50VM	0.750	19.05	0.400	10.16	0.775	19.68	0.250	6.350	0.032	0.813
PT**50-50VM	0.750	19.05	0.400	10.16	0.775	19.68	0.250	6.350	0.028	0.711
PT**75-50VM	0.750	19.05	0.400	10.16	0.775	19.68	0.250	6.350	0.025	0.635
PT**100-50VM	0.750	19.05	0.400	10.16	0.775	19.68	0.250	6.350	0.025	0.635
PT**150-50VM	0.750	19.05	0.400	10.16	0.775	19.68	0.250	6.350	0.020	0.508
PT**200-50VM	0.750	19.05	0.400	10.16	0.775	19.68	0.250	6.350	0.018	0.457
PT**250-50VM	0.750	19.05	0.400	10.16	0.775	19.68	0.250	6.350	0.018	0.457
PT**330-50VM	0.750	19.05	0.400	10.16	0.775	19.68	0.250	6.350	0.018	0.457
PT**10-121VM	0.800	20.32	0.500	12.70	0.950	24.13	0.350	8.890	0.040	1.016
PT**25-121VM	0.800	20.32	0.500	12.70	0.950	24.13	0.350	8.890	0.040	1.016
PT**50-121VM	0.800	20.32	0.500	12.70	0.950	24.13	0.350	8.890	0.036	0.914
PT**75-121VM	0.800	20.32	0.500	12.70	0.950	24.13	0.350	8.890	0.032	0.813
PT**100-121VM	0.800	20.32	0.500	12.70	0.975	24.76	0.350	8.890	0.028	0.711
PT**150-121VM	0.800	20.32	0.500	12.70	0.975	24.76	0.350	8.890	0.025	0.635
PT**250-121VM	0.800	20.32	0.500	12.70	0.975	24.76	0.350	8.890	0.023	0.584
PT**10-59VM	1.210	30.73	0.685	17.40	1.175	29.84	0.400	10.16	0.051	1.295
PT**25-59VM	1.210	30.73	0.685	17.40	1.175	29.84	0.400	10.16	0.051	1.295
PT**50-59VM	1.210	30.73	0.685	17.40	1.175	29.84	0.400	10.16	0.045	1.143
PT**75-59VM	1.210	30.73	0.685	17.40	1.175	29.84	0.400	10.16	0.040	1.016
PT**100-59VM	1.210	30.73	0.685	17.40	1.175	29.84	0.400	10.16	0.036	0.914
PT**150-59VM	1.210	30.73	0.685	17.40	1.175	29.84	0.400	10.16	0.036	0.914
PT**250-59VM	1.210	30.73	0.685	17.40	1.250	31.75	0.400	10.16	0.032	0.813
PT**500-59VM	1.210	30.73	0.685	17.40	1.250	31.75	0.400	10.16	0.028	0.711
PT**750-59VM	1.210	30.73	0.685	17.40	1.250	31.75	0.400	10.16	0.025	0.635
PT**25-894VM	1.450	36.83	0.825	20.95	1.400	35.56	0.600	15.24	0.051	1.295
PT**50-894VM	1.450	36.83	0.825	20.95	1.400	35.56	0.600	15.24	0.051	1.295
PT**75-894VM	1.450	36.83	0.825	20.95	1.400	35.56	0.600	15.24	0.051	1.295
PT**100-894VM	1.450	36.83	0.825	20.95	1.400	35.56	0.600	15.24	0.051	1.295
PT**150-894VM	1.450	36.83	0.825	20.95	1.400	35.56	0.600	15.24	0.045	1.143
PT**250-894VM	1.450	36.83	0.825	20.95	1.400	35.56	0.600	15.24	0.040	1.016
PT**500-894VM	1.450	36.83	0.825	20.95	1.475	37.46	0.600	15.24	0.032	0.813
PT**750-894VM	1.450	36.83	0.825	20.95	1.475	37.46	0.600	15.24	0.032	0.813
PT**1000-894VM	1.450	36.83	0.825	20.95	1.475	37.46	0.600	15.24	0.028	0.711

**Insert HF or KM for complete Part Number


*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

SERIES

EMI0603R, EMI0805R, EMI1206R,
EMI1210R, EMI1806R, EMI1812R

RoHS
Compliant



Actual Size (Max.)

Small size utilizing a monolithic ferrite structure which results in excellent magnetic shielding.

Operating Temperature Range -55°C to +125°C

Terminations Suitable for flow & reflow soldering application.

Current Rating The current at which the Impedance will change by a maximum of $\pm 25\%$.

Note † Test Frequency for EMI1206R-1500 = 50 MHz

*** Test Frequency for EMI1206R-2000 = 30 MHz

Additional values available - contact factory
for your application

*Complete part # must include series # PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com

DASH NUMBER*
IMPEDANCE @ 100 MHz
(OHMS) $\pm 25\%$
DC RESISTANCE
MAXIMUM (OHMS)
CURRENT RATING
MAXIMUM (mA)
Suppressors

SERIES EMI0603R			
-60	60	0.10	600
-68	68	0.10	600
-80	80	0.10	400
-120	120	0.15	400
-220	220	0.30	300
-300	300	0.35	300
-450	450	0.40	300
-600	600	0.45	200
-750	750	0.60	100
-1000	1000	0.60	100
SERIES EMI0805R			
-11	11	0.05	600
-40	40	0.05	600
-90	90	0.10	600
-120	120	0.15	500
-150	150	0.15	500
-220	220	0.22	500
-300	300	0.20	500
-400	400	0.30	500
-600	600	0.30	500
-1000	1000	0.35	300
-1500	1500	0.40	200
-2000	2000	0.50	200
SERIES EMI1206R			
-31	31	0.05	600
-50	50	0.10	600
-70	70	0.10	600
-90	90	0.15	500
-120	120	0.15	500
-150	150	0.15	500
-200	200	0.20	500
-300	300	0.20	500
-600	600	0.30	500
-800	800	0.30	200
-1000	1000	0.40	200
-1200	1200	0.40	200
-1500†	1500	0.50	200
-2000***	2000	0.50	200
SERIES EMI1210R			
-60	60	0.30	400
SERIES EMI1806R			
-80	80	0.10	400
-105	100	0.20	300
-150	150	0.30	200
SERIES EMI1812R			
-125	120	0.40	200


Physical Parameters and Packaging						
	EMI0603R	EMI0805R	EMI1206R	EMI1210R	EMI1806R	EMI1812R
Dimensions						
L - inches (mm)	0.063 $\pm$ 0.006 (1.6 $\pm$ 0.15)	0.079 $\pm$ 0.008 (2.0 $\pm$ 0.2)	0.126 $\pm$ 0.008 (3.2 $\pm$ 0.2)	0.126 $\pm$ 0.008 (3.2 $\pm$ 0.2)	0.177 $\pm$ 0.010 (4.5 $\pm$ 0.25)	0.177 $\pm$ 0.010 (4.5 $\pm$ 0.25)
W - inches (mm)	0.031 $\pm$ 0.006 (0.8 $\pm$ 0.15)	0.049 $\pm$ 0.008 (1.25 $\pm$ 0.2)	0.063 $\pm$ 0.008 (1.6 $\pm$ 0.2)	0.098 $\pm$ 0.008 (2.5 $\pm$ 0.2)	0.063 $\pm$ 0.008 (1.6 $\pm$ 0.2)	0.126 $\pm$ 0.010 (3.2 $\pm$ 0.25)
T - inches (mm)	0.031 $\pm$ 0.006 (0.8 $\pm$ 0.15)	0.035 $\pm$ 0.008 (0.9 $\pm$ 0.2)	0.043 $\pm$ 0.008 (1.1 $\pm$ 0.2)	0.051 $\pm$ 0.008 (1.3 $\pm$ 0.2)	0.063 $\pm$ 0.008 (1.6 $\pm$ 0.2)	0.059 $\pm$ 0.010 (1.5 $\pm$ 0.25)
A - inches (mm)	0.012 $\pm$ 0.008 (0.3 $\pm$ 0.20)	0.020 $\pm$ 0.012 (0.50 $\pm$ 0.300)	0.020 $\pm$ 0.012 (0.50 $\pm$ 0.300)	0.020 $\pm$ 0.012 (0.50 $\pm$ 0.300)	0.022 $\pm$ 0.016 (0.60 $\pm$ 0.400)	0.022 $\pm$ 0.016 (0.60 $\pm$ 0.400)
Packaging Tape & reel (12mm); max. pieces per reel as follows						
	4000	4000	3000	2000	2000	1000

SERIES**4221R -1, -2, -4
4221 -3**RoHS
CompliantTraditional
First Quality**Surface Mount Filter Bead**

DASH NUMBER*

IMPEDANCE (OHMS)
@ 25 MHz (MINIMUM)IMPEDANCE (OHMS)
@ 100 MHz ($\pm 20\%$)

Actual Size (Max.)

**SERIES 4221R / 4221**

-1	22	47
-2	45	95
-3	22	42
-4	43	85

*Complete part # must include series # PLUS the dash #


For surface finish information, refer to www.delevanfinishes.com**Operating Temperature Range** -55°C to $+125^{\circ}\text{C}$ **Current Rating** 5 Amps max. (35°C Rise, 90° Ambient)**Material** Ferrite bead with plated copper lead**Packaging** Tape & reel

Series 4221-1 and 4221-3 (12mm)

Series 4221-2 and 4221-4 (16mm)

7" reel, 500 pieces max.; 13" reel, 4000 pieces max.

	4221 - 1	4221 - 2	4221 - 3	4221 - 4
A in.	$0.197 + 0.011/-0.028$	$0.374 + 0.015/-0.028$	$0.217 + 0.011/-0.028$	$0.350 + 0.015/-0.028$
mm.	$(5.0 + 0.3/-0.7)$	$(9.5 + 0.4/-0.7)$	$(5.5 + 0.3/-0.7)$	$(8.9 + 0.4/-0.7)$
B in.	0.120 ± 0.006	0.120 ± 0.006	0.117 ± 0.006	0.187 ± 0.006
mm.	(3.05 ± 0.15)	(3.05 ± 0.15)	(2.97 ± 0.15)	(4.75 ± 0.15)
C in.	$0.120 + 0.007/-0.015$	$0.120 + 0.007/-0.015$	$0.138 + 0.007/-0.015$	$0.138 + 0.007/-0.015$
mm.	$(3.05 + 0.2/-0.4)$	$(3.05 + 0.2/-0.4)$	$(3.50 + 0.2/-0.4)$	$(3.50 + 0.2/-0.4)$
D in.	0.059 ± 0.025	0.059 ± 0.025	0.059 ± 0.025	0.059 ± 0.025
mm.	(1.50 ± 0.63)	(1.50 ± 0.63)	(1.50 ± 0.63)	(1.50 ± 0.63)
E in.	0.050 ± 0.003	0.050 ± 0.003	0.050 ± 0.003	0.073 ± 0.003
mm.	(1.25 ± 0.07)	(1.25 ± 0.07)	(1.25 ± 0.07)	(1.85 ± 0.07)




For more detailed graphs, contact factory

SERIES

4222R
4222



Surface Mount Common Mode Bead




Mechanical Configuration Ferrite bead with plated copper wire. Provides a common path for the magnetic flux generated by the current to and from the load. The resulting effect is zero magnetic flux in the core.

Physical Parameters

	Inches	Millimeters
A	0.335 ± 0.031	8.51 ± 0.79
B	0.220 ± 0.010	5.6 ± 0.25
C	0.112 ± 0.010	2.85 ± 0.25
D	0.050 ± 0.010	1.27 ± 0.25
E	0.045 ± 0.005	1.10 ± 0.122
F (Ref.)	0.10	2.54
V (Ref.)	0.177	4.5
W (Ref.)	0.295	7.5
X (Ref.)	0.071	1.8
Y (Ref.)	0.118	3.0
Z (Ref.)	0.100	2.54

Packaging Bulk only



Performance Withstands a breakdown voltage of 500 VDC


DCR 0.010 Ohms Max.

Current Rating at 90°C Ambient
35°C Rise, 5 Amps max.

Impedances are measured on the HP4191A Impedance Analyzer

Impedance vs. Frequency (Typical)

@ MHz	Ohms
1	6.0
10	26.
25	38.
50	45.
100	54.
300	80.




For more detailed graphs, contact factory

SERIES

**SMB2.5R
SMB2.5**

RoHS
Compliant
Traditional
First Quality

Surface Mount Shield Beads



Actual Size

Physical Parameters

	Inches	Millimeters
A	0.285 ± 0.010	7.2 ± 0.25
B	0.185 ± 0.015	4.7 ± 0.38
C	0.355 ± 0.020	9.02 ± 0.51
D	0.460 Max.	11.68 Max.
E	0.050 ± 0.005	1.27 ± 0.13
F	0.075 Min.	1.9 Min.

Operating Temperature Range -40°C to +125°C

Impedances are measured on the HP 4291A Impedance Analyzer

Material High resistivity ferrite material eliminates the need to insulate windings

Lead Wire Plated copper

Idc Max. Based on a 35° C rise from 90°C ambient


Parts are available in tape and reel packaging

Packaging Tape & reel (24mm): 13" reel, 700 pieces max.; 7" reel not available

DASH NUMBER*	MINIMUM IMPEDANCE (OHMS) 10 MHz	MINIMUM IMPEDANCE (OHMS) 10 MHz	MINIMUM IMPEDANCE (OHMS) 10 MHz	MINIMUM IMPEDANCE (OHMS) 10 MHz	Idc MAXIMUM (AMPS)	DCR MAXIMUM (OHMS)
-1	2 1/2	210	385	400	375	9.5
-2	2 1/2	N/A	490	635	650	9.5


*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com



Suggested Land Pattern Dimensions

	Inches	Millimeters
U	0.075	1.9
V	0.095	2.4
W	0.265	6.7
X	0.09	2.3
Y	0.19	4.8
Z	0.185	4.7




For more detailed graphs, contact factory

SERIES 4211R 4211



Axial Leaded Filter Bead



Impedance measured at indicated frequencies, utilizing an HP 4191A at 25°C

Lead Material capable of meeting MIL-STD-202, Method 208 solderability requirements

Packaging Tape & reel: 14" reel. Series 4211-1 to 4211-8 and 4211-12 to 4211-30, 4000 pieces max. Series 4211-9 to 4211-11, 1000 pieces max. 12" reel not available

Lead Length 1 Inch min.


DIMENSIONS (Inches)
DASH NUMBER*
DIAMETER ± .010
LEAD SIZE ± .002
LENGTH
TOLERANCE
IMPEDANCE (OHMS)
10 MHz
25 MHz
100 MHz
250 MHz

Suppressors

SERIES 4211 / 4211R FERRITE CORE								
-1	0.138	0.025	0.175	±.010		≥ 39	54 - 82	
-2	0.138	0.025	0.350	±.020		≥ 70	106 - 160	
-3	0.138	0.025	0.263	±.010		≥ 52	80 - 120	
-4	0.138	0.025	0.300	±.020		≥ 60	88 - 132	
-5	0.138	0.025	0.236	±.010		≥ 48	72 - 109	
-6	0.138	0.025	0.375	±.010		≥ 77	120 - 180	
-7	0.138	0.025	0.450	±.015		≥ 93	144 - 216	
-8	0.138	0.025	0.545	±.025		≥ 114	176 - 264	
-9	0.385	0.032	0.450	±.015		≥ 154	216 - 325	
-10	0.385	0.032	0.550	±.020		≥ 188	264 - 397	
-11	0.385	0.032	0.650	±.020		≥ 224	312 - 469	
-12	0.138	0.025	0.206	±.010		≥ 43	66 - 98	
-13	0.138	0.025	0.175	±.010			50 min.	72 - 108
-14	0.138	0.025	0.350	±.020			105 min.	134 - 202
-15	0.138	0.025	0.263	±.010			78 min.	100 - 150
-16	0.138	0.025	0.300	±.020			90 min.	115 - 173
-17	0.138	0.025	0.236	±.010			70 min.	90 - 136
-18	0.138	0.025	0.375	±.010			112 min.	144 - 216
-19	0.138	0.025	0.450	±.015			135 min.	170 - 255
-20	0.138	0.025	0.545	±.025			163 min.	206 - 310
-21	0.138	0.025	0.206	±.010			61 min.	80 - 120
-22	0.138	0.025	0.175	±.010	≥38	49-73		
-23	0.138	0.025	0.350	±.020	≥75	92-138		
-24	0.138	0.025	0.263	±.010	≥56	69-103		
-25	0.138	0.025	0.300	±.020	≥64	79-118		
-26	0.138	0.025	0.236	±.010	≥50	62-93		
-27	0.138	0.025	0.375	±.025	≥88	108-162		
-28	0.138	0.025	0.450	±.015	≥100	124-187		
-29	0.138	0.025	0.545	±.025	≥121	152-228		
-30	0.138	0.025	0.206	±.010	≥44	54-82		

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com




For more detailed graphs, contact factory

SERIES

4212R
4212

RoHS
Compliant
Traditional
First Quality

Wound Beads



MINIMUM IMPEDANCE

DASH NUMBER*

FIGURE

TURNS

10 MHz

50 MHz

100 MHz

150 MHz

200 MHz

220 MHz

SERIES 4212R / 4212								
-1	1-3	2 1/2	—	—	750	700	—	400
-2	1-3	2 1/2	325	—	575	525	—	—
-3	1-1	1 1/2	—	325	425	—	400	—
-4	1-1	1 1/2	170	320	375	—	—	—
-5	1-2	2	—	525	600	—	600	—
-6	1-2	2	240	520	480	—	—	—
-7	1-4	3	—	950	900	—	600	—
-8	1-4	3	400	800	550	—	—	—

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

Physical Parameters

	Inches	Millimeters
Length	0.374 to 0.414	9.50 to 10.51
Diameter	0.216 to 0.256	5.48 to 6.35
Lead Size		
AWG #24 TCW	0.0185 to 0.0215	0.47 to 0.55
A	0.12 Max.	3.05 Max.
B	1.10 Min.	28.0 Min.


Impedances measured on HP 4191A Impedance Analyzer.

High resistivity ferrite material eliminates the need to insulate windings.

Lead Wire Plated copper

Packaging Bulk only

For more detailed graphs, contact factory




SERIES

4214R 4214



Wound Beads



MINIMUM IMPEDANCE								Suppressors
DASH NUMBER*	FIGURE	TURNS	10 MHz	50 MHz	100 MHz	150 MHz	200 MHz	
SERIES 4214R / 4214								
-2	1-5	2 1/2 x2	370	590	450	350	280	
-4	1-6	4 1/2	700	1100	650	350	270	

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

Wide Band Chokes 10 hole ferrite slugs, made in API-2 Material, with 2 x 2.5 or 4.5 turns of tinned copper wire.

Applications Interference suppression

Physical Parameters

	Inches	Millimeters
Length	0.388 to 0.402	9.98 to 10.02
Diameter	0.388 to 0.402	9.98 to 10.02
Lead Size		
AWG #24 TCW	0.0185 to 0.0215	0.47 to 0.55
A	0.14 Max.	3.55 Max.
B	1.10 Min.	28.0 Min.


Impedances measured on HP 4191A Impedance Analyzer.

High resistivity ferrite material eliminates the need to insulate windings.

Lead Wire Plated copper

Packaging Bulk only


For more detailed graphs, contact factory



BF SERIES



Split Ferrite Suppressors for Round Cables




Electronic cables and wires, by virtue of their length-to-width ratios, are perfect natural antennas. In the presence of high speed microprocessor signals, cables will conduct, radiate and/or receive unwanted high frequency interfering signals. Radio interference sources usually radiate their RFI power at frequencies above 30 MHz by way of the main cabling, which acts as an antenna. Control of radio interference can be assured by proper placement of an insertion loss device, such as a ferrite suppressor. Any device used to block an RFI signal between its source and a receiver is an electromagnetic interference (EMI) shield. The measure of this ability to attenuate RFI is shielding effectiveness, "SE", which is expressed in decibels, "dB", the ratio of field strength on one side of the shield to the other side.

One of the most versatile and cost effective shielding methods that can be used today is the API Delevan bisected ferrite cable snap assembly. The bisected styling, or familiar clamshell enclosure design offers the ultimate in adaptability. The RF absorbing material interacts directly with unwanted high frequency energy and dissipates it effectively while allowing data signals to pass unimpeded.

Bisected ferrites have a concentrated, homogeneous magnetic structure with high permeability. These are consistently stable at +20°C to +60°C and provide RF suppression without eddy current losses.

AIR GAP EFFECT


The air gap in bisected ferrites actually extends current carrying capabilities with only an extremely small reduction in impedance versus solid ferrites of the same size. The gap is magnetically insignificant while it is electrically significant as a discontinuation, thereby accommodating more current.



POSITION OF SUPPRESSOR The suppressor should normally be located close to the cable termination where it exits the enclosure. Where a cable connects two enclosures containing RF sources, a suppressor on each end may be required. For circuits within an enclosure, a position close to the RF is best. However, other locations along the circuit may work as well.

Material and U.L. Data API-1 Material, see characteristics and information in the Technical Notes Section of our website, www.delevan.com.

Continued on next page



BF SERIES

RoHS
Compliant

Suppressors for Round Cables

DIMENSIONS
Inches ± 0.04 ; mm ± 1.0

IMPED-
ANCE
(OHMS)*

25 MHz

100 MHz

Suppressors

PART NUMBER

BODY TYPE
UNITS






A

B

C

D

L



SERIES BF - FOR ROUND CABLES

PART NUMBER	UNITS	A	B	C	D	L	25 MHz	100 MHz
BF2930	in. mm	A 29.6	1.16 30.5	1.20 30.5	0.51 13.0	1.30 33.0	—	155 257
BF2223	in. mm	A 22.3	0.87 22.3	0.91 23.3	0.39 10.0	1.28 32.6	—	136 250
BF1719	in. mm	A 17.8	0.70 17.8	0.76 19.5	0.25 6.5	1.28 32.5	—	171 325
BF1835	in. mm	B 18.0	0.70 18.0	0.77 19.7	0.35 9.0	1.37 35.0	—	112 172
BF1125-5	in. mm	B 11.7	0.46 11.7	0.51 13.0	0.19 5.0	0.98 25.0	—	96 154
BF1125-3	in. mm	B 11.7	0.46 11.7	0.51 13.0	0.13 3.5	0.98 25.0	—	139 191
BF1429	in. mm	C 14.5	0.57 14.5	0.61 15.7	0.22 5.6	1.14 29.0	—	85 157
BF1225	in. mm	C 12.8	0.50 12.8	0.57 14.7	0.15 4.0	0.98 25.0	—	82 146
BF3024	in. mm	D 30.5	1.20 30.5	—	0.45 11.4	0.69 17.7	0.94 24.0	51 103
BF2125	in. mm	D 21.5	0.84 21.5	—	0.32 8.15	0.77 19.7	1.01 25.8	50 107
BF2123	in. mm	D 21.5	0.84 21.5	—	0.32 8.15	0.66 16.8	0.90 23.0	42 94
BF1835-9	in. mm	E 18.6	0.73 18.6	—	0.35 9.0	1.22 31.0	1.38 35.2	126 174
BF3121	in. mm	D 31.5	1.24 31.5	—	0.59 15.0	0.60 15.2	0.84 21.5	41 95

Physical Parameters

Material and U.L. Data API-1 Material, see characteristics and information in the Technical Notes Section.

* **Note** Impedance is typical, based on 1/2 turn (4.0") 18 AWG wire. Impedance measurement using HP4191A.


Color Black; Special colors Available for bases on a non-cancellable, non returnable basis C = Cream;
W = White; Gr = Grey

U.L. Recognized

All plastic and adhesive components use U.L. Recognized materials with Flammability Ratings of UL94V-0, UL-510 or UL-746C


SEE Z vs. f GRAPHS ON NEXT PAGE

Split Ferrite Suppressors for Round Cables



Additional Information on Preceding Pages

Note Impedance is typical, based on 1/2 turn (4.0") 18 AWG wire.
Impedance measurement using HP4191A

CF SERIES**Cylindrical EMI Suppression Ferrites**

API's Cylindrical EMI Suppression ferrites provide a cost effective means of reducing common and differential mode EMI. Used to suppress common mode EMI on the internal and external cable assemblies of electronic equipment.

Select a ferrite with an inner diameter most closely matching the outer diameter of the wires to be filtered.

Features

- Wide range of sizes with inner diameters from 1.5 mm (0.059 inches) to 23 mm (0.905 inches)
- Precision formed smooth surfaces prevent damage to wire insulation
- Available in API-1 and API-2 material.
- Custom designs available

Applications

- Internal and external computer data and power cables.


****Note – Impedance Testing** Impedance is typical, measurement using HP4191A. For CF1-4*1.5*10 through CF2-4.6*1.85*6, based on 1/2 turn (4.0") 32 AWG wire. For CF1-7.35*5.1*10 and above, based on 1/2 turn (4.0") 19 AWG wire.

PART NUMBER	IMPEDANCE**			DIMENSION A		DIMENSION B		DIMENSION C	
	@ 25 MHz (Min.)	@ 100 MHz (Typ.)	@ 300 MHz (Typ.)	INCHES	mm	INCHES	mm	INCHES	mm
CF1-4*1.5*10	50	135	300	0.157±.007	4.0±0.2	0.059±.005	1.5±0.15	0.393±.015	10.0±0.4
CF2-4*1.5*10	55	116	269	0.157±.007	4.0±0.2	0.059±.005	1.5±0.15	0.393±.015	10.0±0.4
CF1-4*2*10	40	102	282	0.157±.007	4.0±0.2	0.078±.007	2.0±0.2	0.393±.015	10.0±0.4
CF2-4*2*10	40	86	255	0.157±.007	4.0±0.2	0.078±.007	2.0±0.2	0.393±.015	10.0±0.4
CF1-4.6*1.85*6	35	89	261	0.181±.007	4.6±0.2	0.072±.007	1.85±0.2	0.236±.011	6.0±0.3
CF2-4.6*1.85*6	35	77	237	0.181±.007	4.6±0.2	0.072±.007	1.85±0.2	0.236±.011	6.0±0.3
CF1-7.35*5.1*10	23	68	217	0.289±.011	7.35±0.3	0.200±.007	5.1±0.2	0.393±.015	10.0±0.4
CF2-7.35*5.1*10	23	63	214	0.289±.011	7.35±0.3	0.200±.007	5.1±0.2	0.393±.015	10.0±0.4
CF1-9.5*4.8*20	70	171	263	0.374±.011	9.5±0.3	0.188±.007	4.8±0.2	0.787±.023	20.0±0.6
CF2-9.5*4.8*20	80	142	251	0.374±.011	9.5±0.3	0.188±.007	4.8±0.2	0.787±.023	20.0±0.6
CF1-10.5*5.5*20	65	161	273	0.413±.015	10.5±0.4	0.216±.007	5.5±0.2	0.787±.023	20.0±0.6
CF2-10.5*5.5*20	70	134	261	0.413±.015	10.5±0.4	0.216±.007	5.5±0.2	0.787±.023	20.0±0.6
CF1-12*7.3*15	40	107	273	0.472±.019	12.0±0.5	0.287±.011	7.3±0.3	0.590±.019	15.0±0.5
CF2-12*7.3*15	40	89	242	0.472±.019	12.0±0.5	0.287±.011	7.3±0.3	0.590±.019	15.0±0.5
CF1-14.2*6.35*28.5	115	280	302	0.559±.019	14.2±0.5	0.250±.011	6.35±0.3	1.122±.031	28.5±0.8
CF2-14.2*6.35*28.5	125	230	210	0.559±.019	14.2±0.5	0.250±.011	6.35±0.3	1.122±.031	28.5±0.8
CF1-16*9*17	50	130	281	0.629±.019	16.0±0.5	0.354±.011	9.0±0.3	0.669±.023	17.0±0.6
CF2-16*9*17	55	109	257	0.629±.019	16.0±0.5	0.354±.011	9.0±0.3	0.669±.023	17.0±0.6
CF1-17.5*9.5*28.5	95	217	310	0.688±.023	17.5±0.6	0.374±.011	9.5±0.3	1.122±.031	28.5±0.8
CF2-17.5*9.5*28.5	95	172	296	0.688±.023	17.5±0.6	0.374±.011	9.5±0.3	1.122±.031	28.5±0.8
CF1-21*13.2*21	55	136	309	0.826±.023	21.0±0.6	0.519±.019	13.2±0.5	0.826±.023	21.0±0.6
CF2-21*13.2*21	55	115	305	0.826±.023	21.0±0.6	0.519±.019	13.2±0.5	0.826±.023	21.0±0.6
CF1-26*13*28.5	100	235	325	1.023±.027	26.0±0.7	0.511±.019	13.0±0.5	1.122±.031	28.5±0.8
CF2-26*13*28.5	110	198	316	1.023±.027	26.0±0.7	0.511±.019	13.0±0.5	1.122±.031	28.5±0.8
CF1-28*15.6*7.5	28	85	313	1.102±.031	28.0±0.8	0.614±.019	15.6±0.5	0.295±.011	7.50±0.3
CF2-28*15.6*7.5	28	76	286	1.102±.031	28.0±0.8	0.614±.019	15.6±0.5	0.295±.011	7.50±0.3
CF1-31*19*10	30	91	232	1.220±.031	31.0±0.8	0.748±.023	19.0±0.6	0.393±.015	10.0±0.4
CF2-31*19*10	30	83	320	1.220±.031	31.0±0.8	0.748±.023	19.0±0.6	0.393±.015	10.0±0.4
CF1-36*23*15	40	113	384	1.417±.031	36.0±0.8	0.905±.023	23.0±0.6	0.590±.019	15.0±0.5
CF2-36*23*15	40	101	369	1.417±.031	36.0±0.8	0.905±.023	23.0±0.6	0.590±.019	15.0±0.5

CF SERIES

RoHS
Compliant

Cylindrical EMI Suppression Ferrites





For more detailed graphs, contact factory

FFAM SERIES

RoHS
Compliant

Flexible Ferrite Absorbent Material



Wide Variety of Uses

Case 1 To suppress noise generated between circuit boards, apply between boards.

Case 2 To suppress noise generated by casing, apply directly to casing.

Case 3 To suppress unwanted radiation of noises from LSI, IC and cables. For LSI & IC, apply directly to top surface (Caution - thermal conductivity). For flat cables, apply directly. For round cables, wrap around and apply heatshrink material.

Features

- Provides effective EMI suppression in a wide frequency range (10 MHz to 3 GHz)
- Effective in preventing resonance and suppressing coupling
- Ultra thin (0.25mm through 2.5mm)
- High electrical resistance (10^6 to 10^8 Ohms)
- Non-conductive adhesive backing (UL Recognized) available on one or both sides
- Easy and fast to process
- Extremely flexible

Applications

- Notebook and personal computers, workstations
- Peripheral devices for computers
- Anechoic chambers (irregular surface)
- LNB's for satellite systems
- Wireless equipment
- Mobile communications equipment
- Mobile phones
- Base stations
- Consumer electronics
- Gasketing
- High speed clocks

Ordering Note (Part Numbering Callout)


FFAM 06 3*3 T1

Optional Adhesive Backing (1 = single-sided -or- 2 = double-sided)

Sheet Size (in mm - 3*3 = 300mm x 300mm square)

Material Thickness (in mm - decimal point to the right of 1st character is assumed)

Series Designation - Flexible ferrite absorbent material



IMPEDANCE vs. FREQUENCY TABLE						
FREQ.	FFAM025	FFAM06	FFAM10	FFAM15	FFAM20	FFAM25
1	0.52	0.57	0.57	0.59	0.59	0.60
10	5.3	5.3	6	6	6	0.60
20	12	12	12	12	12	12
30	17	17	17	17	17	18
40	23	23	23	23	23	24
50	26	28	29	29	29	30
60	35	35	35	35	35	36
70	41	41	41	41	42	43
80	47	47	47	48	48	49
90	54	54	54	54	55	56
100	55	58	60	61	62	63
200	135	144	150	154	155	159
300	303	349	370	395	396	412

Impedance Measurement using HP4191A

Physical Parameters

Available Sizes

Inches	Millimeters
3.93 x 3.93	100 x 100
7.87 x 7.87	200 x 200
11.81 x 11.81	300 x 300
15.75 x 15.75	400 x 400

Thicknesses available

(with MH13008 UL Recognized tape)

	Inches	Millimeters
FFAM025	0.009	0.25
FFAM06	0.024	0.6
FFAM10	0.039	1.0
FFAM15	0.059	1.5
FFAM20	0.079	2.0
FFAM25	0.098	2.5


Operating Temperature Range

-55°C to +125°C

FFAT SERIES



Flexible Ferrite Absorbent Tubing



Cable Reference Table

Cable	O.D.
Jacket	
RG-8A/U	0.405
RG-9B/U	0.420
RG-55	0.176
RG-58	0.150
RG-58A	0.195
RG-59	0.191
RG-62	0.191
RG-62A	0.242
RG-71	0.208
RG-140	0.176
RG-141	0.146
RG-141A	0.190
RG-142	0.171
RG-174	0.080
RG-178	0.054
RG-179	0.084
RG-179B/U	0.100
RG-180	0.124
RG-187	0.084
RG-187A/U	0.110
RG-188	0.081
RG-188A/U	0.110
RG-195	0.124
RG-196	0.054
RG-210/U	0.242
RG-213/U	0.405
RG-214/U	0.425
RG-223	0.176
RG-303	0.146
RG-316	0.081
RG-316 DS	0.102

Information compliments of
MegaPhase, 201-D North
First Street, Stroudsburg PA
18360

Features

- Provides effective EMI Suppression in a wide Frequency Range (10MHz to 3GHz)
- High electrical resistance (10^6 to 10^8)
- Easy and fast to process
- Extremely flexible
- Six sizes to choose from
- Can be incorporated into the over-molding process on cable assemblies
- Eliminates the task of soldering braid
- Effectively eliminates EMI and RFI problems on internal and external power, data and signal lines


Manufactured length 39.37 inches $\pm$ 0.50; 1 meter $\pm$ 12.7 mm

Operating Temperature Range -55°C to +125°C

***Note – Impedance Testing** Impedance is typical, based on (10.0") 19 AWG wire, measurement using HP4191A.



Physical Parameters – Sizes available

Part Number		FFAT-32	FFAT-54	FFAT-65	FFAT-96	FFAT-117	FFAT-1410
Outside Diameter	Inches	0.116	0.196	0.255	0.354	0.43	.55
	Millimeters	2.9	5	6.5	9	11	14
Inside Diameter	Inches	0.072	0.157	0.196	0.236	0.275	.393
	Millimeters	1.8	4	5	6	7	10



For more detailed graphs, contact factory

TABLE 1: Typical Impedance (Ohms) vs. Frequency Sample piece tested 4.0" long						
	10 MHz	30 MHz	50 MHz	100 MHz	200 MHz	300 MHz
FFAT-32	11	34	58	140	579	980
FFAT-54	11	34	58	138	583	1004
FFAT-65	11	34	58	132	587	1023
FFAT-96	11	35	59	134	619	921
FFAT-117	12	35	60	137	656	874
FFAT-1410	12	31	64	149	790	570

SERIES**CM6149R**
CM6149**Surface Mount**
Low Profile CM Choke**SCHEMATIC**

Actual Size

Mechanical Configuration A flat top surface mount case with excellent coplanarity of terminals.

Physical Parameters

	Inches	Millimeters
A	0.212 ± 0.010	5.38 ± 0.25
B	0.285 ± 0.010	7.24 ± 0.25
C	0.060 ± 0.010	1.52 ± 0.25
D	0.250 ± 0.010	6.35 ± 0.25
E	0.200 ± 0.010	5.08 ± 0.25
F	0.025 ± 0.010	0.64 ± 0.25
G	0.40 (Ref. only)	1.02 (Ref. only)

Electrical Configuration

- 1) Inductance and DCR in table is for either L1 or L2.
- 2) Leakage Inductance tested at L1 with L2 shorted or at L2 with L1 shorted.
- 3) Windings balanced within 2%
- 4) Inductance tested @ 10 kHz

Operating Temperature Range -55°C to +105°C

Electrical Characteristics Measured at +25°C

Rated RMS Current Based upon 40°C temperaturerise from 25°C ambient.

Maximum Power Dissipation at 25°C 0.200 Watts


Inductance Tolerance Units are supplied to the tolerance indicated in the table.

Dielectric Withstanding Voltage 500 V RMS, 60Hz

DASH NUMBER*	L1 or L2 INDUCTANCE ±35% / ±25% (μH)	DC RESISTANCE MAXIMUM (OHMS)	RATED RMS CURRENT (AMPS) MAXIMUM	LEAKAGE INDUCTANCE TYPICAL (μH)
SERIES CM6149 FERRITE CORE				
-253	25	0.010	3.0	0.20
-473	47	0.015	2.5	0.30
-683	68	0.020	2.0	0.40
-104	100	0.030	1.6	0.50
-154	150	0.040	1.3	0.70
-224	220	0.060	1.0	1.10
-334	330	0.090	0.75	1.50
-474	470	0.125	0.60	1.70
-684	680	0.170	0.50	2.00
-105	1000	0.250	0.40	2.80
-125	1200	0.350	0.30	3.50
-155	1500	0.500	0.24	4.30
-225	2200	0.750	0.18	6.00

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com



Marking DELEVAN; CM6149, inductance with units. Note: An R after CM6149 indicates a RoHS component. A white dot indicates the location of pin 1.

Example: CM6149-154

DELEVAN
CM6149
150 uH

Packaging Tape & reel (16mm):
13" reel, 800 pieces max.; 7" reel not available

Weight (Grams) 0.5 (Ref.)

SERIES

CM1011R CM1011



Horizontal PC Mount
Epoxy Potted Common Mode Chokes

DASH NUMBER*


L (μ H) L1 or L2
@ 1 kHz $\pm 25\%$

DC RESISTANCE
MAXIMUM (OHMS)


CURRENT RATING
MAXIMUM (AMPS)

LEAKAGE INDUCTANCE
MAXIMUM (μ H)

Transformers



Actual Size



SERIES CM1011 FERRITE CORE

-104	100	0.004	12	6
-254	250	0.006	10	9
-504	500	0.008	8.6	12
-754	750	0.013	6.7	15
-105	1000	0.018	5.7	19
-175	1700	0.060	3.1	26
-255	2500	0.073	2.8	32
-335	3300	0.125	2.2	51
-505	5000	0.150	2.0	72
-755	7500	0.300	1.4	94
-106	10000	0.390	1.2	103

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

Marking DELEVAN; part number; inductance with units.

Example: CM1011-104

DELEVAN

CM6594-104

100uH

Packaging Bulk only

Weight (Grams) 25.0 (Ref.)

Physical Parameters

	Inches	Millimeters
A	1.10 $\pm$ 0.03	27.9 $\pm$ 0.76
B	1.10 $\pm$ 0.03	27.9 $\pm$ 0.76
C	0.70 $\pm$ 0.03	17.8 $\pm$ 0.76
D	1.00 $\pm$ 0.03	25.4 $\pm$ 0.76
E	0.600 $\pm$ 0.03	15.2 $\pm$ 0.76
F	0.200 Min.	5.08 Min.
G	0.075 (Ref. only)	1.91 (Ref. only)
H	0.032 $\pm$ 0.004	0.81 $\pm$ 0.10

Operating Temperature Range -55°C to +125°C

Current Rating at 85°C Ambient 40°C Rise

Mechanical Configuration Epoxy potted winding assembly. Case is high-temperature DAP.

Notes

- 1) Inductance in table is for either L1 or L2.
- 2) Leakage Inductance tested at L1 with L2 shorted or at L2 with L1 shorted.
- 3) Windings balanced within 2%



SERIES**CM6296R**
CM6296**Common Mode**
Choke/Isolation Transformer

DASH NUMBER*

L1 or L2 INDUCTANCE
±25% (μH)DC RESISTANCE
MAXIMUM (OHMS)RATED RMS CURRENT
(AMPS) MAXIMUMLEAKAGE INDUCTANCE
TYPICAL (μH)**Transformers****SERIES CM6296 FERRITE CORE**

-253	25	0.014	10.0	0.7
-503	50	0.014	10.0	0.8
-104	100	0.016	9.5	1.4
-154	150	0.016	9.5	1.8
-204	200	0.016	8.5	2.2
-304	300	0.020	7.5	3.3
-454	450	0.024	6.5	4.6
-654	650	0.030	5.5	6.2
-105	1000	0.050	3.5	9.3
-155	1500	0.090	2.5	14.5
-255	2500	0.162	2.2	21.8

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

Actual Size

Physical Parameters


	Inches	Millimeters
A	1.058 ± 0.010	26.87 ± 0.25
B	0.870 ± 0.010	22.10 ± 0.25
C	0.210 Typ.	5.33 Typ.
D	0.200 Typ.	5.08 Typ.
E	0.430 Max.	10.74 Max.

Mechanical Configuration Flat top surface mount case with excellent coplanarity of terminals**Operating Temperature** -55°C to +125°C**Configuration** Two inductors per unit; internal terminals: #1 (start)-#2 (finish) & #4 (start) -#3 (finish)**Electrical Configuration**

- 1) Inductance and DCR in table is for either L1 or L2
- 2) Leakage Inductance tested at L1 with L2 shorted or at L2 with L1 shorted.
- 3) Windings balanced within 2%
- 4) Inductance tested @ 1.0kHz

Rated RMS Current Per Winding Based Upon 20°C temperature rise from 25°C ambient**Maximum Power Dissipation at 25°C** 2.5 Watts**Dielectric Withstanding Voltage**

500 V RMS, 60Hz

LAND PATTERN DIMENSIONS**Marking** DELEVAN; part number, inductance with units. A white dot indicates the location of pin 1.


Example: CM6296R-155

DELEVAN


CM6296R-155

1500 uH

Packaging Bulk only**Weight (Grams)** 9.0 (Ref.)

SERIES**CM6350R**
CM6350**Surface Mount
Common Mode Choke**

Dot, Terminal #1

SCHEMATIC

Actual Size

Mechanical Configuration A flat top surface mount case with excellent coplanarity of terminals.

Physical Parameters

	Inches	Millimeters
A	0.285 ± 0.010	7.24 ± 0.25
B	0.360 ± 0.010	9.14 ± 0.25
C	0.060 ± 0.010	1.52 ± 0.25
D	0.350 ± 0.010	8.90 ± 0.25
E	0.200 ± 0.010	5.08 ± 0.25
F	0.025 ± 0.010	0.64 ± 0.25
G	0.040 (Ref. only)	1.02 (Ref. only)

Electrical Configuration

- 1) Inductance and DCR in table is for either L1 or L2.
- 2) Leakage Inductance tested at L1 with L2 shorted or at L2 with L1 shorted.
- 3) Windings balanced within 2%
- 4) Inductance tested @ 10 kHz

Operating Temperature Range -55°C to +105°C

Electrical Characteristics Measured at +25°C

Rated RMS Current Based upon 40°C temperature rise from 25°C ambient

Maximum Power Dissipation at 25°C 0.400 Watts

Inductance Tolerance Units are supplied to the tolerance indicated in the tables @ 10 kHz


Dielectric Withstanding Voltage

500 V RMS, 60Hz

DASH NUMBER*	L1 or L2 INDUCTANCE ±35% / ±25% (μH)	DC RESISTANCE MAXIMUM (OHMS)	RATED RMS CURRENT (AMPS) MAXIMUM	LEAKAGE INDUCTANCE TYPICAL (μH)
SERIES CM6350 FERRITE CORE				
-333	33	0.007	5.50	0.20
-473	47	0.008	5.00	0.30
-683	68	0.010	4.20	0.42
-104	100	0.014	3.30	0.55
-154	150	0.020	2.70	0.85
-224	220	0.027	2.20	1.20
-334	330	0.040	1.80	1.80
-474	470	0.060	1.50	1.60
-684	680	0.090	1.20	2.10
-105	1000	0.130	0.90	2.80
-155	1500	0.190	0.75	4.20
-225	2200	0.300	0.60	6.00
-335	3300	0.550	0.40	9.00
-475	4700	1.050	0.25	13.00

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com



Marking DELEVAN; CM6350, inductance with units. Note: An R after CM6350 indicates a RoHS component. A white dot indicates the location of pin 1.

Example: CM6350-333

DELEVAN

CM6350

33 μH

Packaging Tape & reel (24mm):

13" reel, 600 pieces max.; 7" reel not available


Weight (Grams) 1.0 (Ref.)

SERIES


CM6460R CM6460



Surface Mount Common Mode Choke



SCHEMATIC



Actual Size

Mechanical Configuration A flat top surface mount case with excellent coplanarity of terminals.

Physical Parameters

	Inches	Millimeters
A	0.400 ± 0.010	10.16 ± 0.25
B	0.530 ± 0.010	13.46 ± 0.25
C	0.125 ± 0.010	3.17 ± 0.25
D	0.490 ± 0.010	12.44 ± 0.25
E	0.290 ± 0.010	7.37 ± 0.25
F	0.030 ± 0.010	0.76 ± 0.25
G	0.060 (Ref. only)	1.52 (Ref. only)

Electrical Configuration

- 1) Inductance and DCR in table is for either L1 or L2.
- 2) Leakage Inductance tested at L1 with L2 shorted or at L2 with L1 shorted.
- 3) Windings balanced within 2%
- 4) Inductance tested @ 10 kHz

Operating Temperature Range -55°C to +105°C

Electrical Characteristics Measured at +25°C

Rated RMS Current Based upon 40°C temperature rise from 25°C ambient

Maximum Power Dissipation at 25°C 0.605 Watts

Transformers

LEAKAGE INDUCTANCE
TYPICAL (μH)

RATED RMS CURRENT
(AMPS) MAXIMUM

DC RESISTANCE
MAXIMUM (OHMS)

L1 or L2 INDUCTANCE
±35% / ±25% (μH)


DASH NUMBER*

SERIES CM6460 FERRITE CORE

-104	100	0.006	7.00	0.7
-154	150	0.010	5.50	1.0
-224	220	0.012	5.00	1.4
-334	330	0.017	4.00	1.8
-504	500	0.024	3.30	2.2
-754	750	0.035	2.70	3.0
-105	1000	0.049	2.20	4.0
-125	1200	0.068	1.70	5.0
-185	1800	0.106	1.40	5.5
-225	2200	0.150	1.10	7.0
-335	3300	0.210	0.85	9.5
-505	5000	0.320	0.70	14.0
-755	7500	0.640	0.44	22.0
-106	10000	0.900	0.33	29.0

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com



Inductance Tolerance Units are supplied to the tolerance indicated in the tables @ 10KHz

Dielectric Withstanding Voltage

500 V RMS, 60Hz

Marking Parts are printed with Delevan, Inductance Value, and dot at terminal #1.

Packaging

Tape & reel (24mm):

13" reel, 350 pieces max.; 7" reel not available

Weight (Grams) 2.5 (Ref.)

SERIES**CM6560R**
CM6560**Surface Mount
Common Mode Choke**



DASH NUMBER*

L1 or L2 INDUCTANCE
±35% / ±25% (μH)

DC RESISTANCE
MAXIMUM (OHMS)

RATED RMS CURRENT
(AMPS) MAXIMUM

LEAKAGE INDUCTANCE
TYPICAL (μH)

Transformers**SCHEMATIC**

Actual Size

Mechanical Configuration

A flat top surface mount case with excellent coplanarity of terminals.

Physical Parameters

	Inches	Millimeters
A	0.495 ± 0.010	12.6 ± 0.25
B	0.630 ± 0.010	16.0 ± 0.25
C	0.150 ± 0.010	3.81 ± 0.25
D	0.620 ± 0.010	15.8 ± 0.25
E	0.310 ± 0.010	7.88 ± 0.25
F	0.030 ± 0.010	0.76 ± 0.25
G	0.070 (Ref. only)	1.78 (Ref. only)

Electrical Configuration

- 1) Inductance and DCR in table is for either L1 or L2.
- 2) Leakage Inductance tested at L1 with L2 shorted or at L2 with L1 shorted.
- 3) Windings balanced within 2%
- 4) Inductance tested @ 10 kHz

Operating Temperature Range -55°C to +105°C

Electrical Characteristics Measured at +25°C

Rated RMS Current Based upon 40°C temperature rise from 25°C ambient.

Maximum Power Dissipation at 25°C 0.725 Watts

Inductance Tolerance Units are supplied to the tolerance indicated in the tables @ 10kHz.

Dielectric Withstanding Voltage


500 V RMS, 60Hz

SERIES CM6560 FERRITE CORE

-104	100	0.005	8.50	0.9
-184	180	0.007	7.00	1.2
-334	330	0.015	4.80	2.7
-504	500	0.023	3.60	4.5
-754	750	0.034	3.00	6.8
-105	1000	0.047	2.40	8.6
-185	1800	0.080	1.90	13.0
-225	2200	0.105	1.50	19.0
-335	3300	0.160	1.20	18.0
-505	5000	0.240	0.95	26.0
-755	7500	0.360	0.75	35.0
-106	10000	0.530	0.55	45.0
-126	12000	0.730	0.45	55.0
-156	15000	1.100	0.35	68.0

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com



Marking DELEVAN; CM6560, inductance with units. Note: An R after CM6560 indicates a RoHS component. A white dot indicates the location of pin 1.

Example: CM6560R-104


DELEVAN

CM6560R

100 uH.

Packaging Tape & reel (24mm): 13" reel, 350 pieces max.; 7" reel not available

Weight (Grams) 4.0 (Ref.)

SERIES**CM6594R**
CM6594**4-Winding
Surface Mount Transformers**

Actual Size

Physical Parameters

	Inches	Millimeters
A	0.435 to 0.465	11.05 to 11.81
B	0.385 to 0.405	9.78 to 10.29
C	0.375 to 0.405	9.53 to 10.29
D	0.205 to 0.235	5.21 to 5.97
E (8 places)		0.028 Typ. 0.71 Typ.
F (6 places)		0.079 Typ. 2.00 Typ.

Mechanical Configuration

ER Core on an 8 Pin Surface Mount Base

Operating Temperature Range -20°C to +80°C**Maximum Power Dissipation at 25°C** 0.140 W**Dielectric Withstanding Voltage**

500V RMS, 60Hz, 5 sec.

Current Rating Current which will cause less than a +35°C temperature rise maximum, from +25°C Ambient, with all windings connected in series

Notes ** 1) Max. leakage inductance measured @ 1 kHz on Pin 1-8 with all other pins shorted. 2) Board connections may be altered to create different transformer/inductor configurations.

DASH NUMBER*

INDUCTANCE EACH WINDING $\pm 25\%$ (μH)

MAXIMUM LEAKAGE INDUCTANCE (μH)*


DC RESISTANCE MAXIMUM (OHMS) EACH WINDING

CURRENT RATING MAXIMUM (AMPS) EACH WINDING

SERIES CM6594 FERRITE CORE

-253	25	0.90	0.04	1.00
-503	50	1.10	0.07	0.90
-104	100	1.30	0.13	0.75
-154	150	1.50	0.19	0.60
-254	250	1.70	0.32	0.50
-504	500	4.30	0.56	0.45
-754	750	6.80	0.90	0.38
-105	1000	6.95	1.19	0.30
-155	1500	7.00	1.90	0.25

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com**PAD DIMENSIONS****Pad Dimensions**


	Inches	Millimeters
C	0.425	10.80
G	0.368	9.35
X	0.063	1.60
Y	0.079	2.00
Z	0.492	12.50

Marking API; CM6594, dash number. Note: An R after CM6594 indicates a RoHS component. A dot indicates the location of pin 1.


Example: CM6594-503

API
CM6594
503

Packaging Tape & reel (24mm): 13" reel, 600 pieces max.; 7" reel not available

SERIES**CM7560R**
CM7560**PC Mount Common Mode Choke**

Actual Size

**Physical Parameters**

	Inches	Millimeters
A	0.860 ± 0.025	21.8 ± 0.64
B	1.070 ± 0.050	27.2 ± 1.27
C	0.830 ± 0.030	21.1 ± 0.76
D	1.060 (Ref. only)	26.9 (Ref. only)
E	0.040 ± 0.025	1.0 ± 0.64
F	0.025 Sq. (Typ.)	0.64 Sq. (Typ.)
G	0.400 ± 0.010	10.2 ± 0.3
H	0.175 ± 0.015	4.4 ± 0.38
J	1.03 (Ref. only)	26.2 (Ref. only)
K	0.400 ± 0.010	10.2 ± 0.3
L	0.630 ± 0.010	16.0 ± 0.3

Operating Temperature Range -55°C to +125°C**Current Rating at 85°C Ambient** 40°C Rise**Mechanical Configuration** Tape wrapped winding sections; varnish impregnated assembly

Notes 1) Inductance in table is for either L1 or L2.
 2) Leakage Inductance tested at L1 with L2 shorted or at L2 with L1 shorted. 3) Windings balanced within 1%.

DASH NUMBER*

L (μH) L1 or L2
@ 1 kHz ±25%DC RESISTANCE
MAXIMUM (OHMS)CURRENT RATING
MAXIMUM (AMPS)LEAKAGE INDUCTANCE
MAXIMUM (μH)**SERIES CM7560 FERRITE CORE**

-563	56	0.013	5.5	3.5
-683	68	0.013	5.5	3.5
-823	82	0.013	5.5	3.5
-104	100	0.013	5.5	3.5
-124	120	0.015	5.5	4.5
-154	150	0.015	5.5	6.0
-184	180	0.019	4.5	7.0
-224	220	0.020	4.5	7.5
-274	270	0.025	4.5	9.0
-334	330	0.025	3.5	12
-474	470	0.030	3.5	14
-564	560	0.035	3.5	18
-684	680	0.040	3.5	20
-824	820	0.060	2.8	24
-105	1000	0.065	2.8	30
-125	1200	0.095	2.2	35
-155	1500	0.115	1.7	40
-185	1800	0.125	1.7	45
-225	2200	0.170	1.4	55
-275	2700	0.180	1.4	75
-335	3300	0.320	1.1	90
-395	3900	0.400	1.1	100
-475	4700	0.450	0.88	130
-565	5600	0.500	0.88	175
-685	6800	0.600	0.88	220
-825	8200	0.750	0.88	230
-106	10000	0.800	0.70	250
-126	12000	0.900	0.70	300
-156	15000	1.00	0.70	350
-186	18000	1.30	0.55	425
-226	22000	1.50	0.55	475
-276	27000	1.80	0.44	550
-336	33000	2.20	0.44	650
-396	39000	2.60	0.44	800
-476	47000	3.00	0.44	900
-566	56000	4.00	0.35	1100
-686	68000	5.00	0.27	1300
-826	82000	5.50	0.27	1800
-107	100000	6.40	0.27	2100
-127	120000	7.80	0.22	2600
-157	150000	9.00	0.22	3000

*Complete part # must include series # PLUS the dash #


For surface finish information, refer to www.delevanfinishes.com**Marking** DELEVAN; part number.

Example: CM7560-563


DELEVAN

CM7560-563

Packaging Bulk only

SERIES**CM9900R**
CM9900**PC Mount Common Mode Chokes**

Actual Size

**Physical Parameters**

	Inches	Millimeters
A	0.740	18.8
B	0.840	21.3
C	0.670	17.0
D	0.900	22.9
E	0.040	1.0
F	0.025	0.64
G	0.200	5.1
H	0.175	4.4
J	0.750	19.1
K	0.200	5.1
L	0.515	13.1

All dimensions are typical

Operating Temperature Range -55°C to +125°C**Current Rating at 80°C Ambient** 40°C rise**Mechanical Configuration** Tape wrapped winding sections; varnish impregnated assembly.**Notes** 1) Inductance in table is for either L1 or L2.

2) Leakage Inductance tested at L1 with L2 shorted or at L2 with L1 shorted.

3) Windings balanced within 1%.

DASH NUMBER*

L (μH) L1 or L2
@ 1 kHz ±25%DC RESISTANCE
MAXIMUM (OHMS)CURRENT RATING
MAXIMUM (AMPS)LEAKAGE INDUCTANCE
TYPICAL (μH)**SERIES CM9900 FERRITE CORE**

-473	47	0.016	3.5	4.0
-563	56	0.018	3.5	4.0
-683	68	0.019	3.5	5.0
-823	82	0.023	2.8	5.5
-104	100	0.025	2.8	6.0
-124	120	0.028	2.8	6.5
-154	150	0.030	2.8	7.5
-184	180	0.038	2.2	8.0
-224	220	0.044	2.2	9.0
-274	270	0.051	2.2	10
-334	330	0.058	1.7	11
-474	470	0.078	1.4	16
-564	560	0.091	1.4	18
-684	680	0.115	1.1	20
-824	820	0.131	1.1	25
-105	1000	0.194	0.88	35
-125	1200	0.219	0.88	47
-155	1500	0.278	0.70	49
-185	1800	0.306	0.70	59
-225	2200	0.431	0.55	76
-275	2700	0.469	0.55	91
-335	3300	0.531	0.55	101
-395	3900	0.669	0.44	135
-475	4700	0.760	0.44	158
-565	5600	0.853	0.44	196
-685	6800	1.24	0.35	257
-825	8200	1.40	0.35	296
-106	10000	1.61	0.35	362
-126	12000	1.98	0.27	410
-156	15000	2.24	0.27	503
-186	18000	2.45	0.27	602
-226	22000	3.49	0.22	730
-276	27000	4.60	0.17	870
-336	33000	5.21	0.17	1150
-396	39000	7.19	0.13	1300
-476	47000	7.80	0.13	1541
-566	56000	8.69	0.13	1875
-686	68000	9.69	0.13	2254
-826	82000	13.10	0.10	2702
-107	100000	14.60	0.10	3269
-127	120000	16.00	0.10	3456

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com**Marking** DELEVAN; part number.

Example: CM9900R-473

DELEVAN

CM9900R-473

Packaging Bulk only


SERIES

6012R-6017R & 6022R-6027R
6012-6017 & 6022-6027


RoHS
Compliant

Traditional
First Quality

Horizontal PC Power Transformers



Actual Size (60x2)



UL Certified

Recognized component
Underwriters Labs, Inc.
CSA Labeled

Primary Voltage

Series 6012 - 6017 115 Single

Series 6022 - 6027 115 -
230 Dual

To Order For Single Voltage, insert
numeral 1 for "x" in Part Number listed in tables; for
Dual Voltage,
insert numeral 2 for "x" in Part Number listed in tables.

Operating Frequency 50/60 Hz

Operating Temperature 130° C

2500 V RMS Hipot

Split bobbin non-concentric winding

Dots on schematic indicate like polarity

Note Series 6017 and 6027 - 4 mounting holes
2³/₁₆ in. x 1³/₄ in. for #6 screw

*Complete part # must include series # PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com

PART NUMBER*	VA	SECONDARY VOLTAGE PARALLEL CONNECTION	SECONDARY VOLTAGE SERIES CONNECTION	SECONDARY CURRENT PARALLEL CONNECTION	SECONDARY CURRENT SERIES CONNECTION
60x2-010	1.1	10.0	5.0	0.110	0.220
60x2-012	1.1	12.6	6.3	0.090	0.180
60x2-016	1.1	16.0	8.0	0.070	0.140
60x2-020	1.1	20.0	10.0	0.055	0.110
60x2-024	1.1	24.0	12.0	0.045	0.090
60x2-028	1.1	28.0	14.0	0.040	0.080
60x2-036	1.1	36.0	18.0	0.030	0.060
60x2-048	1.1	48.0	24.0	0.023	0.046
60x2-056	1.1	56.0	28.0	0.020	0.040
60x2-120	1.1	120.	60.0	0.010	0.020
60x3-010	2.4	10.0	5.0	0.250	0.500
60x3-012	2.4	12.6	6.3	0.200	0.400
60x3-016	2.4	16.0	8.0	0.150	0.300
60x3-020	2.4	20.0	10.0	0.120	0.240
60x3-024	2.4	24.0	12.0	0.100	0.200
60x3-028	2.4	28.0	14.0	0.085	0.170
60x3-036	2.4	36.0	18.0	0.065	0.130
60x3-048	2.4	48.0	24.0	0.050	0.100
60x3-056	2.4	56.0	28.0	0.045	0.090
60x3-120	2.4	120.	60.0	0.020	0.040
60x4-010	6.0	10.0	5.0	0.600	1.200
60x4-012	6.0	12.6	6.3	0.500	1.000
60x4-016	6.0	16.0	8.0	0.400	0.800
60x4-020	6.0	20.0	10.0	0.300	0.600
60x4-024	6.0	24.0	12.0	0.250	0.500
60x4-028	6.0	28.0	14.0	0.200	0.400
60x4-036	6.0	36.0	18.0	0.170	0.340
60x4-048	6.0	48.0	24.0	0.125	0.250
60x4-056	6.0	56.0	28.0	0.110	0.220
60x4-120	6.0	120.	60.0	0.050	0.100
60x5-010	12.	10.0	5.0	1.200	2.400
60x5-012	12.	12.6	6.3	1.000	2.000
60x5-016	12.	16.0	8.0	0.800	1.600
60x5-020	12.	20.0	10.0	0.600	1.200
60x5-024	12.	24.0	12.0	0.500	1.000
60x5-028	12.	28.0	14.0	0.420	0.840
60x5-036	12.	36.0	18.0	0.350	0.700
60x5-048	12.	48.0	24.0	0.250	0.500
60x5-056	12.	56.0	28.0	0.220	0.440
60x5-120	12.	120.	60.0	0.100	0.200
60x6-010	20.	10.0	5.0	2.000	4.000
60x6-012	20.	12.6	6.3	1.600	3.200
60x6-016	20.	16.0	8.0	1.250	2.500
60x6-020	20.	20.0	10.0	1.000	2.000
60x6-024	20.	24.0	12.0	0.800	1.600
60x6-028	20.	28.0	14.0	0.700	1.400
60x6-036	20.	36.0	18.0	0.550	1.100
60x6-048	20.	48.0	24.0	0.400	0.800
60x6-056	20.	56.0	28.0	0.350	0.700
60x6-120	20.	120.	60.0	0.160	0.320
60x7-010	36.	10.0	5.0	3.600	7.200
60x7-012	36.	12.6	6.3	2.850	5.700
60x7-016	36.	16.0	8.0	2.250	4.500
60x7-020	36.	20.0	10.0	1.800	3.600
60x7-024	36.	24.0	12.0	1.500	3.000
60x7-028	36.	28.0	14.0	1.300	2.600
60x7-036	36.	36.0	18.0	1.000	2.000
60x7-048	36.	48.0	24.0	0.750	1.500
60x7-056	36.	56.0	28.0	0.650	1.300
60x7-120	36.	120.	60.0	0.300	0.600

Physical Parameters & Mounting Information

	L		W		H		A		B		C		ML		Screw Size	Weight	
	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm		lbs.	grams
60x2	1.38	34.93	1.13	28.58	0.94	23.81	0.25	6.35	0.25	6.35	1.20	30.48	—	—	none	0.17	77
60x3	1.38	34.93	1.13	28.58	1.19	30.16	0.25	6.35	0.25	6.35	1.20	30.48	—	—	none	0.25	113
60x4	1.63	41.28	1.31	33.34	1.31	33.34	0.25	6.35	0.35	8.89	1.28	32.51	1.06	26.99	4-40	0.44	200
60x5	1.88	47.63	1.56	39.69	1.44	36.51	0.30	7.62	0.40	10.16	1.41	35.81	1.25	31.75	4-40	0.70	317
60x6	2.25	57.15	1.88	47.63	1.44	36.51	0.30	7.62	0.40	10.16	1.60	40.64	1.50	38.10	4-40	0.80	363
60x7	2.63	66.68	2.19	55.56	1.56	39.69	0.40	10.16	0.40	10.16	1.85	46.99	—	See Note	—	1.10	499



SERIES

6051R – 6055R
6051 – 6055

ROHS
Compliant

Traditional
First Quality

Low Profile PC Power Transformers



Actual Size (6051)

UL Certified

Recognized component
Underwriters Labs, Inc.
CSA Labeled

Primary Voltage 115/230 V

Operating Frequency 50/60 Hz

Operating Temperature 130° C

1500 V RMS Hipot

Split bobbin non-concentric winding

Dots on schematic indicate like polarity

Mounting Note

Series 6051, 6052 and 6053 – 4 mounting holes
23/16 in. x 13/4 in. for #6 screw

Series 6054 and 6055 – 2 mounting holes

*See mechanical drawing for correct PCB footprint.

*Complete part # must include series # PLUS the dash #

For surface finish information,
refer to www.delevanfinishes.com

PART NUMBER*	VA	SECONDARY VOLTAGE PARALLEL CONNECTION (V)	SECONDARY VOLTAGE SERIES CONNECTION (V)	SECONDARY CURRENT PARALLEL CONNECTION (A)	SECONDARY CURRENT SERIES CONNECTION (A)
6051-010	2.5	10.0	5.0	0.250	0.500
6051-012	2.5	12.6	6.3	0.200	0.400
6051-016	2.5	16.0	8.0	0.156	0.312
6051-020	2.5	20.0	10.0	0.125	0.250
6051-024	2.5	24.0	12.0	0.104	0.208
6051-034	2.5	34.0	17.0	0.073	0.146
6051-040	2.5	40.0	20.0	0.062	0.124
6051-056	2.5	56.0	28.0	0.044	0.088
6051-088	2.5	88.0	44.0	0.028	0.056
6051-120	2.5	120.	60.0	0.020	0.040
6051-230	2.5	230.	115.	0.010	0.020
6052-010	6.0	10.0	5.0	0.600	1.200
6052-012	6.0	12.6	6.3	0.450	0.900
6052-016	6.0	16.0	8.0	0.350	0.700
6052-020	6.0	20.0	10.0	0.300	0.600
6052-024	6.0	24.0	12.0	0.250	0.500
6052-034	6.0	34.0	17.0	0.170	0.340
6052-040	6.0	40.0	20.0	0.150	0.300
6052-056	6.0	56.0	28.0	0.100	0.200
6052-088	6.0	88.0	44.0	0.065	0.130
6052-120	6.0	120.	60.0	0.050	0.100
6052-230	6.0	230.	115.	0.025	0.050
6053-010	12.0	10.0	5.0	1.200	2.400
6053-012	12.0	12.6	6.3	0.900	1.800
6053-016	12.0	16.0	8.0	0.700	1.400
6053-020	12.0	20.0	10.0	0.600	1.200
6053-024	12.0	24.0	12.0	0.500	1.000
6053-034	12.0	34.0	17.0	0.340	0.680
6053-040	12.0	40.0	20.0	0.300	0.600
6053-056	12.0	56.0	28.0	0.200	0.400
6053-088	12.0	88.0	44.0	0.130	0.260
6053-120	12.0	120.	60.0	0.100	0.200
6053-230	12.0	230.	115.	0.050	0.100
6054-010	24.0	10.0	5.0	2.400	4.800
6054-012	24.0	12.6	6.3	1.900	3.800
6054-016	24.0	16.0	8.0	1.500	3.000
6054-020	24.0	20.0	10.0	1.200	2.400
6054-024	24.0	24.0	12.0	1.000	2.000
6054-030	24.0	30.0	15.0	0.800	1.600
6054-034	24.0	34.0	17.0	0.700	1.400
6054-040	24.0	40.0	20.0	0.600	1.200
6054-056	24.0	56.0	28.0	0.425	0.850
6054-088	24.0	88.0	44.0	0.275	0.550
6054-120	24.0	120.	60.0	0.200	0.400
6054-230	24.0	230.	115.	0.100	0.200
6055-010	48.0	10.0	5.0	4.800	9.600
6055-012	48.0	12.6	6.3	3.800	7.600
6055-016	48.0	16.0	8.0	3.000	6.000
6055-020	48.0	20.0	10.0	2.400	4.800
6055-024	48.0	24.0	12.0	2.000	4.000
6055-030	48.0	30.0	15.0	1.600	3.200
6055-034	48.0	34.0	17.0	1.400	2.800
6055-040	48.0	40.0	20.0	1.200	2.400
6055-056	48.0	56.0	28.0	0.850	1.700
6055-088	48.0	88.0	44.0	0.550	1.100
6055-120	48.0	120.	60.0	0.400	0.800
6055-230	48.0	230.	115.	0.200	0.400

Physical Parameters & Mounting Information

	L		W		H		A		B		C		D		E		Weight	
	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	oz.	kg
6051	1.88	47.62	1.56	39.68	0.65	16.50	1.60	40.63	0.38	9.53			0.25	6.35	0.041	1.04	5	.142
6052	1.88	47.62	1.56	39.68	0.85	21.59	1.60	40.63	0.38	9.53			0.25	6.35	0.041	1.04	7	.219
6053	2.50	63.49	2.00	50.80	1.07	27.05	2.00	50.79	0.50	12.69			0.25	6.35	0.041	1.04	11	.312
6054	2.88	73.02	2.25	57.15	1.25	31.74	1.90	48.26	0.60	15.24	0.53	13.46	0.25	6.35	0.041	1.04	15	.426
6055	3.13	79.37	2.50	63.50	1.38	34.92	2.18	55.37	0.60	15.24	0.66	16.76	0.25	6.35	0.041	1.04	21	.596


SERIES

6443R-6448R
6443-6448


ROHS
Compliant

Traditional
First Quality



VDE PC Mount Transformers





Mounting Style "A" 2 Screws



Schematic 1



Mounting Style "B"
4 Screws



PART NUMBER*	PRIMARY VOLTAGE		SECONDARY VOLTAGE		SECONDARY CURRENT		MOUNTING STYLE	
	CONNECTION	SERIES	CONNECTION	SERIES	CONNECTION	SERIES	CONNECTION	SERIES
6494-010	25	115/130	10.0	5.0	2.50	5.00	1	C
6494-012	25	115/230	12.6	6.3	2.00	4.00	1	C
6494-016	25	115/230	16.0	8.0	1.60	3.20	1	C
6494-020	25	115/230	20.0	10.0	1.25	2.50	1	C
6494-024	25	115/230	24.0	12.0	1.00	2.00	1	C
6494-028	25	115/230	28.0	14.0	0.90	1.86	1	C
6494-036	25	115/230	36.0	18.0	0.70	1.40	1	C
6494-230	25	115/230	230.0	115.0	0.11	0.22	1	C
6495-010	43	115/230	10.0	5.0	4.30	8.60	1	C
6495-012	43	115/230	12.6	6.3	3.40	6.80	1	C
6495-016	43	115/230	16.0	8.0	2.70	5.40	1	C
6495-020	43	115/230	20.0	10.0	2.20	4.40	1	C
6495-024	43	115/230	24.0	12.0	1.80	3.60	1	C
6495-028	43	115/230	28.0	14.0	1.50	3.00	1	C
6495-036	43	115/230	36.0	18.0	1.20	2.40	1	C
6495-230	43	115/230	230.0	115.0	0.19	0.38	1	C
6496-010	80	115/230	10.0	5.0	8.00	16.00	2	D
6496-012	80	115/230	12.6	6.3	6.30	12.60	2	D
6496-016	80	115/230	16.0	8.0	5.00	10.00	2	D
6496-020	80	115/230	20.0	10.0	4.00	8.00	2	D
6496-024	80	115/230	24.0	12.0	3.30	6.60	2	D
6496-028	80	115/230	28.0	14.0	2.80	5.60	2	D
6496-036	80	115/230	36.0	18.0	2.20	4.40	2	D
6496-230	80	115/230	230.0	115.0	0.35	0.70	2	D
6497-010	130	115/230	10.0	5.0	13.00	26.00	2	D
6497-012	130	115/230	12.6	6.3	10.30	20.60	2	D
6497-016	130	115/230	16.0	8.0	8.10	16.20	2	D
6497-020	130	115/230	20.0	10.0	6.50	13.00	2	D
6497-024	130	115/230	24.0	12.0	5.40	10.80	2	D
6497-028	130	115/230	28.0	14.0	4.60	9.20	2	D
6497-036	130	115/230	36.0	18.0	3.60	7.20	2	D
6497-230	130	115/230	230.0	115.0	0.57	1.14	2	D
6498-010	175	115/230	10.0	5.0	17.50	35.00	2	D
6498-012	175	115/230	12.6	6.3	14.00	28.00	2	D
6498-016	175	115/230	16.0	8.0	11.00	22.00	2	D
6498-020	175	115/230	20.0	10.0	8.80	17.60	2	D
6498-024	175	115/230	24.0	12.0	7.30	14.60	2	D
6498-028	175	115/230	28.0	14.0	6.25	12.50	2	D
6498-036	175	115/230	36.0	18.0	4.80	9.60	2	D
6498-230	175	115/230	230.0	115.0	0.76	1.52	2	D

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

UL Certified Recognized component Underwriters Labs, Inc®; CSA Labeled

Primary Voltage Available in either 115V or dual 115/230V

Operating Frequency 50/60 Hz

Operating Temperature 130°C

4000 V RMS Hipot

Split bobbin non-concentric winding

Designed to pass VDE creepage distance




Note Dots on schematic indicate like polarity

Physical Parameters & Mounting Information																					Screw size	# Terminals
	L		W		H		A		B		C		Pin width (sq.)		MW		ML		Weight			
	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kg		
6494	2.81	71.44	1.88	47.63	2.31	58.74	2.25	50.80	1.13	28.58	0.31	7.94	0.19	4.763	—	—	2.38	60.33	1.25	0.567	6	10
6495	3.13	79.38	2.06	52.39	2.69	68.26	2.25	57.15	1.13	28.58	0.19	4.76	0.81	20.64	—	—	2.81	71.44	1.60	0.726	6	10
6496	2.50	63.50	2.38	60.33	3.00	76.20	—	—	1.38	34.93	0.31	7.94	0.19	4.763	2.19	55.56	2.00	50.80	2.80	1.270	6	12
6497	2.81	71.44	2.88	73.03	3.38	85.73	—	—	1.63	41.28	0.38	9.53	0.25	6.350	2.50	63.50	2.25	57.15	4.10	1.860	8	12
6498	3.13	79.38	2.88	73.03	3.75	95.25	—	—	1.63	41.28	0.38	9.53	0.25	6.350	2.50	63.50	2.50	63.50	5.50	2.494	8	12

6494R-6498R
6494-6498



VDE Quick Connect Transformers



PART NUMBER*	SECONDARY VOLTAGE		SECONDARY CURRENT		CONNECTION		MOUNTING STYLE		Transformers	
	VA	PRIMARY VOLTAGE	CONNECTION	SERIES	PARALLEL	CONNECTION	SERIES	PARALLEL		SCHEMATIC
6494-010	25	115/130	10.0	5.0	2.50	5.00	1	C		
6494-012	25	115/230	12.6	6.3	2.00	4.00	1	C		
6494-016	25	115/230	16.0	8.0	1.60	3.20	1	C		
6494-020	25	115/230	20.0	10.0	1.25	2.50	1	C		
6494-024	25	115/230	24.0	12.0	1.00	2.00	1	C		
6494-028	25	115/230	28.0	14.0	0.90	1.86	1	C		
6494-036	25	115/230	36.0	18.0	0.70	1.40	1	C		
6494-230	25	115/230	230.0	115.0	0.11	0.22	1	C		
6495-010	43	115/230	10.0	5.0	4.30	8.60	1	C		
6495-012	43	115/230	12.6	6.3	3.40	6.80	1	C		
6495-016	43	115/230	16.0	8.0	2.70	5.40	1	C		
6495-020	43	115/230	20.0	10.0	2.20	4.40	1	C		
6495-024	43	115/230	24.0	12.0	1.80	3.60	1	C		
6495-028	43	115/230	28.0	14.0	1.50	3.00	1	C		
6495-036	43	115/230	36.0	18.0	1.20	2.40	1	C		
6495-230	43	115/230	230.0	115.0	0.19	0.38	1	C		
6496-010	80	115/230	10.0	5.0	8.00	16.00	2	D		
6496-012	80	115/230	12.6	6.3	6.30	12.60	2	D		
6496-016	80	115/230	16.0	8.0	5.00	10.00	2	D		
6496-020	80	115/230	20.0	10.0	4.00	8.00	2	D		
6496-024	80	115/230	24.0	12.0	3.30	6.60	2	D		
6496-028	80	115/230	28.0	14.0	2.80	5.60	2	D		
6496-036	80	115/230	36.0	18.0	2.20	4.40	2	D		
6496-230	80	115/230	230.0	115.0	0.35	0.70	2	D		
6497-010	130	115/230	10.0	5.0	13.00	26.00	2	D		
6497-012	130	115/230	12.6	6.3	10.30	20.60	2	D		
6497-016	130	115/230	16.0	8.0	8.10	16.20	2	D		
6497-020	130	115/230	20.0	10.0	6.50	13.00	2	D		
6497-024	130	115/230	24.0	12.0	5.40	10.80	2	D		
6497-028	130	115/230	28.0	14.0	4.60	9.20	2	D		
6497-036	130	115/230	36.0	18.0	3.60	7.20	2	D		
6497-230	130	115/230	230.0	115.0	0.57	1.14	2	D		
6498-010	175	115/230	10.0	5.0	17.50	35.00	2	D		
6498-012	175	115/230	12.6	6.3	14.00	28.00	2	D		
6498-016	175	115/230	16.0	8.0	11.00	22.00	2	D		
6498-020	175	115/230	20.0	10.0	8.80	17.60	2	D		
6498-024	175	115/230	24.0	12.0	7.30	14.60	2	D		
6498-028	175	115/230	28.0	14.0	6.25	12.50	2	D		
6498-036	175	115/230	36.0	18.0	4.80	9.60	2	D		
6498-230	175	115/230	230.0	115.0	0.76	1.52	2	D		

*Complete part # must include series # PLUS the dash #

For surface finish information, refer to www.delevanfinishes.com

UL Certified Recognized component Underwriters
Labs, Inc®; CSA Labeled

Primary Voltage Available in either 115V or dual 115/230V

Operating Frequency 50/60 Hz

Operating Temperature 130°C




4000 V RMS Hipot

Split bobbin non-concentric winding

Designed to pass VDE creepage distance

Note Dots on schematic indicate like polarity

Physical Parameters & Mounting Information																					Screw size	# Terminal
Part #	L		W		H		A		B		C		Pin width (sq.)		MW		ML		Weight			
	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kg		
6494	2.81	71.44	1.88	47.63	2.31	58.74	2.00	50.80	1.13	28.58	0.31	7.94	0.19	4.763	—	—	2.38	60.33	1.25	0.567	6	10
6495	3.13	79.38	2.06	52.39	2.69	68.26	2.25	57.15	1.13	28.58	0.19	4.76	0.81	20.64	—	—	2.81	71.44	1.60	0.726	6	10
6496	2.50	63.50	2.38	60.33	3.00	76.20	—	—	1.38	34.93	0.31	7.94	0.19	4.763	2.19	55.56	2.00	50.80	2.80	1.270	6	12
6497	2.81	71.44	2.88	73.03	3.38	85.73	—	—	1.63	41.28	0.38	9.53	0.25	6.350	2.50	63.50	2.25	57.15	4.10	1.860	8	12
6498	3.13	79.38	2.88	73.03	3.75	95.25	—	—	1.63	41.28	0.38	9.53	0.25	6.350	2.50	63.50	2.50	63.50	5.50	2.494	8	12

SERIES**6655R-6658R**
6655-6658**Switchmode Transformers on Ferrite E Cores**

Actual Size (6658-XX)

Power Ranges up to 500 Watts**Frequency Range** 10 kHz-250 kHz**UL Approved** Class 130°C Insulation System**Standardized Components** Fast Samples/Delivery**Easy Printed Circuit Board Insertion****Uses "Standard" E cores**

UnGapped as well as Gapped Available

Suitable for use in all types of switching power supply circuits including:

- ▶ Flyback
- ▶ Forward
- ▶ Pushpull
- ▶ Halfbridge
- ▶ Fullbridge

Physical Parameters & Mounting Information

	L	W	H	A	B	C	# of Pins	AI Ungapped	AI Gapped
6655-XX	0.750	0.868	0.625	0.510	0.150	0.200	8	1450	105
6656-XX	1.030	1.046	0.797	0.660	0.150	0.200	10	2100	152
6657-XX	1.470	1.279	1.000	0.860	0.150	0.200	12	3230	234
6658-XX	1.620	1.359	1.130	0.950	0.200	0.250	12	5400	391

Design Form (General): Photocopy, fill out and fax for fast response**Type**

- ☐ Flyback
☐ Forward
☐ PushPull
☐ HalfBridge
☐ FullBridge
☐ UnGapped
☐ Gapped

Size

- ☐ 6655
☐ 6656
☐ 6657
☐ 6658

Special Features

- ☐ Kool Mu Core
☐ Faraday Shield


Frequency Range _____ to _____ Hz ☐ Continuous ☐ Discontinuous**Power** _____ Watts (Continuous) Duty Cycle _____**Input Voltage** _____ Min. / _____ Max. Number of Output Voltages _____

	Output 1	Output 2	Output 3	Output 4
Voltage	_____	_____	_____	_____
Current	_____	_____	_____	_____
Inductance	_____	_____	_____	_____
DCR	_____	_____	_____	_____

Dielectric Withstand Voltage _____ Operating Temperature _____ @ _____

Construction Specifications (If Applicable):

Winding #	1	2	3	4
Winding Description	_____	_____	_____	_____
Total Turns	_____	_____	_____	_____
Tap Turns	_____	_____	_____	_____
Wire Size	_____	_____	_____	_____
Wire Type	_____	_____	_____	_____
Start Pin	_____	_____	_____	_____
Finish Pin	_____	_____	_____	_____

SERIES**6665R-6668R**
6665-6668RoHS
CompliantTraditional
First Quality**Switchmode Transformers on Ferrite ETD Cores**

Actual Size (6665-XX)

Physical Parameters & Mounting Information

	L	W	H	A	B	# of Pins	C (Square)
6665-XX	1.390	1.390	0.950	1.000	0.200	13	0.028
6666-XX	1.679	1.685	1.375	1.000	0.200	14	0.039
6667-XX	1.876	1.882	1.480	1.200	0.200	16	0.039
6668-XX	2.061	2.055	1.590	1.400	0.200	18	0.039

Power Ranges up to 500 Watts**Frequency Range** 10 kHz-250 kHz**UL Approved** Class 130°C Insulation System**Standardized Components** Fast Samples/Delivery**Easy Printed Circuit Board Insertion****Uses "Standard" ETD cores**

UnGapped as well as Gapped Available

Suitable for use in all types of switching power supply circuits including:

- ▶ Flyback
- ▶ Forward
- ▶ Pushpull
- ▶ Halfbridge
- ▶ Fullbridge

Design Form (General): Photocopy, fill out and fax for fast responseType ☐ Flyback ☐ Forward ☐ PushPull ☐ HalfBridge ☐ FullBridge ☐ UnGapped ☐ GappedSize ☐ 6665 ☐ 6666 ☐ 6667 ☐ 6668Frequency Range _____ to _____ Hz ☐ Continuous ☐ Discontinuous

Power _____ Watts (Continuous) Duty Cycle _____

Input Voltage _____ Min. / _____ Max. Number of Output Voltages _____

	Output 1	Output 2	Output 3	Output 4
Voltage	_____	_____	_____	_____
Current	_____	_____	_____	_____
Inductance	_____	_____	_____	_____
DCR	_____	_____	_____	_____

Dielectric Withstand Voltage _____ Operating Temperature _____ @ _____

Construction Specifications (If Applicable):

Winding #	1	2	3	4
Winding Description	_____	_____	_____	_____
Total Turns	_____	_____	_____	_____
Tap Turns	_____	_____	_____	_____
Wire Size	_____	_____	_____	_____
Wire Type	_____	_____	_____	_____
Start Pin	_____	_____	_____	_____
Finish Pin	_____	_____	_____	_____

Technical

CONTINUED ON NEXT PAGE

Technical

CONTINUED ON NEXT PAGE

Technical

270 Quaker Rd., East Aurora NY 14052 • Phone 716-652-3600 • Fax 716-652-4814 • E-mail: apisales@delevan.com • www.delevan.com

MIL-PRF-83446/ to Delevan Conversion Chart

Technical

MIL-PRF-83446
/04, /08, /10, /11 & /38
TERMINATION FINISH OPTIONS:
CODE A – Final finish gold over nickel
CODE B – Final finish tin-lead over nickel
CODE F – Final finish tin-lead

GOV'T PART # (TERMINATION)	DELEVAN PART #	GOV'T PART # (TERMINATION)	DELEVAN PART #	GOV'T PART # (TERMINATION)	DELEVAN PART #	GOV'T PART # (TERMINATION)	DELEVAN PART #
M83446/ 04-	103-	M83446/ 08-*	108-	M83446/ 10-*	3094-	M83446/ 11-*	4379-
01 ()	121K ()	87 ()	123K ()	62 ()	100 ()	62 ()	101K ()
02 ()	151K ()	88 ()	153K ()	63 ()	120 ()	63 ()	121K ()
03 ()	181K ()	89 ()	183K ()	64 ()	150 ()	64 ()	151K ()
04 ()	221K ()	90 ()	223K ()	65 ()	180 ()	65 ()	181K ()
05 ()	271K ()	91 ()	273K ()	66 ()	220 ()	66 ()	221K ()
06 ()	331K ()	92 ()	333K ()	67 ()	270 ()	67 ()	271K ()
07 ()	391K ()	93 ()	393K ()	68 ()	330 ()	68 ()	331K ()
08 ()	471K ()	94 ()	473K ()	69 ()	390 ()	69 ()	391K ()
09 ()	561K ()	95 ()	565K ()	70 ()	470 ()	70 ()	471K ()
10 ()	681K ()	96 ()	683K ()	71 ()	560 ()	71 ()	561K ()
11 ()	821K ()	97 ()	823K ()	72 ()	680 ()	72 ()	681K ()
12 ()	102K ()	98 ()	104K ()	73 ()	820 ()	73 ()	821K ()
13 ()	122K ()			74 ()	101 ()	74 ()	102K ()
14 ()	152K ()			75 ()	121 ()	75 ()	122K ()
15 ()	182K ()			76 ()	151 ()	76 ()	152K ()
16 ()	222K ()			77 ()	181 ()	77 ()	182K ()
17 ()	272K ()			78 ()	221 ()	78 ()	222K ()
18 ()	332K ()			79 ()	271 ()	79 ()	272K ()
19 ()	392K ()			80 ()	331 ()	80 ()	332K ()
20 ()	472K ()			81 ()	391 ()	81 ()	392K ()
21 ()	562K ()			82 ()	471 ()	82 ()	472K ()
22 ()	682K ()			83 ()	561 ()	83 ()	562K ()
23 ()	822K ()			84 ()	681 ()	84 ()	682K ()
24 ()	103K ()			85 ()	821 ()	85 ()	822K ()
25 ()	123K ()			86 ()	102 ()	86 ()	103K ()
26 ()	153K ()			87 ()	122 ()	87 ()	123K ()
27 ()	183K ()			88 ()	152 ()	88 ()	153K ()
28 ()	223K ()			89 ()	182 ()	89 ()	183K ()
29 ()	273K ()			90 ()	222 ()	90 ()	223K ()
30 ()	100K ()			91 ()	272 ()	91 ()	273K ()
31 ()	150K ()			92 ()	332 ()	92 ()	333K ()
32 ()	220K ()			93 ()	392 ()	93 ()	393K ()
33 ()	330K ()			94 ()	472 ()	94 ()	473K ()
34 ()	470K ()			95 ()	562 ()	95 ()	563K ()
35 ()	680K ()			96 ()	682 ()	96 ()	683K ()
36 ()	101K ()			97 ()	822 ()	97 ()	823K ()
37 ()	100K ()			98 ()	103 ()	98 ()	104K ()
38 ()	120K ()			99 ()	123 ()	99 ()	124K ()
39 ()	150K ()			100 ()	153 ()	100 ()	154K ()
40 ()	180K ()			101 ()	153 ()	101 ()	184K ()
41 ()	220K ()			102 ()	223 ()	102 ()	224K ()
42 ()	270K ()			103 ()	273 ()	103 ()	274K ()
43 ()	330K ()			104 ()	333 ()	104 ()	334K ()
44 ()	390K ()			105 ()	393 ()	105 ()	394K ()
45 ()	470K ()			106 ()	472 ()	106 ()	474K ()
46 ()	560K ()			107 ()	563 ()	107 ()	564K ()
47 ()	680K ()			108 ()	683 ()	108 ()	684K ()
48 ()	820K ()			109 ()	823 ()	109 ()	824K ()
49 ()	101K ()			110 ()	104 ()	110 ()	105K ()
				111 ()	124 ()	111 ()	125K ()
				112 ()	154 ()	112 ()	155K ()
				113 ()	184 ()	113 ()	185K ()
				114 ()	224 ()	114 ()	225K ()
				115 ()	274 ()	115 ()	275K ()
				116 ()	334 ()	116 ()	335K ()
				117 ()	394 ()	117 ()	395K ()
				118 ()	474 ()	118 ()	475K ()
				119 ()	564 ()	119 ()	565K ()
				120 ()	684 ()	120 ()	685K ()
				121 ()	824 ()	121 ()	825K ()
				122 ()	105 ()	122 ()	106K ()

* COTS – “MS” is
for reference only

CONTINUED ON NEXT PAGE

MIL-PRF-83446/ to Delevan Conversion Chart

Technical

GOV'T PART #	DELEVAN PART #	GOV'T PART #	DELEVAN PART #	GOV'T PART #	DELEVAN PART #	GOV'T PART #	DELEVAN PART #	GOV'T PART #	DELEVAN PART #	GOV'T PART #	DELEVAN PART #	GOV'T PART #	DELEVAN PART #	
M83446/ 20- 01F 02F 03F 04F 05F 06F 07F 08F 09F	M0820- 00K 02K 04K 06K 08K 10K 12K 14K 16K	M83446/ 23- 01F 02F 03F 04F 05F 06F 07F 08F 09F 10F 11F 12F 13F	M1330- 94K 96K 00K 02K 04K 06K 08K 10K 12K 14K 16K 18K 20K	M83446/ 26- 01F 02F 03F 04F 05F 06F 07F 08F 09F 10F 11F 12F 13F 14F 15F 16F 17F 18F 19F 20F 21F 22F 23F 24F 25F 26F 27F 28F 29F 30F 31F 32F 33F 34F 35F 36F 37F	M1331- 101K 121K 151K 181K 221K 271K 331K 391K 471K 561K 681K 821K 102K 122K 152K 182K 222K 272K 332K 392K 472K 562K 682K 822K 103K 123K 153K 183K 223K 273K 333K 393K 473K 563K 683K 823K 104K	M83446/ 28- 01F 02F 03F 04F 05F 06F 07F 08F 09F	MIL2510- 00K 02K 04K 06K 08K 10K 12K 14K 16K	M83446/ 31- 01F 02F 03F 04F 05F 06F 07F 08F 09F 10F 11F 12F 13F	MIL1330- 94K 96K 00K 02K 04K 06K 08K 10K 12K 14K 16K 18K 20K	M83446/ 34- 01F 02F 03F 04F 05F 06F 07F 08F 09F 10F 11F 12F 13F 14F 15F 16F 17F 18F 19F 20F 21F 22F 23F 24F 25F 26F 27F 28F 29F 30F 31F 32F 33F 34F 35F 36F 37F	MIL1331- 101K 121K 151K 181K 221K 271K 331K 391K 471K 561K 681K 821K 102K 122K 152K 182K 222K 272K 332K 392K 472K 562K 682K 822K 103K 123K 153K 183K 223K 273K 333K 393K 473K 563K 683K 823K 104K	M83446/ 38- 01 () 02 () 03 () 04 () 05 () 06 () 07 () 08 () 09 () 10 () 11 () 12 () 13 () 14 () 15 () 16 () 17 () 18 () 19 () 20 () 21 () 22 () 23 () 24 () 25 () 26 () 27 () 28 () 29 () 30 () 31 () 32 () 33 () 34 () 35 () 36 () 37 () 38 () 39 () 40 () 41 () 42 () 43 () 44 () 45 () 46 () 47 () 48 () 49 () 50 () 51 () 52 () 53 () 54 () 55 () 56 () 57 () 58 () 59 () 60 () 61 ()	160- 100M () 120M () 150M () 180M () 220M () 270M () 330M () 390M () 470M () 560M () 680M () 820M () 101K () 121K () 151K () 181K () 221K () 271K () 301K () 331K () 361K () 391K () 421K () 471K () 561J () 681J () 821J () 102J () 122J () 152J () 182J () 222J () 272J () 332J () 392J () 472J () 562J () 682J () 822J () 103J () 123J () 153J () 183J () 223J () 273J () 333J () 393J () 473J () 563J () 683J () 823J () 104J () 124J () 154J () 184J () 224J () 274J () 334J () 394J () 474J () 564J ()	
MIL-PRF-83446 TERMINATION FINISH: /20 thru /35 CODE F – Final finish tin-lead /38 Options: CODE B – Final finish tin-lead over nickel CODE F – Final finish tin-lead														

MIL-PRF-83446 TERMINATION FINISH:

/20 thru /35

CODE F – Final finish tin-lead

/38 Options:

CODE B – Final finish tin-lead over nickel

CODE F – Final finish tin-lead

CONTINUED ON NEXT PAGE

MIL-PRF-83446/ to Delevan Conversion Chart

Technical

MIL-PRF-83446
/39 & /40
TERMINATION FINISH OPTIONS:
CODE F – Final finish tin-lead
CODE P – Final finish Pb free

GOV'T PART # (TERMINATION)	DELEVAN PART #	GOV'T PART # (TERMINATION)	DELEVAN PART #	GOV'T PART # (TERMINATION)	DELEVAN PART #	GOV'T PART # (TERMINATION)	DELEVAN PART #
M83446/ 39- -01F -02F -03F -04F -05F -06F -07F -08F -09F -10F -11F -12F -13F -14F -15F -16F -17F -18F -19F -20F -21F -22F -23F -24F -25F -26F -27F -28F -29F -30F -31F -32F -33F -34F -35F -36F -37F -38F -39F -40F -41F -42F -43F -44F -45F -46F -47F -48F -49F -50F -51F -52F -53F -54F -55F -56F -57F -58F -59F -60F -61F	MIL1812- -100M -120M -150M -160M -220M -270M -330M -390M -470M -560M -680M -820M -101K -121K -151K -181K -221K -271K -331K -391K -471K -561K -681K -821K -102J -122J -152J -182J -222J -272J -332J -392J -472J -562J -682J -822J -103J -123J -153J -183J -223J -273J -333J -393J -473J -563J -683J -823J -104J -124J -154J -184J -224J -274J -334J -394J -474J -564J -684J -824J -105J	M83446/ 39- -01P -02P -03P -04P -05P -06P -07P -08P -09P -10P -11P -12P -13P -14P -15P -16P -17P -18P -19P -20P -21P -22P -23P -24P -25P -26P -27P -28P -29P -30P -31P -32P -33P -34P -35P -36P -37P -38P -39P -40P -41P -42P -43P -44P -45P -46P -47P -48P -49P -50P -51P -52P -53P -54P -55P -56P -57P -58P -59P -60P -61P	MIL1812R- -100M -120M -150M -160M -220M -270M -330M -390M -470M -560M -680M -820M -101K -121K -151K -181K -221K -271K -331K -391K -471K -561K -681K -821K -102J -122J -152J -182J -222J -272J -332J -392J -472J -562J -682J -822J -103J -123J -153J -183J -223J -273J -333J -393J -473J -563J -683J -823J -104J -124J -154J -184J -224J -274J -334J -394J -474J -564J -684J -824J -105J	M83446/ 40- -01F -02F -03F -04F -05F -06F -07F -08F -09F -10F -11F -12F -13F -14F -15F -16F -17F -18F -19F -20F -21F -22F -23F -24F -25F -26F -27F -28F -29F -30F -31F -32F -33F -34F -35F -36F -37F -38F -39F -40F -41F -42F -43F -44F -45F -46F -47F -48F -49F	MILS1812- -101K -121K -151K -181K -221K -271K -331K -391K -471K -561K -681K -821K -102K -122K -152K -182K -222K -272K -332K -392K -472K -562K -682K -822K -103K -123K -153K -183K -223K -273K -333K -393K -473K -563K -683K -823K -104K -124K -154K -184K -224K -274K -334K -394K -474K -564K -684K -824K -105K	M83446/ 40- -01P -02P -03P -04P -05P -06P -07P -08P -09P -10P -11P -12P -13P -14P -15P -16P -17P -18P -19P -20P -21P -22P -23P -24P -25P -26P -27P -28P -29P -30P -31P -32P -33P -34P -35P -36P -37P -38P -39P -40P -41P -42P -43P -44P -45P -46P -47P -48P -49P	MILS1812R- -101K -121K -151K -181K -221K -271K -331K -391K -471K -561K -681K -821K -102K -122K -152K -182K -222K -272K -332K -392K -472K -562K -682K -822K -103K -123K -153K -183K -223K -273K -333K -393K -473K -563K -683K -823K -104K -124K -154K -184K -224K -274K -334K -394K -474K -564K -684K -824K -105K

MIL-PRF-27/ to Delevan Conversion Chart

Technical

GOV'T PART #	DELEVAN PART #	GOV'T PART #	DELEVAN PART #	GOV'T PART #	DELEVAN PART #
M27/367	MIL4922	M27/368	MILP1812-	M27/370	MIL85232-
-01	-221	-01	-102K	-01	-01L
-02	-271	-02	-122K	-02	-02L
-03	-331	-03	-152K	-03	-03L
-04	-391	-04	-182K	-04	-04L
-05	-471	-05	-222K	-05	-05L
-06	-561	-06	-272K	-06	-06L
-07	-681	-07	-332K	-07	-07L
-08	-821	-08	-392K	-08	-08L
-09	-01	-09	-472K	-09	-09L
-10	-02	-10	-562K	-10	-10L
-11	-03	-11	-682K	-11	-11L
-12	-04	-12	-822K	-12	-12L
-13	-05	-13	-103K	-13	-13L
-14	-06	-14	-123K	-14	-14L
-15	-07	-15	-153K	-15	-15L
-16	-08	-16	-183K	-16	-16L
-17	-09	-17	-223K	-17	-17L
-18	-10	-18	-273K	-18	-18L
-19	-11	-19	-333K	-19	-19L
-20	-12	-20	-393K	-20	-20L
-21	-13	-21	-473K	-21	-21L
-22	-14	-22	-563K	-22	-22L
-23	-15	-23	-683K	-23	-23L
-24	-16	-24	-823K	-24	-24L
-25	-17	-25	-104K	-25	-25L
-26	-18	-26	-124K	-26	-26L
-27	-19	-27	-154K	-27	-27L
-28	-20	-28	-184K	-28	-28L
-29	-21	-29	-224K	-29	-29L
-30	-22	-30	-274K	-30	-30L
-31	-23	-31	-334K	-31	-31L
-32	-24			-32	-32L
-33	-25			-33	-33L
-34	-26			-34	-34L
-35	-27			-35	-35L
-36	-28			-36	-36L
-37	-29			-37	-37L
-38	-30			-38	-38L
-39	-31			-39	-39L
-40	-32			-40	-40L
-41	-33			-41	-41L
-42	-34			-42	-42L
-43	-35			-43	-43L
-44	-36			-44	-44L
-45	-37			-45	-45L
-46	-38			-46	-46L
-47	-39			-47	-47L
-48	-40			-48	-48L
-49	-41			-49	-49L
-50	-42			-50	-50L
-51	-43			-51	-51L
-52	-44			-52	-52L
-53	-45				
-54	-46				
-55	-47				
-56	-48				
-57	-49				
-58	-50				
-59	-51				
-60	-52				
-61	-53				



Product Index

Series 100	6	Series 4448	76	Series MIL2510	30
Series 103	7	Series 4470	48	Series MIL4922	78
Series 105	8	Series 4501	75	Series MIL8532	80
Series 106	9	Series 4554	60	Series MILP1812	68
Series 108	8	Series 4564	60	Series MILS1812	28
Series 160	10	Series 4590	95	Series P160	63
Series 511	41	Series 4726	35	Series P1330	66
Series 0402R	2	Series 4922	77	Series P1812	67
Series 0603R	3	Series 5022	32-33	Series PDxxxR	87-88
Series 0805R	4	Series 5400	61	Series PT	103-106
Series 0819	37	Series 5526	36	Series PTHF	107-108
Series 0925	49	Series 6012-6027	134	Series PTHF-SM	85-86
Series 1008	14	Series 6051-6055	135	Series PTHF-VM	109-110
Series 1025	38	Series 6443-6448	136	Series PTKM	107-108
Series 1026	38	Series 6494-6498	137	Series PTKM-SM	85-86
Series 1210	18	Series 6655-6658	138	Series PTKM-VM	109-110
Series 1330	21	Series 6665-6668	139	Series S1008	16
Series 1331	23	Series 8532	79	Series S1210	19
Series 1537	40	Series 9405	62	Series S1812	27
Series 1638	42	Series 9406	62	Series S3483R	71
Series 1641	50	Series BF	118-120	Series S4924	31
Series 1782	39	Series CF	121-122	Series SDS130R	72
Series 1812	25	Series CM1011	125	Series SDS680R	73
Series 1840	43	Series CM6149	126	Series SDS850R	74
Series 1944	44	Series CM6296	127	Series SMB2.5	114
Series 1945	44	Series CM6350	128	Series SP1008	64
Series 2020	56	Series CM6460	129	Series SP1210	65
Series 2150	45	Series CM6560	130	Series SP1812	69
Series 2256	93	Series CM6594	131	Series SPD42R	89
Series 2474	94	Series CM7560	132	Series SPD62R	90
Series 2500	46	Series CM9900	133	Series SPD73	91
Series 2510	29	Series DC630	97	Series SPD74	91
Series 2512	70	Series DC780	98	Series SPD125	92
Series 2534	59	Series DC1050	99	Series SPD127	92
Series 2727	57	Series DC1390	100	Series WW1008R	5
Series 2890	47	Series EMI	111		
Series 3090	11	Series ER	52-55	CONVERSION CHARTS	
Series 3094	12	Series FFAM	123	MIL Standard to Delevan	140-142
Series 3443	96	Series FFAT	124	MIL-PRF-83446 to Delevan	143-145
Series 3483R	71	Series HC	101	MIL-PRF-27 to Delevan	146
Series 4211	115	Series HCT	81-82		
Series 4212	116	Series HF1008	15		
Series 4214	117	Series HTPT66	102		
Series 4221	112	Series LLST	84		
Series 4222	113	Series LP4040R	83		
Series 4232	20	Series LP5035R	83		
Series 4302	17	Series LP5050R	83		
Series 4307	51	Series LP5064R	83		
Series 4379	13	Series MIL1330	22		
Series 4426	34	Series MIL1331	24		
Series 4445	58	Series MIL1812	26		

RF


Axial-Leaded, Surface Mount, Established Reliability

- DSCC approvals on MIL-PRF-15305, MIL-PRF-83446, MIL-PRF-39010
- Sole manufacturer for all ten M39010 slash sheets life tested to "R" reliability level
- Shielded configurations result in less than 2% coupling
- Tight tolerances up to $\pm 1\%$ available
- Rugged epoxy molded construction using UL94V-0 materials
- Encapsulation provides resistance to corrosion in extreme environments
- Surface mount industry standard package sizes — with low-profile and temperature stable versions available
- Inductance ranges from $0.0018\mu\text{H}$ to $33,000\mu\text{H}$
- -55°C to $+125^\circ\text{C}$ full Military operating temperature range



POWER

- MIL-PRF-27 approvals on 3 DSCC QPL slash sheets
- Axial-leaded, radial-leaded, and surface mount configurations
- Inductance ranges from $0.22\mu\text{H}$ to $22,000\mu\text{H}$
- Current ratings from 0.050A to 19.9A
- High temperature designs operating at up to $+220^\circ\text{C}$
- Designed to withstand high levels of mechanical shock and vibration



TRANSFORMERS

- Common Mode Chokes
- Isolation Transformers
- Switchmode Transformers
- VDE PC Mount & VDE Quick Connect Transformers
- Custom options available for all standard product offerings



ISO 9001:2008
Certified Facilities



AS 9100:2004
Certified Facilities



270 Quaker Road
East Aurora, New York 14052

716.652.3600
Fax: 716.652.4814

www.delevan.com

apisales@delevan.com
apieng@delevan.com

A Subsidiary of Danaher Corporation
(NYSE: DHR) www.danaher.com