NAME

mbm_xbt - Calculate sound speed from XBT data.

VERSION

Version 5.0

SYNOPSIS

mbm_xbt -I*infile* **[-F***format* **-L***latitude* **-S***salinity* **-V -H]**

DESCRIPTION

mbm_xbt is a perl shellscript to translate various XBT data sets from depth and temperature into depth and sound speed. Header lines are turned into comments beginning with '#' characters. The output filename consists of the input filename with the suffix ".sv". The conversion is done using the DelGrosso equation as referenced in Dusha et al. [1993] (reference below).

AUTHORSHIP

David W. Caress (caress@mbari.org)
Monterey Bay Aquarium Research Institute
Dale N. Chayes (dale@ldeo.columbia.edu)
Lamont-Doherty Earth Observatory
Suzanne H. O'Hara (sohara@ldeo.columbia.edu)
Lamont-Doherty Earth Observatory

OPTIONS

–F *format*
Allows the user to select the type of XBT data. Currently supported formats are: 1 = Sparton XBT, 2 = Sippican MK12 XBT, 3 = Sippican MK21. Default: *format* = 2.

–H This "help" flag cause the program to print out a description of its operation and then exit immediately.

–I *file*
Data file from which the input data will be read.

–L *latitude*
Latitude of the XBT cast.

–S *salinity*
Sets the salinity used to calculate sound speed from temperature and depth. The default value of 35 ppt may be significantly in error in some areas. Default: *salinity* = 35.

–V Causes **mbm_xbt** to operate in "verbose" mode so that it outputs more information than usual.

NOTES

There is a hard limit in the code that prevents temperatures less than -2.0 degrees C from being used. Input lines containing temperatures less than -2.0 will be ignored.

SEE ALSO

mbsystem(l), **mbprocess**(l), **mbset**(l), **mbvelocitytool**(l), **mblevitus**(l)

REFERENCES

Dusha, B. D., P. F. Worcester, B. D. Cornuelle, B. M. Howe, On equations for the speed of sound in seawater, J. Acoust. Soc. Am., 93, 255-275, 1993.

BUGS

Let us know.