



The diagram illustrates a 7-core cable with a 12-inch length. The conductors are arranged in a circular pattern, with the central conductor labeled '1' and the outer conductors labeled '2' through '7'. The cable is labeled 'Parosci' and 'Subconn MCBHRASS'.

Conductor Label	Color	Gauge	Position
Paro 12V Pos	WHT	22 AWG	1
Paro 12V Gnd	WHT	22 AWG	2
RS232 TX	WHT	22 AWG	3
RS232 RX	WHT	22 AWG	4
Parosci +9V	WHT	22 AWG	5
Parosci +9V Rtn	WHT	22 AWG	6
Parosci RS232 TXD	WHT	22 AWG	7

Female Face View
Subconn MCBHRASS
on custom 1" stem




8 Female Face View
Subconn MCBHRASS
on custom 1" stem




Male Face View
Subconn MCIL8M
Molded to SO Cable

1	20 AWG	Black		
2	20 AWG	White		
3	20 AWG	Red	Paro 12V Pos	4
4	20 AWG	Green	Paro 12V Gnd	3
5	20 AWG	Orange	Paro RS232 RX	2
6	20 AWG	Blue		
7	20 AWG	Wht/Blk	Paro RS232 TX	1
8	20 AWG	Red/Blk		



1 Female Face View
Burton 55R1-1508-xxxx CCP
Molded to SO Cable
xxxx denotes length of cable, in feet



Male Face View
Burton 5507-1508-0001

44.0 +/- 1.0 inches length
Measurement of exposed SO jacket