

DVL1000 - 300 m



Bottom-track from over 0.2 to 75 m range; 300 m max. operational depth

The DVL1000 is the world's smallest commercially available Doppler Velocity Log. It combines compact design with unprecedented functionality, being able to fly higher in the water column and closer to the seabed than similar equipment. This version has a maximum operational depth of 300 m and is ideally suited for subsea navigation where size and weight are a concern. This 1 MHz Doppler Velocity Log is used by industry leaders in the subsea market because of its high accuracy and state-of-the-art technology.

DVL1000 - 300 m



Highlights

- ✓ Industry's smallest DVL
- ✓ Bottom track from 0.2-75 m range
- ✓ Quality estimates - per beam and ping

Applications

- ✓ Diver navigation systems
- ✓ Hand-portable unmanned underwater vehicles (UUVs)
- ✓ Shallow-water UUVs

DVL1000 - 300 m

Technical specifications

→ Bottom velocity

Single ping std @ 3 m/s	0.5 cm/s
Long-term accuracy	±0.1% / ±0.1 cm/s
Minimum altitude	0.2 m
Maximum altitude	75 m
Velocity resolution	0.01 mm/s
Maximum ping rate	8 Hz max

→ Water tracking

Minimum accuracy	0.3% of measured value ± 0.3 cm/s
Minimum range	2.0 m

→ Current profiling

Minimum accuracy	0.3% of measured value ± 0.3 cm/s
Velocity resolution	0.1 cm/s
Interval	User-specified Nth ping
Maximum range	30 m
Blanking	0.1 m
Cell size	0.2-2.0 m
Max # cells	150

→ Environmental

Operating temperature	-4 to +40 °C
Storage temperature	-20 to +60 °C

→ Mechanical

Depth rating	300 m
Weight	1.30 kg
Weight in water	0.15 kg

DVL1000 - 300 m

→ Mechanical

Height	158 mm
Diameter	ø114 mm

→ Hardware

Frequency of operation	1 MHz
Beam width	2.9°
Configuration	4-beam Janus array convex transducer, 25° beam angle
Internal memory	16 GB / 64 GB optional

→ Interfaces

Serial (either serial or ethernet)	Configurable RS-232 or RS-422 Subconn connector, 8-pin male
Ethernet	10/100 Mbits Auto MDI-X.TCP/IP, UDP/IP, HTTP protocols. Fixed IP / DHCP client /Auto IP address assignment.UPnP and Nortek proprietary instrument discovery over Ethernet. IEEE1588/PTP and NTP for absolute time stamping. Multiple simultaneous data format transmission possible. Data formats Nortek proprietary
Data formats	Nortek proprietary w/ 1 ms time stamp accuracy, NMEA0183, Variants of PDx
Trigger	Internal 1, 2, 3, 4, 5, 6, 7 or 8 Hz or Trigger In. Trigger option through command (ethernet or serial) External TTL or 485 lines: (configurable Rising/Falling/Edges)

→ Sensors

Pressure	0.1% FS /precision better than 0.002% of full scale per sample
Temperature	-4° to +40 °C ± 0.1 °C

→ Power

DC input	12-48 V
Maximum peak current	1.5 A
Average power	1.3 W

→ Materials

DOPPLER VELOCITY LOG

DVL1000 - 300 m



Standard models

POM housing