


4.6~28.8 WATT NON-ISOLATED DC-DC CONVERTER



OC1V –SC1224

Specifications<DC/DC>	Model							
OC1**SC1224/48 SINGLE	OC1-3.3SC1224		OC1-05SC1224		OC1-06SC1224		OC1-24SC48	
Input Voltage DC[V]	12	24	12	24	12	24	48	
Input Range DC[V]	10.2 to 32						40.8 to 56	
Inrush Current [A]	Not specified							
Input Range								
at no load [mA](typical)	4	5	5	3	5	3	5	
at full load[mA](typical)	814	416	693	355	814	416	645	
Input Current when Remote controll is off	0.2	0.56	0.24	0.6	0.24	1.15	0.56	
Line Back Noise [mVp-p](typical)			1	1	1	1	3	
Efficiency [%] (typical) *1	78	75	84	82	86	84	93	

Block Diagram



OC1_SC

Specifications<DC/DC>	Model			
OC1**SC1224/48 SINGLE	OC1-3.3SC1224	OC1-05SC1224	OC1-06SC1224	OC1-24SC48
Output Voltage [V]	3.3	5	6	24
Output Current [A]	1.4	1.4	1.4	1.2
Voltage Tolerance +/-[mV](maximum)	100	150	180	720
Ripple and Noise [mVp-p](maximum) *2	200			
Regulation				
a.Static Line Regulation [mV](maximum)	18	25	30	120
b.Dynamic Line Regulation +/-[mV](maximum) *3	500	600	600	400
c.Static Load Regulation +/-[mV](maximum) *4	18	25	30	120
d.Temperature Coefficient *5	0.03%/°C(maximum) at temperature -20 to +71°C			
e.Drift[mV](maximum) *6	30	40	45	135
f.Dynamic Load Regulation +/- [mV](maximum) *7	200			
g.Recovery Time *3,*7	5mS(typical)			
Rise up time	5mS(maximum) at rated input/output			
Hold up time	Not specified			
Functions				
Overcurrent Protection	Current Limiting with automatic recovery			
≥10% of Rated Output Current [A]	1.54	1.54	1.54	1.54
Overvoltage Protection	6	6	7.5	12
Remote Control	Turn on by inputing voltage(4.5 to 56V) between "RC"pin and "0V"pin .Put a 5k ohm resistor between "+ in"pin and "RC"pin when remote on/off is not used			
Remote Sence	Not available			
Trimming of output voltage[mV]	Not available			
Input Fuse	Installed[2A]			
Environmental				
Operating Temperature	-20 to +71°C			
(derating)	2%/°C(50°C to 71°C) (out of warranty ≥1°C)			
Operating Humidity	20-90%/RH(non-condensing)			
Storage Temperature	-20 to +85°C			
Storage Humidity	20 to 90%/RH(non-condensing)			
Vibration	5-10Hz:10mm double amplitude,10-55Hz:2G,3minutes' period for 30minutes each along X,Y,Z axes(non-operating)			
Shock	3G			
Cooling	Convection			
? Weight (typical)	open board type:8g			

Conditions:

*1 at 25°Cand rated input/output

*2 measured by a bayonet probe at the output connector at a 0 to 100MHz bandwidth

*3 when input voltage changed from 10.2V to 32V rapidly at rated output


*4 when output current changed from 0mA to rated current keeping the current of other channel below minimum rated current at rated input

*5 at -20 to +71°C

*6 for 7hours from 1hour after switch-on at 25°Cand rated input/output

*7 when output current changed from 25% of rated current to 75% rapidly at rated input

Dimension Diagram



Efficiency Curve

