

SFP-155-LR2



Features

- Single 3.3 V supply
- 29 dB min, 33.5 typical link budget
- -5 to 70 °C temperature operation
- 1550nm DFB Laser
- SFP MSA SFF-8074i compliant
- GR 253/STM G.957 compliant
- Digital Diagnostic SFF-8472 compliant
- Bellcore GR-468 compliant

General Operating

Parameter	Symbol	Min	Typical	Max	Unit
Supply Voltage	V_{cc}	3.135	3.3	3.465	V
Total Current	I_{cc}	-	-	300	mA
Power Supply Noise Rejection ^a		100	-	-	mVp-p
Operating Temperature (case)	T_{op}	-5	-	70	°C
Storage Temperature	T_{st}	-40	-	85	°C
Data Rate OC3	DR	-	155	-	Mb/s

a) 20Hz to 155MHz

Transmitter Specifications

Parameter	Symbol	Min	Typical	Max	Unit
Optical Power	P_{op}	-5	-2.5	0	dBm
Average Launch power of off Tx	P_{off}	-	-	-30	dBm
Extinction Ratio	ER	10	-	-	dB
Eye Mask		-	-	-	SONET/SDH compliant
Optical Jitter generation	J_{gen}	-	-	0.002	UI
Optical Rise time ^b	t_r	-	-	160	ps
Optical Fall time ^b	t_f	-	-	160	ps
Mean Wavelength	λ	1480	1550	1580	nm
Spectral Width (20 dB)	$\Delta\lambda$	-	-	1	nm
Dispersion Penalty (at 80Km)		-	0.5	1	dB
Relative Intensity Noise	RIN	-	-	-120	dB/Hz
Reflectance Tolerance	rp	-24	-	-	dB

b) 20%-80% values

Transmitter Electrical

Parameter	Symbol	Min	Typical	Max	Unit
Input Differential Impedence	R_{in}	80	100	120	Ohm
PECL Single Ended data input swing	$V_{in, pp}$	250	-	1200	mV
TxFault_Fault	V_{fault}	2	-	V_{cc}	V
TxFault_Normal	V_{normal}	V_{ee}	-	$V_{ee}+0.5$	V
TxDisable_Disable	V_d	2	-	V_{cc}	V
TxDisable_Enable	V_{en}	V_{ee}	-	$V_{ee}+0.8$	V

SFP-155-LR2

Receiver Specifications

Parameter	Symbol	Min	Typical	Max	Unit
Receive Power Low ^a	$R_{sens,low}$	-34	-36	-	dBm
Receive Power High	$R_{sens,high}$	-	-	-10	dBm
Damage Threshold for Receiver	$P_{in,damage}$	-	-	4	dBm
Wavelength ^b	λ	1480	1550	1580	nm
Maximum Reflectance of Receiver	RX_r	-	-	-25	dB
LOS Assert		-44	-	-	dBm
LOS De-assert		-	-	-34	dBm
LOS hysteresis		1	-	-	dB

a) at 10^{-10} BER, PRBS $2^{23}-1$

b) Operational over 1200 to 1625 nm range

Electrical Output

Parameter	Symbol	Min	Typical	Max	Unit
PECL Single ended data output swing	$V_{out,pp}$	400	-	800	mV
Data output rise time	T_r	-	-	175	ps
Data output fall time	T_f	-	-	175	ps

Timing and Electrical

Parameter	Symbol	Min	Typical	Max	Unit
Tx Disable Negate time	t_{on}	-	-	1	ms
Tx Disable assert time	t_{off}	-	-	10	μs
Time to initialize, including reset of TX fault	t_{init}	-	-	300	ms
Tx fault Assert time	t_{fault}	-	-	100	μs
Tx Disable to reset	t_{reset}	10	-	-	μs
LOS Assert time	t_{loss_on}	-	-	100	μs
LOS De-assert time	t_{loss_off}	-	-	100	μs
Serial ID Clock Rate	f_{serial_clock}	-	-	100	KHz
RX_LOS Voltage (high)		2	-	-	V
RX_LOS Voltage (low)		-	-	0.8	V
LOS output voltage-Fault	$V_{LOS\ fault}$	2	-	V_{cc}	V
LOS output voltage-Normal	$V_{LOS\ normal}$	V_{ee}	-	$V_{ee}+0.5$	V
MOD_DEF (0:2)-High	V_h	2	-	V_{cc}	V
MOD_DEF (0:2)-Low	V_l	V_{ee}	-	$V_{ee}+0.5$	V

SFP-155-LR2

Diagnostics

Parameter	Range	Accuracy	Unit	Calibration	Formula
Temperature (-T)	-5 to 70	± 3	°C	Internal	$T_c(C) = T_{ad}(16 \text{ bit signed twos complement})/256$
Temperature	-5 to 70	± 3	°C	Internal	$T_c(C) = T_{ad}(16 \text{ bit signed twos complement})/256$
Voltage	0 to V_{cc}	0.1	V	Internal	$V(\text{Volts}) = V_{ad}(16 \text{ bit unsigned integer}) * 0.1$
Bias Current	0 to 120	5	mA	External	$I(\text{mA}) = I_{slope} * I_{ad}(16 \text{ bit unsigned integer}) + I_{offset}$
TX Power	0 to 3.5	± 3 dB	mW	External	$TX_PWR(\mu W) = TX_PWR_{slope} * TX_PWR_{ad}(16 \text{ bit unsigned integer}) + TX_PWR_{offset}$
RX Power	-34 to -10 dBm	± 3 dB	mW	External	$RX_PWR(\mu W) = A0 + A1 * x + A2 * x^2 + A3 * x^3 + A4 * x^4$

EEPROM Serial ID


Name of Field	Description of Field	Address	Hex	ASCII
Vendor Name	SFP Vendor name(ASCII)	20	4C	L
		21	55	U
		22	4D	M
		23	49	I
		24	4E	N
		25	45	E
		26	4E	N
		27	54	T
Vendor OUI	IEEE vendor OUI code for Luminent Inc.	37	00	
		38	06	
		39	B5	
Vendor PN	Part number in ASCII, e.g. SFP-155-LR2	40	53	S
		41	46	F
		42	50	P
		43	31	1
		44	35	5
		45	35	5
		46	4C	L
		47	52	R
		48	32	2

Pinout Definitions


Pin	Function	Notes
1	$V_{ee}T$	TX GND
2	TX_FAULT	Open Collector
3	TX_DISABLE	Internally Pulled High
4	MOD_DEF2	Serial Data Input
5	MOD_DEF1	Serial Clock Input
6	MOD_DEF0	Internally Grounded
7	NC	Not Connected
8	LOS	Open Collector
9	$V_{ee}R$	RX Ground
10	$V_{ee}R$	RX Ground
11	$V_{ee}R$	RX Ground
12	RXD-	RX Data Negative
13	RXD+	RX Data Positive
14	$V_{ee}R$	RX GND
15	$V_{cc}R$	RX Power
16	$V_{cc}T$	TX Power
17	$V_{ee}T$	TX GND
18	TXD+	TX Data Positive
19	TXD-	TX Data Negative
20	$V_{ee}T$	TX GND

SFP-155-LR2

Outline Drawing (I Latch)



Outline Drawing (Bail Latch)



SFP-155-LR2


Ordering Information

Available Options:

SFP-155-LR2

SFP-155-LR2--D1

Part numbering Definition:



Warnings

Handling Precautions: This device is susceptible to damage as a result of electrostatic discharge (ESD). A static free environment is highly recommended. Follow guidelines according to proper ESD procedures.

Laser Safety: Radiation emitted by laser devices can be dangerous to human eyes. Avoid eye exposure to direct or indirect radiation.

Legal Notice

IMPORTANT NOTICE!

All information contained in this document is subject to change without notice, at Luminent's sole and absolute discretion. Luminent warrants performance of its products to current specifications only in accordance with the company's standard one-year warranty; however, specifications designated as "preliminary" are given to describe components only, and Luminent expressly disclaims any and all warranties for said products, including express, implied, and statutory warranties, warranties of merchantability, fitness for a particular purpose, and non-infringement of proprietary rights. Please refer to the company's Terms and Conditions of Sale for further warranty information.

Luminent assumes no liability for applications assistance, customer product design, software performance, or infringement of patents, services, or intellectual property described herein. No license, either express or implied, is granted under any patent right, copyright, or intellectual property right, and Luminent makes no representations or warranties that the product(s) described herein are free from patent, copyright, or intellectual property rights. Products described in this document are NOT intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. Luminent customers using or selling products for use in such applications do so at their own risk and agree to fully defend and indemnify Luminent for any damages resulting from such use or sale.

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROVIDED ON AN "AS IS" BASIS. Customer agrees that Luminent is not liable for any actual, consequential, exemplary, or other damages arising directly or indirectly from any use of the information contained in this document. Customer must contact Luminent to obtain the latest version of this publication to verify, before placing any order, that the information contained herein is current.

© Luminent, Inc. 2002
All rights reserved