


- Low profile socket, sits only .122" above PCB.
- Hi-Rel, 4-finger BeCu #30 clip rated at 3 amps. See page 208 for details.
- Uses Mill-Max #0501 pin. See page 131 for details.

Total number of pins				Quantity per tube	Ordering Information							
	A	B	C									
10	0.5	0.2	0.3	41	XX= Plating Code See Below For High Temperature Insulators Add '100' To End Of Part Numbers							
4	0.2	0.3	0.4	102								
6	0.3	0.3	0.4	67								
8	0.4	0.3	0.4	50								
10	0.5	0.3	0.4	40								
14	0.7	0.3	0.4	28								
16	0.8	0.3	0.4	25								
18	0.9	0.3	0.4	22								
20	1.0	0.3	0.4	20								
22	1.1	0.3	0.4	18								
24	1.2	0.3	0.4	16								
28	1.4	0.3	0.4	14								
20	1.0	0.4	0.5	20								
22	1.1	0.4	0.5	18								
24	1.2	0.4	0.5	16								
28	1.4	0.4	0.5	14								
32	1.6	0.4	0.5	12								
24	1.2	0.6	0.7	16								
28	1.4	0.6	0.7	14								
32	1.6	0.6	0.7	12								
36	1.8	0.6	0.7	11								
40	2.0	0.6	0.7	10								
42	2.1	0.6	0.7	9								
48	2.4	0.6	0.7	8								
50	2.5	0.6	0.7	8								
52	2.6	0.6	0.7	7								
50	2.5	0.9	1.0	8								
52	2.6	0.9	1.0	7								
64	3.2	0.9	1.0	6								
					SPECIFY PLATING CODE XX=				13		93	
					Sleeve (Pin) 				10μ" Au		200μ" Sn/Pb	
					Contact (Clip) 				30μ" Au		30μ" Au	

**For High
Temperature
Insulators
Add '100'
To End Of
Part Numbers**