

- [Conception](#)
- [Tube lamp](#)
- [Small Handlamp](#)
- [High-Tech lamp](#)
- [Handlamp](#)
- [Cell tank](#)
- [Lamp heads](#)
- [Tech-lamp](#)
- [Set Video](#)
- [LED-technics](#)
- [Flashlight](#)
- [Charger](#)
- [Technical Data](#)
- [Price list / Service](#)
- [Test / Award](#)
- [UW-Photo Galerie](#)
- [News/Activities](#)

[illegible]

Strobe ready acoustical signal	standard	standard	standard
TTL under exposed alarm	optical/acoustical	optical/acoustical	optical/acoustical
Cell Low Charge alarm	optical/acoustical	optical/acoustical	optical/acoustical
Synchronisation Socket	standard	standard	standard
Plug In NMH Cell Pack (optional as NC)	12V / 3.0Ah NMH (2.4Ah NC)	12V / 3.0Ah NMH (2.4Ah NC)	6V / 3.0Ah NMH (2.0Ah NC)
Weight (above water)	3.0 kg (6 lbs. 9 oz)	2.5 kg (5 lbs. 8 oz)	1.9 kg (4 lbs. 3 oz)
Weight in Salt Water	0.0 kg	0.0 kg	0.1 kg (3.5 oz)
Dimensions in mm (inches) (Length x Diameter)	215 (8½") x 139 (5½")	220 x 119	225 x 99
No of frames at full power	approx. 90	approx. 190	approx. 190
Pilot light (100%) incl. 36 Frames at full power	approx. 60 Min.	approx. 80 Min.	approx. 60 Min.
Standard charger (LG) included/ Charge time	LG off-shore II / 2 hrs.	LG off-shore II / 2 hrs.	LG off-shore I/6 / 4 hrs.

Technical specifications may change. Copyright Hartenberger. Correct at 01.01.2002

[↑ top](#)