

































































SIZE	MINI-CON SERIES CONTACT CONFIGURATIONS (MALE FACE VIEW ONLY - NOT TO SCALE)										
D	 4#22	 8#28	E	 7#22	 19#28						
G	 3#16 (LONG)	 3#22	 4#22	 5#22	 6#22	 7#20	 10#22				
K	 4#16 (LONG)	 5#16 (LONG)	 6#20	 1#10/6#20 (7 LONG)	 2#14/6#22 (8 LONG)	 10#20	 2#14/8#20 (10 LONG)	 12#22	 6#20/10#22 (16)	 19#22	
L	 2#22/20 ohm COAX (LONG)	 2#20 HV	 1#22/20 ohm COAX 4#20 (5 LONG)	 3#10/3#22 (6 LONG)	 7#16 (LONG)	 3#14/6#22 (9 LONG)	 12#22				
	 2#16/6#20/8#22 (16 LONG)	 18#22	 18#20	 8#20/10#22 (18)	 6#20/14#22 (20)	 24#22					
M	 3#14 (LONG)	 4#10 (LONG)	 4#14 (LONG)	 7#16 (LONG)	 10#16 (LONG)	 4#16/8#20 (12 LONG)	 3#16/12#22 (15 LONG)				
	 16#22	 6#16/12#20 (18 LONG)	 3#16/19#22 (22 LONG)	 3#16/21#22 (24 LONG)	 25#20	 26#20	 37#22				
O	 2#14 HV	 4#14 (LONG)	 8#14 (LONG)	 12#20	 3#10/4#14/6#22 (13 LONG)	 3#10/1#14/9#22 (13 LONG)	 3#14/11#20 (14 LONG)	 14#16			
	 16#22	 4#10/12#22 (16B LONG)	 19#22 HV	 8#14/13#20 (21 LONG)	 44#20	 6#16/9#20/34#22 (49 LONG)	 52#22	 56#22			

NOTES:

- ▼ Available as Glass Sealed style connectors.
- All configurations shown are the face view of the receptacle connector (BCR/FCR/CCR).
- 600 VDC is standard; many of the above can handle higher voltage ratings.
- Please contact SEACON for specific voltage ratings.

SIZE	MINI-CON SERIES CONTACT CONFIGURATIONS (MALE FACE VIEW ONLY - NOT TO SCALE)					
P						
	4#14/2#20 (6 LONG)	1#16/5#22 (6 LONG)	7#10 (LONG)	25#16 (LONG)	1#22/20 ohm COAX 2#14/3#20/19#22 (25 LONG)	4#22/20 ohm COAX 29#22 (33 LONG)
						
Q						
	3#14/2#16/13#22 (18 LONG)	24#20	26#16 (LONG)	56#20	90#22	10#20/82#22 (92)
						106#22
R						
	3#22/20 ohm COAX 8#16 (11 LONG)	12#10 (LONG)	4 20 ohm COAX 9#16 (13A LONG)	15#10 (LONG)	16#14 HV (LONG)	20#16 (LONG)
						4#10/18#16 (22 LONG)
R						
	2#22/20 ohm COAX 2#10/24#16 (28 LONG)	30#16 (LONG)	8#10/24#22 (32A LONG)	32#16 (LONG)	37#16 (LONG)	44#16 (LONG)
						45#20
R						
	24#20/23#22 (47)	56#20	4#10/6#16/74#22 (84 LONG)	96#20	131#22	
						













NOTES:

- ▼ Available as Glass Sealed style connectors.
- All configurations shown are the face view of the receptacle connector (BCR/FCR/CCR).
- 600 VDC is standard; many of the above can handle higher voltage ratings.
- Please contact SEACON for specific voltage ratings.

SIZE	MINI-CON SERIES CONTACT CONFIGURATIONS (MALE FACE VIEW ONLY - NOT TO SCALE)				
T					
	RG8 COAX (LONG)	3#22	8#20/15#22 (23)	30#16 (LONG)	56#16 (LONG)
	10#14/12#16/33#20 (55 LONG)	60#16 HV (LONG)	76#22	87#20	
	38#16/81#22 (119 LONG)	6#16/170#22 (176)	4#10/6#16/193#22 (203 LONG)		
U					
	38#16/81#22 (119 LONG)	6#16/170#22 (176)	4#10/6#16/193#22 (203 LONG)		
X					
	94#16 (LONG)	94#20			

NOTES:

- All configurations shown are the face view of the receptacle connector (BCR/FCR/CCR).
- 600 VDC is standard; many of the above can handle higher voltage ratings.
- Please contact SEACON for specific voltage ratings.

SIZE	REVERSED MINI-CON SERIES (V-MIN) CONTACT CONFIGURATIONS (MALE FACE VIEW ONLY - NOT TO SCALE)										
G				K							
	3#16 (LONG)	7#20	10#22		10#20	12#22	6#20/10#22 (16)	19#22			
L											
	7#16 (LONG)	18#22	24#22								
M											
	3#14 (LONG)	4#10 (LONG)	4#12 (LONG)	7#16 (LONG)	10#16 (LONG)	3#16/21#22 (24 LONG)	26#20	37#22			
O											
	4#14 (LONG)	8#14 (LONG)	12#20	3#10/4#14/6#22 (13A LONG)	3#10/1#14/9#22 (13 LONG)	3#14/11#20 (14 LONG)					
											
	16#22	4#10/12#22 (16B LONG)	8#14/13#20 (21 LONG)	44#20	6#16/9#20/34#22 (49 LONG)	52#22					
P					Q						
	7#10 (LONG)	25#16 (LONG)	4#22/20 ohm COAX /29#22 (33 LONG)	76#22		106#22					
R											
	15#10 (LONG)	20#16 (LONG)	2#22/20 ohm COAX 2#10/24#16 (28 LONG)	30#16 (LONG)	32#16 (LONG)	8#10/24#22 (32A LONG)					
											
	37#16 (LONG)	44#16 (LONG)	56#20	4#10/6#16/74#22 (84 LONG)	131#22 (LONG)						

NOTES:

- All configurations shown are the face view of the receptacle connector (BCR/FCR/CCR).
- 600 VDC is standard; many of the above can handle higher voltage ratings.
- Please contact SEA CON for specific voltage ratings.