

Base enclosure		Continuous or discrete		Gear train		Special options		Enclosure options		Wiring		Thermal management		PCB		Mounting kit		Valve part number		
M	C	M	-		-	0	5	0	AB	-	1	-								
												0	No Valve or Mounting Kits							
												1	Mounting Kit, Customer Supplies Valve but Does Not Send Valve to Hanbay							
												2	Mounting Kit, Customer Supplied Valve Sent To Hanbay							
												3	Mounting Kit, Hanbay Provides Valve							
												AB	Analog Signal Board							
												AI	Analog Signal Board Isolated Input							
												AF	Analog Signal Board Isolated with Feedback							
												DC	Continuous TTL Input Board							
												DT	TTL Input Board with Integrated Feedback							
												AS	Modbus							
M	M-Series							0	No Option											
	C	Continuous							H	Internal Heater										
	D	Discrete							F	External Fan										
	J	Extra Low Torque					0													
	K	M gear train with low torque motor					5													
	L	Low Torque					6													
	M	Medium Torque					7													
	H	High Torque (Additional Gear Stage)					8													
	F	F Gear Stage(with MCL or MCM)					8	TURCK 8 Position Connector w. 20' Cable and Plug (Special Applications)												
						0	Standard Red Alloy Enclosure													
						M	Manual Override (When M in Special Option is not usable)													
						S	Stainless Steel Enclosure													
						N	Black Alloy Enclosure													
				HT	High Temperature Kit															
				0	No Special Options															
				B	Battery Backup															
				G	G-Stage Gate Valve(MCM or MCL)															
				L1	Linear 16 TPI															
				L2	Linear 8 TPI															
				M	Manual Override															
				AC	110vAC Option															
				S	Spring Return															
				RS	Reverse Spring Return															
				TS	Top Stop															
				BS	Bottom Stop															



