


CONTROLLER

A1P1



SUBCONN
MCOM10M



MCOM10M
PINS, FACE VIEW


CABLE LENGTH 8 FT

+28 V	RED	20 AWG
+28 V	ORN	20 AWG
+28 V	YEL	20 AWG
ETH0 TX+	WHT/GRN	23 AWG
ETH0 TX-	WHT	23 AWG
ETH0 RX+	WHT/ORN	23 AWG
ETH0 RX-	WHT	23 AWG
COM1 TXD	GRN	20 AWG
COM1 RXD	BLU	20 AWG
COM1 COM	VIO	20 AWG
SPARE	GRY	20 AWG
28 V COM	WHT	20 AWG
28 V COM	BLK	20 AWG
28 V COM	BRN	20 AWG


FALMAT FM022208-11FG

NOTE: BRN AND BLU TWISTED PAIRS NOT USED

A2P2



SEACON
MINK-10-CCPL-Ti



MINK-10-CCPL
SOCKETS, FACE VIEW

BATTERY SPHERE

Engineer P. McGill		
Title Sedimentation Event Sensor: Controller/Battery Cable		
Size A	Document Number 10020743	Rev 1.1.0
Date:	Tuesday, December 06, 2011	Sheet 1 of 1