



PIEZORESISTIVE OEM PRESSURE TRANSMITTERS

WITH I²C INTERFACE AND EMBEDDED SIGNAL CONDITIONING

With the D-line, KELLER introduces a unique combination consisting of an exceedingly robust industrial pressure transducer and the popular I²C microcontroller interface. Pressure transmitters with this interface are commonly available only in consumer market housings made of plastic or ceramic, where merely the parameters for compensation are stored in an integrated memory. The D-line OEM transmitters however have an unprecedented embedded digital signal processing (DSP) core for the compensation and normalization of the output values.

Technology

The Series 4LD...9LD is based on KELLER's famous Chip-In-Oil (CIO) technology. The «L» stands for the laser welded stainless steel housing and could equally be representative for low-power (typ. 0,1 μ A in idle/sleep mode) and low-voltage (Supply: 1,8...3,6 VDC). The housing is hermetically-sealed, oil-filled and builds a Faraday cage with feed-through capacitors around the entire electronics. The digital interface of the electronics with dual information of pressure and temperature is indicated by the «D».

Interface

The easiest way to couple an OEM pressure transmitter to a microcontroller based system is a digital I/O-compatible interface; no amplification, no analog to digital conversion, no calibration, no temperature coefficients. In short: no problems.

I²C (Inter-Integrated Circuit) is designed for a direct connection between devices on a printed circuit board. It is a BUS-system because it allows the connection of multiple transmitters (slaves) to the same communication lines, but it is not a fieldbus with the classic long distance inter-connectability. So the D-Line combines an industrial pressure interface for harsh environment with an electrical interface for OEM applications.

The values are in 16 Bit unsigned integer format and the scaling is given by constants or by the memory content of the transmitter (two floating point values IEEE 754 for the pressure scaling).

Performance features

- Ultra low power consumption, optimised for battery powered applications
- Hermetically protected sensor electronics – extremely resistant to environmental influences
- Ultra-compact, robust housing made from stainless steel (optional Hastelloy C-276)
- No external electronics for compensation or signal processing
- Extremely accurate, outstanding long-term stability, no hysteresis
- Pressure ranges of 1 bar to 1000 bar
- Easy to integrate into microcontroller based systems
- Internal two-chip solution with pressure sensor and signal processing separation provides a high degree of flexibility

SERIES 4LD...9LD



4LD

7LD

9LD


9FLD

6LHPD / 7LHPD
(high pressure)




Series 4LD

ø 11




Series 7LD

ø 15




Series 9LD

ø 19




Series 9FLD

ø 17 / ø 21




Series 6LHPD

ø 13




Series 7LHPD

ø 15



For proper handling please check our [installation instructions](#) on our product specific web page.

Connection



Label	Description	Wire
SUP	1,8...3,6 V	BK
GND	GND	WH
SCL	I ² C Clock	YE
SDA	I ² C Data	BU
EOC	End of Conversion	RD



Specifications

Pressure Ranges rel. PR	0...1	-0,5...0,5	-1...3	-1...10	-1...30	bar
----------------------------	-------	------------	--------	---------	---------	-----

Pressure Ranges abs. PA			0...3	0...10	0...30	0...100	0...200	0...400	0...600	0...1000	bar
PAA	0...1	0,5...1,5	0...3	0...10							bar

Accuracy ⁽¹⁾ max. $\pm 0,15\%$ FS (600 bar: $\pm 0,25\%$ FS / 1000 bar: $\pm 0,35\%$ FS)
Overpressure 4 x pressure range (max. 350 bar resp. 1200 bar for 6LHPD, 7LHPD)
Long Term Stability typ. $\pm 0,1\%$ FS, max. $\pm 0,2\%$ FS (for pressure ranges $< 1,5$ bar: ± 3 mbar)

Type/ Version	Dimensions [mm] ⁽⁵⁾	Pressure Range	Operating Temperature	Comp. Temp. Range	TEB ⁽²⁾ [%FS]
4LD	$\varnothing 11 \times 4,2$	3...200 bar abs. ⁽³⁾	-10...80 °C	0...50 °C	$\pm 0,7\%$ FS
7LD	$\varnothing 15 \times 5$	3...200 bar abs. 3...30 bar rel. ⁽⁴⁾	-40...110 °C	0...50 °C -10...80 °C	$\pm 0,5\%$ FS $\pm 0,7\%$ FS
9LD	$\varnothing 19 \times 5$	1...200 bar abs. 1...30 bar rel.	-40...110 °C	0...50 °C -10...80 °C	$\pm 0,5\%$ FS $\pm 0,7\%$ FS
9FLD	$\varnothing 17 \times 5,5$ Flange $\varnothing 21$	1...30 bar abs. 1...30 bar rel.			
6LHPD	$\varnothing 13 \times 8$	400...1000 bar abs.	-40...110 °C	0...50 °C	$\pm 0,7\%$ FS
7LHPD	$\varnothing 15 \times 8$			-10...80 °C	$\pm 1,0\%$ FS

⁽¹⁾ Linearity best straight line @ RT; hysteresis, repeatability

⁽²⁾ TEB (Total Error Band): Maximum deviation within specified pressure and compensated temperature range

⁽³⁾ abs: Absolute Pressure Measurement (PAA: Reference pressure at 0 bar abs. (vacuum) PA: Reference pressure at 1 bar abs.)

⁽⁴⁾ rel: Referential version (PR: Reference pressure at ambient pressure)

⁽⁵⁾ Dimensions without glass feed through

Interface	digital I ² C (serial synchronous)
Signal Output	P [bar], T [°C]: normalised to 16 Bit unsigned integer
Pressure Range Reserve	typ. $\pm 10\%$ FS, min. $\pm 5\%$ FS
Supply	1,8...3,6 V
Power Consumption	typ. 1,5 mA during conversion typ. 100 nA in idle mode
Bit Rate	≤ 400 kHz
Start-up Time (Supply ON)	< 1 ms
Conversion Time	typ. 6 ms, max. 8 ms (for P and T)
Logic Levels	LOW: max. $15\%V_{SUP}$, HIGH: min. $85\%V_{SUP}$
Noise Floor	max. $\pm 0,015\%$ FS (temperature 4 Bit)
Temperature Accuracy	typ. ± 2 °C
Supply Voltage Dependency	none
Isolation	> 100 M Ω @ 500 VDC
ESD – Human Body Model	4 kV (HBM: C = 100 pF / R = 1,5 k Ω)
Material in Contact with Media	- Stainless Steel AISI 316L (DIN 1.4404 / 1.4435) - O-Ring: Viton® Shore A (-20...200 °C, exchangeable)
Oil Filling	Silicone oil, others on request
Pressure Endurance	0...100 %FS @ 25 °C: > 10 million pressure cycles with appropriate installation
Vibration Endurance	20 g, 5...2000 Hz, X/Y/Z-Achse
Shock	75 g sine 11 ms
Electrical Connection	- Glass feed through pins $\varnothing 0,45$ mm, L = $4 \pm 0,5$ mm - Plug JST 1 mm, 5-pole. Type: BM05B-SRSS-TB. Only for -20...85 °C and not for 4LD & 6LD As counterpart: Crimp-socket with wires AWG 28. Type: SHR-05V-S-(B), Crimp-contact: SSH-003T-P0.2
Options	- Electrical connection: 7 cm silicone wires 0,09 mm ² on the glass feed through pins - Hastelloy housing (dep. on version also Inconel, Titanium) - Extended temperature range within -50...125 °C
Other possible versions	- Series 9LD: With pressure range 300 mbar rel. - Series 10LD: Type 10L ($\varnothing 19 \times 15$), spec. same as 9LD - Series 20D: With pressure connection G1/4", G1/8" etc. - Series 21D: With screened cable (0,5 to 3 m)
Remarks	- Intermediate press. ranges only for high-volume projects - Series 21D is not available with plug (I ² C is not a fieldbus)

Communication Protocol

D-Line OEM-transmitter samples only on request.
The idle state is the sleep mode to save power.

Sequence for data acquisition:

- Request measurement
2 bytes from master

ADDR	0	0xAC
------	---	------
- Await the end of conversion (three ways)
 - Simple delay of 8 ms
 - Polling of the «Busy?» flag [5] in the status byte (only one byte reading needed)
 - Event triggering by the additional «EOC» handshake pin (goes to VDD)
- Read out measurement results
1 byte from master, 3...5 bytes from slave

ADDR	1	STATUS	P MSB	P LSB	...
			T MSB	T LSB	
- Interpretation of new data
 $P [\text{bar}] = P_{\text{min}}...P_{\text{max}} \Delta 16384...49152$
 $T [^{\circ}\text{C}] = -50...150 \text{ }^{\circ}\text{C} \Delta 384...64384$

The complete communication protocol is available on the KELLER website.

