


MAX-7 series

Compact u-blox 7 GPS/GNSS modules

Highlights

- Small and low power multi-GNSS modules
- Cost and performance optimized versions
- Simple integration with u-blox wireless modules
- Easy migration from MAX-6 family



MAX-7 series:
9.7 x 10.1 x 2.5 mm

Product description

The MAX-7 series of standalone GPS/GNSS modules is built on the exceptional performance of the u-blox 7 multi-GNSS (GPS, GLONASS, Galileo, QZSS and SBAS) engine. The MAX-7 series delivers high sensitivity and minimal acquisition times in the ultra compact MAX form factor.

The MAX-7 series provides maximum sensitivity while maintaining low system power. The MAX-7C is optimized for cost sensitive applications. The MAX-7Q provides best performance and lowest power, while the MAX-7W provides best performance and is optimized for active antennas. The industry proven MAX form factor allows easy migration from MAX-6 modules. Sophisticated RF-architecture and interference suppression ensure maximum performance even in GPS-hostile environments.

The MAX-7 series combines a high level of integration capability with flexible connectivity options in a miniature package. This makes it perfectly suited for industrial and mass-market end products with strict size and cost requirements. The DDC (I²C compliant) interface provides connectivity and enables synergies with u-blox SARA, LEON and LISA wireless modules.

u-blox 7 modules use GPS/GNSS chips qualified according to AEC-Q100 and are manufactured in ISO/TS 16949 certified sites. Qualification tests are performed as stipulated in the ISO16750 standard: "Road vehicles – Environmental conditions and testing for electrical and electronic equipment". MAX-7Q complies with green/halogen free standards.

Product selector

Model	Type						Supply	Interfaces				Features												
	GPS	QZSS	GLONASS	Timing	Dead Reckoning	Precise Point Positioning	2.7 V – 3.6 V	1.65 V – 3.6 V	Lowest power (DC/DC)	UART	USB	SPI	DDC (I ² C compliant)	Programmable (Flash)	Data logger	Extra front-end LNA	Front-end SAW filter	Oscillator	RTC crystal	Antenna supply	Antenna short circuit detection / protection	Antenna open circuit detection pin	Timepulse	External interrupt / Wakeup
MAX-7C	•	•	•				•	•		•			•					C	■	○	○	○	•	•
MAX-7Q	•	•	•				•		•	•			•					T	•	○	○	○	•	•
MAX-7W	•	•	•				•			•			•					T	•	•	•	○	•	•

○ = Optional, not activated per default or requires external components

C = Crystal / T = TCXO

■ = higher backup current

Features

Receiver type	56-channel u-blox 7 engine GPS/QZSS L1 C/A, GLONASS L1 FDMA, SBAS: WAAS, EGNOS, MSAS		
Navigation update rate	up to 10 Hz		
Accuracy	Position	GPS 2.5 m CEP	GLONASS 4.0 m
	SBAS	2.0 m CEP	n.a.
Acquisition	Cold starts:	29 s	30 s
	Aided starts:	5 s	n.a.
	Reacquisition:	1 s	3 s
Sensitivity	Tracking:	−162 dBm	−158 dBm
	Cold starts:	−148 dBm	−140 dBm
	Warm starts:	−148 dBm	−145 dBm
Assistance	AssistNow Online AssistNow Offline AssistNow Autonomous OMA SUPL & 3GPP compliant		
Oscillator	TCXO (MAX-7Q/7W), crystal (MAX-7C)		
RTC crystal	Built-In (MAX-7Q/7W)		
Anti jamming	Active CW detection and removal		
Memory	Onboard ROM		
Supported antennas	Active and passive		

Electrical data

Supply voltage	1.65 V to 3.6 V (MAX-7C) 2.0 to 3.6 V (MAX-7Q/7W)
Digital I/O voltage level	1.65 – 3.6 V
Power Consumption	47 mW @ 1.8 V (Continuous) ¹ 51 mW @ 3 V (Continuous) ¹ 14 mW @ 1.8V Power Save mode (1 Hz) ¹
Backup Supply	1.4 to 3.6V

¹ MAX-7C

Interfaces

Serial interfaces	1 UART 1 DDC (I ² C compliant)
Digital I/O	Configurable timepulse 1 EXTINT input for Wakeup
Timepulse	Configurable 0.25 Hz to 1 kHz
Protocols	NMEA, UBX binary, RTCM

Legal Notice

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.


The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.

Copyright © 2013, u-blox AG

Package

18 pin LCC (Leadless Chip Carrier): 9.7 x 10.1 x 2.5 mm

Pinout



Environmental data, quality & reliability

Operating temp.	−40° C to 85° C
Storage temp.	−40° C to 85° C
RoHS compliant (lead-free)	
Green (halogen-free): MAX-7Q	
Qualification according to ISO 16750	
Manufactured in ISO/TS 16949 certified production sites	
Uses u-blox 7 chips qualified according to AEC-Q100	

Ordering information

MAX-7C-0	u-blox 7 GPS/GNSS Module, 1.65–3.6V, 9.7x10.1mm, 500 pcs/reel
MAX-7Q-0	u-blox 7 GPS/GNSS Module, TCXO, 9.7x10.1mm, 500 pcs/reel
MAX-7W-0	u-blox 7 GPS/GNSS Module, TCXO, antenna supply, 9.7x10.1mm, 500 pcs/reel

Available as samples and tape on reel

Contact us

HQ Switzerland / EMEA
+41 44 722 7444
info@u-blox.com

Americas
+1 703 483 3180
info_us@u-blox.com

APAC – Singapore
+65 6734 3811
info_ap@u-blox.com

China
+86 10 68 133 545
info_cn@u-blox.com

India
+91 959 1302 450
info_in@u-blox.com

Japan
+81 3 5775 3850
info_jp@u-blox.com

Korea
+82 2 542 0861
info_kr@u-blox.com

Taiwan
+886 2 2657 1090
info_tw@u-blox.com