


DESCRIPTION: FEMALE - 0.283 RIGHT ANGLE / MACHINED - ECONOMY



MATERIAL:

SHELL: STEEL, NICKEL PLATED
INSULATOR: UL 94V-O RATED, WHITE PA6T
PROCESS TEMP.: 260° PROCESS TEMPERATURE
CONTACT: PRECISION MACHINED COPPER

ELECTRICAL:

CURRENT RATING: 5 AMPS
CONTACT RESISTANCE: 10 mOhms Max.
INSULATION RESISTANCE: 5 G Ohms min.
VOLTAGE: 1000 V AC FOR 1 MINUTE
TEMPERATURE: -55° C TO +125° C

RoHS COMPLIANT

DIMENSIONS						
No. OF PINS	A	B	C	D	E	F
9	1.213	0.984	0.642	0.311	0.228	0.492
	30.80	25.00	16.30	7.90	5.80	12.50
15	1.541	1.312	0.970	0.311	0.228	0.492
	39.20	33.30	24.60	7.90	5.80	12.50
25	2.089	1.852	1.512	0.311	0.228	0.492
	53.05	47.05	38.40	7.90	5.80	12.50
37	2.728	2.500	2.157	0.311	0.228	0.492
	69.40	63.50	54.80	7.90	5.80	12.50
50	2.638	2.402	2.055	0.429	0.236	0.602
	67.00	61.00	52.20	10.90	6.00	15.30


173-EYY-21YRYY1

SERIES _____
POSITIONS _____
E09
E15
E25
E37
E50
GENDER _____
2 = FEMALE
TERMINATION _____
1 = PC MOUNTING
SHELL PLATING _____
3 = NICKEL
RoHS COMPLIANT _____
HARDWARE OPTIONS _____
00 = NO HARDWARE
0A = 0.098" CLINCH NUT (BOARD SIDE)
14 = SHORT BRACKET WITH 4-40 SCREW LOCK
24 = SHORT BRACKET WITH 4-40 SCREW
46 = BRACKET WITH 4-40 INSERT & BOARDLOCK
PLATING OPTIONS _____
1 = GOLD FLASH
2 = 30MICRO-INCH GOLD
3 = 50MICRO-INCH GOLD


UNITS = inch [mm] DO NOT SCALE FROM DRAWING

	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWN: PAM JENKINS		DATE: 11-28-05	
		SCALE: NTS		SHEET 1 OF 3	
NorComp		DWG NO. 173-EYY-21YRYY1			
		REV 19			


DESCRIPTION: PCB LAYOUT - STANDARD "D" - MALE & FEMALE




9 POSITION




15 POSITION



25 POSITION



37 POSITION



50 POSITION

* TYP.
SUGGESTED SIZE
MAY NOT BE SUITABLE FOR ALL APPLICATIONS

UNITS = inch

DO NOT SCALE FROM DRAWING




THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

NorComp


DRAWN: PAM JENKINS		DATE: 11-28-05	
SCALE: NTS	SHEET 2 OF 3		REV 19
DWG NO. 173-EYY-21YRY1			

DESCRIPTION: CLINCH NUT HARDWARE




14Y = SHORT BRACKET & 4-40
FEMALE HEX SOCKET
24Y = SHORT BRACKET & 4-40
SCREW



CLINCH-NUT HAS 4-40 INTERNAL THREADS



46Y = BRACKET WITH 4-40 INSERT AND
BOARDLOCK



50 POSITION
CONNECTOR
BRACKET
NOTE: LOCATOR PLATE PRESENT ON 50 PIN ONLY



BRACKETS MOUNTED ON CONNECTOR

UNITS = inch [mm]

DO NOT SCALE FROM DRAWING

RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

NorComp

DRAWN:
PAM JENKINS

DATE:
11-28-05

SCALE:
NTS

SHEET
3 OF 3

REV
19

DWG NO. 173-EYY-21YRYY1