

Inductive Washdown Sensors *Uprox+*



Housing Style	Part Number	ID Number	Features	Sensing Range (mm)	Output
18 mm - Embeddable, eurofast Connection 	Bi 8U-EM18WD-AN6X-H1141	M1634839	<i>Uprox+</i> , Washdown	8	3-Wire DC NPN
	Bi 8U-EM18WD-AP6X-H1141	M1634816	<i>Uprox+</i> , Washdown	8	3-Wire DC PNP
18 mm - Nonembeddable, eurofast Connection 	Ni 15U-EM18WD-AN6X-H1141	M1634835	<i>Uprox+</i> , Washdown	15	3-Wire DC NPN
	Ni 15U-EM18WD-AP6X-H1141	M1634818	<i>Uprox+</i> , Washdown	15	3-Wire DC PNP
18 mm - Embeddable, Potted-in Cable 	Bi 8U-EM18WD-AN6X	M1634840	<i>Uprox+</i> , Washdown	8	3-Wire DC NPN
	Bi 8U-EM18WD-AP6X	M1634815	<i>Uprox+</i> , Washdown	8	3-Wire DC PNP
18 mm - Nonembeddable, Potted-in Cable 	Ni 15U-EM18WD-AN6X	M1634836	<i>Uprox+</i> , Washdown	15	3-Wire DC NPN
	Ni 15U-EM18WD-AP6X	M1634817	<i>Uprox+</i> , Washdown	15	3-Wire DC PNP

For detailed sensor specifications see Section M.
Normally Closed versions available upon request, consult factory.



Voltage	Switching Freq. (Hz)	Operating Current (mA)	Operating Temp. (°C)	Protection	Housing	Face	Power LED	Output LED	Mating Cord Cable Length/Jacket	Wiring Diagram #	Wiring Diagrams
10-30 VDC	1500	≤200	-40 to +100	IP 68, 69K	SS	LCP	N/A	YE	RKV 4T-*/S90	1	Diagram 1
10-30 VDC	1500	≤200	-40 to +100	IP 68, 69K	SS	LCP	N/A	YE	RKV 4T-*/S90	2	Diagram 2
10-30 VDC	1000	≤200	-40 to +100	IP 68, 69K	SS	LCP	N/A	YE	RKV 4T-*/S90	1	Diagram 3
10-30 VDC	1000	≤200	-40 to +100	IP 68, 69K	SS	LCP	N/A	YE	RKV 4T-*/S90	2	Diagram 4
10-30 VDC	1500	≤200	-40 to +100	IP 68, 69K	SS	LCP	N/A	YE	2M/PP	3	
10-30 VDC	1500	≤200	-40 to +100	IP 68, 69K	SS	LCP	N/A	YE	2M/PP	4	
10-30 VDC	1000	≤200	-40 to +100	IP 68, 69K	SS	LCP	N/A	YE	2M/PP	3	
10-30 VDC	1000	≤200	-40 to +100	IP 68, 69K	SS	LCP	N/A	YE	2M/PP	4	

* Length in meters.

For material descriptions see page M36.