



IPS1-120-01-S-D-RA

IPT1-110-01-S-D

IPS1-120-01-S-D-VS

MINI MATE[®] CONNECTOR SET IPT1, IPS1

SPECIFICATIONS

For complete specifications see www.samtec.com?IPT1 or www.samtec.com?IPS1

Insulator Material: Black LCP

Contact Material: Phosphor Bronze

Plating: Sn or Au over 50µ" (1.27µm) Ni

Operating Temp Range: -55°C to +105°C with Tin; -55°C to +125°C with Gold

Insertion Depth: (3.71mm)

Wiping Distance: (0.38mm) .015"

Insertion Force (SMT): 3.0oz (0.83N) avg.

Withdrawal Force (SMT): 2.6oz (0.72N) avg.

Insertion Force (T/H): 6.0oz (1.67N) avg.

Withdrawal Force (T/H): 5.0oz (1.39N) avg.

Voltage Rating: 550 VAC

RoHS Compliant: Yes


CURRENT RATING

AMBIENT TEMP	IPT1/IPS1
20°C	8A
40°C	7.2A
60°C	6A
95°C	4.1A
6 POSITIONS (2x3)	

APPLICATION SPECIFIC OPTION

Latching feature available. Call Samtec.

APPLICATION



Processing:

Max Processing Temp: 230°C for 60 seconds, or 260°C for 20 seconds 3x
Lead-Free Solderable: Yes
SMT Lead Coplanarity: (0.13mm) .005" max (05-10) (0.15mm) .006" max (15-25)

Note: Other Gold plating options available. Contact Samtec.

Note: Some sizes, styles and options are non-standard, non-returnable.

IPT1 - **1** NO. PINS PER ROW - **LEAD STYLE** - **PLATING OPTION** - **D** - **TAIL OPTION** - **OTHER OPTION**

Mates with: IPS1

05, 10, 15, 20, 25
(Call Samtec for other sizes)

Specify LEAD STYLE from chart

-S
= 30µ" (0.76µm)
Gold on contact, Matte Tin on Tail

Requires -01 Lead Style (Leave blank for Through-Hole)

-RA
= Right Angle

-VS
= Surface Mount

-K
= (6.00mm) .236" DIA Polyimide film Pick & Place Pad (-VS only)

-LC
= Locking Clip (-VS only) (N/A with -A)

-A
= Alignment Pin (-VS only) (N/A with -LC)

-POL
= No. 1 position polarized

LEAD STYLE	A	B	C
-01	(11.05) .435	(5.84) .250	(2.16) .085
-01-VS	(13.59) .535	(5.84) .250	N/A
-02	(14.00) .551	(9.30) .366	(2.64) .104
-03	(16.00) .630	(11.30) .445	(2.16) .085
-04	(17.00) .669	(12.30) .484	(2.69) .106
-05	(19.00) .748	(14.30) .563	(2.46) .097
-06	(20.00) .787	(15.30) .602	(2.35) .093
-07	(25.00) .984	(20.30) .799	(2.31) .091
-08	(30.00) 1.181	(25.30) .996	(2.39) .094
-09	(35.00) 1.378	(30.30) 1.193	(2.46) .097

No. of positions x (2.54) .100 + (0.51) .020

Through-hole Surface Mount

(5.08) .200 (2.54) .100 (2.54) .100 (7.16) .282 (1.27) .050 (0.51) .020 (2.30) .090 (1.50) .060 (2.54) .100

(0.64) .025 SQ

RUGGEDIZED
by SAMTEC

IPS1 - **1** NO. PINS PER ROW - **01** - **PLATING OPTION** - **D** - **TAIL OPTION** - **OTHER OPTION** - **POL OPTION**

Mates with: IPT1

05, 10, 15, 20, 25
(Call Samtec for other sizes)

-S
= 30µ" (0.76µm)
Gold on contact, Matte Tin on Tail

Leave blank for Through-hole

-VS
= Surface Mount

-RA
= Right Angle

-K
= (5.50mm) .217" DIA Polyimide film Pick & Place Pad (-VS only)

-LC
= Locking Clip (-VS only)

-POL
= No. 1 position polarized

-TR
= Tape & Reel Packaging

No. of positions x (2.54) .100 + (0.38) .015

Through-hole Surface Mount

(2.54) .100 (2.54) .100 (4.95) .195 (8.51) .335 (2.54) .100 (1.27) .050 (7.87) .310 (2.54) .100 (0.51) .020 (0.79) .031 (0.41) .016

TIGER BUY CONTACT

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 • Fax: 812-948-5047
 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0 • Fax: +49 (0) 89 / 89460-299
 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 • Fax: +46-8420413
 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 • Fax: 65 6841-1502
 SAMTEC HONG KONG • Tel: 852-26904858 • Fax: 852-26904842
 SAMTEC SILICON VALLEY • Tel: 408-395-5900 • Fax: 408-395-1520
 SAMTEC FRANCE • Tel: 33 01 60 95 06 60 • Fax: 33 01 60 95 06 61
 SAMTEC ISRAEL • Tel: 972-3-7526600 • Fax: 972-3-7526690
 SAMTEC CHINA • Tel: 86-21-61103766 • Fax: 86-21-61103765
 SAMTEC SOUTH AFRICA • Tel: 27 11 452 8112 • Fax: 27 86 6714432
 SAMTEC UK • Tel: 44 01236 739292 • Fax: 44 01236 727113
 SAMTEC ITALY • Tel: 39 039 6890337 • Fax: 39 039 6890315
 SAMTEC INDIA • Tel: +91-80-3272 1612 • Fax: +91-80-4152 8187
 SAMTEC TAIWAN • Tel: 886-2-2735-6109 • Fax: 886-2-2735-5036
 SAMTEC ANZ • Tel: 613 9512 7747 • Fax: 613 9512 7745