




Semiconductor Fuse

0.250-7A, 500 Volts

BIF Document
35785256
Size **6 x 32**



Pre-Arcing Time-Current Characteristic Curves
FWH .250A6F-007A6F

Approved: **NN** Page **1 of 1**
Rev. Date: **OCT-95** Pub. Date: **JAN-98**

COOPER Bussmann
12-28-98
SB98107 Rev. A

BUSSMANN
P.O. Box 14460
St. Louis, MO 63178-4460
U.S.A.
Phone: 314-394-2877
Fax: 800-544-2570
Int'l Fax: 314-527-1413

BUSSMANN U.K.
Burton-on-the-Wolds
Leicestershire LE12 5TH
England
Phone: 44-1509-882737
Fax: 44-1509-882786

BUSSMANN
DENMARK
5 Literbuen
DK-2740 Skovlunde
Copenhagen, Denmark
Phone: 45-4485-0900
Fax: 45-4485-0901

The only controlled copy of this BIF document is the electronic read-only version located on the Bussmann Network Drive. All other copies of this BIF document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.